Reply to Reviewers – Smith, Rheinwalt, and Bookhagen

Reviewer #1 (Remarks to the Author):

The manuscript by Smith et al. deals with the identification of the optimal grid resolution for slope and aspect derivation from LiDAR dataset. The topic is relevant and of utmost importance in the quantitative geomorphology and hydrology fields since aspect and, especially, slope are fundamental parameters for different analyses commonly carried out such as synthetic channel network derivation, feature extraction and modeling. The paper presents the theoretical steps and a real-world application of a quality metric for slope and aspect calculations developed to determine the optimal resolution minimizing truncation error and the propagated elevation uncertainty. In my opinion, the work is very well structured and the method is robust and clearly outlined in the manuscript. This innovative approach is highly promising and will be most likely of great interest for the geomorphometric community thanks also to the fact that made available the developed code in the GitHub repository. My only minor concern about this high quality work is related to the assumption that the optimal grid resolution of a Digital Elevation Model (DEM) is the one minimizing the total error. This is certainly true in most cases but for several applications, the choice of the DEM resolution is mainly controlled by the dimension of the feature investigated that is some cases may be quite small (e.g. ephemeral gully, colluvial channels) and, thus, a fine resolution may be the best choice. Typically, this is addressed by choosing a high resolution and then computing geomorphometric parameters using large moving window to filter out the noise. Apart from the sentence at lines 1-2, page 18, this issue is not mentioned in the manuscript. I suggest adding some text on this to better clarify your assumption on the "optimal" grid size.

Thank you for your comments on our paper. The issue of scale is difficult – there are many studies which use one-meter or sub-meter gridding of airborne lidar (such as we use in this study) to study small-scale features. Our analysis shows that the uncertainties for these very high resolution datasets become large; in many cases the uncertainties can grow larger than the scale of the fine-scale topography that is studied. While such high-resolution analysis should not be ruled out, it is important to be aware of the uncertainties involved, and whether or not the dataset is precise enough to support the analysis of very small landscape features – with or without using larger window sizes as an approach to smooth out noise. We have added an additional comment in the paper (page 18) to further clarify this.

Specific Comments:

L. 22, p. 1 (and throughout the text): lidar-> LiDAR

In our paper we use the lower-case 'lidar', similar to how radar is used as an abbreviation of RAdio Detection And Ranging. While LiDAR is being used in some literature, the National Academy of Sciences and other national institutions in the UK rely on lidar (https://essp.nasa.gov/essp/files/2018/02/2017-Earth-Science-Decadal-Survey.pdf; http://lidarmag.com/wp-content/uploads/PDF/LiDARNewsMagazine_DeeringStoker-CasingOfLiDAR_Vol4No6.pdf). In the literature, lidar shows the most common usage (http://lidarmag.com/wp-content/uploads/PDF/LiDARNewsMagazine_DeeringStoker-CasingOfLiDAR_Vol4No6.pdf).

L. 24-25, p.1: please consider providing a range of resolutions for "high" and "low" resolution in place of e.g 1 and 30 meters

This has been changed in-text.

L. 3-10, p. 2: I suggest mentioning also stream power studies that are quite relevant in hydrology and soil science.

We have added some relevant citations here.

L. 7, p. 8: differently->different?

This has been corrected.

Figure 13 caption: sq km->km^2

This has been changed.

L. 7, p. 21: also averaging values could be tested as resampling method, maybe the results are different with respect to those obtained using bilinear resampling. In general, I know it is out of the scope of the paper but it would be interesting to compare different resampling techniques in order to suggest the best method to resample resolution

We have added an additional panel to Figure 15 (also below as Figure 1 of this Reply) which shows the results of nearest-neighbor resampling. The four- and five-meter resampled distributions are significantly worse with nearest-neighbor, but the one- and two-meter resampled distributions match the optimal three-meter distribution quite closely. We attribute this to the methodology by which we created the lidar DEMs – the one-meter data is derived from same set of neighborhoods which are aggregated into the three-meter data. The three-meter data is thus quite similar to a nearest-neighbor resampling of the underlying one-meter DEM. We have added an additional comment on this in the paper.



Figure 1 – Impact of two different resampling mechanisms on slope distributions.

Reviewer #2 (Remarks to the Author):

The manuscript "Determining the optimal grid resolution..." presents an analysis of two types of errors that affect DEMS and offers a method for finding the DEM resolution that will minimize these errors for real data. I think that this is a very nice study. The analysis is thorough (23 supplemental figures!), and the combination of theoretical derivations, synthetic data, and application to a real dataset makes for a convincing combination. It is definitely something that will be of interest to people working with airborne lidar data, and since you offer a readily applicable method, I think that people will find this quite useful. I find the paper just about ready to publish, so I have only a few minor comments.

I am curious about the impact of irregular topography on the choice of resolution – if you have a stepped landscape (such as terraced hillslopes), would that change the consideration of the optimal resolution?

Irregular topography will likely result in two distinct optimal resolutions – in your example the flat and steep parts of the terrain likely have different error distributions, and do not see the same impacts from TE and PEU. If the landscape is analyzed together, the calculated optimal grid resolution might not be applicable to all parts of the landscape, as we found in our analysis of individual watersheds on SCI (MS Figure 13). Depending on the analysis approach, the landscape could be broken into two segments and analyzed separately.

You show at the end that resampling gridded data to the optimal resolution is not sufficient to achieve the same quality as creating the DEM at that resolution, but it does seem to improve the slope distributions for the 1m data (it is interesting that resampling the 2 m data appears to move the distribution away from the ideal distribution). Assuming that you have the standard deviations and could calculate the optimal resolution, it seems that resampling could still be helpful if you don't have access to the ungridded point data?

We have added an additional panel to this figure (Figure 15 in the MS, Figure 1 of this Reply), which covers nearest neighbor resampling. Interestingly, the one-meter distribution is almost identical to the three-meter when nearest neighbor resampling is used. We attribute this to the lidar gridding approach we used – the three-meter neighborhood is essentially the same as the nine one-meter neighborhoods which then form the basis for the nearest neighbor resampling. In that specific case, the resampling might improve the error distribution. However, in general, the slope distributions of resampled data will not match the distribution of the target resolution. Any resampling will also introduce new biases into the data which are hard to account for.

Specific Comments:

Fig. 7: It's interesting that the optimal aspect spacing for the two highest noise levels is the same. Does this mean that the optimal spacing maxes out at this point?

This is due to the limits on grid spacing from our theoretical data – the smallest useful Gaussian Hill we can model is on an 11x11 grid. In theory, the very high noise level case should also have an optimal grid resolution – we just aren't able to model it because the data cannot be gridded any more coarsely. Note that the grid spacing values here are an expression of the width-to-height ratio of the surface, and thus aren't a 'hard' limit on grid spacing, but more related to the dimensions of the grid used to model the Gaussian Hill.

Fig. 11: I find it hard to see much of anything with the color scale in panel C. Maybe one with more contrast would be better?

This has been updated.

Watch your use of grid spacing vs. grid resolution - because higher resolution= smaller grid spacing, it can be a little confusing if you suddenly switch between them, as you do in the caption to Fig. 13.

Thank you for catching this inconsistency. This has been updated.

It would also be nice to keep the figures consistent with slope and aspect shown in the same order (ie. slope always on the left/top and aspect on the right/below) - i.e. in fig. 5 it is reversed from fig. 3.

This has been updated throughout.

pg. 22 line 16: I guess you mean <3 meters

This has been fixed.

Determining the Optimal Grid Resolution for Topographic Analysis on an Airborne Lidar Dataset

Taylor Smith¹, Aljoscha Rheinwalt¹, and Bodo Bookhagen¹

¹Institute of Earth and Environmental Sciences, Universität Potsdam, Germany

Correspondence: Taylor Smith (tasmith@uni-potsdam.de)

Abstract. Digital Elevation Models (DEMs) are a gridded representation of the surface of the earth and typically contain uncertainties due to data collection and processing. The topographic metrics slope and aspect contain errors and uncertainties inherited both from the representation of a continuous surface as a grid (referred to as truncation error, TE), and from any DEM uncertainty. We analyze in detail the impacts of TE and propagated elevation uncertainty (PEU) on slope and aspect.

5 Using synthetic data as a control, we define functions to quantify both TE and PEU for arbitrary grids. We then develop a quality metric which captures the combined impact of both TE and PEU on the calculation of topographic metrics. Our quality metric allows us to examine the spatial patterns of error and uncertainty in topographic metrics, and to compare calculations on DEMs of different sizes and accuracies.

Using lidar data with point density of ~10 pts/m² covering Santa Cruz Island in southern California, we are able to generate
DEMs and uncertainty estimates at several grid resolutions. Slope (aspect) errors on the one-meter dataset are on average
0.3° (0.9°) from TE, and 5.5° (14.5°) from PEU. We calculate an optimal DEM resolution for our SCI lidar dataset of four meters that minimizes the error bounds on topographic metric calculations due to the combined influence of TE and PEU for both slope and aspect calculations over the entire SCI. Average slope (aspect) errors from the four meter DEM are 0.25° (0.75°) from TE and 5° (12.5°) from PEU. While the smallest grid resolution possible from the high-density SCI lidar is not

15 necessarily optimal for calculating topographic metrics, high point-density data are essential for measuring DEM uncertainty across a range of resolutions.

1 Introduction

20

Continuous surfaces are often projected onto an evenly sampled grid – digital elevation models (DEMs) are a common example. The accuracy of the gridded representation of the underlying surface is controlled by the spacing of the grid, the variability of the surface (i.e., the terrain itself), and the amount of uncertainty added during data collection and processing.

In recent years, an ever-growing array of DEM datasets have become available across a range of resolutions and spatial scales. As new data acquisition and processing strategies – such as lidar, stereo photogrammetry, and structure from motion – mature, the number and variability of features represented in a DEM will grow dramatically. In this manuscript, we refer to DEMs as high resolution when their grid spacing is low (e.g., <u>a one meter DEMone to three meters</u>), and low resolution when

25 their grid spacing is high (e.g., a $\frac{30}{10+}$ meter DEM). Across all DEM resolutions, it is important to quantify the uncertainties

in DEMs, and their potentially large impacts on metrics calculated from the DEM (Florinsky, 1998; Zhou and Liu, 2004; Oksanen and Sarjakoski, 2005; Wechsler and Kroll, 2006; Wechsler, 2007).

The estimation of topographic metrics, such as slope and aspect, is a common task across scientific disciplines. Slope and aspect provide important boundary conditions for hillslope stability analysis (e.g., Montgomery and Dietrich, 1994; Tucker

5 and Bras, 1998) and landslide monitoring (e.g., Guzzetti et al., 1999; Ayalew and Yamagishi, 2005), geomorphic transport laws (e.g., Roering et al., 1999; Dietrich et al., 2003; Pelletier, 2008; Grieve et al., 2016), hydrologic applications (e.g., Band, 1986; Zhang and Montgomery, 1994; Tarboton, 1997; Pelletier, 2010, 2013) including flood risk modeling (e.g., Ouma and Tateishi, 2014) and stream power analysis (e.g., Bookhagen and Strecker, 2012; Lague, 2014), tectono-geomorphic modeling (e.g., Whipple and Tucker, 1999; Snyder et al., 2000; Tucker and Hancock, 2010; Kirby and Whipple, 2012; Bookhagen

10 and Strecker, 2012), ecologic modeling (e.g., Franklin, 1995; Guisan and Zimmermann, 2000; Thompson et al., 2001), and vegetation analysis (e.g., Pierce et al., 2005; Kent, 2011).

A wide range of methods have been developed to accurately derive slope and aspect from elevation data using a range of approaches, each optimized for different use cases (e.g., Evans, 1980; Zevenbergen and Thorne, 1987; Skidmore, 1989; Tarboton, 1997; Dunn and Hickey, 1998; Schmidt et al., 2003). For example, the methods D-8 and D-Infinity are optimized

15 towards hydrologic flow-routing problems, particularly on DEMs of low spatial resolution (Tarboton, 1997), and the methods of Evans (1980) and Zevenbergen and Thorne (1987) include some smoothing of the underlying DEM to minimize the impacts of DEM noise. However, all of these methods contain some intrinsic error due to truncation error (TE) – the deviation of the gridded sample from the continuous original surface (Figure 1). The TE describes the error made by truncating an infinite sum and approximating it by a finite sum. It often includes a discretization error, which arises from taking a finite number of steps

20

to approximate an continuous surface. Several authors have explored the theoretical limitations of estimations of slope and aspect calculations on gridded surfaces (e.g., Heuvelink et al., 1989; Hunter and Goodchild, 1997; Florinsky, 1998; Abarbanel et al., 2000; Zhou and Liu, 2004); in general, TE can be related directly to the grid-sampling – more tightly sampled grids will deviate less from the original surface.



Figure 1. (A) Slope and (B) aspect distribution differences from analytical solutions of slope and aspect on a Gaussian Hill, on one-degree bins. None of the methods perfectly match the analytical solution, with slightly different offset magnitudes. In particular, each method produces aspect errors at the cardinal directions.

In addition to TE, real-world DEMs will have some degree of measurement uncertainty. The magnitude of that uncertainty varies across data collection methods and data post-processing, but also depends on the terrain itself and is often difficult to estimate (Heuvelink et al., 1989; Lee et al., 1992; Bolstad and Stowe, 1994; Florinsky, 1998; Fisher, 1999; Smith and Sandwell, 2003; Farr et al., 2007; Wechsler and Kroll, 2006; Wechsler, 2007; Mukul et al., 2017; Purinton and Bookhagen, 2017, 2018; Wessel et al., 2018). Any uncertainty in elevation estimates will propagate into the calculated topographic metrics.

5

The impacts of TE and DEM uncertainty on slope and aspect estimations can be quantified for any gridded data. We first use synthetic data with known properties as a control to define generalized functions applicable to any DEM, and to develop a quality metric for slope and aspect calculations. Following this analysis, we turn to a high-resolution lidar dataset covering complex terrain to study the spatial structure of uncertainty in topographic metrics propagating from both TE and DEM

10 uncertainty. This novel approach allows us to identify the optimal grid resolution that minimizes the error bounds from the

combination of TE and PEU, and to analyze the implications of using sub-optimal DEM resolutions for calculating slope and aspect.

2 Data and Methods

In this analysis, we demonstrate the limitations of calculating slope and aspect using synthetic data surfaces. These surfaces serve as a valuable control dataset, as the precise analytical values for slope and aspect at each grid cell are known. We further add normally distributed random noise with a known mean and standard deviation to our synthetic data to investigate the impacts of DEM uncertainty on topographic metrics. Following the discussion of synthetic data, we apply the same methods to high-resolution lidar data interpolated to DEMs with varying spatial resolutions.

2.1 Synthetic Data

10 We generate regular $n \times n$ grids of size n=11, 101, 1001 describing a Gaussian hill with a maximum height of one, with elevations defined as $z = e^{(-x^2-y^2)}$ (Figure 2). A second surface describing a sphere is included in the Supplement. It is important to note that the horizontal and vertical units for the synthetic data are arbitrary – the grid cell spacings generated by using differently sized grids are an expression of the width-to-height ratio of the surface. The python functions used to generate our synthetic surfaces can be found on GitHub: https://github.com/UP-RS-ESP/TopoMetricUncertainty.



Figure 2. Gaussian hill elevations at n=11, 101, and 1001. As grid sizes increase, a smoother surface is generated. Note that the horizontal and vertical units are arbitrary and that the grid-cell spacings are an expression of the width-to-height ratio of the surface. Cross sections of the shapes at all grid sizes can be seen in Supplemental Figure 1.

15 2.2 Topographic Metrics

In this study, we focus on the topographic metrics slope S(x,y) and aspect A(x,y) which we define as,

$$S(x,y) = \frac{180^{\circ}}{\pi} \times \arctan \sqrt{\left(\frac{\partial z}{\partial x}\right)^2 + \left(\frac{\partial z}{\partial y}\right)^2} \tag{1}$$

and

$$A(x,y) = \frac{180^{\circ}}{\pi} \times \arctan\left(\frac{\partial z}{\partial y} \times \frac{\partial x}{\partial z}\right) + 180^{\circ}$$
(2)

with x and y being the spatial coordinates. Key in calculating slope and aspect is the calculation of the directional derivatives $\frac{\partial z}{\partial x}$ and $\frac{\partial z}{\partial y}$.

- 5 There exist a wide range of methods for calculating the directional derivatives on gridded data that broadly fall into three classes: (1) four-neighborhood methods, (2) eight-neighborhood methods, and (3) steepest descent methods (e.g. Evans, 1980; Zevenbergen and Thorne, 1987; Skidmore, 1989; Tarboton, 1997; Dunn and Hickey, 1998; Schmidt et al., 2003; Zhou and Liu, 2004; Oksanen and Sarjakoski, 2005). In our analysis, we use the standard second-order finite difference approximation as implemented in Python Numpy (Fornberg, 1988; Durran, 1999), which is a four-neighborhood method. We tested additional
- 10 methods using eight-neighborhoods (e.g., singular-value decomposition plane fitting and the method of Evans (1980)) which provide some underlying DEM-smoothing and are well-suited to noisy DEM data and using steepest descent (e.g., D-8 and D-Infinity (Tarboton, 1997)), which identify the steepest slope that water would take and are optimized for hydrologic use cases. However, these methods do not necessarily provide the most representative slope of the terrain, and show distinct differences from the analytical solutions of slope and aspect (cf. Supplemental Figures 2 and 3). We choose to use the simple
- 15 four-neighbor method in our analysis as it results in the lowest relative error when compared with the analytical solution for slope and aspect (Supplemental Figure 2) and does not include any smoothing of the underlying DEM.

3 Sources of Uncertainty in Topographic Metrics

Biases in topographic metrics can be determined both numerically, by comparing the results of calculations to known values, and analytically, by deriving the impacts of both TE and DEM uncertainty on topographic metrics.

20 3.1 Truncation Error

We derive the TE from the formulas of topographic metrics by propagating the uncertainty of the second-order finite difference approximation for the directional derivatives $\frac{\partial z}{\partial y}$ and $\frac{\partial z}{\partial y}$. Neglecting rounding errors, we assume the uncertainty ε of the second-order finite difference to be bounded by

$$\left| \frac{\partial z}{\partial a} - \frac{z(a+h) - z(a-h)}{2h} \right| \lesssim \frac{h^2}{6} \left| \frac{\partial^3 z}{\partial a^3} \right| = \varepsilon_a \tag{3}$$

25 where a represents either x or y, and h is the grid spacing.

The considered topographic metrics slope S(x,y) and aspect A(x,y) depend on both directional derivatives $\frac{\partial z}{\partial x}$ and $\frac{\partial z}{\partial y}$. As the corresponding uncertainties ε_x and ε_y are not independent, propagated TE T for slope (T_S) and aspect (T_A) are given by

$$|T_{S}(x,y)| = \sqrt{\left(\partial_{\frac{\partial z}{\partial x}}S\right)^{2}\varepsilon_{x}^{2} + \left(\partial_{\frac{\partial z}{\partial y}}S\right)^{2}\varepsilon_{y}^{2} + 2\left(\partial_{\frac{\partial z}{\partial x}}S\right)\left(\partial_{\frac{\partial z}{\partial y}}S\right)\varepsilon_{x}\varepsilon_{y}}$$
(4)

$$|T_A(x,y)| = \sqrt{\left(\partial_{\frac{\partial z}{\partial x}}A\right)^2} \varepsilon_x^2 + \left(\partial_{\frac{\partial z}{\partial y}}A\right)^2 \varepsilon_y^2 + 2\left(\partial_{\frac{\partial z}{\partial x}}A\right) \left(\partial_{\frac{\partial z}{\partial y}}A\right) \varepsilon_x \varepsilon_y \tag{5}$$

5 These can be more explicitly expressed using Equation (3) as

$$|T_S(x,y)| = \frac{180^{\circ}}{\pi} \times \sqrt{\frac{\left(\frac{\partial z}{\partial x}\right)^2 \varepsilon_x^2 + \left(\frac{\partial z}{\partial y}\right)^2 \varepsilon_y^2 + 2\frac{\partial z}{\partial x}\frac{\partial z}{\partial y}\varepsilon_x\varepsilon_y}{\left(\frac{\partial z}{\partial x} + \frac{\partial z}{\partial y}\right)\left(1 + \frac{\partial z}{\partial x} + \frac{\partial z}{\partial y}\right)^2}}$$
(6)

$$|T_A(x,y)| = \frac{180^{\circ}}{\pi} \times \sqrt{\frac{\left(\frac{\partial z}{\partial x}\right)^2 \varepsilon_x^2 + \left(\frac{\partial z}{\partial y}\right)^2 \varepsilon_y^2 - 2\frac{\partial z}{\partial x}\frac{\partial z}{\partial y}\varepsilon_x\varepsilon_y}{\left(\frac{\partial z}{\partial x}\right)^4 \left(1 + \frac{\partial z}{\partial x} + \frac{\partial z}{\partial y}\right)^2}}$$
(7)

The sign of the TE is derived from symmetry considerations in the following way:

$$\operatorname{sign}\left(T_{S}\right) = \operatorname{sign}\left(\operatorname{arctan}\sqrt{\left(\frac{\partial z}{\partial x} + \varepsilon_{x}\right)^{2} + \left(\frac{\partial z}{\partial y} + \epsilon_{y}\right)^{2}} - \operatorname{arctan}\sqrt{\left(\frac{\partial z}{\partial x} - \varepsilon_{x}\right)^{2} + \left(\frac{\partial z}{\partial y} - \epsilon_{y}\right)^{2}}\right)$$

$$(8)$$

10 and

$$\operatorname{sign}\left(T_{A}\right) = \operatorname{sign}\left(\arctan\frac{\frac{\partial z}{\partial y} + \varepsilon_{y}}{\frac{\partial z}{\partial x} + \epsilon_{x}} - \arctan\frac{\frac{\partial z}{\partial y} - \varepsilon_{y}}{\frac{\partial z}{\partial x} - \epsilon_{x}}\right) \tag{9}$$

Equations 6-9 allow us to calculate the magnitude of the TE at each point (x, y) on our synthetic surfaces (Figure 3).



Figure 3. Gaussian hill slope (A, C, E) and aspect (B, D, F) errors from the analytical TE. All grid sizes show clear spatial patterns in slope and aspect errors. Offset magnitudes scale with grid size. Errors on the n=1001 grid (bottom row: E, F) are generally two orders of magnitude smaller than those for the n=101 grid (middle row: C, D). Colors scaled from 5th to 95th percentiles of error magnitudes.

As can be seen in Figure 3, the magnitude of the slope and aspect error decreases with increasing n. This implies that as more tightly sampled models of a surface are used, the accuracy of slope and aspect estimations increases. This follows the work of Abarbanel et al. (2000), which shows that finite-difference derivative estimations have error magnitudes that scale with the inverse of the grid spacing for evenly spaced grids. However, even with increasingly accurate surface models, there remains some TE simply due to the fact that a smooth surface cannot be perfectly represented by gridded data. At very fine scales, computer rounding will also lead to errors in slope and aspect calculations. In this study, however, we do not use fine enough grids for this to impact our error estimates.

As the precise mathematical definitions of our synthetic surfaces are known, we can analytically derive their slope and aspect values at each point and compare those results to numerical calculations (see Supplemental Figure 4). In the absence of DEM uncertainty, the difference between analytically- and numerically-derived topographic metrics will be dominated by the TE from the second-order finite difference approximation. Additionally, modifying the absolute magnitude of the shape

10

5

heights (e.g., a maximum height of 100 instead of one), does not modify the absolute magnitudes of slope and aspect TE (see Supplemental Figure 5).

While the magnitudes of the errors are small, they have important impacts on distributions drawn from larger grids (e.g., entire surfaces, see Figure 4). In the case of aspect, the alternating spatial pattern of its TE pushes aspect values towards the

5 cardinal directions – leading to distinct positive and negative spikes in the aspect distribution. This error is not confined only to the cardinal directions – there exists symmetry across the aspect distribution that is easiest to see with very fine binning (see Supplemental Figure 6).



Figure 4. (A) Density histogram of synthetic data (n=1001) using the four-neighbor method, on one-degree bins. Spikes clearly occur around the cardinal directions. The symmetry across the aspect distributions can be further explored in the Supplemental Figure 5 with very fine binning. (B) Conceptual diagram of aspect errors. Aspect values are pushed towards and away from certain angles (0/45/90/etc).

Slope and aspect calculations have very differently different spatial error patterns (see Figure 3). However, as with aspect errors, slope errors depend on the orientation of the grid despite the radial symmetry of the surface. This is easiest to see in the slope difference map of the Gaussian hill, where error magnitudes are not simply scaled by slope (see Figure 3E).

3.2 **DEM Uncertainty**

10

Elevation models are never perfect – there are always errors and uncertainties due to data collection or processing. The uncertainty in calculated topographic metrics can be constrained by propagating DEM uncertainties into their calculations (e.g. Heuvelink et al., 1989; Hunter and Goodchild, 1997; Zhou and Liu, 2004; Oksanen and Sarjakoski, 2005); we refer to the un-

certainty introduced into slope and aspect calculations from elevation uncertainty as propagated elevation uncertainty (PEU). 15 For our synthetic data, we assume the simplistic but straight forward error model of spatially uncorrelated white noise. We define noise to be normally distributed and consider two cases: (1) homogeneous white noise, i.e., noise drawn from one unique normal distribution $\mathcal{N}(\mu = 0, \sigma^2 = const)$, and (2) slope dependent, spatially varying white noise, i.e., noise drawn from a family of normal distributions $\mathcal{N}(\mu = 0, \sigma_S^2)$. Since for each grid cell noise is drawn independently, the PEU for slope (E_S) 20 and aspect (E_A) is given by

$$E_{S} = \sqrt{\sum_{i \in \{x-h,x+h\}} \sum_{j \in \{y-h,y+h\}} \left(\frac{\partial S}{\partial z_{ij}}\right)^{2} \sigma_{z_{ij}}^{2}}$$

$$E_{A} = \sqrt{\sum_{i \in \{x-h,x+h\}} \sum_{j \in \{y-h,y+h\}} \left(\frac{\partial A}{\partial z_{ij}}\right)^{2} \sigma_{z_{ij}}^{2}}$$

$$(10)$$

As before, this can be expressed more explicitly using Equation (3) as

10

$$E_{S} = \frac{90^{\circ}}{h\pi} \sqrt{\frac{\left(\frac{\partial z}{\partial x}\right)^{2} \left(\sigma_{z_{x+h,y}}^{2} + \sigma_{z_{x-h,y}}^{2}\right) + \left(\frac{\partial z}{\partial y}\right)^{2} \left(\sigma_{z_{x,y+h}}^{2} + \sigma_{z_{x,y-h}}^{2}\right)}{\left(\left(\frac{\partial z}{\partial x}\right)^{2} + \left(\frac{\partial z}{\partial y}\right)^{2}\right) \left(1 + \left(\frac{\partial z}{\partial x}\right)^{2} + \left(\frac{\partial z}{\partial y}\right)^{2}\right)^{2}}}$$
(12)

5
$$E_{A} = \frac{90^{\circ}}{h\pi} \sqrt{\frac{\left(\frac{\partial z \partial x}{\partial y \partial z}\right)^{2} \left(\sigma_{z_{x+h,y}}^{2} + \sigma_{z_{x-h,y}}^{2}\right) + \sigma_{z_{x,y+h}}^{2} + \sigma_{z_{x,y-h}}^{2}}{\left(\frac{\partial z}{\partial x}\right)^{2} \left(1 + \left(\frac{\partial z \partial x}{\partial y \partial z}\right)^{2}\right)^{2}}}$$
(13)

As with TE, PEU introduces distinctive spatial patterns into the slope and aspect estimates (Figure 5). Both slope and aspect uncertainties are higher on shallow slopes, as has been shown in previous work (Florinsky, 1998; Zhou and Liu, 2004). On flat or nearly flat terrain, the elevation uncertainty will more strongly impact the estimated partial derivatives, and thus lead to erroneous slope and aspect estimates. It is also important to note that aspect varies between [0, 360) and slope only between [0, 90), which is why we expect standard deviations to be different by a factor of four (see Figure 5).



Figure 5. [FIGURE UPDATED] Gaussian hill (n=101) slope and aspect standard deviations for spatially invariant noise (std= $1e^{-4}$), derived from elevation uncertainty propagation (Equations 12-13). Aspect has higher standard deviations than slope, as aspect varies between [0, 360) and slope only between [0, 90). This is evident especially on flat terrain (e.g., the edges of the Gaussian hill).

When we compare our analytically-derived topographic metric uncertainty patterns (Figure 5) to those generated from actual random noise – using an ensemble of 10,000 synthetic surfaces, each generated with normally distributed noise – the spatial patterns and magnitudes are nearly identical between the two methods (cf. Supplemental Figure 7).

4 Optimal Grid Spacing

Both TE and PEU yield distinct spatial patterns, implying that the error and uncertainty in topographic metrics will vary throughout a DEM. Using both the TE and PEU magnitudes, we can examine whether TE or PEU is dominant at an arbitrary grid spacing, given a known DEM uncertainty (Figure 6).



Figure 6. TE and PEU magnitudes for two noise levels, (A) $1e^{-4}$ and (B) $1e^{-6}$, compared to grid spacing. Aspect plotted in black, slope plotted in gray. Solid lines for PEU, dashed lines for TE. TE decreases with decreasing grid spacing, while PEU increases as the noise standard deviation relative to grid spacing increases.

As can be seen in Figure 6, TE will approach zero for sufficiently small grid spacings, while PEU will rise as the amount of noise relative to the grid spacing increases. Using both TE and PEU magnitudes across grid spacings, an optimal grid spacing for a given noise level which minimizes their combined influence can be chosen. Note that we do not assume that the quality of the data is maximized when the combination of TE and PEU is minimized, but that the error bounds on topographic metric calculations are minimized. Thus, the optimal grid spacing is preferred for calculating slopes and aspects for use in applications where uncertainty across the entire grid should be minimized.

4.1 Metric Quality Ratios

The trade off between TE and PEU can also be thought of as a quality ratio. Simply put, the impact of DEM uncertainty on topographic metrics is modulated by the grid spacing - i.e., 1 cm of vertical noise on a 10 m grid will have a very different impact than 1 cm of vertical noise on a 1 cm grid. As both TE and PEU have distinct spatial patterns, a combined Quality Ratio

(QR) can capture a holistic view of the overlapping influence of TE and PEU. The QR can be defined from the combination of the TE and PEU as:

$$QR = \left(\frac{1}{1 + (m \times |TE|)}\right) \times \left(\frac{1}{1 + (m \times |PEU|)}\right) \tag{14}$$

5

where m is a normalization factor which accounts for the four-fold difference in the range of possible values between slope and aspect. On a surface without noise, the QR will approach one as grid spacing and TE approach zero. The influence of TE and PEU on calculated QRs can be seen by comparing the same synthetic grid with two noise levels (see Supplemental Figure 8). High noise levels reveal similar spatial patterns to those seen in Figure 5, while low noise levels show the influence of TE (cf. Figure 3).



Figure 7. Gaussian hill slope (A, top) and aspect (B, bottom) QRs vs grid spacings, for a range of noise levels $(1e^{-2} \text{ to } 1e^{-6})$. 25th-75th percentile QRs shaded for each noise level. Optimal grid spacings (maximum QR) for each noise level are marked with vertical lines. Slope calculations result in lower optimal grid spacings compared to aspect. Higher noise levels lead to higher optimal grid spacings for both slope and aspect calculations. Note that the purple and yellow lines in panel B have the same optimal grid spacing, and thus only the yellow line is visible.

The QR can also used as a normalized metric to compare DEMs across grid spacings and noise levels (Figure 7, and Supplemental Figure 9). Each noise level/grid spacing pair has a point at which the QR of the DEM is maximized. This point represents the optimal trade off between TE and PEU over the entire grid.

As can be seen in Figure 7, as noise levels increase, the optimal grid spacing increases, and the QR of that optimal spacing
decreases. For very noisy datasets (purple and yellow lines, Figure 7), very large grid cell spacings – i.e., aggregation – can help reduce the combined influence of TE and PEU on slope and aspect estimates.

There are distinct differences between the optimal slope and aspect grid spacings for the same dataset. For any given noise level, the optimal grid spacing to calculate aspect is higher than that for slope. The difference in optimal grid spacing is driven by the relative magnitudes of the PEU between slope and aspect calculations – the PEU for aspect calculations is always higher than that for slope due to differences in the formulas for slope and aspect (see Figure 6 and Equations 12-13).

10

4.2 Heterogeneous Noise

In practice, datasets will not have homogeneous noise across grid spacings – coarser parameterizations of a surface will include more uncertainty as fine-scale features are aggregated into single pixels. Additionally, noise in real-world datasets is influenced by non-uniform landscape features such as slope, aspect, terrain relief, and vegetation cover (e.g., Kraus and Pfeifer, 1998;

- 15 Kyriakidis et al., 1999; Holmes et al., 2000; Smith and Sandwell, 2003; Carlisle, 2005; Oksanen and Sarjakoski, 2006; Rodriguez et al., 2006; Shortridge and Messina, 2011; Purinton and Bookhagen, 2017, 2018). While several authors (e.g., Hunter and Goodchild, 1997; Zhang and Goodchild, 2002; Fisher and Tate, 2006) have examined complex error models in real data, we choose to use a simplistic error model based on terrain slope – e.g., higher slopes have higher noise levels – to look at the first-order impacts of heterogeneous noise on the calculation of topographic metrics.
- 20

When we compare the heterogeneous noise result to the analysis shown in Figure 7 (cf. Supplemental Figure 10), the results are very similar, albeit with higher optimal grid spacings. We can also compare the optimal grid spacings for homogeneous and heterogeneous noise directly for a set of noise levels from $1e^{-8}$ to $1e^{-2}$ (Figure 8).

As can be seen from Figure 8, slope can be calculated on a smaller grid spacing with slope-biased noise, while aspect should be calculated with a larger grid spacing. The divergence in the optimal grid spacings between homogeneous and heterogeneous noise are driven by the differences in the influence of terrain slope on slope and aspect QRs. While both slope and aspect calculations have similar grid-spacing dependent TE magnitudes, the differences in the relative magnitudes of the PEU lead to different responses to the distribution of noise on the DEM (see Figure 6). The simplistic slope-dependent error model used here is unlikely to translate to a real-world setting; however, it is clear that the spatial distribution of noise on the DEM influences the choice of optimal grid spacing for both slope and aspect calculations.

25



Figure 8. Optimal grid spacing for slope (A) and aspect (B) across a range of noise levels $(1e^{-2} \text{ to } 1e^{-8})$. Points in the upper triangle have smaller optimal grid spacings with homogeneous noise. Points in the lower triangle have smaller optimal grid spacings with heterogeneous noise. Points on the dashed line have the same optimal grid spacings regardless of the noise distribution. Heterogeneous noise leads to smaller slope grid spacings but larger aspect spacings for the same average noise level.

5 Impacts of Noise on Topographic Distributions

 $1e^{-3}$, $1e^{-4}$). We then bin the ensemble data into one-degree slope and aspect bins.

As can be seen in Figures 5-7, the introduction of noise has non-trivial impacts on slope and aspect calculations. As was evident in Figures 1 and 4, TE can significantly modify the ensemble distributions of topographic metrics. To examine the impact of both TE and PEU on the frequency distributions of slope and aspect, we generate 1,000 member ensembles of slope and aspect for each combination of two different grid sizes (n=101, 1001) and three different noise levels (homogeneous noise, std=1 e^{-2} ,

5



Figure 9. [FIGURE UPDATED] Aspect Slope (A, C) and Slope Aspect (B, D) probability distributions (one-degree bins) for a Gaussian hill with homogeneous noise at variable levels (std=0, $1e^{-2}$, $1e^{-3}$, $1e^{-4}$) for n=101 (A, B) and n=1001 (C, D). The introduction of small levels of noise washes the spikes out of the aspect distribution. Slope distributions are steeper with the introduction of higher noise levels. Similar density functions are generated at similar QRs, despite differences in absolute noise levels.

When homogeneous noise is added to synthetic surfaces, the large spikes in aspect distributions related to points moving in and out of cardinal directions (e.g., at 45/90/135 degrees, see Figure 4) are smoothed out into neighboring bins. However, this does not imply that the calculated aspects are 'better', just that they have a more even distribution - the PEU overprints the TE as seen in Figure 3. This can clearly be seen in Supplemental Figure 11, which shows the impact of noise on slope and aspect grids.

Slope distributions are systematically shifted towards higher values as more noise is added to the synthetic surfaces. This effect is due to the presence of more large 'steps' in the synthetic data, where smooth transitions across elevation gradients are replaced with more stepped hills and dips. Across noise levels and grid sizes, distributions with similar QRs maintain the same general shape. This indicates that the QR captures how 'wrong' the aggregate distribution is when compared to the original synthetic surface.

```
10
```

5

If different window sizes are used to calculate slope and aspect (e.g., 5x5 and 7x7), slope estimates are higher and the aspect 'spikes' at cardinal directions are slightly diminished. Larger window sizes somewhat – but not completely – remove the impacts of noise on aspect distributions. They do not, however, help minimize differences in the slope distributions (see Supplement Figure 12).

6 Case Study: Multi-Resolution Lidar on Santa Cruz Island

6.1 Dataset Description

 ~ 10 points/m².

5

The Santa Cruz Island (SCI, see Figure 10) is part of the Channel Islands off the coast of south-central California. It is a tectonically active island (Neely et al., 2017) with steep topography and pronounced erosion (Perroy et al., 2010, 2012), diverse lithologic cover (Dibblee, 2001), and moderate and species-rich vegetation cover (Baguskas et al., 2014). The lidar point cloud data used to derive DEMs at a range of spatial resolutions were obtained from the 2010 US Geological Survey Channel Islands Lidar Collection (OpenTopography, 2012). The point cloud has an average point ground-classified density of



Figure 10. Topographic setting of Santa Cruz Island (SCI), showing elevation (A), slope (B) and aspect (C) derived from a 1-m DEM and calculated from a total of 2.3×10^9 ground-classified lidar points. The SCI covers a wide range of terrain types, slope regimes, and all aspect directions. Black polygon (southwest SCI) indicates the Pozo catchment shown in Figure 11. For a canopy height model, we refer to Supplemental Figure 13.

6.2 Deriving Elevations and Uncertainties from Point Cloud Data

Using LAStools (LAStools, 2017), we use a triangulated irregular network approach to derive average point cloud elevations at each grid cell center, for each of our chosen grid resolutions (1-30 meters, in one meter steps, and 90 meters). We have tested simpler interpolation schemes, including the lowest elevation and the central location for each grid cell, but the resulting

- 5 uncertainties in topographic metrics remain the same. Thus, we decided to use the more commonly applied triangulated irregular network approach. In addition to producing DEMs, we generate pixel-wise standard deviations estimated from the point cloud. That is, we determined the standard deviation of all ground-classified lidar points falling into each grid cell for each grid resolution. While vegetation cover may impact ground-classification results, our calculations are based on ground-classified points only. Because of the high point-cloud density, this standard deviation metric should reflect terrain variability and not
- 10 vegetation cover. This measure serves as a DEM uncertainty and is highly spatially heterogeneous. Elevation and standard deviation maps for additional grid resolutions can be found in the Supplement (Supplemental Figures 14-16). An island-wide canopy-height model can be found in Supplemental Figure 13.

6.3 Mapping Uncertainty on SCI

Using our standard deviation grids, we can then calculate both TE and PEU on SCI (see Supplemental Figure 17). Using these
two grids as inputs, we can also derive the QR across the entire SCI (Figure 11). Note that maximal QRs are low when compared to the theoretical models shown in Figures 7 and 9; this is due to both the much higher inherent noise in the real-world data, and to the more complex terrain represented by the lidar data.



Figure 11. Selected metrics for the Pozo catchment in the southwestern part of SCI, calculated on the optimal grid resolution for this catchment (three meter grid). (A) Elevation, (B) lidar point density, (C) elevation standard deviation, (D) slope quality ratio (see Equation 14). The aspect quality ratio is shown in Supplemental Figure 18. A comparison of the elevation standard deviation and the lidar canopy height model is shown in Supplemental Figure 19.

6.4 Identification of Optimal Grid Resolution

Using our pixel-wise standard deviations – and derived QRs – at each grid resolution, we can determine the island-wide optimal grid resolution for the calculation of topographic metrics which minimizes the combined influence of TE and PEU on our lidar dataset.

- 5 Unlike the synthetic data examined in Figure 7, the optimal grid resolution for aspect calculations is the same as that for slope. This is due to the distribution of both elevations and elevation uncertainties in the SCI DEM, and the different responses of slope and aspect calculations to the diverse terrain on SCI. Whole-island median TE, PEU, and QR can be found in Supplemental Table 1 for grid spacings resolutions from one to ten meters. While four meters is the calculated optimal grid resolution, the QR peak is quite flat (see Figure 12), implying that both three-meter and five-meter DEMs will yield slope and
- 10





Figure 12. Median Quality Ratios (QRs) for all slopes, low slopes (<10) and high slopes (>30) across grid resolutions (1-30m). There is a clear trend where low slopes have better slope QRs, but worse aspect QRs. The optimal grid resolution for SCI is four meters for both slope and aspect. For inter-quartile ranges on the QRs, see Supplemental Figure 20.

It should be noted that a four-meter optimal grid resolution is likely too large for many applications, particularly those interested in micro-topography or other small-scale features. In those cases, a higher-resolution DEM should be used with caution – PEU will continue to grow as grid spacing shrinksresolution increases, and the rate of that increase will accelerate (see Figure 6). This effect will occur even if the DEM uncertainty decreases at smaller scales simply due to the larger impacts

of PEU at very small grid spacingshigh grid resolutions. This means that the uncertainty bounds on slope and aspect estimates 5 on very high resolution DEMs will increase quickly, which may limit some analyses. It is important to examine whether the data are precise enough to effectively resolve the features of interest. For high-resolution analyses, very high quality DEMs are required.

In this analysis of the airborne lidar dataset from SCI, we find that a four-meter DEM resolution minimizes the combined influence of TE and PEU. Slope and aspect analyses performed at this grid resolution have the smallest error bounds, and thus provide the most reliable data for analysis of topographic metrics over the entire island.

While a single, whole-island, grid resolution is useful in some applications, it is clear from Figure 11 that there are large spatial variations in the DEM uncertainty and the resulting QR, and hence in the optimal grid resolution. We can extend our method of identifying the optimal grid resolution on a catchment-by-catchment basis (Figure 13, map view in Supplemental Figure 21).

15

10

There exist large spatial variations in the optimal grid resolution across SCI, driven by differences in terrain slope and DEM quality. When these differences are compared to median catchment slope and median catchment standard deviation, a clear pattern emerges (Figure 13). While there remains significant scatter in the data, catchments with high median slopes tend to



Figure 13. Optimal grid resolution for minimizing error bounds on slope and aspect calculations across SCI compared to catchment median slope. Point sizes are scaled to catchment size, from 0.1 to $34 \frac{\text{sq}}{\text{sq}} \text{km}^2$. Dashed lines show the 25th percentile to 75th percentile of optimal grid resolution, colored by the standard deviation of that point. Stars show the whole-island optimal resolution and median slope. There exists a clear trend where lower median slopes lead to lower optimal grid resolutions. Standard deviations also tend to be smaller in these catchments, due to higher DEM fidelity over flat terrain. Catchments with high-low (>10 meter) optimal grid spacings resolutions are small and have complex topography. For a map view of these results, we refer to Supplemental Figure 21.

have both higher standard deviations and lower optimal grid resolutions. The data is bimodal, with the majority (83% for slope, 95% for aspect) of catchments having optimal resolutions below ten meters.

It is worth noting that the vast majority of the catchments with optimal slopes and aspect slope and aspect resolutions above ten meters are small catchments concentrated on the northwestern edge of SCI (see Supplemental Figure 21). These catchments have two unique topographic features which contribute to the high optimal grid sizes. (1) They have two distinct slope regimes: one steep hill of nearly constant slope, followed by one flatter residual marine terrace with a different constant slope. (2) The

- 5 catchments drain into steep, deeply incised, cliffs. Interestingly, neither removing the steep cliffs (which have high elevation uncertainty), nor aggregating several small catchments into one larger analysis unit (to improve the statistical reliability of the median QR) result in smaller optimal grid spacingshigher optimal grid resolutions. We posit that the high optimal grid spacings low optimal grid resolutions are a product of the unique two-stage topography in this region. However, an in-depth analysis of the specific factors which drive the optimal terrain resolution in each individual zone is outside of the scope of this manuscript.
- 10 In applying this method of deriving optimal grid spacingsresolution, it is important to take into account the possibility of large differences in the optimal grid spacing resolution over relatively small spatial scales.

6.5 Island-Wide Slope and Aspect Distributions

As has been shown in Figures 7 and 12, there is clearly an optimal spatial resolution for the calculation of slope and aspect on our SCI lidar dataset. Furthermore, in Figure 9, it was shown that changes in QR can have a substantial impact on the slope and aspect distributions of a synthetic surface. This analysis can be extended to the SCI lidar data at a range of spatial scales



15



Figure 14. (A) Slope and (B) aspect differences across SCI DEMs, with QR calculated using SCI DEM elevation standard deviations (see Figure 11 and Supplemental Figures 13-15). Optimal slope and aspect distributions plotted in black. (C) Quantile-quantile plot showing difference between the entire SCI slope distribution vs the 'optimal' (four meter) resolution. We observe a clear pattern in slope distributions where resolutions below the optimal resolution tend to overestimate slope, those below tend to underestimate slope.

There are clear differences in the slope and aspect distributions with increasingly poor QRs. This effect can also be seen in quantile-quantile plots of the entire SCI slope distribution when compared to the optimal grid resolution (see Figure 14C). Grid resolutions higher than the optimal result in slope distributions that are dominated by higher slopes, while lower resolutions tend towards lower slopes. This effect can be seen even when the grid resolution is only slightly removed from the optimal

5

resolution (Supplemental Figure 22). Notably, grid resolutions close to the optimal (e.g., three meters and five meters), have QRs and slope distributions that are very similar to the optimal four meter distribution.

As a final test of grid-resolution dependence, we resampled several grids to nominally match the optimal grid resolution – in this case we chose three meters for the Pozo catchment (see Figure 10, Supplemental Figure 23) as the reference distribution. As can be seen in Figure 15A, there are differences between test (one to five meter) resolutions and the reference three meter

- histogram. When the test datasets are resampled to the three meter reference resolution (using bilinear resampling (Figure 10 15B) and nearest neighbor resampling (Figure 15C), the histograms generally do not converge to the reference three meter distribution(Figure 15B). Slope. The exception to this is when the one-meter data are resampled with a nearest neighbor approach, they converge to the three meter distribution. We attribute this effect to the lidar-gridding method - the three-meter data is drawn from the same neighborhood as the nine one-meter neighborhoods which are used for the one-meter gridding.
- In general, slope distributions from resampled data should be used with caution; simply resampling elevation data to the 15 optimal grid resolution before calculating slope will not yield does not guarantee better results - the DEM has to be created from the ungridded point data to fully take advantage of optimal gridding for slope calculations.



Figure 15. [FIGURE UPDATED] (A) Divergence of higher and lower grid-resolution slope distributions from that at the optimal resolution for the Pozo catchment (see Figure 10). Excepting the one meter histogram, the differences between resolutions are small. (B) Slope Right panels show slope distributions taken from one, two, four, and five meter data resampled to three meter resolution using (B) bilinear resampling and (C) nearest neighbor resampling. The resampled data distributions do not converge on the reference three meter distribution, excepting the one-meter data resampled with a nearest neighbor approach.

7 Conclusions

This study presents a detailed accounting of uncertainties and errors in the topographic metrics slope and aspect derived from both truncation errors and uncertainty in the underlying source digital elevation model (DEM). We first develop our analysis on synthetic data, which acts as a control dataset. We then extend our methodology onto a high point-density lidar dataset, which

5 allows us to compare the relative impacts of gridding truncation errors and propagated elevation uncertainty on the calculation of topographic metrics.

From the analysis of both synthetic and real-world data, we identify the following key points: (1) the relative impact of truncation error and propagated elevation uncertainty can be captured in a single quality metric, which we coin the Quality Ratio. This metric can be used to compare the accuracy of topographic metrics across DEM spatial resolutions and uncertainty

- 10 distributions. (2) There exists an optimal grid resolution at which to calculate the topographic metrics slope and aspect for a given dataset that minimizes the total impact of both truncation error and propagated elevation uncertainty; the distribution of DEM uncertainties leads to spatial variation in the optimal grid resolutions at which to calculate slope and aspect. For the Santa Cruz Island in southern California, we find an optimal grid resolution of four meters, with island-average slope (aspect) errors of 0.25° (0.75°) for truncation error, and 5° (12.5°) for propagated elevation uncertainty. (3) Topographic metrics calculated at
- sub-optimal grid resolutions will have potentially large errors in their slope and aspect distributions. Resampling grids to the optimal resolution does not completely ameliorate these issues; it is important to generate the DEM at the optimal resolution from the underlying lidar dataset. (4) Slope and aspect calculations at high DEM resolutions (><3 meters) are significantly impacted by the nonlinear relationship between grid spacing and propagated elevation uncertainty. A DEM with very low uncertainties is required to support robust analysis of fine-scale topography.
- 20 Given that grid-resolution-driven effects on regional slope and aspect distributions could have significant impacts on the interpretation of landscape morphology, we recommend that region-specific optimal DEM resolutions be determined before the calculation of topographic metrics.

Code and data availability. All codes and data for reproducing the results can be found in on GitHub (https://github.com/UP-RS-ESP/TopoMetricUncertainty).

25 Author contributions. T.S. led the development and writing of the MS, as well as the primary data analysis. A.R. contributed to the development of the methods and developed most of the python codes. B.B. contributed to the development of the methods and processed the lidar data.

Competing interests. The authors declare no competing financial interests.

Acknowledgements. The State of Brandenburg (Germany) through the Ministry of Science and Education and the NEXUS project supported

30 T.S. for part of this study (grant to. B.B.). The authors thank Fiona Clubb and Ben Purinton for comments on an earlier version of the manuscript.

References

- Abarbanel, S., Ditkowski, A., and Gustafsson, B.: On error bounds of finite difference approximations to partial differential equations—temporal behavior and rate of convergence, Journal of Scientific Computing, 15, 79–116, 2000.
- Ayalew, L. and Yamagishi, H.: The application of GIS-based logistic regression for landslide susceptibility mapping in the Kakuda-Yahiko
 Mountains, Central Japan, Geomorphology, 65, 15–31, 2005.
- Baguskas, S. A., Peterson, S. H., Bookhagen, B., and Still, C. J.: Evaluating spatial patterns of drought-induced tree mortality in a coastal California pine forest, Forest Ecology and Management, 315, 43–53, 2014.

Band, L. E.: Topographic partition of watersheds with digital elevation models, Water resources research, 22, 15-24, 1986.

Bolstad, P. V. and Stowe, T.: An evaluation of DEM accuracy: elevation, slope, and aspect, Photogrammetric Engineering & Remote Sensing,
60, 7327–7332, 1994.

Bookhagen, B. and Strecker, M. R.: Spatiotemporal trends in erosion rates across a pronounced rainfall gradient: Examples from the southern Central Andes, Earth and Planetary Science Letters, 327, 97–110, 2012.

Carlisle, B. H.: Modelling the spatial distribution of DEM error, Transactions in GIS, 9, 521-540, 2005.

Dibblee, T. W.: Geologic Map of Western Santa Cruz Island, Dibblee Geological Foundation, 2001.

15 Dietrich, W. E., Bellugi, D. G., Sklar, L. S., Stock, J. D., Heimsath, A. M., and Roering, J. J.: Geomorphic transport laws for predicting landscape form and dynamics, Prediction in geomorphology, 135, 103–132, 2003.

Dunn, M. and Hickey, R.: The effect of slope algorithms on slope estimates within a GIS, Cartography, 27, 9–15, 1998.

Durran, D. R.: Numerical methods for wave equations in geophysical fluid dynamics, vol. 32, Springer Science & Business Media, 1999.

Evans, I. S.: An integrated system of terrain analysis and slope mapping, Zeitschrift fur Geomorphologie, 36, 274–295, 1980.

20 Farr, T. G., Rosen, P. A., Caro, E., Crippen, R., Duren, R., Hensley, S., Kobrick, M., Paller, M., Rodriguez, E., Roth, L., et al.: The shuttle radar topography mission, Reviews of geophysics, 45, 2007.

Fisher, P. F.: Models of uncertainty in spatial data, Geographical information systems, 1, 191-205, 1999.

25 Florinsky, I. V.: Accuracy of local topographic variables derived from digital elevation models, International Journal of Geographical Information Science, 12, 47–62, 1998.

Fornberg, B.: Generation of finite difference formulas on arbitrarily spaced grids, Mathematics of computation, 51, 699–706, 1988.

- Franklin, J.: Predictive vegetation mapping: geographic modelling of biospatial patterns in relation to environmental gradients, Progress in physical geography, 19, 474–499, 1995.
- 30 Grieve, S. W., Mudd, S. M., Milodowski, D. T., Clubb, F. J., and Furbish, D. J.: How does grid-resolution modulate the topographic expression of geomorphic processes?, Earth Surface Dynamics, 4, 627, 2016.

Guisan, A. and Zimmermann, N. E.: Predictive habitat distribution models in ecology, Ecological modelling, 135, 147-186, 2000.

Guzzetti, F., Carrara, A., Cardinali, M., and Reichenbach, P.: Landslide hazard evaluation: a review of current techniques and their application in a multi-scale study, Central Italy, Geomorphology, 31, 181–216, 1999.

35 Heuvelink, G. B., Burrough, P. A., and Stein, A.: Propagation of errors in spatial modelling with GIS, International Journal of Geographical Information System, 3, 303–322, 1989.

Fisher, P. F. and Tate, N. J.: Causes and consequences of error in digital elevation models, Progress in physical Geography, 30, 467–489, 2006.

- Holmes, K., Chadwick, O., and Kyriakidis, P. C.: Error in a USGS 30-meter digital elevation model and its impact on terrain modeling, Journal of Hydrology, 233, 154–173, 2000.
- Hunter, G. J. and Goodchild, M. F.: Modeling the uncertainty of slope and aspect estimates derived from spatial databases, Geographical Analysis, 29, 35–49, 1997.
- Kent, M.: Vegetation description and data analysis: a practical approach, John Wiley & Sons, 2011.
 Kirby, E. and Whipple, K. X.: Expression of active tectonics in erosional landscapes, Journal of Structural Geology, 44, 54–75, 2012.
 Kraus, K. and Pfeifer, N.: Determination of terrain models in wooded areas with airborne laser scanner data, ISPRS Journal of Photogrammetry and remote Sensing, 53, 193–203, 1998.
- Kyriakidis, P. C., Shortridge, A. M., and Goodchild, M. F.: Geostatistics for conflation and accuracy assessment of digital elevation models,
 International Journal of Geographical Information Science, 13, 677–707, 1999.

Lague, D.: The stream power river incision model: evidence, theory and beyond, Earth Surface Processes and Landforms, 39, 38–61, 2014. LAStools: Efficient LiDAR Processing Software (version 180831, academic), http://rapidlasso.com/LAStools, 2017.

- Lee, J., Fisher, P., Snyder, P., et al.: Modeling the effect of data errors on feature extraction from digital elevation models, Photogrammetric Engineering and Remote Sensing, 58, 1461–1461, 1992.
- 15 Montgomery, D. R. and Dietrich, W. E.: A physically based model for the topographic control on shallow landsliding, Water resources research, 30, 1153–1171, 1994.
 - Mukul, M., Srivastava, V., Jade, S., and Mukul, M.: Uncertainties in the Shuttle Radar Topography Mission (SRTM) Heights: Insights from the Indian Himalaya and Peninsula, Scientific Reports, 7, 41 672, 2017.
 - Neely, A., Bookhagen, B., and Burbank, D.: An automated knickzone selection algorithm (KZ-Picker) to analyze transient landscapes: Calibration and validation, Journal of Geophysical Research: Earth Surface, 122, 1236–1261, 2017.
 - Oksanen, J. and Sarjakoski, T.: Error propagation of DEM-based surface derivatives, Computers & Geosciences, 31, 1015–1027, 2005.
 - Oksanen, J. and Sarjakoski, T.: Uncovering the statistical and spatial characteristics of fine toposcale DEM error, International Journal of Geographical Information Science, 20, 345–369, 2006.
 - OpenTopography: 2010 channel islands lidar collection, https://doi.org/10.5069/G95D8PS7, 2012.

20

25 Ouma, Y. O. and Tateishi, R.: Urban flood vulnerability and risk mapping using integrated multi-parametric AHP and GIS: methodological overview and case study assessment, Water, 6, 1515–1545, 2014.

Pelletier, J. D.: Quantitative modeling of earth surface processes, Cambridge University Press, 2008.

- Pelletier, J. D.: Minimizing the grid-resolution dependence of flow-routing algorithms for geomorphic applications, Geomorphology, 122, 91–98, 2010.
- 30 Pelletier, J. D.: A robust, two-parameter method for the extraction of drainage networks from high-resolution digital elevation models (DEMs): Evaluation using synthetic and real-world DEMs, Water Resources Research, 49, 75–89, 2013.

Perroy, R. L., Bookhagen, B., Asner, G. P., and Chadwick, O. A.: Comparison of gully erosion estimates using airborne and ground-based LiDAR on Santa Cruz Island, California, Geomorphology, 118, 288–300, 2010.

Perroy, R. L., Bookhagen, B., Chadwick, O. A., and Howarth, J. T.: Holocene and Anthropocene landscape change: arroyo formation on
 Santa Cruz Island, California, Annals of the Association of American Geographers, 102, 1229–1250, 2012.

Pierce, K. B., Lookingbill, T., and Urban, D.: A simple method for estimating potential relative radiation (PRR) for landscape-scale vegetation analysis, Landscape Ecology, 20, 137–147, 2005.

- Purinton, B. and Bookhagen, B.: Validation of digital elevation models (DEMs) and comparison of geomorphic metrics on the southern Central Andean Plateau., Earth Surface Dynamics, 5, 2017.
- Purinton, B. and Bookhagen, B.: Measuring Decadal Vertical Land-level Changes from SRTM-C (2000) and TanDEM-X (~ 2015) in the South-Central Andes, Earth Surf. Dyn, 2018.
- 5 Rodriguez, E., Morris, C. S., and Belz, J. E.: A global assessment of the SRTM performance, Photogrammetric Engineering & Remote Sensing, 72, 249–260, 2006.

Roering, J. J., Kirchner, J. W., and Dietrich, W. E.: Evidence for nonlinear, diffusive sediment transport on hillslopes and implications for landscape morphology, Water Resources Research, 35, 853–870, 1999.

- Schmidt, J., Evans, I. S., and Brinkmann, J.: Comparison of polynomial models for land surface curvature calculation, International Journal of Geographical Information Science, 17, 797–814, 2003.
- Shortridge, A. and Messina, J.: Spatial structure and landscape associations of SRTM error, Remote Sensing of Environment, 115, 1576– 1587, 2011.
 - Skidmore, A. K.: A comparison of techniques for calculating gradient and aspect from a gridded digital elevation model, International Journal of Geographical Information System, 3, 323–334, 1989.
- 15 Smith, B. and Sandwell, D.: Accuracy and resolution of shuttle radar topography mission data, Geophysical Research Letters, 30, 2003. Snyder, N. P., Whipple, K. X., Tucker, G. E., and Merritts, D. J.: Landscape response to tectonic forcing: Digital elevation model analysis of stream profiles in the Mendocino triple junction region, northern California, Geological Society of America Bulletin, 112, 1250–1263, 2000.

Thompson, J. A., Bell, J. C., and Butler, C. A.: Digital elevation model resolution: effects on terrain attribute calculation and quantitative soil-landscape modeling, Geoderma, 100, 67–89, 2001.

- Tucker, G. E. and Hancock, G. R.: Modelling landscape evolution, Earth Surface Processes and Landforms, 35, 28–50, 2010.
 Wechsler, S.: Uncertainties associated with digital elevation models for hydrologic applications: a review, Hydrology and Earth System Sciences, 11, 1481–1500, 2007.
 - Wechsler, S. P. and Kroll, C. N.: Quantifying DEM uncertainty and its effect on topographic parameters, Photogrammetric Engineering & Remote Sensing, 72, 1081–1090, 2006.
- 30 Wessel, B., Huber, M., Wohlfart, C., Marschalk, U., Kosmann, D., and Roth, A.: Accuracy assessment of the global TanDEM-X Digital Elevation Model with GPS data, ISPRS Journal of Photogrammetry and Remote Sensing, 139, 171–182, 2018.
 - Whipple, K. X. and Tucker, G. E.: Dynamics of the stream-power river incision model: Implications for height limits of mountain ranges, landscape response timescales, and research needs, Journal of Geophysical Research: Solid Earth, 104, 17661–17674, 1999.
 - Zevenbergen, L. W. and Thorne, C. R.: Quantitative analysis of land surface topography, Earth surface processes and landforms, 12, 47–56, 1987.

35 1

10

20

Tarboton, D. G.: A new method for the determination of flow directions and upslope areas in grid digital elevation models, Water resources research, 33, 309–319, 1997.

Tucker, G. E. and Bras, R. L.: Hillslope processes, drainage density, and landscape morphology, Water Resources Research, 34, 2751–2764, 1998.

Zhang, J. and Goodchild, M. F.: Uncertainty in geographical information, CRC press, 2002.

Zhang, W. and Montgomery, D. R.: Digital elevation model grid size, landscape representation, and hydrologic simulations, Water resources research, 30, 1019–1028, 1994.

Zhou, Q. and Liu, X.: Error analysis on grid-based slope and aspect algorithms, Photogrammetric Engineering & Remote Sensing, 70, 957–962, 2004.