

Morphometric properties of alternate bars and water discharge: a laboratory investigation

Marco Redolfi¹, Matilde Welber¹, Mattia Carlin¹, Marco Tubino¹, and Walter Bertoldi¹

¹Department of Civil, Environmental and Mechanical Engineering, University of Trento, Italy

Correspondence: Marco Redolfi (marco.redolfi@unitn.it)

Abstract. The formation of alternate bars in straightened river reaches represents a fundamental process of river morphodynamics that has received great attention in the last decades. It is well-established that migrating alternate bars arise from an autogenic, instability mechanism occurring when the channel width-to-depth ratio is sufficiently large. While several empirical and theoretical relations for predicting how bar height and length depend on the key dimensionless parameters are available, there is a lack of direct, quantitative information about the dependence of bar properties on flow discharge. We performed a series of experiments in a long, mobile-bed flume with fixed and straight banks, at different discharges. The self-formed bed topography was surveyed, different metrics were analysed to obtain quantitative information about bar height and shape, and results were interpreted in the light of existing theoretical models. The analysis reveals that the shape of alternate bars highly depends on their formative discharge, with remarkable variations in the harmonic composition and a strong decreasing trend of the skewness of the bed elevation. Similarly, the height of alternate bars clearly decreases with the water discharge, in quantitative agreement with theoretical predictions. However, the disappearance of bars when discharge exceeds a critical threshold is not as sharp as expected, due to the formation of so-called “diagonal bars”. This work provides basic information for modelling and interpreting short-term morphological variations during individual flood events and long-term trajectories due to alterations of the hydrological regime.

1 Introduction

Alternate bars are large-scale bedforms, characterized by a repetitive sequence of scour holes and depositional diagonal fronts with longitudinal spacing on the order of several channel widths, which are observed in both sand and gravel bed rivers (e.g., Engels, 1914; Jaeggi, 1984; Rhoads and Welford, 1991; Church and Rice, 2009; Jaballah et al., 2015; Rodrigues et al., 2015). They have been extensively studied in the last fifty years, because of both their practical and theoretical relevance. From the point of view of river engineering, alternate bars are undesired for their erosional effect on banks and bridge piers and their depositional effect that can disturb navigation and increase flooding risk. From an ecosystem perspective, alternate bars represent one of the relevant morphological units, creating suitable habitats for aquatic fauna and riparian vegetation, which contributes to ecological diversity (Gilvear et al., 2007; Zeng et al., 2015). Lastly, from a theoretical point of view, they represent a fascinating phenomenon, which plays a fundamental role in the dynamics of a variety of fluvial systems, such as meandering rivers, channel bifurcations and braided rivers (e.g., Lewin, 1976; Parker, 1976; Fredsoe, 1978).

A number of studies (e.g., Hansen, 1967; Callander, 1969; Sukegawa, 1972; Parker, 1976; Fujita and Muramoto, 1982; Nelson, 1990) have demonstrated that downstream-migrating alternate bars spontaneously develop in straight, channelized reaches as the result of the instability of a cohesionless bed. Due to this autogenic formation mechanisms, this kind of bed morphology is often referred to as “free bars” (Seminara and Tubino, 1989). More specifically, theoretical and laboratory
30 experiments (Fredsoe, 1978; Jaeggi, 1984; Fujita and Muramoto, 1985; Colombini et al., 1987; Lanzoni, 2000a) identified the channel width-to-depth ratio as the key controlling parameter for the formation of free alternate bars: when the channel is relatively narrow, the effect of gravitational pull on the bed load transport is relatively strong and tends to suppress any transverse bed gradient; conversely, in relatively wide channels initially small, periodic perturbations of the bed elevation generate a topographic steering of the flow field that in turn produces a growth of the bed perturbation itself, which leads to
35 the spontaneous, self-sustained development of alternate bars. Therefore, it is possible to define a threshold value of the aspect ratio (i.e. the half width-to-depth ratio), β_{cr} , representing the lower limit for which alternate bars are expected to form.

However, when the width-to-depth ratio is smaller than the threshold value, the equilibrium bed configuration is not necessarily planar, as other bed features may result from different instability mechanisms, such as short, shallow and fast migrating three-dimensional bedforms, usually called “diagonal bars” (Einstein and Shen, 1964; Jaeggi, 1984; Colombini and Stocchino,
40 2012). Since the transition between alternate and diagonal bars is not always sharp, and since they are both characterized by a diagonal pattern, they can be easily confused. Nonetheless, as highlighted by Colombini and Stocchino (2012), diagonal bars represent a clearly distinct kind of bedform and should be regarded as three-dimensional oblique dunes. In fact, they are the product of different formation mechanisms (e.g., they can not be described by shallow-water two-dimensional models), and they depend on different controlling parameters (water depth and Froude number). Conversely, when the aspect ratio becomes
45 very large, transition to more complex, wandering and braiding multi-thread channels is observed (e.g., Parker, 1976; Fredsoe, 1978; Eaton et al., 2010; Ahmari and Da Silva, 2011; Garcia Lugo et al., 2015), which poses an upper limit to the range of β values where free alternate bars are expected to form.

Under steady flow conditions, free bars attain an equilibrium state, where they migrate downstream without changing their morphology (Ikeda, 1984; Colombini et al., 1987). Several theoretical and empirical relations for estimating the equilibrium
50 bar height and wavelength are available (e.g., Ikeda, 1984). Specifically, weakly nonlinear theories (Colombini et al., 1987; Bertagni and Camporeale, 2018) allow for a physically based, analytical prediction of how the equilibrium bar configuration depends on the dimensionless channel and flow parameters.

Nevertheless, there is basically no direct, quantitative analysis regarding how equilibrium properties of alternate bars depend on water discharge. In particular, very few data exist about the shape of alternate bars, as previous experiments have mainly
55 focused on bar height, wavelength, and growth rate (e.g., Ikeda, 1984; Jaeggi, 1984; Fujita and Muramoto, 1985; Lanzoni, 2000a). Moreover, there is little knowledge about the transition from alternate bars to plane-bed, or diagonal bars configurations, which may occur when varying the flow discharge. This lack of information makes it difficult to understand how changes in the flow regime may alter bed morphology. In this work we follow an integrated experimental and theoretical approach, to address the following research questions: (i) how do geometrical properties of alternate bars depend on water discharge? (ii)
60 is it possible to identify different bar styles depending on flow conditions? (iii) is there a sharp transition from alternate bar

morphology to a plane-bed configuration? To answer these questions a series of experiments were performed in a flume with identical channel conditions and sediment characteristics, but differing flow discharge, and experimental results were compared with theoretical predictions from the weakly nonlinear model of Colombini et al. (1987).

2 Methods

65 2.1 Laboratory setup

Laboratory experiments were conducted in a 24m long flume at the Hydraulics Lab of the University of Trento. The physical model consisted of a straight channel of width $W = 0.305$ m, with vertical banks built out of plywood covered by a thick plastic tarp. Uniform sand with a median diameter of $d_{50} = 1.01$ mm was used as feed and bed material. Discharge and sediment input to the flume was set automatically using a recirculating pump and a calibrated screw feeder. At the downstream end of the flume, 70 the output bed load accumulated in a large filtering crate, which was weighted every 10 seconds by means of four load cells. A laser profiler moving on high-precision rails mapped the topography of the drained bed with vertical accuracy of 0.1 mm and spatial resolution 50×5 mm (longitudinal and transverse direction, respectively). A set of 16 steady flow runs were performed, with discharge ranging from $Q = 0.5$ to 4.21 s^{-1} ; all but two of the discharge values (1.5 and 4.21 s^{-1}) were repeated twice to obtain a larger dataset of bed topographies. The chosen discharge values ensure a wide range of channel aspect ratios, and are 75 associated with the hydraulic conditions reported in Table 1. At the beginning of each model run, the bed was graded to a slope $S = 0.01$ using a blade mounted on a movable trolley. Sediment supply for each run was first assigned on the basis of previous experiments carried out with a similar setup (Garcia Lugo et al., 2015), and gradually adjusted during the transient phase of the run to match bed load output. The duration of experimental runs was chosen to ensure equilibrium conditions, which amounts to 10–20 times the Exner timescale (see Garcia Lugo et al., 2015). Wetted width (W_w) and active width (W_a) were measured 80 at 20 regularly spaced cross sections, twice per each run, and averaged in space and time. Migration rate of the alternate bars was estimated by tracking the position of up to 15 individual bar fronts at fixed time intervals. At the end of each run the bed was drained to acquire topography data. Laser surveys covered a 20.5 m long area starting 2 m downstream of the inlet to exclude the effect of local disturbances. The average sediment flux, Q_s , was estimated on the basis of the total weight of the transported material, excluding the first transitory part of the experiment (an equilibrium condition was considered achieved 85 when the cumulative mean of the bed load signal fell within 5% of the global mean).

2.2 Topography data processing

Laser surveys were processed by removing points falling outside the channel bed and by subtracting the average longitudinal slope. This allowed for obtaining DEMs of the detrended bed elevation. The investigation of the geometric properties of alternate bars required the identification of individual bar units. To this aim, we applied the widely accepted definition of bar 90 wavelength as the length between two successive troughs (Eekhout et al., 2013) and developed an automatic procedure to map the position of troughs on DEMs. Elevation maps of individual bars were obtained by splitting DEMs at trough points. Bars that

Table 1. Summary data of the laboratory experiments. Channel width, slope and median grain size are constant and equal to $W = 0.305$ m, $S = 1.0\%$ and $d_{50} = 1.01$ mm, respectively. The Rouse number is defined as $Ro = w_s / (\kappa u_*^*)$, where $\kappa = 0.4$ is the Von Kármán constant, u_*^* is the friction velocity, and w_s is the settling velocity of the bed particles, computed according to Ferguson and Church (2004). Water depth, Froude number, Shields number, Rouse number and aspect ratio are computed by assuming uniform flow conditions over a plane bed, and considering the friction formula of Eq. (9).

Case #	1	2	3	4	5	6	7	8	9
Discharge Q [l s^{-1}]	0.5	1.0	1.5	2.0	2.5	2.7	3.0	3.4	4.2
Run duration T [h]	20	10	6	5	5	5	5	5	2
Sediment transport Q_s [$\text{cm}^3 \text{s}^{-1}$]	0.08	0.45	1.22	1.81	2.47	2.59	3.04	3.63	4.97
Relative wetted area W_w/W [-]	0.97	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Relative active area W_a/W [-]	0.39	0.76	0.88	0.95	0.98	1.00	1.00	1.00	1.00
Water depth D [cm]	0.72	1.06	1.34	1.58	1.79	1.87	1.99	2.14	2.42
Froude number Fr [-]	0.86	0.96	1.02	1.06	1.09	1.10	1.12	1.13	1.17
Shields number θ [-]	0.043	0.064	0.080	0.095	0.108	0.112	0.120	0.129	0.145
Rouse number Ro [-]	12.0	9.9	8.8	8.1	7.6	7.4	7.2	6.9	6.5
Aspect ratio $\beta = W/(2D)$ [-]	21.3	14.4	11.4	9.7	8.5	8.1	7.7	7.1	6.3
Critical aspect ratio β_{cr} [-]	3.2	5.0	5.9	6.5	7.0	7.1	7.3	7.5	7.9
Resonant aspect ratio β_{res} [-]	4.2	7.0	8.7	10.0	11.0	11.4	11.9	12.6	13.8

were very irregular or only partially within the study area were excluded from further calculations. Bar DEMs were normalized by subtracting the elevation mean.

To facilitate the comparison of the shape of individual bars, spatial coordinates of each bar DEM (x, y , see Fig. 1a) were scaled by the bar wavelength (L) and the channel width (W), which resulted in stretched DEMs where both coordinates ranged from 0 to 1. Individual DEMs were then resampled using an inverse distance weighted routine, to obtain elevation data on the same, regular grid of 64×64 points. An ensemble bar was defined as the mean elevation of each grid point across the bars formed at the same discharge, thus representing a characteristic, average bar shape that can be used to study the effect of different experimental conditions.

2.3 Different metrics to characterize bar properties

Alternate bars are commonly described in terms of their wavelength, height, and migration rate. Bar wavelength is the distance between consecutive, corresponding points along the flow direction. Bar height is usually defined as the vertical distance between the bottom of the pool and the top of the bar surface, with several method and metrics proposed in the literature. Finally, for freely migrating bars, the migration rate is the speed at which the bar front moves downstream. However, the geometrical properties of bars are not limited to their height and wavelength, as more detailed information about their geometrical shape can be derived by analyzing the bed morphology.




Figure 1. Panel (a): reference system (x, y) for and individual bar of wavelength L in a straight channel of width W , with the curved line indicating the typical position of bar fronts. Panel (b): picture of the flume at the end of the experiment with $Q = 2.51 \text{ s}^{-1}$, showing the presence of alternate bars. Flow is from top to bottom.

2.3.1 Metrics for bar height and bed relief

The most intuitive and widely used way to define bar height is the difference between the maximum and the minimum elevation along a bar unit, where the bed elevation η is usually computed after removing the mean bed slope. Though different symbols
 110 have been used in the literature, we refer to the Ikeda (1984) notation, namely:

$$H_{BM} = \max(\eta) - \min(\eta), \quad (1)$$

where η indicates the (detrended) bed elevation. A slightly different definition of bar height (e.g., Fujita and Muramoto, 1985) is based on computing the elevation difference along individual transverse cross sections (H_{Bsec}) and then taking its maximum value (H_B):

$$115 \quad H_{Bsec} = \max_{sec}(\eta) - \min_{sec}(\eta), \quad H_B = \max(H_{Bsec}), \quad (2)$$

where max_{sec} and min_{sec} denote the maximum and the minimum elevation along individual cross sections.

The above definitions have a clear physical meaning, as they directly represent the bar height, from the crest to the trough. However, being based on extreme elevation values, such metrics are sensitive to outliers and measurement errors. Therefore, it is sometimes convenient to estimate the topographic effect of alternate bars through different metrics, which measure the “relief” rather than the bar height. Specifically, the bed relief can be defined through the standard deviation of the elevation distribution:

$$SD = std(\eta), \quad (3)$$

or, alternatively, through the Bed Relief Index (e.g., Hoey and Sutherland, 1991; Liébault et al., 2013), which is defined on a cross-sectional basis as follows:

$$BRI_{sec} = std_{sec}(\eta), \quad BRI = mean(BRI_{sec}), \quad (4)$$

where std_{sec} indicates the standard deviation calculated along individual cross sections.

All of these metrics are first computed for each individual bar, and then averaged among all bars formed at the same discharge. It is important to note that, while H_{BM} and SD are based on the full 2-D distribution of elevation, H_B and BRI are based on the elevation along individual cross sections. Since the highest and lowest points of a bar do not necessarily occur along the same cross section, H_B and BRI are expected to provide a lower estimate of height if compared to H_{BM} and SD , respectively.

2.3.2 Metrics for the bar shape

One method to characterize the shape of bars is via the skewness parameter (SK), which measures the asymmetry of the bed elevation distribution, thus providing information on the relative proportion of high and low areas within a bar. River bed elevation maps often show negative skewness, with deep, narrow channels carved into large, higher elevation bars (e.g., Bertoldi et al., 2011; Garcia Lugo et al., 2015).

Being based on the relative frequency of the elevation values, the above metrics, however, do not provide information about the spatial arrangement of the bedforms. To obtain synthetic information about the spatial structure of bars, we analysed the bed elevation maps through the two-dimensional Fourier transform (e.g., Garcia and Nino, 1994; Zolezzi et al., 2005). As detailed in Appendix A, the topography of an individual bar of wavelength L (see Fig. 1a) can be represented as follows:

$$\eta(x, y) = \sum_{m=0}^{\infty} \sum_{n=0}^{\infty} |A_{nm}| \cos(\pi m y / W) \cos(2\pi n x / L + \phi_{nm}), \quad (5)$$

where x is the longitudinal coordinate, y is the transverse coordinate (with origin at the right bank), while $|A_{nm}|$ and ϕ_{nm} represent amplitude and phase of each Fourier component. The amplitudes of the main components provide information about possible symmetry properties, the relative importance of two-dimensional and three-dimensional topographic effects, and the deviation from the simple sinusoidal structure that arises from linear stability analyses (e.g., Fredsoe, 1978).

2.4 Application of the weakly nonlinear theory of Colombini et al. (1987)

The theory of Colombini et al. (1987) is based on a weakly nonlinear solution of the two-dimensional shallow water and Exner model for a straight channel of constant width and downstream gradient. Specifically, they considered the following relation for the bed load transport rate per unit width, q_b [$\text{m}^2 \text{s}^{-1}$]:

$$150 \quad q_b = \sqrt{g\Delta d_{50}^3} \Phi, \quad (6)$$

where g is the gravitational acceleration, $\Delta = 1.65$ is the relative submerged weight of sediment, and Φ represents the dimensionless sediment transport, whose expression depends on the choice of the transport formula. Moreover, the effect of the lateral bed slope on the direction of the bed load transport was modeled according to the Ikeda (1982) formulation:

$$\tan(\gamma) = -\frac{r}{\sqrt{\theta}} \frac{d\eta}{dy}, \quad (7)$$

155 where γ is the angle between the velocity vector and the sediment transport vector, θ is the Shields number, and r is an empirical dimensionless parameter, typically ranging from 0.3 to 0.6.

The model of Colombini et al. (1987) allows for different choices of the transport and friction formulas. For the present analysis, we considered the Parker (1978) relation, which gives the following expression for the dimensionless sediment transport:

$$160 \quad \Phi = 11.2\theta^{1.5} \left(1 - \frac{\theta_i}{\theta}\right)^{4.5}, \quad \theta_i = 0.03, \quad (8)$$

where θ_i indicates the Shields number of incipient sediment motion. This transport formula was chosen for two reasons: (i) it exhibits a critical threshold that is consistent with our experiments; (ii) it is suitable for analytical treatment, because for $\theta > \theta_i$ it is continuous and has continuous derivatives. Moreover, as in the original formulation of Colombini et al. (1987), we used the logarithmic friction formula of Engelund and Fredsoe (1982), which gives the following expression for the dimensionless

165 Chézy coefficient:

$$c = 6 + 2.5 \log\left(\frac{D}{2.5 d_{50}}\right), \quad (9)$$

where D indicates the water depth. Finally, we calibrated the empirical parameter r of Eq. (7) by minimizing the difference between experimental and analytical values of H_{BM} , which resulted in a value of 0.40.

3 Results

170 The bed topographies obtained under different discharges are illustrated in Fig. 2. A regular pattern of large-scale bedforms can be recognized in all maps, with substantial differences in shape and relief. At the lowest discharge (0.51 s^{-1}) the bed shows a complex topography with alternate, elongated pools along the banks, but few clearly discernible bar fronts and several small channels cutting the main bedforms. In these conditions, the tops of bars (3% of the area, see Table 1) begin to emerge and less

than half of the bed surface is actively transporting sediments. At higher flows (1.0 and 1.51s^{-1}), bed topography is dominated
175 by a coherent pattern of bars with elongated pools and a sharp front that is almost transverse to the flow direction. Between
 $Q = 2.0$ and 2.71s^{-1} , relief progressively decreases and bar fronts become curved and oblique in a regular fish-scale pattern.
Finally, between $Q = 3.0$ and 4.21s^{-1} , bars are shorter and shallower. It is important to note that for increasing discharge,
well defined bars progressively disappear from the upstream end of the channel, where the bed shows a superimposition of
low-relief, irregularly spaced oblique fronts.

180 3.1 Bar height and bed relief

A comparison of metrics for bar height and bed relief is presented in Fig. 3a and 3b. The bar height H_{BM} is maximum (almost
40 mm) for the $Q = 1.01\text{s}^{-1}$ run, then it gradually decreases with discharge until it attains a relatively constant value of about
13 mm for $Q \geq 3.01\text{s}^{-1}$. At the lowest discharge (0.51s^{-1}), bar height is lower than the peak value, showing a value around
33 mm. As expected, H_B is smaller than H_{BM} for all runs, but the difference is minimal and does not show a clear trend with
185 discharge. An analogous behavior is observed for the bed relief metrics SD and BRI (Fig. 3b). Specifically, BRI tends to be
only slightly smaller than SD , and both metrics exhibit a variation with discharge that follows the same trend observed for the
bar height metrics H_{BM} and H_B . However, the variation of SD and BRI with discharge is less gradual, with bars formed at
 $Q = 1.0$ and 1.51s^{-1} showing distinctively higher values (nearly +50%) than the other cases. In general, values of SD and
 BRI are much lower than H_{BM} and H_B , as bed relief metrics cover a range of values that is about one fifth the observed
190 range of bar height.

Bars are downstream migrating with a speed of the order of a few millimeters per second. At the lowest discharge, migration
rate was not measured because of the lack of easily recognizable fronts and the presence of complex patterns of erosion and
deposition. For higher flows, migration rate gradually increases from almost zero to 3mm s^{-1} for $Q = 3.01\text{s}^{-1}$ (see Fig. 3c),
while between $Q = 3.0$ and 3.41s^{-1} it exhibits a sudden growth to values around 5mm s^{-1} . Mean bar wavelength (see Fig.
195 3d) is higher at low flows (~ 3 to 3.5m , corresponding to 10 to 12 channel widths) and decreases at higher discharges to
approximately 1m (about three channel widths). Specifically, the bar wavelength shows a rapid drop between $Q = 1.5$ and
 2.01s^{-1} , followed by a gradual decrease.

3.2 Predictions by the weakly nonlinear theory

The values of the equilibrium bar height predicted by the weakly nonlinear theory are reported in Fig. 4, which shows a de-
200 creasing trend of H_{BM} with the water discharge, until it vanishes when the channel aspect ratio, β , matches its threshold value
 β_{cr} (no bars). Therefore, it is possible to define a corresponding threshold value of the flow discharge (a “critical discharge”,
 $Q_{cr} = 3.171\text{s}^{-1}$), which separates the formative conditions for alternate bars ($Q < Q_{cr}$) from the region where bars do not
develop ($Q > Q_{cr}$).

We note that the weakly nonlinear theory is formally valid near the critical conditions, although the comparison with exper-
205 imental data suggests its applicability within a wider range of conditions (Colombini et al., 1987; Lanzoni, 2000b). However,
at relatively low values of discharge, the predicted equilibrium elevation of the top of the bars would exceed the water surface




Figure 2. Maps of detrended bed elevation, showing the equilibrium bed morphology for increasing values of discharge. Flow is from top to bottom. Longitudinal scale is compressed for clarity.




Figure 3. Mean properties of bars depending on discharge: (a) bar height H_{BM} and H_B ; (b) bed relief, as measured by the standard deviation of the bed elevation distribution (SD) and the bed relief index (BRI); (c) bar migration rate C ; (d) bar wavelength L .

elevation, which makes the equilibrium value of H_{BM} no longer meaningful. Therefore, when the discharge is smaller than the so-called fully-wet threshold, Q_{fw} (see Adami et al., 2016) the system cannot reach equilibrium bar height. Under these conditions it is then reasonable to assume that bar growth stops as bar tops start to emerge, which means the maximum bar elevation must be set equal to the water surface elevation. This concept of emersion-limited bar height is represented by the dash-dot line in Fig. 4, which shows an opposite (i.e. increasing with the discharge) trend with respect to the theoretical equilibrium height. Ultimately, a lower limit of the region of possible bar formation is set by the flow discharge corresponding to incipient sediment motion, $Q_i = 0.261 \text{ s}^{-1}$, which defines the third relevant threshold illustrated in Fig. 4.

The theoretical response of bar height to varying flow conditions is then compared with the laboratory data, which gives the results illustrated in Fig. 5. Consistently with the theoretical analysis, all the metrics are represented in dimensionless form, by scaling bar height and relief with the median grain size d_{50} , the bar wavelength by the channel width W , and the migration rate by the flow velocity U_0 . Moreover, we define a dimensionless discharge as:

$$\Delta Q^* = \frac{Q - Q_{cr}}{Q_{cr} - Q_i}, \quad (10)$$




Figure 4. Bar height as a function of discharge, according to the weakly nonlinear theory of Colombini et al. (1987). Solid line represents the equilibrium solution, while the dash-dot line indicates the bar height we obtained by limiting the bar growth to the fully-wet condition. The development of alternate bars highly depends on discharge state with respect to the three key thresholds (vertical dashed lines), which represent: (i) the critical condition of incipient sediment motion, $Q_i = 0.261 \text{ s}^{-1}$; (ii) the conditions for which bars at equilibrium are fully wet, $Q_{fw} = 1.261 \text{ s}^{-1}$; and (iii) the critical condition for bar formation, $Q_{cr} = 3.171 \text{ s}^{-1}$.

so that values from -1 to 0 cover the entire range of bar formation, from the threshold of incipient sediment transport Q_i to
 220 the critical threshold Q_{cr} .

From this comparison it is apparent that bars observed at 3.4 and 4.21 s^{-1} are anomalous, for a number of reasons: (i) they occur outside the region of bar formation (i.e. at $Q > Q_{cr}$); (ii) they exhibit a much faster migration rate, and (iii) their wavelength is much shorter with respect to the typically observed values ($L = 5\text{--}12W$, see Tubino et al., 1999). This type
 225 of bedform closely resembles the “diagonal bars” described by Jaeggi (1984) as three-dimensional mesoforms characterized by a wavelength of around three times the channel width, limited relief, symmetrical elevation distribution, and the presence of shallow pools. These bedforms were observed at Froude numbers close to one and did not match the region for alternate bar formation. Experimental observations by Jaeggi (1984) suggested that diagonal bars can be considered as intermediate
 230 bedforms associated with the transition of dunes from two- to three-dimensional configurations. This idea was confirmed by the theoretical work of Colombini and Stocchino (2012), which provided an interpretation of diagonal bars as three-dimensional oblique dunes, distinct from alternate bars. Herein, we will therefore refer to bars observed at $\Delta Q^* > 0$ as diagonal bars, reserving the term “alternate bars” to the remaining cases.

The analytical model reproduces remarkably well both the bar height and the bed relief of alternate bars (Figures 5a and 5b). However, when the discharge approaches the critical threshold Q_i the weakly nonlinear model is no longer valid and the solution for the equilibrium amplitude diverges. As discussed previously, when discharge is lower than the fully-wet threshold
 235 Q_{fw} the singularity of the analytical solution can be mitigated by considering the fully-wet limited bar height, which provides a reasonable estimate of H_{BM} and SD . Similarly, the bar migration rate (Fig. 5c) is well reproduced by the analytical model,

both for the overall trend and for the absolute values, although the theory significantly overestimates the observed value at $Q = 1.01\text{s}^{-1}$. Furthermore, the theory properly predicts the wavelength of bars only for intermediate values of discharge (see Fig. 5d), while it does not capture the overall decreasing trend, and therefore sharply underestimates the length of bars observed in the three runs with $Q \leq 1.51\text{s}^{-1}$.




Figure 5. Dimensionless bar parameters as a function of the scaled discharge, from theory (lines) and experiments (markers). Panels (a) and (b): height and standard deviation of bed elevation distribution (scaled with the median grain size d_{50}), with solid line indicating equilibrium conditions and dash-dot line representing the bar height limited by the fully-wet condition. Panels (c) and (d): bar migration rate and wavelength (scaled with the flow velocity U_0 and the channel width W , respectively).

3.3 Quantitative analysis of the bar shape

In order to filter out the relatively small differences of single bar units, we computed for each discharge value an ensemble bar shape, defined as the average topography of all the bars formed under the same flow conditions. The resulting ensemble topographies represented in Fig. 6 show a rather regular pattern. We then analysed the response of the bar shape to changing discharge by computing the skewness and the Fourier components of the ensemble bars for each discharge value.




Figure 6. Maps of ensemble bars, representing variation of the average bar topography for increasing values of discharge. Spatial coordinates (x,y) are normalized with respect to the bar wavelength (L) and the channel width (W). Contour spacing is 5 mm (upper panels) and 2 mm (lower panels), with the thicker contour indicating the mean (i.e. zero) elevation and white contours representing negative elevation values. Flow is from top to bottom.

Figure 7 shows that the skewness is always negative, which indicates a left-tailed bed elevation distribution. For the lowest discharge the skewness is around -1.5 , which matches typical values observed for wandering and braided channels (see Garcia Lugo et al., 2015). Highly negative values of the skewness are associated with the presence of narrow, deep troughs and wide, relatively flat bar crests that are clearly detectable in Fig. 6 for the ensemble bars at $Q \leq 1.51 \text{ s}^{-1}$. This morphological characteristic becomes progressively less pronounced, as the ensemble bars corresponding to the range $Q = 2.5\text{--}3.01 \text{ s}^{-1}$ show a comparable extension of regions of scour and deposition, and the presence of distinct diagonal fronts. The observed trend of the skewness parameter is in qualitative agreement with the theory, which predicts an increase from negative values at low flow to vanishing values (i.e. nearly symmetrical bed elevation distribution) when approaching the critical condition for bar formation (i.e. $\Delta Q^* \simeq 0$). However, the magnitude of the observed skewness is much larger than the theoretical estimate, due to the limited capability of the theoretical model to fully represents the complex, highly nonlinear morphodynamic processes (see Colombini et al., 1987).




Figure 7. Skewness of the bed elevation distribution as a function of the scaled discharge. Markers indicate the skewness of the experimental ensemble bars; lines illustrate results from the weakly nonlinear theory, with the dash-dot line referring to the solution obtained by limiting the bar growth to the fully-wet condition.

The analysis of the Fourier spectral composition of bed topography provides the amplitude of each component along the transverse and longitudinal direction. An example is shown in Fig. 8 for the ensemble bar of the $Q = 2.51 \text{ s}^{-1}$ run. The plot illustrates the amplitude of the first 36 (6×6) harmonic components, identified by their longitudinal (n) and transverse (m) mode. In this representation, $n = 1$ indicates a complete sinusoidal period in one bar wavelength, while $m = 1$ indicates half a wave period in one channel width. Harmonic components with $n = 0$ and $m = 0$ are constant along the x and y axis, respectively. The component A_{00} , which represents a horizontal plane, has amplitude equal to zero, because the original DEM was normalized by removing the mean. As revealed by their total energy content, E_n , the most important components of the spectrum are those with longitudinal mode $n = 1$. Specifically, alternate bars are dominated by the component A_{11} , which represents a double sinusoidal bed deformation. Components with $n = 1$ and higher, odd transverse mode m , such as the A_{13} and the A_{15} , also appear in the spectrum, contributing to the deviation of the cross section from a purely sinusoidal variation

to a more complex (but still antisymmetric) shape. However, components with longitudinal modes $n = 0$ and $n = 2$ are also relevant. The longitudinal mode $n = 0$ is dominated by the component A_{02} , which represents a sinusoidal symmetric bed deformation that is constant in x , while the components with longitudinal mode $n = 2$ include a number of (even) transverse modes (i.e. A_{22} , A_{24}), which represent a symmetric bed deformation that completes two periods in one bar wavelength (see Fig. 9 for a schematic representation). All $m = 0$ harmonics, which represent a purely longitudinal bed deformation, turn out to be negligible, showing that the transversally averaged bed elevation is nearly zero for all the cross sections. Analogously, components with $n = 0$ and odd transverse mode m are also vanishingly small, which implies that on average the bed structure does not exhibit any asymmetry with respect to the channel axis. For all tested conditions, the Fourier spectrum exhibits a clear checkerboard pattern, where at least 98% of the energy is contained in even-even and odd-odd modes, while other harmonics have negligible power (on average 0.7%). This distinctive pattern indicates that despite their morphological complexity, both alternate and diagonal bars are “purely alternate”, in the sense that the second half of the bar is nearly identical to the first half but mirrored across the channel axis.

We note that the above results are valid in general, regardless of the value of flow discharge. However, relevant variations of the Fourier spectrum composition occur when changing Q . The amplitude of the four dominant components A_{11} , A_{02} , A_{22} and A_{22} is illustrated in Fig. 9 as a function of the dimensionless discharge previously defined in Eq. (10). The amplitude of the fundamental harmonic, A_{11} , which is illustrated in Fig. 9a, closely follows the trend observed for bar height parameters (see Fig. 3a and 3b), with maximum values for $Q = 1.0$ and 1.51s^{-1} , a steady decrease up to $Q = 3.01\text{s}^{-1}$ and lower, almost constant values afterwards. This is not surprising, as the A_{11} is the dominant component of the bed topography, which therefore mostly determines the bar height.

To quantify the shape of the bars, regardless of their absolute height, we then refer to the relative amplitude of the Fourier modes, given as a proportion of the amplitude $|A_{11}|$ as illustrated in Fig. 9b,c,d. Excluding the first case ($Q = 0.51\text{s}^{-1}$), the trend observed for alternate bars is rather clear, with a decreasing importance of both the symmetric component A_{02} and the asymmetric component A_{13} , from amplitudes of about 60–70% of $|A_{11}|$ to significantly smaller values when approaching the critical threshold Q_{cr} . Specifically, the amplitude of the component A_{02} decreases by about an order of magnitude. However, the component A_{22} shows an inverse (i.e. increasing) trend, from the nearly vanishing amplitude observed at $Q = 1.0$ and 1.51s^{-1} to values of about 1/3 of $|A_{11}|$ when approaching Q_{cr} . The weakly nonlinear theory of Colombini et al. (1987) resolves the first 2×2 modes of the Fourier spectrum, thus allowing for calculation of the expected variation of the main components illustrated in Fig. 9, except for the A_{13} . The amplitude of the fundamental harmonic A_{11} (Fig. 10b) is fairly well reproduced, at least for values of the flow discharge that do not differ much from the critical threshold Q_{cr} , which is where the theory is expected to work best. However, for lower discharge values the theoretical curve clearly overestimates the measured data, and the predicted equilibrium amplitude diverges as discharge approaches the threshold value Q_i . In this case, as also noticed earlier, an approximate solution can be derived by assuming that the bar growth is limited by the fully-wet condition.

To investigate the overall importance of the $m = 2$ components with respect to the fundamental, we first analyse the sum of the absolute values of the coefficients A_{02} and A_{22} , scaled with the amplitude of the fundamental harmonic A_{11} . As illustrated in Fig. 10b, this metric tends to decrease with discharge, theoretically approaching zero near the critical conditions (i.e. at




Figure 8. Amplitude of the first 6×6 longitudinal and transverse modes for the ensemble bar at $Q = 2.51 \text{ s}^{-1}$. Histograms on the bottom and on the right report the total energy E_n and E_m , representing the variance of the bed elevation associated with all the components having longitudinal mode n and transverse mode m , respectively.




Figure 9. Amplitude of the main Fourier components depending on discharge. Panel (a): amplitude of the fundamental harmonic (A_{11}). Panels (b,c,d): ratio between the amplitudes A_{02} , A_{22} , A_{13} and the fundamental. The 3-D plots on the right illustrate the bed deformation associated with each Fourier component.

$\Delta Q^* \simeq 0$). Despite its limited capability to quantify the fully nonlinear interactions, the theory allows for a proper estimation of the observed values. However, the main difference between theory and experimental data lies in the relative amplitude of the individual $m = 2$ components, A_{02} and A_{22} . As illustrated in Fig. 10c, the values of the ratio $|A_{02}|/|A_{11}|$ are strongly
305 underestimated by the theory, with experimental values being roughly four times their theoretical counterpart. Conversely, values of the ratio $|A_{22}|/|A_{11}|$ reported in Fig. 10d are significantly overestimated. This indicates that the mode-2 component is not dominated by the presence of regular, periodic central bars (see map of Fig. 9c), as suggested by the theory, but it is mainly associated with a bell-shaped distortion of the average cross section (Fujita and Muramoto, 1985), as represented in Fig. 9b. Finally, the ratio $|A_{22}|/|A_{11}|$, illustrated in Fig. 10d, does not tend to zero as predicted by the theory. From a morphological
310 point of view this implies that for $Q \rightarrow Q_{cr}$, while “theoretical” bars tend to become purely sinusoidal (A_{11} component only) as the solution approaches its linear limit, observed bars retain a certain degree of non-linearity, showing a $m = 2$ component that derives from the presence of clear diagonal fronts (see Fig. 6).




Figure 10. Amplitude of the main Fourier components depending on the scaled discharge, from theory (lines) and experiments (markers). Panel (a): amplitude of the fundamental component A_{11} , scaled with the grain size d_{50} . Panels (b,c,d): amplitude of the $m = 2$ components, scaled with $|A_{11}|$, with (b) reporting the sum of the absolute values of the coefficients A_{02} and A_{22} , and (c,d) referring to the individual components A_{02} and A_{22} . Solid line indicates theoretical results at equilibrium, while dash-dot line indicates theoretical results obtained by limiting the bar growth to the fully-wet condition.

4 Discussion

4.1 Discharge and bar height

315 Experimental data reveal that bar height and relief generally decrease with increasing discharge, and are therefore inversely
correlated with the sediment transport rate. This finding, which at a first sight may appear counterintuitive, is a direct conse-
quence of the decrease of channel aspect ratio for progressively higher flows that is typical of single-thread rivers. This implies
that the largest bars tend to develop under moderate flow conditions, where discharge is high enough to mobilize the bed ma-
terial and at the same time is sufficiently low with respect to the critical discharge for bar formation, Q_{cr} . The decreasing bed
320 relief with discharge is expected to have a direct impact on the sediment transport rate. Specifically, for relatively low values of

discharge the presence of bars can promote a transverse variability of the Shields number, which leads to a net increase of the sediment transport rate with respect to equivalent, flat bed conditions (e.g., Paola, 1996; Francalanci et al., 2012). This effect can mitigate the reduction of the average transport rate when decreasing discharge, thus making the sediment rating curve more linear (Ferguson, 2003; Redolfi et al., 2016).

325 Our results reveal that the weakly nonlinear model allows for reproducing both qualitatively and quantitatively the observed bar height. Despite the calibration of the parameter r , this is a significant result, as it highlights the capacity of the theoretical model to accurately capture the sharp decreasing trend of bar height from intermediate values of discharge to the critical threshold. However, the variation of the bar height with discharge is not everywhere monotone, as when discharge becomes relatively low, bars tend to emerge, and their relief tends to reduce. In these conditions the equilibrium amplitude predicted
330 by the Colombini et al. (1987) model is clearly unphysical. This is not surprising, as the theory assumes a simply connected domain, where the bed is fully submerged. To mitigate this issue, we propose a modified curve for the bar height, obtained by limiting the growth of the bars by the fully-wet condition. Situations where bars emerge are expected to be more important for wider channels, due to the larger range of discharge states between the threshold of incipient sediment transport and the fully-wet threshold. Specifically, as the channel width-to-depth ratio grows, the equilibrium becomes increasingly complex,
335 ultimately leading to wandering and braiding channels (see Ashmore, 2013; Garcia Lugo et al., 2015; Redolfi et al., 2016).

4.2 Discharge and bar shape

The definition of suitable metrics for quantifying variations of the bar shape allows us to highlight how the shape of alternate bars at equilibrium changes with discharge. The weakly nonlinear theory of Colombini et al. (1987), as well as the bar predictor of Crosato and Mosselman (2009), suggest that when discharge is relatively small (i.e. high width-to-depth ratio) the channel
340 tends to form regular, periodic central bars (also called double-row bars, see Ikeda, 1984; Crosato and Mosselman, 2020) where scour and deposition are equally distributed between the center of the channel and the area near the banks. However, as also evident from existing laboratory and numerical data (e.g., Fujita and Muramoto, 1985; Garcia Lugo et al., 2015; Qian et al., 2017; Cordier et al., 2019) it is clear that deposition preferentially occurs near the center of the channel (mid-channel bars), while deep pools are mostly concentrated near the banks. This produces a bell-shaped distortion of the average cross section,
345 which gives a Fourier component A_{02} that at low flows is by far more important than the A_{22} component. As highlighted by Colombini and Tubino (1991) this behavior can be explained by fully taking into account the nonlinear effects, which tend to be progressively more important when the channel aspect ratio increases. Moreover, mid-channel bars are typically not symmetric with respect to the channel centerline, but they often appear as compound bars, with the water flow mainly concentrating near the banks and sometimes cutting the entire channel width through the formation of channel bifurcations (e.g., Schuurman and
350 Kleinhans, 2015; Duró et al., 2016). In experimental modelling of wandering and braided rivers (e.g., Ashmore, 1982; Garcia Lugo et al., 2015) the tendency of the channels to “stick to the banks” is often considered as a side effect of the physical model. However, this may be not necessarily the result of a scaling issue, nor a consequence of the low roughness of the banks, but it could be associated with a natural tendency of the flow to follow the banks when they are sufficiently straight, with the bars mainly occupying the mid part of the channel. The Fourier analysis also reveals that the component A_{22} (as well as the

355 A_{13}) does not vanish when approaching the critical conditions, as the theory predicts. Considering that near Q_{cr} the weakly nonlinear analysis should provide an accurate solution of the shallow water and Exner equations, this mismatch is likely to originate from the model equations themselves. Specifically, this may be related to three-dimensional effects, which could be locally important in determining the formation of relatively steep bar fronts that mark a significant difference with respect to the theoretical, sinusoidal bed structure.

360 4.3 The observed transition between different types of bars

Experimental observations presented in this study provide detailed information on the relationship between bar characteristics and discharge, while other relevant channel properties, such as grain size and slope, are kept constant. Within the tested flow range, bars exhibit a variety of sizes and shapes and pass smoothly from one shape to the other as discharge increases. On the basis of their geometrical properties and migration rate it is possible to identify four main types of bars:

- 365 1. At low flows, when channel aspect ratio is high, alternate bars are very irregular, and the channel tends to switch to a more complex, wandering morphology. Sediment transport occurs on a limited portion of the bed, and the bed evolution is not dominated by the downstream migration of bar fronts, but rather by lateral erosion and cutoffs. This kind of bar is associated with conditions where the top of the bars emerges, so that the bed is not fully wet ($W_w < W$, see Table 1). The emersion limits the growth of the bar height, and consequently restricts bed relief.
- 370 2. At low to intermediate flows, bars are clearly delineated and relief is high. Their transverse shape is highly asymmetric, with narrow, deep, elongated pools and high, flat bar tops occupying a large proportion of the cross section, so that the elevation along the centerline of the channel is always above the median detrended elevation. The distribution of elevation is strongly negatively skewed, and the Fourier components A_{02} (symmetrical deformation) and A_{13} (asymmetrical deformation) are relatively strong. Bar fronts are clearly delineated, steep and almost orthogonal to channel banks.
375 Immediately downstream of fronts, where the deepest pools are located, there is no sediment in motion. Moreover, bar migration is slow and the wavelength is significantly higher than theoretically predicted values.
3. At intermediate to high flows, relief and bar wavelength decrease with increasing discharge, and bar fronts become curved and oblique. The bed elevation distribution is less skewed and higher-order components of the Fourier spectrum become less relevant with respect to the fundamental harmonic A_{11} . As deep pools tend to disappear, sediment motion
380 occurs on the entire channel surface. This kind of bed morphology represents the typical shape of alternate bars (i.e. that sketched in Fig. 1a), and shows a very close match with theoretical predictions in terms of height, wavelength, and migration rate.
4. Finally, at high flows diagonal bars form. Despite preserving an alternate shape, diagonal bars are rather different from alternate bars in terms of both geometrical properties and formation mechanism. The height of these bedforms is small
385 and largely independent of discharge, and their elevation distribution is almost symmetrical. Diagonal bars are relatively short (less than five channel widths), with oblique, almost straight fronts that migrate downstream at high speed. They

are observed outside the range of alternate bar formation (i.e. for $Q > Q_{cr}$), for discharge values that are also consistent with the empirical criterion proposed by Jaeggi (1984). According to Colombini and Stocchino (2012) diagonal bars are associated with the transition from two- to three-dimensional oblique dunes. This transition is expected when reducing the relative roughness d_{50}/D , i.e. when approaching typical conditions of gravel bed rivers.

The three-dimensional character of the flow field is fundamental for explaining the morphology of diagonal bars. Specifically, when $Q > Q_{cr}$ the two-dimensional, depth-averaged model of Colombini et al. (1987) would predict plane-bed conditions (no bars), while a three-dimensional, non-hydrostatic analysis is needed to reproduce the observed formation of diagonal bars (Colombini and Stocchino, 2012). For this reason, all depth-averaged numerical models for alternate bars (e.g., Crosato et al., 2011; Siviglia et al., 2013; Qian et al., 2017; Cordier et al., 2019) likely suffer from the same limitation. Since diagonal bars are of small amplitude, they are expected to have a limited effect on sediment transport and flow resistance. Moreover, they may easily disappear as the result of the interaction with other, more prominent bedforms (e.g., free alternate bars and forced bars) that are expected to form because of the natural variability of flow and channel geometry in rivers. Nevertheless, attention should be paid in the interpretation of numerical results and in their comparison with field and laboratory observations.

From a visual inspection of the topographies illustrated in Fig. 2, it is evident that bars forming at $Q > 2.01\text{s}^{-1}$ are not spatially uniform, but they grow in the initial part of the channel, before adapting to fully developed conditions. This behavior has been observed by laboratory and numerical experiments (Fujita and Muramoto, 1985; Defina, 2003; Nicholas, 2010; Qian et al., 2017) and has been associated with the fact that bar formation needs to be triggered by small perturbations, whose effect propagates downstream in the form of wave packages (i.e. trains of bars). Specifically, the spatial adaptation is probably a consequence of the convective (rather than absolute) nature of bar instability highlighted by Federici and Seminara (2003), which implies that the effect of local perturbations tends to be convected downstream rather than being spread throughout the whole domain.

On the basis of theoretical results, it is possible to define an additional threshold value of discharge, corresponding to conditions where the channel aspect ratio β equals the resonant value β_{res} , originally defined by Blondeaux and Seminara (1985) (see Table 1). We name this threshold value “resonant discharge” (Q_{res}), which turns out to equal 1.941s^{-1} . Although not directly affecting the theoretical solution for free migrating bars, the resonant threshold is fundamental for defining the propagation of morphological effects that can be generated by any flow disturbance (e.g., that associated with boundary conditions). Specifically, as first highlighted by Zolezzi and Seminara (2001), under sub-resonant conditions (i.e. $Q > Q_{res}$) morphological effects tend to manifest themselves downstream of the disturbance, while an upstream propagation is possible in the super-resonant regime (i.e. when $Q < Q_{res}$). The different behavior of bars observed at relatively low flows, which tend to be well-developed along the entire flume (see Fig. 2), may be associated with the super-resonant character of the experiments. In this case the possible upstream propagation of the morphological information may favour an upstream diffusion of the bed instability, which can therefore reach the initial part of the channel.

4.4 The alternate nature of both alternate bars and diagonal bars

420 The checkerboard pattern of the Fourier spectra indicates that both alternate and diagonal bars are “purely alternate”, in the sense that the elevation map of the upstream half wavelength is nearly identical to the downstream half but mirrored along the channel centerline. Note that this does not imply a point symmetry with respect to the center of the bar ($y = W/2$ and $x = L/2$), but rather a switching of the same erosion and deposition pattern between the two sides of the channel. Interestingly, this is valid even for the ensemble bars at the lowest discharge ($Q = 0.51 \text{ s}^{-1}$), despite the complexity of the bed topography
425 displayed in Fig. 2.

This particular pattern is intrinsically linked to bar formation mechanisms. To some extent, both alternate and diagonal bars can be considered “free bars”, in the sense that they both arise from an autogenic, three-dimensional instability of the erodible bed. This kind of instability does not break the overall symmetry of the problem; therefore, if a deposition patch tends to form near one bank, a similar feature should appear somewhere else, but on the opposite side of the channel. This suggests that if
430 periodic, three-dimensional bedforms develop, they should follow an alternate pattern, at least in an average, statistical sense.

From a mathematical point of view, the checkerboard pattern can be explained by considering that free bars tend to initially appear as a bed deformation having a double sinusoidal shape (A_{11} component only), while as they grow, nonlinear interactions gives rise to the second-order, A_{00} , A_{02} , A_{20} , A_{22} harmonics (see Colombini et al., 1987; Bertagni and Camporeale, 2018). Extending the analysis to higher order of approximation would give other even-even modes, but no odd-odd modes.

435 Finally, it is worth noting that the dominance of the even-even and the odd-odd modes has an experimental significance, as it indicates that: (i) there are no systematic trends associated with channel asymmetries (e.g., product of initial bed levelling); (ii) random effects resulting from measurement errors, experimental imperfections, or the intrinsic stochasticity of sediment transport processes, are not significantly affecting the shape of the ensemble bar.

4.5 Suitable metrics for quantifying bar height and relief

440 The laboratory dataset used for this work allowed for the comparison of a number of methods and metrics to characterize bar height and relief. Historically, interest in the quantification of bar height arose from their influence on human activities and interaction with artificial structures (Jaeggi, 1984). Therefore, maximum scour and deposition were the most relevant parameters utilized to evaluate the risk of levee instability and levee overtopping, respectively. However, metrics of bar height based on maxima and minima (H_{BM} and H_B) are highly sensitive to measurement errors and uncertainties that derive from
445 the presence of vegetation on the bar top and from the difficulty of measuring the bottom elevation in deep pools. Moreover, the estimation of both H_{BM} and H_B requires the identification of individual bar units, which introduces potential sources of uncertainties and limits its application to bed configurations where a dominant longitudinal wavelength is clearly recognizable.

Comparatively, SD and BRI are robust indices that do not depend on extreme values of elevation, but on the entire bed elevation distribution. Moreover, these bed relief metrics can be applied to a range of different morphologies, thus allowing
450 for comparisons between bars and other bedforms. Since SD and BRI show the same trend observed for H_{BM} and H_B , the

formers can provide better data when the purpose is not to quantify the maximum scour and deposition, but to rather measure morphological trajectories and to compare study cases with experimental and numerical simulations.

It is also important to note that metrics based on the comparison of elevation values at different longitudinal positions (i.e. H_{BM} and SD) require detrending the bed elevation by removing an average slope that is often not obvious to define. Our
455 experiments show that results are very similar when considering instead the cross section based indices H_B and BRI , with the advantage that they are fully independent on how the average slope is detrended. This similarity is linked to the presence of deep, small pools and large, flat bar tops. Cross-sectional relief is more strongly influenced by the formers, and the maximum elevation along the cross section where the lowest point is located is not very different from the highest point of the entire bar.

5 Conclusions

460 We explored how the equilibrium properties of free, migrating alternate bars depend on water discharge through a series of laboratory experiments, where width, channel slope and bed material were kept constant. A proper definition of the most suitable metrics, the analysis of the experimental results, and the comparison with existing theoretical models, allow us to draw the following conclusions:

1. the equilibrium bar height generally decreases with increasing discharge. However at low flows, when bars start emerging
465 from the water surface, an opposite trend is observed, which implies that moderate flows are mainly responsible for the formation of large alternate bedforms;
2. the shape of alternate bars significantly changes with discharge, where relatively low flow conditions are characterized by a high negative skewness of the bed elevation distribution and an important contribution of the higher-order Fourier modes with respect to the fundamental harmonic;
- 470 3. at low discharge, when the width-to-depth ratio is relatively high, the mode-2 Fourier components become increasingly important. However, the channel does not tend to develop regular central bars, but rather a bell-shaped distortion of the average cross section, with deposition preferentially occurring near the center of the channel (mid-channel bars), and scour pools mainly located near the banks;
4. the significant variations of the bar morphology and the associated metrics, allow for identifying four main types of bars,
475 which are associated with different flow conditions with respect to the relevant morphodynamic thresholds;
5. the weakly nonlinear theory allows for a satisfactory prediction of bar height and migration speed, while its capability to reproduce bar shape is limited to a qualitative analysis. Moreover, limiting the bar growth to the fully-wet condition allows for correcting the theoretical predictions at low values of discharge, for which alternate bars tend to emerge from the water surface;

- 480 6. the transition from alternate bar morphology to plane-bed configuration that is expected when discharge exceeds the critical threshold Q_{cr} is not sharp, due to the formation of diagonal bars, which should be regarded as three-dimensional oblique dunes;
7. the definition of ensemble bars that represent the average bar topography clearly highlights the “purely alternate” character of both alternate bars and diagonal bars, which manifests itself as a checkerboard pattern of the Fourier spectrum.
- 485 In general, our definition of ensemble topography can be used for analysing any quasi-periodic morphological pattern, such as curvature-driven point bars forming in meandering rivers.

Code and data availability. A Matlab code for the computation of the critical and resonant conditions (Redolfi et al., 2019) is available at https://bitbucket.org/Marco_Redolfi/bars_res-crit, while a Matlab function for the Fourier analysis of bed topographies is provided at https://bitbucket.org/Marco_Redolfi/fourier_transform_bars. Laboratory data are available at <https://doi.org/10.5281/zenodo.3929371> (Welber et al., 490 2020).

Appendix A: Calculation of Fourier coefficients

Here we detail the procedure needed to expand the signal in the form of Eq. (5), and to calculate the associated coefficients A_{nm} . We start by considering a generic real-valued, two-dimensional signal f_{jk} , defined on a regular grid of $J \times K$ points, whose indexes j and k run from 0 to $J - 1$ and from 0 to $K - 1$, respectively. The two-dimensional, discrete Fourier transform 495 allows for expressing the signal as follows:

$$f_{jk} = \sum_{m=0}^{J-1} \sum_{n=0}^{K-1} F_{nm} \exp \left[2\pi i n \frac{j}{J} + 2\pi i m \frac{k}{K} \right], \quad (\text{A1})$$

where i is the imaginary unit and the complex Fourier coefficients F_{nm} can be calculated through standard Fast Fourier Transform algorithms (e.g., the Matlab FFT2 function).

Considering the $L \times W$ domain illustrated in Figure A1, with the system of reference (x, y) originating at the lower left 500 corner, the coordinates of the grid points can be determined as $x = (j + 0.5) dx$ and $y = (k + 0.5) dy$, where $dx = L/J$ and $dy = W/K$ are the grid spacing in the longitudinal and transverse directions, respectively. In this system of reference, the Fourier expansion of the signal can be expressed as:

$$f_{jk} = \sum_{m=0}^{J-1} \sum_{n=0}^{K-1} F_{nm}^* \exp \left[2\pi i n \frac{x}{L} + 2\pi i m \frac{y}{W} \right], \quad (\text{A2})$$

whose Fourier coefficients can be readily computed as:

$$505 \quad F_{nm}^* = F_{nm} \exp \left[-\pi i \left(\frac{n}{J} + \frac{m}{K} \right) \right]. \quad (\text{A3})$$

Equation (A2) contains both sines and cosines in both the x and y directions, as evident when expanding the complex exponential by means of the Euler's identity:

$$f_{jk} = \sum_{m=0}^{J-1} \sum_{n=0}^{K-1} F_{nm}^* \left[\cos\left(2\pi n \frac{x}{L}\right) \cos\left(2\pi m \frac{y}{W}\right) - \sin\left(2\pi n \frac{x}{L}\right) \sin\left(2\pi m \frac{y}{W}\right) + \right. \\ \left. i \cos\left(2\pi n \frac{x}{L}\right) \sin\left(2\pi m \frac{y}{W}\right) + i \sin\left(2\pi n \frac{x}{L}\right) \cos\left(2\pi m \frac{y}{W}\right) \right]. \quad (\text{A4})$$

Here we are interested to obtain an expression where, consistently with theoretical analyses (e.g., Colombini et al., 1987), only cosines appear in the transverse structure. To obtain such an expression, we start by considering that the signal f_{ij} can be represented in a different way by adding virtual, external points at which arbitrary values are assigned to the signal. This technique is rather common in signal analysis to obtain a different Fourier representation of the same signal: for example, a zero padding is often used to increase the wavelengths of the fundamental harmonic. Specifically, if we extend the grid by adding K virtual points in the y -direction as illustrated in Figure A1, and we compute the Fourier transform as detailed above, we obtain the following expression:

$$f_{jk} = \sum_{m=0}^{J-1} \sum_{n=0}^{2K-1} F_{nm}^* \exp\left[2\pi i n \frac{x}{L} + 2\pi i m \frac{y}{2W}\right], \quad (\text{A5})$$

which is similar to Eq. (A2), except for the transverse wavelength of the fundamental harmonic being twice the channel width ($2W$). The key to eliminate the sine components along the y -direction, is to properly assign the values of f_{ij} at the virtual points. Specifically, if the signal is mirrored with respect to the $y = W$ axis, the sum of all the terms containing $\sin(y)$ identically vanishes, so that the Fourier expansion (A5) can be written as follows:

$$f_{jk} = \sum_{m=0}^{J-1} \sum_{n=0}^{2K-1} F_{nm}^* \cos\left(2\pi m \frac{y}{W}\right) \left[\cos\left(2\pi n \frac{x}{L}\right) + i \sin\left(2\pi n \frac{x}{L}\right) \right]. \quad (\text{A6})$$

Equation (A6) contains redundant information, as components actually having an identical structure appear more than once in the sum. Specifically, it is possible to demonstrate that only $M \times N$ components are needed to exactly represent a real signal, where $N = K$ and M equals $J/2 + 1$ or $(J + 1)/2$, depending on J being an even or an odd number, respectively. Therefore, a proper definition of the coefficients A_{nm} allows for expanding the signal f_{ij} in the following parsimonious way:

$$f_{jk} = \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} \cos\left(2\pi m \frac{y}{2W}\right) \text{Re} \left\{ A_{nm} \left[\cos\left(2\pi n \frac{x}{L}\right) + i \sin\left(2\pi n \frac{x}{L}\right) \right] \right\}, \quad (\text{A7})$$

which can be equivalently written in the form of Eq. (5) after expressing the complex coefficients in terms on their amplitude and phase:

$$A_{nm} = |A_{nm}| \exp(i \phi_{nm}). \quad (\text{A8})$$

The Fourier coefficients A_{mn} can be directly derived from the F_{nm}^* coefficients, and can be computed for a generic f_{jk} signal using the Matlab code we made available at https://bitbucket.org/Marco_Redolfi/fourier_transform_bars.




Figure A1. Illustration of the grid used to discretize a domain of size $L \times W$, where W is the channel width. Grid points are identified by the indexes j and k (x and y direction, respectively), and are equally spaced at intervals dx and dy . The original grid contains $J \times K$ points (closed circles), while the extended grid, obtained by adding virtual external points (open circles), is formed by $J \times 2K$ points that cover a total width $2W$.

Author contributions. MR analysed the data, wrote the manuscript, and responded to the referees' comments; MW designed and performed
535 the experiments, processed data and wrote part of the manuscript; MC performed the calculations by means on the weakly nonlinear theory;
MT supervised the work; WB designed the experiments and revised the paper. All authors contributed in the interpretation of the results.

Competing interests. The authors declare that they have no conflict of interest.

Acknowledgements. The research was funded by the project: GLORI - Glaciers-to-rivers sediment transfer in Alpine basins (Autonomous
540 discussion. Province of Bozen-Bolzano). We thank Chris Paola and Eric Prokocki for the stimulating comments and Marco Colombini for the interesting

References

- Adami, L., Bertoldi, W., and Zolezzi, G.: Multidecadal dynamics of alternate bars in the Alpine Rhine River, *Water Resources Research*, <https://doi.org/10.1002/2015WR018228>, 2016.
- Ahmari, H. and Da Silva, A. M. F.: Regions of bars, meandering and braiding in da Silva and Yalin's plan, *Journal of Hydraulic Research*, 49, 718–727, <https://doi.org/10.1080/00221686.2011.614518>, 2011.
- Ashmore, P.: Morphology and Dynamics of Braided Rivers, in: *Treatise on Geomorphology*, vol. 9, pp. 289–312, Elsevier, <https://doi.org/10.1016/B978-0-12-374739-6.00242-6>, 2013.
- Ashmore, P. E.: Laboratory modelling of gravel braided stream morphology, *Earth Surface Processes and Landforms*, 7, 201–225, <https://doi.org/10.1002/esp.3290070301>, 1982.
- 550 Bertagni, M. B. and Camporeale, C.: Finite amplitude of free alternate bars with suspended load, *Water Resources Research*, <https://doi.org/10.1029/2018WR022819>, 2018.
- Bertoldi, W., Gurnell, A. M., and Drake, N. A.: The topographic signature of vegetation development along a braided river: Results of a combined analysis of airborne lidar, color air photographs, and ground measurements, *Water Resources Research*, 47, <https://doi.org/10.1029/2010WR010319>, 2011.
- 555 Blondeaux, P. and Seminara, G.: A Unified Bar Bend Theory of River Meanders, *Journal of Fluid Mechanics*, 157, 449–470, 1985.
- Callander, R. A.: Instability and river channels, *Journal of Fluid Mechanics*, 36, 465–480, <https://doi.org/10.1017/S0022112069001765>, 1969.
- Church, M. and Rice, S. P.: Form and growth of bars in a wandering gravel-bed river, *Earth Surface Processes and Landforms*, 34, 1422–1432, <https://doi.org/10.1002/esp.1831>, 2009.
- 560 Colombini, M. and Stocchino, A.: Three-dimensional river bed forms, *Journal of Fluid Mechanics*, 695, 63–80, <https://doi.org/10.1017/jfm.2011.556>, 2012.
- Colombini, M. and Tubino, M.: Finite-amplitude free bars: a fully non-linear spectral solution, in: *Euromech*, vol. 262, pp. 163–169, 1991.
- Colombini, M., Seminara, G., and Tubino, M.: Finite-amplitude alternate bars, *Journal of Fluid Mechanics*, 181, 213, <https://doi.org/10.1017/S0022112087002064>, 1987.
- 565 Cordier, F., Tassi, P., Claude, N., Crosato, A., Rodrigues, S., and Pham Van Bang, D.: Numerical Study of Alternate Bars in Alluvial Channels With Nonuniform Sediment, *Water Resources Research*, pp. 2976–3003, <https://doi.org/10.1029/2017WR022420>, 2019.
- Crosato, A. and Mosselman, E.: Simple physics-based predictor for the number of river bars and the transition between meandering and braiding, *Water Resources Research*, 45, 1–14, <https://doi.org/10.1029/2008WR007242>, 2009.
- Crosato, A. and Mosselman, E.: An Integrated Review of River Bars for Engineering, Management and Transdisciplinary Research, *Water*, 12, 596, <https://doi.org/10.3390/w12020596>, 2020.
- 570 Crosato, A., Mosselman, E., Beidmaria Dest, F., and Uijtewaal, W. S. J.: Experimental and numerical evidence for intrinsic nonmigrating bars in alluvial channels, *Water Resources Research*, 47, <https://doi.org/10.1029/2010WR009714>, 2011.
- Defina, A.: Numerical experiments on bar growth, *Water Resources Research*, 39, 1–12, <https://doi.org/10.1029/2002WR001455>, 2003.
- Duró, G., Crosato, A., and Tassi, P.: Numerical study on river bar response to spatial variations of channel width, *Advances in Water Resources*, 93, 21–38, <https://doi.org/10.1016/j.advwatres.2015.10.003>, 2016.
- Eaton, B. C., Millar, R. G., and Davidson, S.: Channel patterns: Braided, anabranching, and single-thread, *Geomorphology*, 120, 353–364, <https://doi.org/10.1016/j.geomorph.2010.04.010>, 2010.

- Eekhout, J. P., Hoitink, A. J., and Mosselman, E.: Field experiment on alternate bar development in a straight sand-bed stream, *Water Resources Research*, 49, 8357–8369, <https://doi.org/10.1002/2013WR014259>, 2013.
- 580 Einstein, H. A. and Shen, H. W.: A study on meandering in straight alluvial channels, *Journal of Geophysical Research*, 69, 5239–5247, <https://doi.org/10.1029/jz069i024p05239>, 1964.
- Engels, H.: *Handbuch des Wasserbaues: für das Studium und die Praxis*, vol. 1, W. Engelmann, 1914.
- Engelund, F. and Fredsoe, J.: Sediment Ripples and Dunes, *Annual Review of Fluid Mechanics*, 14, 13–37, <https://doi.org/10.1146/annurev.fl.14.010182.000305>, 1982.
- 585 Federici, B. and Seminara, G.: On the convective nature of bar instability, *Journal of Fluid Mechanics*, 487, 125–145, <https://doi.org/10.1017/S0022112003004737>, 2003.
- Ferguson, R. and Church, M.: A Simple Universal Equation for Grain Settling Velocity, *Journal of Sedimentary Research*, 74, 933–937, <https://doi.org/10.1306/051204740933>, 2004.
- Ferguson, R. I.: The missing dimension: Effects of lateral variation on 1-D calculations of fluvial bedload transport, *Geomorphology*, 56, 590 1–14, [https://doi.org/10.1016/S0169-555X\(03\)00042-4](https://doi.org/10.1016/S0169-555X(03)00042-4), 2003.
- Francalanci, S., Solari, L., Toffolon, M., and Parker, G.: Do alternate bars affect sediment transport and flow resistance in gravel-bed rivers?, *Earth Surface Processes and Landforms*, 37, 866–875, <https://doi.org/10.1002/esp.3217>, 2012.
- Fredsoe, J.: Meandering and Braiding of Rivers, *Journal of Fluid Mechanics*, 84, 609–624, <https://doi.org/10.1017/S0022112078000373>, 1978.
- 595 Fujita, Y. and Muramoto, Y.: Experimental Study on Stream Channel Processes in Alluvial Rivers, Tech. Rep. 288, 1982.
- Fujita, Y. and Muramoto, Y.: Studies on the Process of Development of Alternate Bars, Tech. Rep. 3, 1985.
- Garcia, M. and Nino, Y.: Dynamics of sediment bars in straight and meandering channels: Experiments on the resonance phenomenon, *Journal of Hydraulic Research*, 32, 632–635, <https://doi.org/10.1080/00221686.1994.9728360>, 1994.
- Garcia Lugo, G. A., Bertoldi, W., Henshaw, A. J., and Gurnell, A. M.: The effect of lateral confinement on gravel bed river morphology, 600 *Water Resources Research*, 51, 7145–7158, <https://doi.org/10.1002/2015WR017081>, 2015.
- Gilvear, D., Francis, R., Willby, N., and Gurnell, A.: 26 Gravel bars: a key habitat of gravel-bed rivers for vegetation, *Developments in Earth surface processes*, 11, 677–700, [https://doi.org/10.1016/S0928-2025\(07\)11154-8](https://doi.org/10.1016/S0928-2025(07)11154-8), 2007.
- Hansen, E.: The formation of meanders as a stability problem, *Basic Res. Prog. Rep.*, 13, 9–13, 1967.
- Hoey, T. B. and Sutherland, A. J.: Channel morphology and bedload pulses in braided rivers: a laboratory study, *Earth Surface Processes and Landforms*, 16, 447–462, <https://doi.org/10.1002/esp.3290160506>, 1991.
- 605 Ikeda, S.: Incipient motion of sand particles on side slopes, *Journal of Hydraulic Division*, 108, 95–114, 1982.
- Ikeda, S.: Prediction of Alternate Bar Wavelength and Height, *Journal of Hydraulic Engineering*, 110, 371–386, [https://doi.org/10.1061/\(ASCE\)0733-9429\(1984\)110:4\(371\)](https://doi.org/10.1061/(ASCE)0733-9429(1984)110:4(371)), 1984.
- Jaballah, M., Camenen, B., Pénard, L., and Paquier, A.: Alternate bar development in an alpine river following engineering works, *Advances in Water Resources*, 81, 103–113, <https://doi.org/10.1016/j.advwatres.2015.03.003>, 2015.
- 610 Jaeggi, M. N. R.: Formation and Effects of Alternate Bars, *Journal of Hydraulic Engineering*, 110, 142–156, [https://doi.org/10.1061/\(ASCE\)0733-9429\(1984\)110:2\(142\)](https://doi.org/10.1061/(ASCE)0733-9429(1984)110:2(142)), 1984.
- Lanzoni, S.: Experiments on bar formation in a straight flume: 1. Uniform sediment, *Water Resources Research*, 36, 3337–3349, <https://doi.org/10.1029/2000WR900160>, 2000a.

- 615 Lanzoni, S.: Experiments on bar formation in a straight flume 2. Graded sediment, *Water Resources Research*, 36, 3351–3363, <https://doi.org/10.1029/2000WR900161>, 2000b.
- Lewin, J.: Initiation of bed forms and meanders in coarse-grained sediment, *Bulletin of the Geological Society of America*, 87, 281–285, [https://doi.org/10.1130/0016-7606\(1976\)87<281:IOBFAM>2.0.CO;2](https://doi.org/10.1130/0016-7606(1976)87<281:IOBFAM>2.0.CO;2), 1976.
- Liébault, F., Lallias-Tacon, S., Cassel, M., and Talaska, N.: Long profile responses of alpine braided rivers in se France, *River Research and Applications*, 29, 1253–1266, <https://doi.org/10.1002/rra.2615>, 2013.
- 620 Nelson, J. M.: The initial instability and finite-amplitude stability of alternate bars in straight channels, *Earth Science Reviews*, 29, 97–115, [https://doi.org/10.1016/0012-8252\(0\)90030-Y](https://doi.org/10.1016/0012-8252(0)90030-Y), 1990.
- Nicholas, A. P.: Reduced-complexity modeling of free bar morphodynamics in alluvial channels, *Journal of Geophysical Research: Earth Surface*, 115, 1–16, <https://doi.org/10.1029/2010JF001774>, 2010.
- 625 Paola, C.: Incoherent structure: turbulence as a metaphor for stream braiding, *Coherent Flow Structures in Open Channels*, 65, 705–723, 1996.
- Parker, G.: On the cause and characteristic scales of meandering and braiding in rivers, *Journal of Fluid Mechanics*, 76, 457, <https://doi.org/10.1017/S0022112076000748>, 1976.
- Parker, G.: Self-formed straight rivers with equilibrium banks and mobile bed. Part 2. The gravel river, *Journal of Fluid Mechanics*, 89, 127, <https://doi.org/10.1017/S0022112078002505>, 1978.
- 630 Qian, H., Cao, Z., Liu, H., and Pender, G.: Numerical modelling of alternate bar formation, development and sediment sorting in straight channels, *Earth Surface Processes and Landforms*, 42, 555–574, <https://doi.org/10.1002/esp.3988>, 2017.
- Redolfi, M., Tubino, M., Bertoldi, W., and Brasington, J.: Analysis of reach-scale elevation distribution in braided rivers: Definition of a new morphologic indicator and estimation of mean quantities, *Water Resources Research*, 52, 5951–5970, <https://doi.org/10.1002/2015WR017918>, 2016.
- 635 Redolfi, M., Zolezzi, G., and Tubino, M.: Free and forced morphodynamics of river bifurcations, *Earth Surface Processes and Landforms*, 44, <https://doi.org/10.1002/esp.4561>, 2019.
- Rhoads, B. L. and Welford, M. R.: Initiation of river meandering, *Progress in Physical Geography*, 15, 127–156, <https://doi.org/10.1177/030913339101500201>, 1991.
- 640 Rodrigues, S., Mosselman, E., Claude, N., Wintenberger, C. L., and Juge, P.: Alternate bars in a sandy gravel bed river: Generation, migration and interactions with superimposed dunes, *Earth Surface Processes and Landforms*, 40, 610–628, <https://doi.org/10.1002/esp.3657>, 2015.
- Schuurman, F. and Kleinhans, M. G.: Bar dynamics and bifurcation evolution in a modelled braided sand-bed river, *Earth Surface Processes and Landforms*, 40, 1318–1333, <https://doi.org/10.1002/esp.3722>, 2015.
- Seminara, G. and Tubino, M.: Alternate Bars and Meandering : Free , Forced and Mixed Interactions, in: *River Meandering*, edited by Ikeda, S. and Parker, G., vol. 12, pp. 267 – 320, AGU, Washington, D.C., 1989.
- 645 Siviglia, A., Stecca, G., Vanzo, D., Zolezzi, G., Toro, E. F., and Tubino, M.: Numerical modelling of two-dimensional morphodynamics with applications to river bars and bifurcations, *Advances in Water Resources*, 52, 243–260, <https://doi.org/10.1016/j.advwatres.2012.11.010>, 2013.
- Sukegawa, N.: Criterion for alternate bar formation in experimental flumes, *Proceedings of the Japan Society of Civil Engineers*, pp. 47–50, https://doi.org/10.2208/jscej1969.1972.207_47, 1972.
- 650 Tubino, M., Repetto, R., and Zolezzi, G.: Free bars in rivers, *Journal of Hydraulic Research*, 37, 759–775, <https://doi.org/10.1080/00221689909498510>, 1999.

- Welber, M., Redolfi, M., and Bertoldi, W.: Laboratory experiments on river alternate bars [Data set], Zenodo, <https://doi.org/10.5281/zenodo.3929371>, 2020.
- 655 Zeng, Q., Shi, L., Wen, L., Chen, J., Duo, H., and Lei, G.: Gravel bars can be critical for biodiversity conservation: A case study on Scaly-sided Merganser in South China, PLoS ONE, 10, 1–13, <https://doi.org/10.1371/journal.pone.0127387>, 2015.
- Zolezzi, G. and Seminara, G.: Downstream and upstream influence in river meandering. Part 1. General theory and application to overdeepening, Journal of Fluid Mechanics, 438, 213–230, <https://doi.org/10.1017/S002211200100427X>, 2001.
- Zolezzi, G., Guala, M., Termini, D., and Seminara, G.: Experimental observations of upstream overdeepening, Journal of Fluid Mechanics, 660 531, 191–219, <https://doi.org/10.1017/S0022112005003927>, 2005.