Beyond 2D <u>landslide</u> inventories <u>and their rollover</u>: synoptic 3D <u>landslide inventories and</u> volume <u>calculation</u> from repeat LiDAR data

Thomas G. Bernard, Dimitri Lague, Philippe Steer Univ Rennes, CNRS, Géosciences Rennes - UMR 6118, 35000, Rennes, France

5

10

Abstract. Efficient and robust landslide mapping and volume estimation is essential to rapidly infer landslide spatial distribution, to quantify the role of triggering events on landscape changes and to assess direct and secondary landslide-related geomorphic hazards. Many efforts have been made during the last decades to develop landslide areal-mapping methods, based on 2D satellite or aerial images, and to constrain the empirical volume-area (V-A) relationship allowing in turn to offer indirect

- estimates of landslide volume. Despite these efforts, some major issues remain including the uncertainty of the V-A scaling, landslide amalgamation and the under-detection of reactivated landslides. To address these issues, we propose a new semiautomatic 3D point cloud differencing method to detect geomorphic changes, obtain robust landslide inventories with an <u>uncertainty metric</u> and directly measure the volume and geometric properties of landslides. This method is based on the M3C2
- 15 algorithm and was applied to a multi-temporal airborne LiDAR dataset of the Kaikoura region, New Zealand, following the M_w 7.8 earthquake of 14 November 2016.

WeIn a 5 km² area, our 3D workflow detects 524 landslide sources and 304 deposits with a minimum size of 20 m² and a total volume of 752,616 \pm 154,165 m³ and 949,742 \pm 150,014 m³, respectively. Geometric properties of the 3D inventory, including the V-A relationship, are consistent with previous results, except for the lack of the classically observed rollover of the

- 20 distribution of source area. A 2D inventory hand-crafted from aerial image comparison only identified 258 landslide scars, exhibits a rollover in the distribution of source area and severely underestimates the total area and volume of 3D detected sources by 75 % and 60 %, respectively. Detection and delimitation errors in 2D occurs in areas with limited texture change (bare rock surfaces, forests) and at the transition between sources and deposits that the 3D method accurately captures. Large rotational/translational landslides are missed in the 2D inventory owing to the dominant vertical topographic change. Our data
- 25 show a systematic size-dependent under-detection in the 2D inventory below 200 m² that may explain all or part of the classical rollover observed in 2D landslide source area distribution. While the 3D segmentation of complex clustered landslides sources remains challenging, we demonstrate that 3D point cloud differencing offers a greater sensitivity to detect small changes than a classical difference of DEMs (digital elevation models), In a small 5 km² area, prone to landslide reactivation and amalgamation, where a previous study identified 27 landslides, our method is able to detect 1431 landslide sources and 853
- 30 deposits with a total volume of 908,055 ± 215,640 m³ and 1,008,626 ± 172,745 m³, respectively. This high number of landslides is set by the ability of our method to detect subtle changes and therefore small landslides with a carefully constrained lower limit of 20 m² (90% with A<300 m²). Moreover, the analysis of landslide geometric properties reveals the absence of a rollover

Mis en forme : Anglais (États-Unis)
Mis en forme : Anglais (États-Unis)

Mis en forme : Couleur de police : Texte 1

in the landslide area distribution, which is a feature classically described in the literature. This result suggests that the rollover behaviour previously observed is due to an under detection of small landslides. Reactivated landslides represent 27.2 % of the 35
total landslide source area and 29.9 ± 12.8 % of the total volume. Reactivated landslides are located in areas where landslide mapping methods based on 2D images are assumed to perform poorly due to the weak contrast in texture and colour between the two epochs. Our result therefore suggests that the number, area and volume of landslides can be significantly underestimated by these methods. To our knowledge, this is the first approach to create a regional landslide inventory map from 3D point cloud differencing. Our results call for a more systematic useOur results underline the vast potential of high resolution
3D topographic data to assess3D-derived inventories in quantifying exhaustively and objectively the impact of extreme events

40 3D topographic data to assess 3D-derived inventories in quantifying exhaustively and objectively the impact of extreme events on topographic ehangeschange in regions prone to landsliding and to inferexplore in new ways the geometric scaling properties of landslides.

1. Introduction

- 45 In mountain areas, extreme events such as large earthquakes and typhoons can trigger thousands of landslides.important topographic changes through landsliding. Landslides are a key agent of hillslope and landscape erosion (Keefer, 1994; Malamud et al., 2004) and represent a significant hazard for local populations. Efficient and rapid mapping of landslides is required to robustly infer their spatial distribution, their total volume, and the induced landscape changes-and the associated. Such information are crucial to understand the role of triggering events on landscape evolution and to manage direct and
- 50 secondary landslide-related hazards (Guzzetti et al., 2012; Hovius et al., 1997; Marc et al., 2016; Parker et al., 2011). Following a triggering event, total landslide volume over a regional scale is classically determined in two steps: (i) individual landslide mapping using 2D satellite or aerial images (e.g., Behling et al., 2014; Fan et al., 2019; Guzetti et al., 2012; Li et al., 2014; Martha et al., 2010; Massey et al., 2018; Parker et al. 2011)Following a triggering event, total landslide volume over a regional scale is classically determined in two steps: (i) individual landslide mapping using 2D satellite or aerial images (e.g., Behling
- 55 et al., 2014; Fan et al., 2019; Guzzetti et al., 2012; Li et al., 2014; Malamud et al., 2004; Martha et al., 2010; Massey et al., 2018; Parker et al., 2011) and (ii) indirect volume estimation using a volume-area relationship (e.g. Simonett, 1967; Larsen et al., 2010); e.g. Simonett, 1967; Larsen et al., 2010):

$$V = \alpha A^{\gamma} \tag{1}$$

with *V* and *A* the volume and area of individual landslides, α a prefactor and γ a scaling exponent ranging between 1.3 and 1.6 60 (e.g., Larsen et al., 2010, Massey et al., 2020).1 and 1.6 (e.g. Larsen et al., 2010; Massey et al., 2020).

A first source of error comes from the uncertainty on the values of α and γ which tend to be site specific and <u>potentially</u> process specific (e.g. shallow versus bedrock landsliding). This uncertainty could lead to an order magnitude of difference in total estimated volume given the non-linearity of eq. (1) (Larsen et al., 2010).(Larsen et al., 2010). Two other sources of error arise from the detectability of individual landslides themselves and the ability to accurately measure the distribution of landslide

- 65 areas, due to landslide amalgamation and under-detection of reactivated-landslides. Landslide amalgamation can produce up to 200 % error in the total volume estimation (Li et al., 2014; Mare and Hovius, 2015)(Li et al., 2014; Marc and Hovius, 2015) and occurs because of landslide spatial clustering or incorrect mapping due, for instance, to automatic processing. Indeed, automatic landslide mapping (Behling et al., 2014; Marc et al., 2019; Martha et al., 2010; Pradhan et al., 2016) relies on the difference in texture, color and spectral properties such as NDVI (Normalized difference vegetation index) of multispectral
- 2D images between pre- and post-landslide images, assuming that landslides lead to vegetation removal or significant texture change. During this process, difficulties in automatic segmentation of landslide sources can result in incorrect estimate of individual landslide area, which propagates into a much larger estimate of volume owing to the non-linearity of eq. (1). Manual mapping and automatic algorithms based on geometrical and topographical inconsistencies can-enable to reduce the amalgamation effect on landslide volume estimation (Mare and Hovius, 2015) (Marc and Hovius, 2015), but it remains a source
- 75 of error due to the inherent spatial clustering of landslides and the overlapping of landslide deposits and sources. Underdetection of reactivated landslides occurs because the spectral signature of images is not sufficiently altered by a new failure. This phenomenon is particularly important in areas with thin soils and sparse or total lack of vegetation (Behling et al., 2014). Guzetti et al. (2009) show that the proportion of landslide volume mobilized by reactivations can reach 62% for an individual snowmelt or rainfall events. Yet, the level of landslide reactivation in a given inventory remains generally largely unknown.
- 80 The delimitation of reactivated landslides is therefore critical to robustly infer total landslide volume. To better detect reactivated landslides, Behling et al. (2014, 2016) developed a method using temporal NDVI-trajectories which describe Under-detection of landslides can occur because the spectral signature of images is not sufficiently altered by a new failure. Notably, under-detection of small landslides is one hypothesis put forward to explain the rollover classically observed in the distribution of landslide area (e.g., Stark and Hovius, 2001), even if the emergence of a rollover is predicted by mechanical
- 85 models of landslide failures at the regional scale (e.g. Jeandet et al., 2019; Tanyaş et al., 2019 and references therein). Underdetection can be particularly important in areas with thin soils and sparse or missing vegetation (Behling et al., 2014). It can be further complicated when using different image sources with different resolution, spectral resolution, projected shadows and consequent ability to detect surface change. Yet, the level of under-detection of landslide in a given inventory remains generally largely unknown. The delimitation of landslides in areas with poor or total lack of vegetation is therefore critical to
- 90 robustly infer landslide area distribution and total volume. To deal with poor vegetated areas, Behling et al. (2014, 2016) developed a method using temporal NDVI-trajectories which describes the temporal footprints of vegetation changes but cannot fully address complex cases when texture is not significantly changing such as bedrock landsliding on bare rock hillslopes.
- _Addressing these three sources of uncertainty volume-area scaling uncertainty, landslide amalgamation and the under-95 detection of landslide reactivationlandslides - requires-to explore new approaches to obtain and analyse landslide inventories. 96 In the last decade, the increasing availability of multi-temporal high resolution 3D point cloud data and digital elevation models 97 (DEM), based on aerial or satellite photogrammetry and Light Detection and Ranging (LiDAR), has opened the possibility to 98 better quantify landside volume and displacement (Bull et al., 2010; Mouyen et al., 2019; Okyay et al., 2019; Passalacqua et

al., 2015; Ventura et al., 2011)(Bull et al., 2010; Mouyen et al., 2019; Okyay et al., 2019; Passalacqua et al., 2015; Ventura et al., 2011).

- The most commonly used technique is the difference of DEM (DoD) which consists in computingcomputes the vertical elevation differences between two DEMs of different time (Corsini et al., 2009; Giordan et al., 2013; Mora et al., 2018; Wheaton et al., 2010). Even though this method is fast and works properly on planar surface, a vertical difference can be prone to strong errors when used to quantify changes on vertical or very steep surfaces where landsliding typically occurs (e.g., Lague et al., 2013). Even though this method is fast and works properly on planar surface, a vertical difference can be prone to strong errors when used to quantify changes on vertical or very steep surfaces where landsliding typically occurs (e.g., Lague et al., 2013). Even though this method is fast and works properly on planar surface, a vertical difference can be prone to strong errors when used to quantify changes on vertical or very steep surfaces where landsliding typically occurs (e.g., Lague et al., 2013).
- et al., 2013). The "Multiscale model-to-model cloud comparison" (M3C2) algorithm implemented by Lague et al. (2013) rather considers a direct 3D point cloud comparison. This algorithm has three main advantages over a DoD: (i) it operates directly on 3D point clouds, avoiding a phase of DEM creation that is conducive to a loss of resolution imposed by the pixelcell size
- 110 and potential data interpolation, (ii) it computes 3D distances along the normal direction of the topographic surface, allowing to better capture of subtle changes on steep surfaces, and (iii) it computes a spatially variable confidence interval that accounts for surface roughness, point density and uncertainties in data registration. Applicable to any type of 3D data to measure the orthogonal distance between two point clouds, this approach has generally been used for Terrestrial Lidarterrestrial lidar
- UAV photogrammetry over sub-kilometer scales. In the context of landsliding, it has been used to infer the displacement and volume of individual landslides, using point clouds obtained by UAV photogrammetry (e.g., Esposito et al., 2017; Stumpf et al., 2015), as well as for rockfall studies (Benjamin et al.2016; Williams et al., 2018). Yet, to our knowledge, the systematic detection and segmentation of hundreds of landslides, at a regional scale, from 3D point cloud have not yet been attempted.(Benjamin et al., 2020; Williams et al., 2018) and sediment tracking in post-wildfire conditions (DiBiase and Lamb, 2020). To our knowledge, systematic detection and segmentation of hundreds of landslides from 3D point clouds have not yet
- 120 been attempted.

Here, we produce an inventory map of landslide topographic changes using a semi-automatic 3D point cloud differencing (<u>3D-PcD</u>) method based on M3C2 and applied to multi-temporal airborne LiDAR data. We <u>investigateuse</u> the <u>potentialgeneric term</u> of this method to robustly infer-"landslide-volumes" to define the spatially coherent changes detected by our method on hillslopes that result in a region prone to at least several decimeter of erosion (i.e., scars or sources) or deposition. This definition

- 125 therefore includes all the types of mass wasting processes which involves the rapid displacement of soil, rocks and debris. The <u>3D</u> landslide reactivation and amalgamation. inventory is then compared to a traditional manually mapped inventory of landslide scars based on aerial image comparison, hereafter called the 2D inventory. We applied apply our method to a complex topography located near Kaikoura, New Zealand, where the 2016 Mw 7.8 earthquake triggered nearly 30,000 landslides over a 10,000 km² area (Massey et al., 2020). We choose a 5 km²A large part of these landslides have been mapped by Massey et al.
- 130 <u>al. (2020) providing a region based landslide distribution</u> area characterized by a high landslide spatial density along the Conway segment of the Hope fault, inactive during the earthquake, where pre- and post earthquake LiDARV-A scaling relationships. We choose a 5 km² area characterized by a high landslide spatial density along the Conway segment of the Hope

fault, inactive during the earthquake, where pre- and post-earthquake LiDAR and aerial images were available and investigate the proportion of reactivated landslide volume on the total budget (Fig. 1). This area has a variety of vegetation cover (e.g. trees, shrubsforest, sparse or low vegetation, bare bedrock) and pre-existing landslides, and typically represents a challenge for conventional 2D landslide mapping. We illustrate the benefits of working directly on 3D data to generate landslide <u>source</u> and deposit inventories, and discuss the methodological advantages to operate directly on point clouds with M3C2 compared to DoD in terms of detection accuracy and error for total landslide volume.

The paper is organized as followed: first, the LiDAR dataset is presented followed by a <u>detailed</u> description of the 3D-point cloud differencing_PcD method. Second, results of the geomorphic changeschange detection and <u>identification of individual</u> landslides <u>individualization method applied to in</u> the <u>studystudied</u> area are presented. <u>Detected landslidesThe remaining part</u> of the paper focuses only on landslide sources. First, the comparison with conventional 2D landslide mapping is presented. <u>Then, the statistical</u> properties <u>of the 3D and 2D landslide source inventories</u> are then-investigated in terms of area and volume₇ specifically for reactivated and new landslides. Finally, current limitations of the method are discussed as well as knowledge gained on the importance of landslide reactivationunder-detection on the co-seismic landslide inventory budget and landslide







Figure 1: Maps of the regional context_x and location and visualization of the study area. (a) Regional map of Kaikoura with the location of the 2016 M_b. 7.8 earthquake, associated active faults and the study area. (b) Orthophotos-c) Orthoimages focused on the study area dated before and after the earthquake with the 5 km² LiDAR dataset extent used in this paper (all imageriesimages are available at https://datalinz.govt.nz/set/4702-nz-aerial-imagery/, Aerial survey 2017).

Mis en forme : Indice

2. Data description

In this study, we compare two 3D point clouds obtained from airborne LiDAR data <u>collected</u> before and after the November 14 2016 Kaikoura earthquake (Table.). Both airborne LiDAR surveys were acquired during summer. Pre-earthquake (<u>pre-EQ</u>) LiDAR data represents a combination of were collated over six flights performed from March 13, 2014 to March 20, 2014 for a resulting ground point density of 3.8 ± 2.1 pts/m². The vertical accuracy of this dataset has been estimated at 0.068 m to 0.165 m from check points located on highways (Dolan and Rhodes, 2016). The post-earthquake<u>as</u> the standard deviation of the difference between the elevation of GPS points located on highways and the nearest neighbour LiDAR shot elevation

160 (Dolan and Rhodes, 2016). The post-earthquake (post-EQ) LiDAR survey took place rapidly after the earthquake from December 3, 2016 to January 6, 2017 for an average ground point density of 11.5 ± 6.8 pts/m². Vertical The vertical accuracy of this dataset assessed on ground classified points ishas been estimated following the same protocol than the pre-earthquake LiDAR data with a mean of 0.00 m and a standard deviation of 0.04 m (Aerial survey, 2017). The difference in acquisition dates represents a period of 2 years and 8 months. The vegetation of For both datasets was removed using LiDAR point clouds,

- 165 only ground points defined by the data provider are selected (see details of the classification provided by the downloaded data in Dolan, 2014). Manual quality control showed that some points located on vegetation remained in the pre-EQ data. As these points are located a few meters above the ground, they can lead to keep only ground points. false landslide detection. We thus reprocessed this dataset to remove incorrectly classified points (details in section S1 in the supplements). Removed points represent 0.3% of the pre-EQ original point cloud.
- 170 In addition-to LiDAR data, orthophotos, orthoimages were used to visually validateperform a manual mapping of landslides to compare the detection of landslides from the 3D approach for new landslide sources.and a more classical approach. The pre-earthquake orthophotoEQ orthoimage was obtained on January 24 2015 (available at https://data.linz.govt.nz/layer/52602canterbury-03m-rural-aerial-photos-2014-2015) and the post-earthquakeEQ one on December 15 2016. The resolutions are 0.3 and 0.2 m, respectively.

175

Table 1+1 : Information about LiDAR data used in this study.

	Pre-earthquake LiDAR	Post-earthquake LiDAR
Date of acquisition	13/03/2014 - 20/03/2014	03/12/2016 - 06/01/2017
Commissioned		I and Information News
Commissioned	USC-UCLA-GNS science/NCALM	
by/provided by		Zealand/AAM NZ
Availability	https://doi.org/10.5069/G9G44N75	On request <u>at</u>
	mtps.//doi.org/10.5007/070441175	gisbasemap.ecan.govt.nz
Original point density		
(pts/m ²)	9.02	-19.2 ± 11.7
Number of ground		10 5 0 0 0 0
points	10,660,089	63,729,096
Ground point density	28 + 21	115 . 69
(pts/m ²)	3.8 ± 2.1	11.3 ± 0.8
Vertical accuracy (m)	0.068 - 0.165	0.04 m
Study area (m ²)	5,253,133	5,253,133

Mis en forme : Police :8 pt, Motif : Transparente (Blanc)

Mis en forme : Paragraphes solidaires

3. Methods: 3D point cloud differencing to detect and measure landslidesparameter choice

3.1. 3D point cloud differencing with M3C2

180 The method developed here to detect landslides consists in a 3D point cloud differencing between two epochs using the M3C2 algorithm (Lague et al., 2013)The method developed here to detect landslides consists of 3D point cloud differencing between

two epochs using the M3C2 algorithm (Lague et al., 2013) available in the Cloudcompare software (Cloudcompare v2.11, 2020). This algorithm estimates orthogonal distances along the surface normal directly on 3D point clouds without the need for surface interpolation or gridding. While M3C2 can be applied on all points, the algorithm can use an accessory point cloud,

185 called core points, of arbitrary geometry which we impose in. In our case to be, core points constitute a regular grid with constant horizontal spacing generated by the rasterization of one of the two clouds. AllIn the following, all the M3C2 calculations will beare done in 3D using the raw point clouds, but the results will beare "stored" on the core points. The use of a regular grid of core points has four advantages: (i) a regular sampling of the results which allows to compute computation of robust statistics of changes, unbiased by spatial variations in point density; (ii) it facilitates the volume calculation and the uncertainty assessment on total volume; (iii) it can be directly reused with 2D GIS as a raster; (rather than a non-regular point

cloud): and (iv) it speeds up calculations, although in the proposed workflow, computation time is not an issue and can be done on a regular laptop.

The first step of M3C2 consists in the calculation of computing a 3D surface normal for each core point at a scale D (called the normal scale) by fitting a plane to the <u>core</u> points of the first dataset located within a radius of size D/2-of the core point. Once the normal vectors are defined, the local distance between the two clouds is computed for each core point as the distance of the average positions of the two point clouds at a scale d (projection scale). This is done by defining a cylinder of radius d/2, oriented along the normal with a maximum length p_{max} . Distances are not computed if no intercept is found in the second point cloud. M3C2 also provides uncertainty on the computed distance at 95% of confidence based on local roughness, point density and registration error as followfollows:

$$LoD_{95\%}(d) = \pm 1.96\left(\sqrt{\frac{\sigma_1(d)^2}{n_1} + \frac{\sigma_2(d)^2}{n_2}} + reg\right)$$
(2)

where LoD_{95%} is the Level of Detection, σ₁(d) etand σ₂(d) are the detrended roughnessstandard deviation of distances of each cloud, at scale d₂ measured along the normal direction, n₁ and n₂ are the number of points and reg is the co-registration error between the two epochs, <u>Reg is</u> assumed to be spatially uniform and isotropic in our case, but which could be spatially variable and anisotropic (James et al., 2017). Because point density and surface roughness are spatially variable, <u>LoD_{95%} is also spatially variable</u>. For instance, M3C2 has the option to compute the distance vertically which bypasses the normal calculation, and we use this option several time in the workflow. We use the abbreviation vertical M3C2 in that case and 3D M3C2 otherwise.
3.2 Parameters in forested steep hillslopes, points located under the canopy, with a lower point density, or vegetation points incorrectly filtered out creating locally high roughness, result into a higher LoD_{95%} makes the conservative choice of adding the registration error to the combined standard error related to point cloud roughness, rather than taking the square root of the sum of squared standard error and squared registration. This choice is dictated by the simplistic hypothesis of using a spatially uniform and isotropic reg, while in reality reg varies spatially due to intra-survey registration errors of flight lines, and inter-

Mis en forme : Couleur de police : Automatique

survey rigid registration (Passalacqua et al., 2015). M3C2 has the option to compute the distance vertically which bypasses the normal calculation, and we use this option several times in the workflow. We use the abbreviation vertical-M3C2 in that case

3.2. The Same Surface Different Sampling test

Following the approach proposed in Lague et al. (2013), we use a test based on using different sampling of the same natural surface to tune parameters of the workflow and apply the entire workflow. To this end, we create two randomly sub-sampled
versions of the post-earthquake LiDAR data (which has the largest point density) with an average point density equal to the pre-EQ data. The resulting point clouds corresponds exactly to the same surface (i.e., *reg=*0), with roughness characteristics typical of the studied area, but with different point sampling. Applying the entire workflow to these two point clouds, allows to evaluate the prevalence of false landslide sources and deposits only related to the difference in sampling of a rough surface. We subsequently refer to this type of approach as a Same Surface Different Sampling test (SSDS test).

225 3.3. Parameter selection and 3D point cloud differencing performance

In this section, we explain how to select the appropriate normal scale D and projection scale d to detect landslides using M3C2. The normal scale D should be large enough to encompass enough points for a robust calculation, and smooth out small-scale point cloud roughness that resultresults in normal orientation flickering and overestimation of the distance between surfaces (Lague et al., 2013). However, D should also be small enough to track the large-scale variations in hillslope geometry. By

- 230 studying roughness properties of various natural surface, Lague et al. (2013) proposed a criterion for which that the ratio of the normal scale and the surface roughness, measured at the same scale, should be larger than about 25. We thus set <u>D</u> as the minimum scale for which a majority of core points verify this criteria (details of the analysis can be found in section \$1.1 in the supplements).condition. As roughness is a scale and point density dependent measure, we explore a range of normal scales for <u>D</u> from 2 m to 15 m for the pre-earthquakeEQ dataset, which has the lowest point density. (Fig.2.a). We found that
- 235 $\underline{P} \sim 10$ m represents a threshold scale below which the number of core points verifying the roughness criteriathis condition significantly drops.

The projection scale *d* should be chosen such that it is large enough to compute robust statistics using enough points, but small enough to avoid spatial smoothing of the distance measurement. Following Lague et al. (2013), M3C2 computes eq. (2) only if 5 points are included in the cylinder of radius d/2 for each cloud. In our case, the pre-EQ data with the lowest point density

240 will in practicethus set the value of d. We ran 3D-use a SDDS test applying M3C2 with a normal scale D == 10 m and d varying from 1 to 40 meters, and foundm. Results show that for d=5 m, eq. (2) (Fig.2.b): (i) when it can be computed with the LoD_{95%} actually predicts no significant change for at least 5 data points for 95 % of the surface. The remaining 5 % time, indicating that the statistical model behind eq. (2) (Lague et al., 2013) is correct for this dataset; (ii) the fraction of points

Mis en forme : Interligne : Double

Mis en forme : Police : Italique

Mis en forme : Police : Italique

	Mis en forme : Police : Italique
	Mis en forme : Police :Non Italique
-	Mis en forme : normaltextrun
	Mis en forme : normaltextrun, Couleur de police : Texte 1
	Mis en forme : normaltextrun
	Mis en forme : normaltextrun



For this study case, the lower ground point density-The spacing of the pre-EQ lidar data controls *D* and core point grid should be smaller than half the projection scale *d*-If to ensure that all potential points are covered by at least one M3C2 measurement, while being larger than the pre-EQ dataset had a typical point density similar to cloud spacing of the post EQ data, values of D=4 m and d=3.5 m could have been used, improving the spatiallowest resolution dataset. Because the ground point density 260 on steep forested hillslope of the change detection-2014 survey is of the order of 1 pt/m², we set a core point spacing of 1 m. Finally, the maximum cylinder length p_{max} was set to 30 m as it allowed to compute compassed the maximum change observed in the study area. This is generally obtained by trial and error. Setting p_{max} too large₇ increases significantly computation time significantly and may result in two different surfaces of the same point cloud being averaged (e.g., near very steep divides or in narrow gorges).





Mis en forme : normaltextrun Mis en forme : normaltextrun Mis en forme : normaltextrun normal scale is 25 times larger than the local roughness. (b) Percentage of computed points with a confidence interval of 95% versus projection scale d. The percentage of non-significant points is represented as well as the percentage of points where the Level of Detection (LoD_{95%}) was computed (i.e., with at least 5 points on each point cloud).

3.3. 3D Landslide landslide mapping workflow and parameter selection

Our 3D landslide mapping workflow is divided in fourfive main steps (Fig. 3).



275 Figure 3: Workflow of the 3D point cloud differencing method for landslide detection and volume estimation with schematic representations of the different steps (a,b,c). (a) Schematic representation of the(a) 3D measurement step with the shadow zone effect. Redlines are, where the red lines show the normal orientation. (b) Schematic representation of the 3D measurementVertical-M3C2 step with the shadow zone effect. Redlines are normal orientation. (b) Schematic representation of the segmentation step. (c) Segmentation by connected component. The resulting sources and deposits are individual point clouds illustrated in the figure with 280 different colors. (c) Schematic representation of the volume estimation step. Redlines are normal orientation. by different colours.

270

3.3.1. Registration of the datasets and registration error estimate

To detect geomorphic changes and landslides, the two datasets need to be co-registered as closely as possible and any largescale tectonic deformation need to be adjusted. No significant intra-dataset deformation was detected, but the produced LiDAR datasets did have a vertical shift larger than 1 m. To correct for it, a grid of core points is first created by rasterizing the dataset with the largest point density-corrected. The registration error to be used in eq. (2) must also be estimated.

- 285 with the largest point density-corrected. The registration error to be used in eq. (2) must also be estimated. First, a preliminary quality control is performed to evaluate the internal registration quality of each dataset. This is feasible if the individual flight lines can be isolated, by using for instance, the pointID information specific to each line and provided in the las file format. The intra-survey registration quality can be investigated with 3D-M3C2 measurements of overlapping flight lines using a 1 m regular grid of core points, from which we define the registration bias and error as the mean and standard
- 290 deviation of the 3D-M3C2 distances, respectively. The point cloud of the pre-EQ dataset results from 12 flight lines (Fig S2 in supplements), while the post-EQ corresponds to 5 flight lines. Result shows that for each dataset, no significant bias is measured between lines (maximum of 3 cm for the pre-EQ survey and 1 cm for the post-EQ survey; Tab. S3 in the supplements), but the registration error ranges from 13 to 20 cm for the pre-EQ survey, and is typically around 6 cm, with one instance at 12 cm for the post-EQ survey. Hence, the internal registration quality of the pre-EQ is significantly worse than the
- 295 post-EQ dataset, a likely consequence of differences in instrument precision and post-processing methods. Second, the registration between the two surveys must be evaluated, and in general improved. As delivered, the LiDAR datasets have a vertical shift between 1 and 2 m. To correct for this shift, a grid of core points is first created by rasterizing the dataset with the largest point density with a 1 m grid spacing. Then, a vertical-M3C2 calculation is performed and the mode of the resulting distribution is used to adjust the two datasets by a vertical shift of 1.36 m. This approach is valid only when the
- 300 fraction of the surface affected by landsliding is small. A subsequent 3D-M3C2 calculation is performed to obtain a preliminary map of geomorphic change. By manually selecting a threshold of change, one can identify areas that are assumed to be stable. In our case, this corresponds to regions displaying a change smaller than 0.6 m. At this stage, a visual inspection of the pre-EQ and post-EQ orthoimages and of the preliminary 3D-M3C2 distances allow us to determine that there is no significant internal tectonic displacement. Then, we manually define areas deemed stable, 25 % of the studied area (Fig.4a), to perform a
- 305 cloud matching registration. The stable areas were defined as surfaces (1) with a 3D-M3C2 distance smaller than 1 m, (2) with no visual texture changes in orthoimages, and (3) away from mass-wasting processes and forested area. Attention has been paid to select areas uniformly distributed in terms of location and slopes in the studied region to maximize the registration quality.

An Iterative Closest Point (ICP) algorithm (Besl and McKay, 1992) is <u>then</u> performed on the stable areas, and the obtained rigid transformation is applied to the entire post-earthquake point cloud to -align it with the pre-earthquake one-<u>(Tab. S4). The</u> mean 3D-M3C2 distance on stable areas is -0.01 m, showing that there is almost no bias left in the registration, and the standard <u>deviation of 3D-M3C2 distances is 0.17 m (Fig. 4b)</u>. At this stage, the two datasets are considered optimally registered for the stable areas but with an unknown registration error *reg*. To estimate this error, the M3C2 algorithm is re applied on the registered data, and the registration error is estimatedWe propose to define *reg* as the maximum of the standard deviation of
 the intra-survey and inter-survey 3D-M3C2 distances measured on stable areas. In the ideal case of two very high quality lidar datasets, *reg* would be equal to the inter-survey registration error. In the studied case, the pre-EQ intra-survey registration error is locally worse (0.2 m) than the inter-survey registration error (0.17 m). We thus set *reg*=0.2 m. Consequently, and according to eq. (2), with *reg*=0.2 m, our workflow cannot detect a 3D change that is smaller than 0.39 m in the ideal case of negligible roughness surface. At this stage, a 3D map of topographic change is available, but the statistically-significant geomorphic change changes and individual landslides have not been isolated.

The registration error is defined as the standard deviation of the 3D-M3C2 distances measured between the pre- and post-event point clouds, considering only stable areas that are uniformly distributed in the studied region. These were manually selected and represent 23% of the area (Fig. 3). The mean 3D-M3C2 distance is -0.01 m, showing that there is almost no bias in the registration. 95% of the measured distances are within a range of -0.33 to 0.35 m (Fig. 3). The standard deviation is 0.17 m, and we thus set *reg* to 0.17 m. According to eq. (2), *LoDasse* cannot be smaller than 0.33 m in the ideal case of negligible roughness surface. The relatively large registration error in this dataset is related to errors related to flight line imperfect alignment, some classification residual errors (e.g. low vegetation classified as ground) and residual errors related to the ICP

(Fig. 3).



Figure 4: Map of 3D-M3C2 distances on stable areas used to estimate the registration error and the associated histogram. Map is a point cloud colored with the prepost-earthquake orthophotoorthoimage (Aerial survey, 2017).

3.3.2. Geomorphic change detection

The registration error reg is then used in a first application of 3D-M3C2, using the pre-determined projection scale d=5m5 m,

- 335 to estimate the spatially variable LoD_{95%} according to eq. (.(2). Then, a second 3D M3C2 is performed at a larger projection scale (d=10m) only on For problematic core points for which, where a confidence interval could not be estimated due to the insufficient points at d=5m, a second application of 3D-M3C2 is performed at a larger projection scale d=10. These problematic core points generally correspond to ground points under canopy on steep slopes, and represented represent typically 9.5 % of the core points over the entire area, but ~ 15.20 and up to 12% of steep slopes prone to landsliding. The statistically
- 340 significant Significant geomorphic changes at the 95% confidence interval are then obtained by considering core points for which the associated to a 3D-M3C2 distance is larger than the LoD95%. This process highlights Significant geomorphic changes can be associated to allany geomorphic processes, including landsliding, but also fluvial erosion and deposition-processes in the fluvial domain. Detected changes. Changes located in the river bed, and specifically related to river dynamics are removed manually to select only landslides sources and deposits. This phase is performed by manual visual inspection to prevent and not to landslide deposited at deposits, are manually removed using the post-EQ orthoimage. With the selection of the stable
- 345

area, this is the bottomonly manual phase of valleys to be removed the workflow.

3.3.3. Landslide source and deposit segmentation

Prior to landslide segmentation, a vertical M3C2 is performed on the remaining erosion and deposition points located on hillslopes in order to estimate landslide volume afterwards. This operation will be described in the next section. Core points 350 with significant change are segmented by a connected component analysis (Fig.2.c). This technique segments a point cloud into compact sub-clouds based on a minimum distance threshold D_m and a minimum number of points per N_p sub-clouds Core points with negative and positive significant changes are first separated into tow point clouds of sources and deposits, respectively. A vertical-M3C2 is performed on each of these point clouds to estimate the volume of landslide sources and deposits (see section 3.3.5). As for any 2D landslide inventory, a critical component of the workflow is to segment each point 355 cloud into individual landslide sources and areas. Segmenting complex patterns of erosion and deposition in 3D, with a very wide range of sizes is still a challenge. Here, for the sake of simplicity we use a classical clustering approach by a 3D label connected component algorithm (Lumia et al., 1983), available in CloudCompare (Fig.3.c). The point cloud is segmented into

which neighbouring points, measured in a 3D euclidian sense, belong to the same cluster (Lumia et al., 1983). A minimum 360 distance of 2 m was chosen as it corresponds to the scale where both the amalgamation effect and the over segmentation are limited (section S2.2.2 in the supplements). Due to the large M3C2 cylinder length p_{mex} required to detect deep landslides, small artefacts with a large distance value, near pmax, occur. To ensure that the smallest detected landslides are not affected by

individual clusters based on two criteria: a minimum number of points Np defining a cluster and a minimum distance D_m below

these artefacts, the landslide mapping workflow was performed on the subsample versions of the densest point cloud (section 3.2) with a minimum number of points N_p set to 1 during the segmentation step. All detected changes are thus artefacts. The artefact area distribution was then compared with the landslide area distribution using the pre– and post–earthquake data (details in section 2.2.1 in the supplements). We finally impose a minimum surface of 20 m², corresponding to 20 points, as it corresponds to the smallest area where artefacts are limited. The final dataset represents all the individualized landslide sources and deposit zones detected Np, or the minimum detectable landslide source or deposit area, was set to 20 m² to be consistent with the area of the projection cylinder used to average the point cloud position in the M3C2 distance calculation, $\pi(d/2)^2 = 19.6 \text{ m}^2$ with d=5 m. D_m is an important parameter which, if chosen too large, will favour landslide amalgamation in identical clusters, and if is too small, in relation to the core point spacing, may over-segment landslides. In any case, D_m must be larger

- clusters, and it is too small, in relation to the core point spacing, may over-segment landslides. In any case, D_m must be larger than the core point spacing. As there is no objective way to a priori choose D_m , we explore various values and choose $D_m=2$ m as an optimal value between landslide amalgamation and over-segmentation. The impact of D_m on the statistical distribution of landslide sources is addressed in the discussion.
- 375 We note that density based clustering algorithms based on DBSCAN (Martin Ester, Hans-Peter Kriegel, Jiirg Sander, 1996) have been used for 3D rockfall inventories segmentation (e.g., Benjamin et al., 2020; Tonini and Abellan, 2014). These algorithms separate dense clusters of points, considered as coherent topographic change, from areas of low point density, considered as noise. As shown in supplementary material (S5), density based clustering approaches do not yield a significantly better segmentation than a connected component. However, they have several drawbacks ranging from slow computation time,
- 380 to less intuitive selection of parameters. We have therefore not used density based clustering in the following.

3.3.4. Definition of a confidence metric for each source and deposit: the SNR

Applying the previous workflow to an SSDS test results in 89 sources and deposits detected with an area between 20 and 37 m². This represents less than 1 % of the total surface, consistent with our definition of the *LoD*_{95%}. However, in a context of very low landslide activity, artefacts (either negative or positive false detection) may represent a large fraction of the final
inventory. Moreover, despite attempts to minimize the source of errors, false detection of sources and deposits could occur due for instance to classification errors of the LiDAR data or to the large M3C2 cylinder length *p_{max}* required to detect deep landslides intercepting different part of the same cloud in narrow gorge. To minimize these potential errors, that a label connected component cannot detect, we compute for each segmented deposit or source an equivalent signal-to-noise (SNR) ratio measured as the mean of the ratio between the 3D-M3C2 distance and the associated LoD_{95%} for each core point. The SNR can then be used to filter the landslide inventory. We propose to estimate an optimal SNR once the landslide mapping workflow is performed on the real dataset, by comparing it to the number of sources and deposits generated via a SSDS test. The optimal SNR is then chosen to minimize the number of artefacts compared to the number of real landslide.

3.3.5. Landslide area and volume estimation

While 3D normal computation is optimal to detect geomorphic changes, it is not suitable for volume estimation which requires 395 to consider normals with parallel directions for a given landslide. As shown in figure 2.a, consideringConsidering 3D normals can lead to "shadow zones", due to surface roughness, which would result in a biased volume estimate- (Fig. 2a). Therefore, distances and in turn volumes are computed by using a vertical-M3C2 on a grid of core points corresponding to the significant changes -(Fig.3.b). As the core points are regularly spaced by 1 m, the landslide volume is simply the sum of the vertical-M3C2 distances estimated from the individualized landslides. While the distance uncertainty predicted by the vertical-M3C2 400 could be used as the volume uncertainty, it significantly overpredicts the true distance uncertainty due to non-optimal normal orientation for the estimation of point cloud roughness on steep slopes (i.e., the roughness is not the detrended roughness). For each landslide source and deposit, we thus compute the volume uncertainty from the sum of the 3D-M3C2 uncertainty measured at each core point, not the vertical-M3C2 uncertainty. The volume uncertainty is specific to each landslide sources and deposits and depends on the local surface properties such as roughness, the number of pointpoints considered and the global registration error, but not on the volume itself. For each individual landslide source, the area A was obtained by 405 computing the number of core points inside the source region. This represents the vertically projected area, to be consistent with the existing literature based on 2D studies of landslide statistics. The difference between planimetric area and true surface area (i.e., measured parallel to the surface) is addressed in the discussion.

3.4. Comparison with a manually mapped inventory based on orthoimagery

- 410 To estimate the potential in terms of landslide topographic change detection between the 3D-PcD method (3D inventory) and a traditional approach, we created a second inventory (2D inventory) by manually delineating landslide sources based on a visual interpretation of the pre- and post-EQ orthoimages. The 3D data was not used in the process, and the mapmaker did not have a detailed knowledge of the 3D inventory. Deposits were not mapped. The 2D and 3D landslide source inventories are then compared in terms of number of landslides and intersection of mapped surfaces in planimetric view using GIS software.
 415 For areas only detected by manual mapping, we define 4 classes: (1) areas located on deposit zone detected by the 3D-PcD
- method, (2) areas under the *LoD*_{95%}, (3) areas filtered by the minimum area of 20 m² and (4) areas filtered by the application of the SNR threshold. For areas only detected by the 3D-PcD method, we first distinguish landslide areas located on forested regions from those located in forest-free areas based on the number of laser returns of the post-EQ dataset (Fig. S9 and S10). We then separate the forest-free areas into 2 classes corresponding to typical textures found on the orthoimages, and delineate
- 420 <u>manually: (1) bare-rock areas and (2) sparse or low vegetation areas. We finally analyse the proportion of under-detected areas that are connected to a landslide source in the 2D inventory.</u>

4. Results: Landslide analysis

4.1. Geomorphic change and <u>3D</u> landslide detectionsources and deposit inventory

The map of the 3D-M3C2 distances (Fig. 5a) prior to statistically significant change analysis and segmentation provide a rare
insight into topographic changes following large earthquakes. At first order, it highlights areas of coherent patterns of large (3D-M3C2 > 4 m) erosion (i.e. negative 3D distances) and deposition areas (i.e. positive 3D distances) located on hillslopes and in the river (Fig. 4a). This provide a rare insight into topographic changes following large earthquakes. Most of the detected changes on hillslopes correspond to mass movements such as corresponding to major landslides. Simple configurations with one major source area and a single deposit area can be easily recognized. A more complex pattern of intertwined landslides
and rockfalls with variable sizes, shapes and a high portion of them occurredoccur on a previous unstable bare-_rock zonesurface in the westwestern part of the study area. Small patch of erosion ranging between 10 m² to 100 m² occur over the entire study area. Their large number illustrate how difficult it would be to manually extract them. Most of the deposit areas are-with a large variety of source sizes and aggregation of deposits. Most of the deposits are located on hillslopes while some the deposits of three large landslides have reached the river. The erosion and and altered its geometry. At second order, a variety of patches of smaller amplitude (< 2 m) is visible on hillslopes. Erosion/deposition of sediments by patterns in relation

- to fluvial processes activity can also be observed in the riverdocumented on the river bed. The flight line mismatch, identified during the preliminary quality control, leads to low amplitude and long wavelength patterns of negative and positive 3D distances, notably visible on the central northern part of the studied area.
- The area extent of significant changes, where the absolute amplitude of change is greater than *LoDyssk*, represents 17.5 % of the study area (Fig 4.b). Most points associated to stable areas or artificial changes are correctly filtered by the local confidence interval calculation. In particular, points located under the canopy, or associated to a low point density, or wrongly classified as ground while being vegetation points, leading to locally high values of roughness, result into a higher LoDyssk, and therefore requires a larger topographic change to be detected as significant.<u>15 % of the study area (Fig 5.b)</u>. After the manual removal of changes in the fluvial domain related to fluvial processes, the minimum <u>and maximum</u> 3D-M3C2 distance (or minimum
- 445 LoD_{95%}<u>distances</u> on significant change areas isare 0.3440 ± 0.3340 m and the maximum is 29.997 ± 0.6167 m, both corresponding to erosion areasrespectively (Fig.45.b). -Due to surface roughness, the minimum LoD_{95%} observed is thus 0.40 m.

The point cloud of significant changes was segmented to identify the landslide sources (i.e. net erosion) and deposits (i.e. net deposition). During this step, clusters smaller than the detection limit of 20 m² are removed. They account for an area of 29,823

450 m², that is 4.2 % of the total area of significant change. Before application of a SNR threshold, the 3D inventory contained 1270 sources and 748 deposits. Applying the workflow to evaluate the optimal threshold SNR, we found that for a SNR = 1.5, the percentage of false detection in the inventory is expected to be minimum, equal to 2.1 % (Fig.6). Applying a SNR threshold of 1.5 removes 746 sources and 442 deposits, characterized by a mean area and standard deviation of 88.6 ± 98 m² and 234 ± 198 m², respectively. Hence, the SNR filtering removed about 59 % in number of the sources and deposits, but only 17.6 %

455	and 27.6 % of their total surface, respectively. This latter highlights the small individual area of the sources and deposits
	filtered. A large fraction of small patches in steep forested hillslopes are removed by the SNR filtering (Fig.5.b). The pre- and
	post-EQ raw point clouds of 20 patches with SNR < 1.5 were visually inspected in detail. It was difficult for a human expert
	to confirm a topographic change with high confidence owing to the very low point density and the rough topography of steep
	forested hillslopes On the contrary, the final filtered dataset shows coherent patterns of upslope erosion and downslope
460	deposition in forested areas, indicative of landslides or large rockfalls. The orthoimagery cannot however help in confirming
	this due to the dense canopy cover and/or the pronounced projected shadows. The SNR filtering also removed large patches
	of very low amplitude topographic changes on open ground (< 0.5 m, either positive or negative), located in the pre-EQ data
	flight line mismatch, and did not correspond to a visible change in the orthoimagery (e.g., in the central-northern part of the
	studied area, Fig.5.b). While the SNR filtering removes more than half of the initial number of sources and deposits, these
465	patches are of small size, close to the LoD _{25%} and only correspond to 5.96 % and 3.4 % of the total source and deposit volumes,
	respectively.
	The final landslide inventory, (3D inventory) contains a total of 1431524 sources and 853304 deposits (Fig. 45c). The
	difference in the number occurs because and 7a), with many sources sharesharing the same deposits that are concentrated at
	the toe of hillslopes. For sources, the mean absolute vertical-M3C2 distance is 2.1469 m, the standard deviation 2.6291 m and
470	the maximum absolute value $\frac{22.8 \pm 1.1723.06 \pm 0.53}{2.373.40}$ m. For deposits, the mean absolute vertical-M3C2 distance is $\frac{2.373.40}{2.373.40}$
	m, the standard deviation 3.0868 m and the maximum absolute value maximum 29 is 27.9 ± 0.61 m. 49 m. The area of detected
	landslides ranges from 20 to 40,679 m ² for sources and from 20 to 28,037 m ² for deposits, and the total source and deposit
	areas are 286,445 and 283,661 m ² , respectively. The resulting individual landslide volume ranges from 0.56 ± 41.5 m ³ to
	$169,890 \pm 20,188 \text{ m}^3$ for source areas, with a total of $752,616 \pm 154,165 \text{ m}^3$, and from $3.5 \pm 19.5 \text{ m}^3$ to $151,706 \pm 15,082 \text{ m}^3$
475	for deposits, with a total of 949,742 \pm 150,014 m ³ . The uncertainty on total volume estimation represents 20% for sources and
	16% for deposits.

Mis en forme : Couleur de police : Automatique







inventory with after application of a minimum area of 20 m² and a minimum SNR =1.5. Data is overlaid on the post-earthquake orthophotoorthoimagery (12-15-2016, Aerial survey, 2017). The number of landslidesLandslide sources is 1431are in blue and landslide deposits is 853are in red.

4.2 Landslide area and volume analysis

Recall that the subsequent analysis is based on a grid of core points with 1 m spacing. For each individual landslide, the area



Figure 6: Percentage of the number of artefacts compared to the total number of landslides as a function of the signal-to-noise ratio.

A was obtained by computing the number of core points inside the sources region.

490

4.2. 3D vs 2D landslide source inventory

In the following analysis we separate two types of errors: detection errors, corresponding to landslides present in only one of the 2D and 3D inventories, and delimitation errors, corresponding to differences in the planimetric contours of landslides. 258 495 landslide sources, called hereafter 2D-sources as opposed to 3D-sources derived from 3D-PcD, were mapped from visual inspection of pre-EQ and post-EQ orthoimages (Fig. 7b). The 2D-sources represent a total area of 147,039 m² (Tab.2) with a minimum area of 7.2 m² and a maximum of 40,679 m². The minimum area detected shows that the resolution capability of the 2D inventory is finer than the 3D-PcD workflow. From the 258 2D-sources, 171 intersect 3D-sources and 87 are not detected by the 3D-PcD method. These 87 2D-sources range from 14 m² to 599 m² with 63% smaller than 100 m². However, 22 are 500 actual deposits in the 3D inventory, highlighting detection errors in the 2D inventory. These detection errors represent 16 % of the surface of the 2D inventory and are removed in the following, leading to 65 2D-sources not detected by the 3D-PcD method. The 3D-PcD method thus detects 72.4 % of the 2D-sources, and 57.4 % of the total surface of the 2D inventory (Tab.2). The 65 2D-sources not detected by the 3D-PcD method correspond to 32 2D-sources located in areas with no statistically significant change (i.e., 3D-M3C2 distance < LoD95%), 29 2D-sources filtered by the SNR threshold and 4 2D-505 sources below the minimum detectable size of 20 m². In terms of planimetric surface however, the area not captured by 3D- PcD is overwhelming dominated by non-statistically significant change (40.9 % of the total 2*D*-sources surface are < LoD_{95%}), as opposed to SNR filtering (1.5%) or the minimum detectable size (0.2%). The surface of non-statistically significant change corresponds to delimitation errors located on the edges of sources and deposits, owing to the averaging effect of the M3C2 approach, and the transition between landslide sources and deposits (Fig.7c). The volume missed in *3D*-sources was computed

- 510 by using the intersection between the contours of the 2D-sources not shared in 3D and the vertical M3C2 field of the core points. We find that the volume that would be missed in the 3D inventory is 0.6% of the total volume of 3D-sources. While 171 2D-sources are common to 3D-sources, this corresponds to 144 3D-sources owing to the difference in landslide segmentation in the two inventories (Fig.7a). The 2D inventory misses 72 % (380) of the landslide sources detected in 3D, including landslides as large as 12,928 m² (blue polygon in the frame of figure 7a). The detection errors are predominantly in
- 515 forest (222, 58% of detection errors) and bare rock (88, 23% of detection errors). They also occur on sparse or low vegetation (70, 18% of detection errors) as is the case of two large landslides where pronounced shadows in the post-EQ, and where the topographic change is mostly vertical (Fig.7c). 75% of the total surface of *3D-sources*, is not detected in the 2D inventory, with 26% under forest, 34% on bare rock and 40% on sparse or low vegetation areas (Tab. 2 and Fig. S11). The landslide scars in this latter domain should be generally visible owing to strong spectral contrast between pre-EQ vegetation and post-EQ rock
- 520 surface. However, the large source of error is explained by the incorrect delimitation of upslope topographic subsidence related to large scars (Fig.7c), as well as the under-detection of vertical subsidence related to translational and rotational landslides (Fig. 10b). These vertical movements of metric amplitude or less do not correspond to a clear change of orthoimagery texture, or create scarps that are too small or not easily detectable if they do not generate a shadow. Detection and delimitation errors contribute roughly equally to the 2D area under-detection (47 % detection error, 53 % delimitation error). The 2D-sources misses 60 % of the total volume of the 3D-sources. In contrast to the missed planimetric surface, the volume missed is
- predominantly on bare rock (32.8 %), nearly three times larger than in forest (13.9 %) or sparse/low vegetation (13.4 %).



Figure 7: Comparison between landslide source inventories from a) the 3D point cloud detection workflow and b) a manual mapping based on 2D orthoimage comparison. Each landslide source is shown as a single colored polygon. c) Detailed comparison of typical

530	mapping differences between the 2D and 3D approach. Data are overlaid on the post-earthquake orthoimagery (12-15-2016, Aerial
	survey, 2017).

Table 2 : Summary of the comparison between 2D and 3D landslide source inventories. For the 2D inventory, the percentages are calculated with respect to the corrected total in which the 2D sources corresponding to 3D deposits are removed.

			landslide	Area	<u>a</u>	Volume*			
		<u>Category</u>	sources	<u>m²</u>	<u>%</u>	<u>m³</u>	<u>% of 3D</u> <u>total</u>		
		Total	<u>258</u>	147,039		NA			
		On 3D deposit	<u>22</u>	<u>23,497</u>	<u>16</u>	<u>NA</u>			
OLY		Corrected total	<u>236</u>	123,542	<u>100</u>	305,095	40.5		
vent		Shared	<u>171</u>	70,936	<u>57.4</u>	300,249	<u>39.9</u>		
D in	Ð	< min area (20 m ²)	<u>4</u>	<u>295</u>	<u>0.2</u>	<u>179</u>			
(1)	tin 3	< SNR threshold	<u>29</u>	<u>1848</u>	<u>1.5</u>	<u>1,790</u>	<u>0.6</u>		
	Noi	<u>< LoD_{95%}</u>	<u>32</u>	<u>50,463</u>	<u>40.9</u>	2,877			
		Total	<u>524</u>	286,445	<u>100</u>	752,616	<u>100</u>		
N		Shared	<u>144</u>	70,936	24.7	300,249	<u>39.9</u>		
intor		Forest	<u>222</u>	56,288	<u>19.7</u>	104783	<u>13.9</u>		
inve	1 2D	Bare rock	<u>88</u>	<u>73,191</u>	<u>25.5</u>	246851	<u>32.8</u>		
<u>3</u> D	Not ir	Sparse or low	<u>70</u>	86,124	<u>30.1</u>	<u>100731</u>	<u>13.4</u>		

*: volumes for the 2D inventory are computed from the vertical-M3C2 of core points located within the sources delimitations

535 4.3. Landslide sources area, depth and volume analysis

This represents the vertically projected area, to be consistent with the existing literature based on 2D studies of landslide statistics. The area of detected landslides ranges from 20 to 42,650 m² for sources and from 20 to 33,513 m² for deposits, and the total source and deposit areas are 438,124 and 376,363 m², respectively. The area distribution of landslide sources is computed as follow (Hovius et al., 1997; Malamud et al., 2004):

540

$$p(A) = \frac{1}{N_{LT}} \times \frac{\delta N_L}{\delta A}$$
(3)

where p(A) is the probability density of a given area <u>range</u> within a <u>substantial</u> landslide inventory, N_{LT} is the total number of landslides and A is the landslide source area. δN_{LT} corresponds to the number of landslides with areas between A and $A + \delta A$. The landslide area bin widths δA are equal in logarithmic space.

545 TheFirst, the area distribution of landslides<u>landslide sources inventories</u> obeys a power-law scaling relationship consistent with previous studies (e.g., Hovius et al., 1997; Malamud et al., 2004), with an exponent c = -1.79 ± 0.03 (Fig.5a). We do not observe a rollover at small landslide areas which is considered a characteristic of landslide distribution (Guzzetti et al., 2002; Malamud et al., 2004; Malamud and Turcotte, 1999). Varying the parameters of the segmentation does not alter this result (section S2.2.2), nor is a rollover visible at lower surface area if we reduce the minimum landslide size to 10 m² (section S2.2.1). This behaviour differs from the one observed from the landslide area distribution from Massey et al. (2020) in the

Landslide volume V was measured with a vertical M3C2 on landslide areas detected with a 3D M3C2. The resulting individual landslide volume ranges from $0.75 \pm 9.57 \text{ m}^3$ to $171,175 \pm 18,593 \text{ m}^2$ for source areas, with a total of $908,055 \pm 215,640 \text{ m}^3$; and from $0.75 \pm 17.5 \text{ m}^3$ to $154,599 \pm 15,188 \text{ m}^2$ for deposits, with a total of $1,008,626 \pm 172,745 \text{ m}^3$. The uncertainty on total

- 555 volume estimation represents 23.7 % for sources and 17.1 % for deposits. The volume distribution of the landslides sources. The exponents are respectively c = -1.78 ± 0.07 and c = -1.72 ± 0.04 for the 2D and 3D inventory, respectively (Fig. 8a). The landslide area distribution of the 2D inventory shows a cut-off around 100 m² and a roll-over, characteristic of landslide distributions, around 20 m² (Guzzetti et al., 2002; Malamud et al., 2004; Malamud and Turcotte, 1999; Tanyaş et al., 2019). The landslide area distribution of the 3D inventory does not exhibit a rollover but a cut-off of the power-law behaviour around
- 40 m². This behaviour differs from the one observed from the landslide area distribution from Massey et al. (2020) in the broader Kaikoura region for which a cut-off appears around 1000 m² with a rollover at 100 m².
 The volume distribution of the landslide sources of the 3D inventory was defined using equation (3), replacing A by the volume V, and also exhibitexhibits a typical negative power-law scaling (Fig.-5.a.8b) of the form: p(V) = dV^e. The exponent
- of the power-law relationship is e = -1.7161 ± 0.04. In contrast to landslide source areas distribution, a08. A roll-over is visible
 on the landslide volume distribution around 5 to 1020 m³. Considering that the minimum LoD_{95%} observed in 3D is 0.3440 m, and that the minimum landslide area is 20 m², the minimum volume that we can confidently measure should be 6.8 m³, a value consistent withclose to the observed rollover. 3510 landslides are indeed smaller than 6.8 m³ in our inventory. They correspond to peculiar cases of very small landslides in which where negative 3D distances close to the LoD_{95%} are positive when measured vertically and thus reduce the apparent volume of eroded material. Volume estimation in these cases should be done locally in 3D, but requires further development not deemed necessary given that it is restricted to the smallest and shallowest landslides

of the inventory.

Kaikoura region.

With a direct measurement of landslide volume, it is possible to compute the volume-area relationship (eq-((11)); Simonett, 1967; Larsen et al., 2010) and to compare it with <u>pre-existing previous</u> results in New Zealand (Larsen et al., 2010, Massey et al., 2020). Here we determine V-A scaling coefficients using two methods: by fitting a linear model (1) on log-transformed

575 data and (2) on <u>averaged</u> log-binned data. While the first method leads to a V-A relationship best describing the volume of each landslide, the second one is not affected by the varying number of landslides in each range of landslide area and leads to a V-A relationship that best matches the total landslide volume. Using the first approach, we find a volume-area scaling exponent of $\gamma = 1.1816 \pm 0.0402$ and an intercept $\log \alpha = -0.4228 \pm 0.02 \text{ m}^{54}04 \text{ m}^{07}$ with a determination coefficient

Mis en forme : Police : Italique

Mis en forme : Couleur de police : Texte 1

 $R^2 = 0.9988$ (Fig.5.c), 8.c). Using the second method, we find $\gamma = 1.2017 \pm 0.02$, an intercept log $\alpha = -0.4126 \pm 0.0708$ 580 $m^{0.62}$ and a determination coefficient $R^2 = 0.99$. We also obtain a good correlation R^2 of 0.8683 and 0.8279 with the Larsen et al. (2010) relationships derived from soil landslides and from mixed soil landslides and bedrock landslides, respectively (Table 2). However, Tab.333). R² of 0,61 and 0.72 are85 is obtained when considering the parameters of the V-A relationships of the Kaikoura region, derived by Massey et al. (2020), based on the 8,442 cleaned landslides or only soil dominated ones. respectively, of the Kaikoura region. including all their mapped landslides. At first order, the V-A relationships we obtained 585 are thus consistent with previous studies. Yet, the V A scaling relationship obtained with log binned data best predicts the volume directly measured from difference of LiDAR point clouds (Table 2). If Yet, if the relationships from Larsen et al. (2010) and Massey et al. (2020) were applied to our landslide area inventory, the total volume would vary from $0.541 \times 10^6 376 \times 10^6$ m^{3} to 1.347x10⁶005x10⁶ m³ (Table 2 Tab.3), compared to 0.908x10⁶753x10⁶ ± 0.215x10⁶154x10⁶ m³ that we estimate directly, This highlights the overarching sensitivity of the total volume of eroded material to the V-A relationship (Li et al., 2014; Mare 590 and Hovius, 2015). The closest evaluation of the total volume is based on the Massey et al. (2020) V-A relationship-for soil landslides, that predicts a total volume of $0.934 \times 10^6 653 \times 10^6 \text{ m}^3$. However, this V A relationship gets close to The farthest evaluation of the total landslide volume by significantly overpredicting is the volume of small landslides. The opposite is true for the V-A relationship from Larsen et al. (2010) V-A relationship for all landslides (1.347x10⁶005x10⁶ m³) which overpredicts the volume of large landslides,), while their soil-landslides relationships-dominated landslide relationship only predicts 595 half of the total volume. This latter results hints at the transition from shallow dominated landsliding at small areas to deeper bedrock landsliding that may obey a

We presented the V-A relationship as it classically used in co-seismic volumes estimate from 2D inventories, however the volume being the product of mean depth and area, the V-A relationship hides an indirect correlation with area which may hinder subtle variations of depth with landslide size. Fig 8c shows that mean depth increases on average with area as a power

- 600 law with an exponent 0.16±0.03 consistent with the V-A relationships we derived. However, the binned data suggests potentially two different trends: one for landslides smaller than 1000 m² in which, mean depth is nearly constant and exhibits a factor 4 of variation for given area (~ 0.7 m to ~ 3 m), while depth increases with area for sources larger than 1000 m². However, the limited number of landslides in our inventory is insufficient to be conclusive on the existence of two different V-A relationship at large area. Our inventory is not large enough to confidently define a specific trend for deep and large to the existence of the e
- 605 landslides. regimes.

Mis en forme : Couleur de police : Texte 1



Figure 8: Landslide sources inventory analysis of the study area (NLT=1431). Landslide area (a) and volume (b) probability density distribution. (a) also contains the original V2 landslide inventory. (a) Landslide area distribution of both 3D and 2D inventory and
 Massey et al. (2020). Power-law fits begin respectively at 20 m² and 20 m², (b) Landslide probability density in function of landslide volume. distribution of the 3D inventory. (c) Volume-area power-law scaling relationshipselity density with uncertainty on volume and comparison with Larsen et al. (2010) and Massey et al. (2020) relationships obtained in New Zealand. The landslide mean depth

vs area is also presented in inset. All scaling parameter values are summarized in Table 2. Grey lines are depth vs area relationship for different mean depths.3.

615

Table $\frac{2:3}{2}$: Power-law scaling parameter values of the relations show in figure 58. Log α and γ are scaling parameters from the landslide area-volume relationship. Unit of α is $[L(3-2\gamma)]$ with L in meters. Landslide source area and volume distribution coefficients are b and d while exponents are c and e respectively. The coefficient of determination \mathbb{R}^2 is also given for each power-law fit function. The total volume corresponds refers to the application of a specificte V-A relationship to the landslide areas of ourthe 3D inventory.

	log b- <u>, log</u> d <mark>/or</mark> log α	c- <u>, e</u> <u>/or</u> γ	R ²	Total Volume (m ³) •		Mis en forme : Police :Non Italique
		-1. 79 72 ±			\mathbb{Z}^{\prime}	Mis en forme : Police :Non Italique
Landslide area distribution (3D inventory)	0.7570 ± 0.0912	0.0304	0.99			Tableau mis en forme
Landslide volume area distribution (2D		-1 7478 +		<u>0 908 × 106</u>		Mis en forme : Anglais (Royaume-Uni)
inventory)	$1.07 \pm 0.41 \pm 0.14 \underline{20}$	0.99	0.99	(limit meaning)		
V A relationship from avaraged data (this		1 2061 +	0.00	0.0007E2 × 106		
V-A relationship from averaged data (this	-0.41 <u>39</u> ± 0. 07 26	<u>-1.2001</u> ±	0.55	0. 900 /55 × 10 ⁻		
study)Landslide volume distribution		0.0208	<u>98</u>	(direct measurement)		
V-A relationship from rawaveraged log-binned	-0.4226 ± 0.0208	$1.\frac{1817}{12} \pm 0.01$	0. 86	0.740643×10^{6}		
data (this study)	-0.42 <u>20</u> ± 0.02 <u>00</u>	<u>02</u>	<u>99</u>	0.740043 × 10		Mis en forme : Police :Non Gras
V-A relationship for soil landslides						
(Larsen et al., 2010from log-transformed data	-0.3728 ± 0.0604	1. 13<u>16</u> ±	0.86	0. <mark>541</mark> 524 × 10 ⁶		Mis en forme : Police :Italique
(this study)		0. 03<u>02</u>⊾			_	Mis en forme : Non Exposant/ Indice
V-A relationship for mixed soil and bedrock						Mis en forme : Non Exposant/ Indice
landslide landslides	-0.8637 ± 0.0506	1. 36<u>13</u> ±	0. 82	$\frac{1.3470.376 \times 10^6}{1.3470.376 \times 10^6}$		
$(\mathbf{I}, \mathbf{arsen}, \mathbf{et}, \mathbf{al}, 2010)$	0.00 <u>57</u> ± 0.05 <u>00</u>	0. 01<u>03</u>	<u>83</u>			Mis en forme : Exposant
						Mis en forme : Exposant
V-A relationship for <u>mixed</u> soil landslides		1. 06<u>36</u> ±	0. 61			Mis en forme : Police :Gras
-(Masseyand bedrock landslide (Larsen et al.,	-0.1286 ± 0.0405	0.0201	79	0.9341.005 × 10°	$\overline{\}$	Mis en forme : Anglais (Royaume-Uni)
2020 2010)			<u></u>		$\langle \rangle$	Mis en forme : Anglais (Royaume-Uni)
V-A relationship for all landslidesthe landslide		1 100	0.72		$\left(\right) \right)$	Mis en forme : Anglais (Royaume-Uni)
inventory of	-0.05 ± 0.02	1.109 ±	0.72	0. <mark>947653</mark> × 10 ⁶	$\langle \rangle$	Mis en forme : Anglais (Royaume-Uni)
-(Massev et al., 2020)		0. <u>00801</u>	85			Mis en forme : Anglais (Royaume-Uni)
					//	Mis en forme : Anglais (Royaume-Uni)

Mis en forme : Police : Non Italique

Mis en forme : Police :Non Italique

Mis en forme : Police : Non Gras

620 4.3 Reactivated landslides and new failures

Because the 3D measurement approach only depends on local topographic change, we evaluate the fraction of reactivated landslides in the population that would have been hard or impossible to detect with 2D imagery based on texture change (Fig.6.a). We hereinafter distinguish between new and reactivated landslides, by considering that reactivated landslides occur on bare rock areas in the pre-earthquake imagery or on vegetated areas with limited texture and colour contrast between the

two epochs. These definitions were chosen following classical approaches for landslide detection based on vegetation cover analysis (Bchling et al., 2014; Marc et al., 2019; Martha et al., 2010; Massey et al., 2018; Pradhan et al., 2016). Most of the detected landslides are new failures with a total area of 318,726 m² and volume of 636,359 ± 163,496 m³ (Fig.6.a). We find that reactivated landslides have a total area 119,398 m² and volume of 271,695 ± 52,144 m³, which represents 27.2 % and 29.9 ± 12.8 % of the total landslide area and volume, respectively (Table 3). Figure 6b illustrates in detail an area experiencing active rock avalanches and debris flow in the pre-earthquake imagery, for which the change in contrast and shadows is likely too complex to detect a topographic change from a texture based analysis. On the contrary, the 3D change detection shows that landslide erosion is pervasive in this sector, and corresponds indeed, to the largest landslide detected by our approach. The difficulty to detect small and reactivated landslides is illustrated by plotting the version 1.0 of the landslide inventory from Massey et al. (2018) in our study area (Fig.6.a), which is a database manually validated, and constantly updated.
Only 27 landslide sources were initially mapped and none in reactivated zones, where we found 1431 landslides for which 27.2% of the total area are reactivated.



Figure 6: New failure and reactivation areas identified from detected landslide sources. A) Map of landslide source areas colorized according to new failure or reactivation zone. The centroids of the landslide inventory (version 1.0) mapped by Massey et al. (2018) are shown in comparison (n=27). B) Zoom on a reactivation zone, from the left to the right: pre-carthquake orthophoto (January

24, 2015), post-carthquake orthophoto (December 15, 2016) and detected reactivation area (only source area) super-imposed to the pre-carthquake orthophoto (Aerial survey, 2017).

Table 3: Area and associated volume of the considered new failure and reactivation zones.

	New failures	% Total	Reactivation	% Total
Area (m ²)	318,726	69.9	119,398	27.2
Volume (m ³)	636,359 ± 163,496	70.1 ± 34.6	$271,695 \pm 52,144$	29.9 ± 12.8

645 5. Discussion

660

The aim of this paper is to investigatepresent a semi-automatic workflow, called 3D-PcD, for the potentialdetection and geometric characterization of methods based on 3D point cloud differencing to provide a landslide inventory map at a region scalesources and deposits from repeated airborne LiDAR data, a total landslide volume estimate and. We specifically aim to overcome issues such as <u>under-detection of landslides in inventories based on imagery analysis</u>, landslide amalgamation effects on total estimated landslide volume, under-detection of reactivated landslides in 2D imagery analysis as well as limitations of the DoD approach on steep slopes. Here we first discuss the 3D workflow we have developed in comparison to traditional DoD approach, and then discussand V-A relationship biases on total volume calculation. In the following, we discuss 1) the benefits and limits of the 3D-PcD method, 2) the benefits of 3D change detection forto create landslide inventories, and 3) how 3D landslide inventories creation compared to 2D imageryshed new light on the scaling properties of landslide detectionsources.

5.1. 3D point cloud differencing and landslide detection

3D point cloud differencing methods have already been applied in previous studies to detect geomorphic changes on single landslides using point clouds obtained by photogrammetry with drone-based images (Esposito et al., 2017; Stumpf et al., 2014, 2015). Larger-scale approaches have been attempted to evaluate the impact of a given landslide (Bossi et al., 2015). However, the DoD, based on gridded data, remains the dominant approach to evaluate topographic changes in the context of glacier dynamics, fluvial dynamics or tectonic deformation analysis (e.g. Passalacqua et al., 2015 for a review). To our knowledge, the systematic detection and segmentation of hundreds of landslides from 3D point cloud have not yet been attempted.

5.1.1 Vertical versus 3D change detection capability, and the M3C2 algorithm

The importance of detecting changes in 3D₇ (3D-M3C2), as opposed to vertically (vertical-M3C2), in steep slopes can be illustrated by a simple exercise, similar<u>SSDS test applied</u> to section 3.2, in which we use two random sub-sampled versions of the post-event<u>EQ</u> point cloud that represent exactly the same surface without any registration error, have similar point density but different sampling of the surface. We apply a vertical M3C2 and a 3D-M3C2 to the two point clouds, and the maps of change and distance distributions are shown on figure(Fig, 7a.9). Typical of change measurement methods on rough surfaces Mis en forme : Police :Gras Mis en forme : Normal with random point sampling (e.g., Lague et al., 2013), a non-null <u>mean</u> distance is often measured, even though the two point clouds are samples of exactly the same surface. The distribution of measured distances is centred near zero, with a <u>meanmeans</u> of -2.10^{-4} and 1.10^{-4} m, for the vertical and 3D approach respectively. However, the 3D approach results in a standard deviation, σ =0.05 m, four times smaller than using a vertical differencing, σ = 0.20 m. The map of distance shows that vertical differencing systematically results in much <u>higherlarger</u> distances on steep slopes than the 3D approach, while they both yield similar, low distances, on horizontal surfaces.

- 675 We thus find that <u>the 3D point cloud differencing-PcD method</u> offers a greater sensitivity to detect changes compared to classical vertical DoD. This difference is particularly important as it propagates into a lower level of detection and uncertainty on volume <u>calculationcalculations</u>. Using the M3C2 algorithm in 3D (Lague et al., 2013) also offers the benefit of accounting for spatially variable point density and roughness in estimating a distance uncertainty for each core point, that can subsequently be used in volume uncertainty calculations. 3D-M3C2
- 680 reduces the sensibility of change detection in vegetated areas to a lower ground point density and potentially to a higher roughness due to vegetation misclassification. In turn, this advantage prevents in part the detection of false sources or deposits by using 3D-M3C2. By using a regular grid of core points as in Wagner et al. (2017), -For instance, this approach leads to a reduced detection sensitivity in vegetated areas due to a lower ground point density and potentially higher roughness due to vegetation misclassification. By using a regular grid of core points as in Wagner et al. (2017), our workflow combines the benefits of working directly with the raw unorganized 3D data, as opposed to DoD where the relationship with the underlying higher point density data is lost, while producing a result with. This approach also produces results with a regular sampling that can easily be used for unbiased spatial statistics, volume calculation and easy integration into 2D GIS software. Compared

to DoD, if an interpolation is needed, it is performed on the results rather than on the original DEM which can lead to uncontrolled error budget management.



31



Figure 9: Comparison between 2D-vertical differencing (vertical-M3C2) and 3D differencing (3D-M3C2) on the post-EQ point cloud, sub-sampled randomly two times to generate two point clouds of the same surface with a different sampling-(<u>Same Surface Different</u> <u>Sampling test</u>). A) Resulting change detection maps of the two different techniques. B) Histogram of the computed distances with the two techniques.

5.1.2-Tectonic internal deformation, data quality and point clouds registration

One. Current limits of the mostmethod

695

Registration: A critical partaspect of any the comparison of 3D point eloud processing method clouds is thetheir coregistration of the two point clouds, in particular in the context of co-seismic landsliding. With LiDAR data, the registration 700 error will generally set the minimum detectable change on bare planar surfaces. HereIn this study, a rigid translation has beentransformation is applied onto the entire areadatasets using an ICP algorithm (Besl and McKay, 1992), de facto-assuming that internal deformation duringinduced by the earthquake wasis negligible. After applying a vertical displacement of 1.36 m, we didThe 3D-M3C2 map does not observe aexhibit any systematic horizontal shift of the difference map either north or south of the Hope fault. We thus conclude that the internal deformation, if any, was below the typical registration error in our study 705 area. For larger studied regions with internal deformation and in the absence of a 3D co-seismic deformation model that could be applied to the post-EQ point cloud (e.g., Massey et al., 2020), our workflow should be applied in a piecewise manner with boundaries corresponding to the main identified faults or deformation zones. For landslide inventories following climatic events, the application to very large datasets should be straightforward as no significant internal deformation is expected. Similarly, we also noted annote internal flight line height mismatchmismatches of 0.0513-0.1220 m in the pre-EQ 710 survey, that wasare difficult to correct after data delivery and generated generate some apparent large scale low amplitude topographic changes (Fig. 4, Tab. S3 and section S2 in supplements). Interestingly, in the M3C2 calculation, flight line mismatches are averaged out in the distance measurement but leads to a higher local point cloud standard deviation, and thus to an increase of the LoD95% and to a lower probability of incorrect topographic change (Fig. 3). detection. Despite some

significant flight line mismatches in the pre-EQ dataset, using a SNR filtering approach efficiently removes the few false
positive sources related to this issue. This highlights 1) the need for a detailed quality control (e.g., by applying M3C2 on overlapping lines) to ensure the highest accuracy possible of the LiDAR dataof the LiDAR data, 2) the importance of the statistical significance tests performed at the core point scale, and 3) the need for confidence metrics at the landslide scale, such as the SNR, to filter out a variety of potential false landslides. Ideally, a spatially variable model for point cloud errors and registration should be developed for each survey and combined into a more accurate and complete form of *LoD* than what
the M3C2 approach currently offers (e.g., Glennie, 2008; Passalacqua et al., 2015). However, the position and attitude information of the sensor (e.g., Smoothed Best Estimate of Trajectory file) and raw LiDAR data area rarely available on LiDAR data repositories. Additionally, a dense network of ground control points is hard to get in mountainous environment. It is thus frequently impossible either to reprocess the LiDAR data to improve its quality (e.g., Glennie et al., 2014), or to create a spatially variable registration and point cloud error model.

725 5.1.3 Landslide segmentation

Another important aspect of the method is the segmentation procedure to individualize sources and deposits. We performed a sensitivity analysis to evaluate the impact of the minimum distance between sub clouds *D_{mr}*, on the number of segmented landslides and related geometric characteristics (section 3.2, Suppl. Material S.2.2.2). We show that below 4 m, the choice of *D_{mr}* has little impact on the pdf of area, pdf of volume, and the volume area relationship. However, above 4 m, amalgamation starts to significantly alter the landslide geometry statistics. A similar analysis should be performed for each new dataset to evaluate the best segmentation scale. The connected component segmentation is a simple and rapid way to individualize landslides but given the complexity of the 3D dataset, and in particular the very large range of landslide sizes, inevitably exhibits some drawbacks and is subject to improvement. For instance, landslides occurring on both side of a same collapsed divide are considered as one landslide if they are close enough (Fig. 8.a). More advanced segmentation approaches accounting for normal direction, divide organization and 3D depth maps of amalgamated scars would be needed to improve the segmentation and get more robust results on very large datasets. We note however that these issues do not affect the total landslide volume calculation.

5.1.4 Landslide topographic changes and feature tracking

Our approach focuses on landslide detection and volume calculation. The workflow we have designed is not suitable for deformation measurement based on feature tracking (Passalacqua et al., 2015). Except for a few landslides with limited displacement in which point cloud features could be potentially tracked, the severity of landsliding and the long runout of many landslides preclude any attempt in tracking features. Our approach may miss translational landslides on planar hillslopes for which topographic change occurs in the direction of the surface normal. Given that hillslopes are generally not perfectly planar, any significant translation
The connected component segmentation is a simple, objective and rapid way to separate landslides in 3D that can be scaled up to much larger datasets. However, given the complexity of the 3D data, and in particular the very large range of landslide sizes (i.e., 4 orders of magnitude in the studied case), it inevitably exhibits some drawbacks and is subject to improvement. In particular, landslide amalgamation occurs, between two sources or deposits, if two of their core points are closer than D_{m_c} . Hence, landslides occurring on the two sides of a collapsed divide can be connected. This is the case for the largest landslide of our database located on the rock cliffs on the western part of the

- 750 study area (Fig. 7a and Fig. 10a). In this example, the landslide source could reasonably be segmented in at least 5 smaller landslides. However, there does not seem to be a unique way to segment such a complex set of amalgamated events, even manually, underlining that landslide segmentation, can never be fully objective. We have explored the use of fast implementations of density based spatial clustering algorithm derived from DBSCAN (Martin Ester, Hans-Peter Kriegel, Jiirg Sander, 1996), an algorithm used for segmentation of 3D point clouds of rockfalls and removal of noisy points (e.g., Benjamin)
- 755 et al., 2020; Tonini and Abellan, 2014; details in section S5 in supplements). We applied OPTICS (Ankerst et al., 1999), recently used for rockfall segmentation of 3D lidar data (Carrea et al., 2021) and HDBSCAN (McInnes et al., 2017) which has a better ability to detect clusters of various sizes compared to DBSCAN, and is much faster. However, none managed to provide a significantly better segmentation of the largest landslides of our database, and the density probability of source area they produce is very similar to the one generated by a connected component. These approaches are however significantly
- 760 longer to run than a connected component in Cloudcompare (S5 in supplementary material), and have parameters which are less intuitive to set than *D_m*, which is a distance directly comparable to core point spacing. New segmentation approaches accounting for normal direction, divide organization and 3D depth maps of amalgamated sources are needed to improve the segmentation of complex cases. We note however that segmentation issues do not affect the total landslide volume calculation in our study and that a sensitivity analysis of the impact of *D_m* shows that landslide source statistics are not severely affected by this parameter as long as it is close to the value we have used (see section 5.2).
- Landslide volume calculation: Landslide volume is computed using a vertical-M3C2 on regular core points. This facilitates volume calculation on potentially complex 2D landslide geometry, but may lead to incorrect volume estimates on very steep slopes. Yet, the median slope distribution of the source core points (measured on the pre-EQ surface, Fig S12) is 34.6°, and only 0.74 % of the core points have slopes higher than 60°. We thus expect this effect to affect a very small fraction of our
- 770 inventory. Measuring landslide volume in 3D would be preferable, for instance along a constant surface normal direction defined for each source or deposits, but such simple approach is not better than a vertical measurement for the complex surface geometry of large landslides observed in the dataset and which are properly segmented (e.g., Fig. 7c). New approaches based on 3D mesh reconstruction have been used recently for rockfall volume estimation (Benjamin et al., 2020) and represent a future improvement of our workflow.
- 775 Landslide surface area: Another simplification of our approach is the calculation of planimetric surface areas, rather than true surface area. This choice was made to be consistent with previous results based on 2D inventories and to facilitate the comparison with our image based inventory. Measuring surface parallel to the hillslope will generate a topographic change, especially in the source area. As shown in fig. 8b, our approach detects area with 3D data would potentially help unravel new relationships between normal depth and area that are independent of topographic slope. Yet, this calculation is not trivial for

Mis en forme : Couleur de police : Texte 1

780 complex landslide geometries in which assuming a unique normal orientation to get a surface parallel area measurement could result in a strong bias (e.g., Fig. 7c). Approaches based on 3D mesh surface calculation could help resolve this. Given that the median of the slope distribution of our landslide source inventory is 34.1°, a back of the envelope estimate of the true area gives a total landslide source area of 356,876 m² rather than 286,445 m².

Translational landslides: The 3D-PcD workflow we have designed is not designed for the measurement of translational landslides for which the dominant movement is parallel to the topographic surface. As in figure_10b, these landslides will appear as negative surface elevation in the source area and positive in the downslope accumulation area with little or non-significant 3D-M3C2 distance over much of the landslide body. These landslides can be detected with the 3D-PcD workflow, but the corresponding volume and area of sources may not be fully relevant to the bulk of the landslide inventory for which the source material has travelled further downslope exposing a large part of the slip surface. For mostly translational landslides, although it cannot compute the deformation parallel to the hillslopes. The only elementthe surface parallel component of the deformation may be evaluated with feature tracking approaches as long as there are features to track (e.g., Aryal et al., 2012; Teza et al., 2007). The only elements that could be easily tracked in this inventorythe 3D-PcD workflow are the barycenter of the source and associated deposit of each landslide, to explore runout dynamics, but we have not investigated this option yet.



795 Significant changes and geomorphic processes: While not a limitation per se, the 3D-PcD workflow detect changes, but cannot classify the nature of this change into various types of geomorphic processes. Given the current *LoD*_{95%} (i.e., > 0.40 m) only large topographic changes, correspond to landslide type processes on hillslopes and fluvial processes, are detected. Debris-flow processes could be detected, and may actually be part of the processes that remobilize landslide debris, however, they potentially create erosion in narrow steep channels that are likely below our spatial resolution capability, or will generate very small sources. They could however contribute to generate very large deposits. Fluvial processes are removed by the only manual operation performed in 3D-PcD, deemed necessary to preserve landslide deposits that have reached the river. While we do not have independent field constraints for all our detected sources, we are confident that the strict handling of error and

SNR filtering approach filters out artefacts, and that our inventory of sources only contains landslide processes. Our approach does not directly resolve the typology of the landslides, including their failure mechanism (sliding, flow, fall), the failed materials (rock, soil, debris) and the velocity of the displacement (Hungr et al., 2014). Yet, combining the 3D-M3C2 distance field with orthoimages (Fig. 10), we have identified the presence of rock avalanches, slumps (rotational failures), debris slides (translational failure) and we suspect the occurrence of some large rockfalls, although pre-EQ slopes steeper than 60° are extremely rare in the detected sources. We did not try to separate these as: (1) we were primarily interested in co-seismic volumes rather than detailed landslide mechanics which would have required field data; (2) there is no way to univocally identify, for the vast majority of our sources, the dominant landslide mechanism with either the 3D-M3C2 distance field and/or the orthoimages; (3) large landslides for which a dominant mechanism can be identified are too few in our inventory to draw a robust inference on scaling properties and geometry.

5.1.3. Landslide topographic change detection compared to manual passive imagery mapping

We presented for the first time a comparison between a classical handcrafted inventory of landslide sources from 2D
 orthoimagery comparison, and a 3D inventory based on LiDAR change detection where landslides are detected according to the topographic change they produce, not a change in optical passive imagery. Results show how different two landslide inventories of the same region, constructed from fundamentally different data sources (passive vs active remote sensing), can be. While the 3D inventory cannot be considered exhaustive, as it has a non-null *LoD*_{95%}, it nonetheless detects roughly 3 times more landslides than the 2D imagery and a planimetric area affected by landsliding nearly two times larger. Most importantly, the 3D-PcD workflow knows its detection limit as one of its outcome is a spatially variable confidence interval (*LoD*_{95%}) and

- confidence metrics (SNR) for each segmented source and deposit. While the resolution capability of 2D image analysis can be evaluated based on pixel size and is better than the LiDAR based approach in our study case, the detection capability is much more difficult to quantify, especially if the inventory is manually handcrafted.
- Both detection and delimitation errors equally contribute to under-detection of the total area in the 2D inventory. They are, as
 expected (Zhong et al., 2020), frequent in areas with poor spectral contrasts between successive orthoimages such as bare rock surfaces or forests. But under-detection also occurs in sparse or low vegetation zones where some very large areas corresponding to vertical subsidence at the top of rotational or translational landslides were not detected (e.g., Fig. 10b) or incorrectly mapped (e.g., Fig. 7c). We note that under-detection in forest, while very significant (58 % of all detection errors), only corresponds to 19.7% of total area and 13.9% of the total volume. This is explained by the small size of missed landslides,
- 830 as large ones strip out vegetation and are easily detectable. Hence, we do not expect that under-detection on forested area represent a large contribution in previously published co-seismic landslide volume estimates. However, it may limit the detection of subsidence area associated to new retrogressive slip planes (Fig 7c) which may prove important for subsequent landslide hazard management. Delimitation and detection errors are dominant on sparse and bare rock surfaces corresponding to 55.6% of the total landslide area. In particular, it is extremely difficult to map the transition between sources and deposits,
- 835 especially on large and amalgamated landslides (e.g., Fig 7c). Here the ability of the 3D-PcD approach to not only detect

sources but also deposits is essential. Our results thus indicate that existing landslide inventories, manually mapped from 2D images, may significantly suffer from under-detection of landslide area at least in regions dominated by sparse or absent vegetation cover.

We show that the main reason the 3D-PcD method did not detect surfaces mapped on the 2D inventory is that these surfaces
 are located in areas where the 3D-M3C2 distance is below the *LoD*_{95%}. The detection limits of the 3D-PcD will improve in future years, by using the latest generation of LiDAR instrument generating dense (> 10 pts/m²) and more accurate 3D point clouds (< 5 cm Z error). With such data, the registration error could become of the order of 5 cm or less, further improving the detection capability of 3D-PCD both in terms of spatial resolution and *LoD*_{95%}.



Figure 10: Two different point<u>points</u> of interest of the <u>landslide inventory results</u>. a) Zoom to the biggest <u>landslide of the inventory</u> showing amalgamation across the divide.<u>3D inventory illustrating various type of landslide mechanisms</u>. a) Area mostly dominated by rock avalanche, where large rockfalls are also expected. b) DetectedDebris slide with mostly translational sliding of a part of the hillslope.movement (A) and slump with likely rotational to translational displacement (B). The point cloud is superimposed with the post-earthquake orthophoto_orthoimage is overlaid on the point cloud (December 15, 2016; Aerial survey, 2017)

5.1.4. Toward a limitation of amalgamation and under-detection biases on total landslide volume estimation

By a direct measurement from topographic data, the amalgamation effect is no longer an issue for total landslide volume estimation of an inventory even though our segmentation approach cannot resolve the amalgamation of individual landslides perfectly. Bypassing the use of a non-linear V-A relationship also avoid uncertainty inherent to the choice of the best suited scaling parameters. As we show, the total landslide volume vary significantly (from 0.376x10⁶ m³ to 1.005x10⁶ m³; Tab.3) depending on the V-A scaling relationship applied to our landslide inventory. For instance, we observe a difference of 18% in total volume estimation only due to the method used to fit data (i.e. on log-transformed or on averaged log-binned data). We also note that total landslide volume estimation from such relationship can get close to the volume estimated from the 3D-PcD for wrong reasons. As instance, applying our V-A relationship to both versions of the 2D inventory with and without deposit areas (Tab.2) lead to a difference of 17% in total volume. These results highlight the overarching sensitivity of the total volume of eroded material to the V-A relationship biases (Li et al., 2014; Marc and Hovius, 2015).

37

Our 3D-PcD approach also allows to estimate total landslide volume without the issue of under-detection of landslides. Due to the difference in the type of under-detection and delimitation errors between both 2D and 3D inventories, these issues do not propagate into total landslide volume estimate in similar ways. The area not detected by the 3D-PCD 865 method in the 2D inventory represents only 0.6 % of the total volume. This is a negligible component owing to the fact that only very shallow landslides, or shallow parts of very large landslides are missed. On the contrary, the area not detected by the 2D inventory represents 60 % of the total volume, highlighting the pronounced underestimation of total volume estimate if one uses image based detection followed by volume calculation. Most of this missed volume is due to the landslide delimitation errors on bare rock and sparse vegetation cover surfaces which represent 42% of the total 870 volume while the under-detection of entire landslides only represents 18%. We also note that a third of the total volume is missed on bare rock surfaces. Our study area was chosen based on LiDAR data availability and contains a particularly high proportion of under-detected landslides in the 2D inventory due to the presence of actively eroding bare bedrock hillslopes. We expect this proportion to significantly vary when considering other landscapes with potentially varying proportions of vegetation cover, vegetation density and type (e.g. grass, shrubs, trees), lithology and 875 ground shaking intensity. 5.2 Landslide population analyses

5.2.1 VolumeNonetheless, our finding represents a first approach to the issue of considering the under-detection of landslides in total landslide volume estimates. We show that extreme caution should be put on co-seismic volumes estimated on landscapes where a large fraction of bare rock surfaces and sparse vegetation cover are present before earthquake, such as the Kaikoura ranges.

880 5.2. Landslide source scaling properties

885

The use of 3D data opens up a very large range of new geometric analysis of landslide sources and deposits. Here, we revisit traditional size-distributions and scaling relationships of landslide sources generated from 2D inventories. We systematically perform sensitivity analysis of these relations to the main parameters of the 3D-PcD workflow: the registration error *reg*, the minimum distance for segmentation D_m and the SNR threshold for removing landslides with limited confidence (See Fig.11, Appendix A, S13 and S14 in supplementary materials).

5.2.1. Total volume of landslide sources and deposits

Over the studied area of ~5 km², <u>1431524</u> landslide sources and <u>853304</u> landslide deposits were detected with the 3D point cloud processing workflow. This relatively large number of landslides is mostly associated to the large number of small landslides (< 100 m², n = 977) that were detected thanks to the resolution of the data. The scaling of the The scaling of pdf(V),
with an exponent of volume of sources, *e* = -1.7161 ± 0.08, indicates a slight tendency for the overall eroded volume to be dominated by the largest landslide (<u>171,175151,706</u> m³, that is <u>18.820</u> % of the total volume). The uncertainty on total landslide volume, <u>17.116</u>% to <u>23.720</u> % for deposits and sources, respectively, might appear large, <u>butas it</u> is based on a conservative 95% confidence interval that we use throughout our analysis. <u>It is mostly These uncertainties are</u> dominated by the registration error (*reg* = 0.472 m) and by the lower point cloud density of the pre-earthquake LiDAR data (Table.). Within this uncertainty these uncertainties, the total volume of sources (<u>908,055 ± 215,640752,616 ± 154,165</u> m³) and deposits (<u>1,008,626</u> ± <u>172,745949,742 ± 150,014</u> m³) are not statistically different. The larger volume of deposit is however consistent with rock decompaction during landsliding. We also note that , which could be constrained by using a joint gravity survey in future

studies (Mouyen et al., 2020). On top of this effect, we also expect an increased likelihood for sources to be more systematically filtered out than deposits as they are thinner (mean 3D-M3C2 distance are 2.69 m for sources and 3.4 m for deposits). This is
 consistent with the tendency for debris deposits form more concentrated and, located on convergent parts of the landscape (e.g., hillslope hollows, debris flow channels), to collect different upslope sources in thicker patches at the toe of hillslopes, and are thus more systematically above the detection threshold. Very shallow rockfalls might not be detected and accounted for in the source volume. Hence, we expect to detect more of the population of landslide deposits than of the population of sources.than the initial individual sources (e.g., Fig. 10a)

905 5.2.2. Distribution of landslide volumesource area and area: power-law behaviourlack of rollover

We obtain a range of landslide area over 3 to 4 orders of magnitude (20 to 42.650 m²) for which we constructed the pdf of area and volume. In landslide analysis, the pdf of landslide area represents the basis to estimate large-scale landslide erosion (Larsen et al. 2010). This distribution has generally a negative power law behaviour for landslide areas larger than a given threshold and displays a rollover for smaller landslides (Fan et al. 2019; Guzzetti et al., 2002; Malamud et al., 2004; Malamud and 910 Turcotte, 1999; Stark and Hovius, 2001). In this study, we find that the exponent c of the power law for the landslide area distribution is -1.79 ± 0.03 (Fig.5a). This is roughly consistent with the exponents obtained over the entire Kaikoura coseismic landslide inventory of $-1.88 (N_{LT} = 10, 195; \text{Massey et al., } 2018)$ and more recently of $-2.10 (N_{LT} = 29, 557; \text{We obtain a range})$ of landslide area over 3 to 4 orders of magnitude (20 to 42,679 m²) which obey a clear power-law relationship for $A > 40 m^2$ with an exponent $c = -1.72 \pm 0.04$ (Fig.8a). The negative power law behaviour for landslide area is generally observed for 2D 915 landslide inventories, although only for source areas typically larger than 500- 5000 m² (Guzzetti et al., 2002; Malamud et al., 2004; Malamud and Turcotte, 1999; Medwedeff et al., 2020). Our exponent is roughly consistent with the exponents obtained over the entire Kaikoura coseismic landslide inventory of -1.88 ($N_{LT} = 10,195$; Massey et al., 2018) but differs significantly from the most recent estimate of -2.10 (N₁ = 29.557; Massev et al., 2020). We present here, one of the first landslide volume distribution derived directly from 3D topographic data, rather than inferred from the combination of detection of the landslide 920 area distribution on 2D data and an estimated volume-area relationship which is much more difficult to precisely estimate. Our direct measurements show that the landslide volume distribution indeed obeys a power-law relationship with an exponent e = -1.71 ± 0.04 , consistent with exponents estimated in previous studies $1.0 \le e \le 1.9$ and $1.5 \le e \le 1.9$ for soil landslides (Brunetti et al., 2009; Malamud et al., 2004). Further analyses, similar to ours are necessary to get a better handle on the landslide volume

distribution, a critical information with respect to risk analysis and landslide erosion calculation.

925 5.2.3 Rollover in the distribution of landslide area

, Fig. 7a) for which the power-law scaling is expressed for A > 500 m². A sensitivity analysis of the impact of the workflow parameters (Fig. 11), in particular D_m which affects the level of amalgamation in the dataset, does not yield values of *c* smaller than -1.85 and cannot reconcile our results with Massey and co-authors (2020). Either, our limited study area overemphasizes, by chance, the occurrence of large landslides generating a smaller value of c, the manual inventory of Massey et al., 2020 may



Most importantly, the landslide area distribution that we derive does not exhibit a rollover classically observed in 2D landslide inventories. Only a small deviation of the power-law behaviour appears for A < 40 m². Varying *reg* or D_m does not change this behaviour (Fig. 11a and 11b), nor using a density based clustering approach (Fig. S8). Increasing the SNR threshold to 2 (Fig.

935 11c), and thus censoring a larger number of small/intermediate landslides with small depth, increases the deviation from the power-law behaviour, but never creates a rollover. Hence, we are confident that our probability density of source area, generated by a purely objective and automatic approach, does not exhibit a rollover. If there is any, it would occur for sizes much smaller than 20 m².



(c) signal-to-noise (SNR) values. All plots share the same y-axis. Value of the parameters used for this study are colored in red. Several hypothesishypotheses, related to landslide mechanics or to landslide detection capabilities, have been put forward to explain the rollover behaviour at lowfor small landslide area, including. These include the transition to a cohesion dominated regime reducing the likelihood of rupture (Frattini and Crosta, 2013; Jeandet et al., 2019; Stark and Guzzetti, 2009), a cohesion 945 gradient with depth (Frattini and Crosta, 2013), landslide amalgamation (Tanyas et al., 2019) or the under-detection of small landslides (Hovius et al., 1997; Stark and Hovius, 2001). The landslide area distribution in our study does not display a rollover. We have proposed a method to rigorously evaluate the likelihood of detecting spurious landslides due to different data sampling of a rough surface at small landslide areas (Fig S.2.2.1). We set a conservative lower bound of 20 m² above which we are confident that all detected changes are true topographic change. We have also checked that the segmentation distance does not 950 impact the absence of a rollover in our data (Fig S2.2.2 in the supplementary material). Given that Massey et al. (2020) reports a rollover at ~ 50 m² for the Kaikoura earthquake landslide inventory based on 2D optical image analysis (Fig.5.a), our results supports the idea that the rollover behaviour observed in previous studies is likely caused by an under detection of small landslides, even with high resolution imagery (Hovius et al., 1997; Stark and Hovius, 2001). If this hypothesis is correct, the number of landslides potentially missed in previous studies can be important. If we consider the power law fitting statistics for 955 landslide area distribution from Massey et al. (2020), the number of landslides between 20 m² $\leq A < 500$ m² potentially missed would be around 169,000. This represents 92% of total landslides that would not be considered. While the under detection of small landslides would not greatly affect the total landslide volume estimation, it could have consequences for our understanding of natural hazards mechanics. This promising result possibly highlights the advantages of using LiDAR data combined to our 3D differencing workflow with low level of change detection to generate more accurate and complete landslide inventory datasets... Our segmentation approach tends to amalgamate landslides rather than over-segment large ones and cannot explain the lack of rollover. On the contrary, this would create or accentuate a rollover by suppressing small landslides through amalgamation. The lack of rollover may also hint at a transition towards a different landsliding process, where rockfall dominates for instance. However, core points in sources with slopes > 60° represent only 0.74 % of the source area, pointing at an extremely limited contribution of rockfall processes originating from near-vertical cliffs.

965 5.2.4 Landslide volume-area relationship

970

985

The landslide volume-area (V-A) scaling relationships obtained in this study are close to the one of Larsen et al. (2010) for soil landslides. This is consistent with the fact that 50% of the landslide thicknesses are lower than 1 m, showing that most of our inventory is relevant to shallow landsliding. The V A scaling relationship of Massey et al. (2020) for soil landslides gives the best estimation of total landslide volume but overestimate the volume of small landslides. The differences in total volume predicted by our two V A scaling relationships show that estimates of landslide volume deduced from such relationships greatly depend on the method used to fit data. Our results suggest that fitting model on log-binned data gives a better result in total landslide volume estimation. However, measuring the volume directly from topographic data overcome the issue of choosing a peculiar V A relationship.

5.3 Toward a limitation of amalgamation and reactivation biases on landslide volume estimation

- 975 The amalgamation effect is a classical issue for 2D landslide mapping and volume assessment (e.g., Li et al., 2014; Mare and Hovius, 2015b), which leads to a higher number of large landslides than should be expected, and a significant overestimation of the total volume of landslides when using a non-linear V-A relationship. A simple solution to this last problem consists in directly measuring the total landslide volume by comparing pre- and post-earthquake topographic data (e.g., LiDAR) with a DoD (Massey et al., 2020) or with the method described in this paper. While our simple segmentation approach cannot resolve
- 980 the amalgamation of individual landslides perfectly, the total volume associated to sources and deposit can be robustly estimated independantly of a V-A relationship.

The detection of reactivated landslides from 2D optical imagery remain challenging due to to the weak contrast of vegetation between pre- and post-earthquake periods, or even the absence of vegetation. Recent methods have been developped to detect reactivated landslide based on NDVI trajectory induced by differences in revegetation rate (Behling et al., 2014, 2016) but the impact of possibly missed reactivated landslide on total volume estimation is still poorly understood (Guzzetti et al., 2009).

2D or 3D topographic differencing methods are insensitive to the lack of texture variation and can resolve the issue of reactivation. Because vegetation barely develops on very steep slopes and eliffs, the 3D differencing approach oriented

perpendicular to the local topographic slope, as opposed to vertical differencing, is critical in detecting subtle changes. Hence, our 3D approach detects landslide occurring in steep areas with poor vegetation cover (Fig.6.b) that would have otherwise 990 been missed with 2D optical imagery approaches, or incorrectly detected with vertical differencing. In this study area, the proportion of reactivated landslide area, 27.2%, is lower than new landslide failures (Table.3), and most of the large reactivated landslides that we find have not been included in the initial mapping of 27 landslides by Massey et al. (2018). Assuming that reactivated landslides cannot be detected by classical methods, the volume potentially lacking represents 29.9 ± 12.8% of the total estimated landslide volume, including some of the largest failures of the studied area. Our study area was chosen based 995 on LiDAR data availability, and may contain a particularly high proportion of reactivated landslides due to the presence of actively eroding bare bedrock hillslopes compared to the size of the study area. We expect this proportion to significantly vary when considering other landscapes with potentially varying proportion of vegetation cover, vegetation density and type (e.g. To evaluate the degree of under-detection as a function of landslide size, we can leverage the two inventories we have created. For this, we compute a completeness ratio as the number of detected sources in 2D over the number detected in 3D, per range 1000 of source area. Fig.12 shows that the completeness ratio is around 0.25 for areas ~20-40 m² and systematically increases with landslide size up to 0.8-0.9 for sizes larger than 200-500 m². The behaviour above 500 m² suggests a slight increase of the completeness ratio which would asymptotically tend towards 1 for very large landslide source that cannot be missed both in 2D and 3D. However, we caution that our inventories contain too few landslides above 1000 m² (~ 20 each) to draw robust conclusions on this behaviour or derive a functional relationship. As some very shallow landslides detected in 2D are not 1005 detected in 3D, we cannot consider the 3D inventory as complete for small sizes and the true completeness ratio may actually be slightly overestimated at very small sizes. Yet, the 3D inventory is however far more complete than the 2D inventory. As such, our results demonstrate that in this study area, the rollover behaviour of the 2D inventory is caused by a size-dependent under-detection of small landslides below 500 m², existing even when using high resolution imagery with a better resolving capability than our 3D-PcD workflow (7 m² vs 20 m²) (Hovius et al., 1997; Stark and Hovius, 2001). This size-dependent 1010 under-detection of small landslides is expected to be systematically present in other image-based landslide inventories, even if carefully hand-crafted. Whether this effect systematically explains all the rollovers observed in past landslide inventories, or if other hypothesis such as a transition to cohesion dominated regime also contribute or are only expressed at even smaller scales remain to be explored. In any case, the number of landslides potentially missed in previous studies can be important given the level of under-detection that we report for small sizes. For instance, we note that in the first manual inventory of the 1015 Kaikoura EQ landslides (Massey et al., 2018), only 27 landslides were detected in our study area. The volume corresponding to under-detected small landslides may actually not matter in terms of total volume produced by earthquake derived landsliding. However, the presence or not of a rollover significantly matters in terms of hazards management (i.e. impact on the exposed population, infrastructure damage etc.) owing to the very large differences in the probability of small landslides.



specifically acquired to bridge the gap between large scale airborne lidar and terrestrial lidar are needed to get a better handle on the volume distribution of landslides, a critical information with respect to risk analysis and landslide erosion calculation.

5.2.4. Landslide depth and volume-area relationship

- Our 3D-PcD approach opens the possibility to directly quantify the variations of landslide depth with size. We show that landslide mean depth does not vary for landslide area smaller than 1000 m². The same behaviour has been observed by Larsen et al. (2010) for soil failures suggesting that our landslide inventory may be relevant to shallow landslide. This is consistent with the fact that 50% of the landslide thicknesses are lower than 1.2 m and that the landslide volume-area (V-A) scaling relationships obtained in this study are close to that of Massey et al. (2020) and Larsen et al. (2010) for soil landslides.
- Moreover, for bedrock failures, Larsen et al. (2010) did observe an increase of landslide depth with size. Our landslide inventory may exhibit a slight increase of landslide depth for landslide area larger than 1000 m² that may hint at the transition from shallow to deeper bedrock landslide. However, the limited number of large landslides in our inventory does not allow to draw robust conclusions on this point.

The sensitivity analyses to the workflow parameters show that the V-A exponent γ is not significantly affected by the variations of the *reg* and SNR values we explored. Respectively, γ vary from 1.16 ± 0.03 to 1.19 ± 0.01 with the explored range of *reg* and varies from 1.17 ± 0.02 to 1.21 ± 0.02 with the SNR threshold (Fig S14, Appendix A). It is also not affected by the segmentation distance for $D_m < 4$ m, beyond which landslide amalgamation becomes significant and γ decreases to 1.1 for $D_m=6$ m.

-grass, shrubs, trees), lithology and ground shaking intensity. Nonetheless, our finding represents a first approach to the issue
 of considering reactivated landslides in total landslide volume estimates, and our results indicates that this should not be neglected at least in regions dominated by a low or absent vegetation cover.

To evaluate the difference of volume that would have been estimated from traditional methods impacted by under detection of reactivated landslides, we apply the Massey et al. (2020) V A relationship for all landslides only to the new failures detected in our inventory. As our inventory has very likely a much lower detection level than optical methods (see 5.2.3), we only consider new failures with a minimum area of 50 m² (typical of the rollover observed in Massey et al. 2020). This amount to a 2D traditional processing of the study area. This traditional approach would predict a total volume of 616,308 m³, significantly lower than the volume measured directly by our approach. This highlights the need to more systematically generalize the use of 3D data to improve the creation of robust landslide inventories and generate more accurate estimate of the total volume of sediment produced by earthquakes or climatic events.

1070 6. Conclusion

In this paper, we introduced introduce a new workflow for semi-automated landslide sources and deposit detection and volume estimation using 3D differencing based on high resolution topographic point cloud data. This method uses the M3C2 algorithm

developed by Lague et al. (2013) for accurate change detection based on the 3D distance normal to the local surface-as well as a vertical-M3C2 for volume calculation of landslide. Landslide sources and deposits onecare segmented, using a 3D connected component segmentation procedure has been applied to individualize landslidesapproach, and their volumes are computed by a vertical-M3C2. Spatially variable uncertainties on distance and volume are provided by the calculation and used in the workflow to evaluate if a change is statistically significant or not, and for volume uncertainty estimation- and to define a confidence metric per source or deposit (Signal to Noise Ratio). The SNR is used to filter out potentially remaining artefacts. We provide various tests and recipes to estimate the registration error and to choose the parameters of the M3C2 algorithm as function of the point cloud density to ensure the lowest level of change detection, and the best resolution of the 3D map of change. Applied to a 5 km² area located in the Kaikoura region in New Zealand with pre- and post-earthquake LiDAR, we showedgenerate the first automatic inventory of landslide sources and deposits based on repeat 3D airborne LiDAR data. We show that:

085

1090

1095

100

1105

A <u>minimum</u> level of 3D change detection at 95% confidence of 0.3440 m can be reached with airborne LiDAR data, which is largely set by the registration error. In our case, the limited quality of flight line alignment of the pre-EQ data was the dominant source of registration uncertainty. Because it operates on raw data, M3C2 accounts for sub-pixel characteristics such as point density and roughness that are not accounted for when working on DEMs, and results in more robust statistics when it comes to evaluate if a change is significant or not. 3D point cloud differencing is critical on steep slopes, and allows to decrease the lower level of change detection compared to the traditional DoD.

- Adding elevation information inConsidering 3D topographic change for landslide detection removes the amalgamation effect on the total landslide volume-estimation by directly measuring it in 3D rather than considering an *ad hoc* V-A relationship. Amalgamation in 3D is still a potentialan issue when exploring individual landslide area and volume statistics given the simplistic segmentation approach that we have used, however, However, our approach has the benefits of more systematically capturing small landslides than traditional approaches based on 2D imagery with manual or automatic landslide mapping.
- Landslide reactivation_andslides on surfaces lacking a significant with low or no vegetation cover is are classically missed with 2D imagery processing due to the lack of texture or spectral change. 3D processing fully accounts for reactivated landslides. In our study case, 75 % of surface area, 29.9 ± 12.8 was missed when considering a 2D inventory, corresponding to 60% of the total volume was due to determined with the 3D inventory. Missing area both correspond to detection error (landslide reactivation, highlighting that in areas with a mixture of vegetatedfully missed) and non-vegetated steep slopes, 2D approaches can significantly underestimate the numberdelimitation error (uncertainty in contours). Our method also shows the ability to detect subsidence related to slip failure propagation and volumethe initiation or displacement of landslidestranslational and rotational large landslides, which cannot be detected with 2D imagery.

-	Mis en forme : Couleur de police : Automatique
-	Mis en forme : Couleur de police : Automatique
-	Mis en forme : Couleur de police : Automatique
-	Mis en forme : Couleur de police : Automatique

45

- As this method provides direct 3D measurement, landslide geometry properties can be explored and tested such as the V A relationship, landslidevolume, area, depth and volumetheir distribution and others.can be explored. Our results are broadly consistent with the V-A relationship scaling parameters determined by Larsen et al. (2010) and Massey et al. (2020) for soil landslides, and Massey et al. (2020), with a scaling exponent of 1.20. The largest and deepest landslides deviate significantly from this trend, but they are too few in our database to confidently infer a scaling relationship for these.17.
- No rollover is observed in the landslide area distribution down to 20 m², our conservative resolution limit. Inventories based on 2D images analysis following the Kaikoura EQ typically observe a rollover at 50 m² (Massey et al., 2020). This lend credit to the hypothesis that the rollover systematically observed in landslide area distributions generated 1115 from 2D images is related to an under detection of small landslide., using the 3D landslide inventory. However, we demonstrate, for the first time, a size-based under-detection in landslide mapped from repeat 2D images, which in turn results in a rollover of the landslide source area distribution for the 2D inventory. This result lends credit to the hypothesis that the rollover systematically observed in landslide area distributions generated from 2D images is entirely or partially related to an under-detection of small landslides (Stark and Hovius, 2001).
- 120 Our 3D processing workflow is a first step towards harnessing the full potential of repeatrepeated 3D high resolution topographic surveys to automatically create complete and accurate landslide inventories-that. However, high density LiDAR flights are not always available in landslide-prone regions for which a 2D image-based approach remains the most suited approach. Nevertheless, we recommend to systematically perform a 3D-PcD approach where repeat LiDAR data exist. This is critically needed to improve landslide science and managing the cascade of hazards following large earthquakes or storm
- 1125 events, by automatically identifying landslide deposits, and subtle features such as subsidence developing around landslides missed in 2D inventories. Current bottlenecks to apply this workflow over larger scales, beyond the availability of high-quality 3D data itself, are the registration of pre- and post-EQ data when complex co-seismic deformation patterns occur, and limitations of the segmentation method in high landslide density areas. While airborne LiDAR is best suited to vegetated environments and currently results in the best precision compared to aerial or spatial photogrammetry, the workflow operates
- 1130 for any kind of 3D data.

1110

Appendix A: Table of the result of the sensitivity analyses to the workflow parameters: reg, Dm and SNR. Unit for the registration error reg and the minimum segmentation distance D_m is in meter and SNR has no unit.

<u>Workflow</u> parameter	<u>Val</u> <u>ue</u>	<u>N_{LT}</u>	Landslide	e area distribu	<u>ition</u>	Landside volume distribution			V-A relationship		
			Log b	<u>c</u>	<u>R²</u>	Log d	<u>e</u>	<u>R²</u>	Log a	Υ	<u>R²</u>
P /Q	0.2*	<u>524</u>	0.70 ± 0.12	-1.72 ± 0.04	<u>0.99</u>	0.39 ± 0.26	-1.61 ± 0.08	<u>0.98</u>	-0.26 ± 0.08	$\underline{1.17 \pm 0.02}$	0.99
reg	0.3	329	$\underline{0.50\pm0.12}$	-1.64 ± 0.04	<u>0.99</u>	0.25 ± 0.16	-1.53 ± 0.05	<u>0.99</u>	$\underline{-0.13\pm0.10}$	$\underline{1.16\pm0.03}$	<u>0.99</u>

	<u>0.4</u>	<u>200</u>	$\underline{0.28\pm0.27}$	-1.55 ± 0.09	<u>0.96</u>	$\underline{0.20\pm0.22}$	-1.49 ± 0.06	<u>0.98</u>	$\underline{-0.08\pm0.06}$	$\underline{1.17\pm0.02}$	<u>0.99</u>
	<u>0.5</u>	<u>234</u>	$\underline{0.11 \pm 0.19}$	$\underline{-1.49 \pm 0.07}$	<u>0.98</u>	$\underline{0.17 \pm 0.21}$	$\underline{-1.50\pm0.17}$	<u>0.99</u>	$\underline{-0.08\pm0.04}$	$\underline{1.19\pm0.01}$	<u>0.99</u>
	<u>1.5</u>	<u>550</u>	$\underline{0.70\pm0.12}$	-1.73 ± 0.04	<u>0.99</u>	0.40 ± 0.26	-1.62 ± 0.08	<u>0.98</u>	-0.13 ± 0.10	1.17 ± 0.02	<u>0.99</u>
	<u>2*</u>	<u>524</u>	$\underline{0.70 \pm 0.12}$	-1.72 ± 0.04	<u>0.99</u>	0.39 ± 0.26	-1.61 ± 0.08	<u>0.98</u>	$\underline{-0.26\pm0.08}$	$\underline{1.17 \pm 0.02}$	0.99
\underline{D}_m	<u>3</u>	<u>443</u>	$\underline{0.61 \pm 0.16}$	-1.68 ± 0.05	<u>0.99</u>	$\underline{0.35 \pm 0.17}$	$\underline{-1.58\pm0.05}$	<u>0.99</u>	$\underline{-0.26\pm0.04}$	$\underline{1.17\pm0.01}$	<u>0.99</u>
	<u>4</u>	<u>373</u>	$\underline{0.42\pm0.18}$	-1.59 ± 0.06	<u>0.98</u>	$\underline{0.44 \pm 0.23}$	-1.61 ± 0.06	<u>0.99</u>	$\underline{-0.08\pm0.06}$	$\underline{1.14\pm0.03}$	<u>0.99</u>
	<u>6</u>	<u>259</u>	$\underline{0.13 \pm 0.14}$	$\underline{-1.45\pm0.04}$	<u>0.99</u>	$\underline{0.30\pm0.23}$	$\underline{-1.54\pm0.07}$	<u>0.98</u>	$\underline{-0.08\pm0.04}$	$\underline{1.10\pm0.03}$	<u>0.99</u>
	<u>1</u>	<u>1270</u>	$\underline{0.86\pm0.11}$	-1.85 ± 0.04	<u>0.99</u>	0.32 ± 0.24	-1.69 ± 0.07	<u>0.99</u>	-0.42 ± 0.06	1.21 ± 0.02	<u>0.99</u>
<u>SNR</u>	<u>1.5*</u>	<u>524</u>	0.69 ± 0.12	-1.72 ± 0.04	<u>0.99</u>	0.39 ± 0.26	<u>-1.61 ± 0.08</u>	<u>0.98</u>	<u>-0.26 ± 0.06</u>	$\underline{1.17 \pm 0.02}$	<u>0.99</u>
	2	<u>166</u>	$\underline{0.22\pm0.14}$	$\underline{-1.49\pm0.04}$	<u>0.99</u>	-0.1 ± 0.26	$\underline{-1.38\pm0.08}$	<u>0.98</u>	$\underline{-0.25\pm0.09}$	$\underline{1.19\pm0.03}$	<u>0.99</u>

*: reference case used in the study.

1135 Code availability

The code producing the landslide inventory in this study is available as a jupyter notebook form at https://github.com/Thomas-Brd/3D_landslide_detection, and is also archived in Zenodo: http://doi.org/10.5281/zenodo.4010806.

Data availability

LiDAR data used in this study can be found at: http://doi.org/10.5281/zenodo.4011629

 1140
 The final landslide source and deposit information supporting the findings of this paper can be found at https://github.com/Thomas-Brd/3D_landslide_detection, or in Zenodo: http://doi.org/10.5281/zenodo.401080610.5281/zenodo.4558905

Supplement link

The supplement related to this article is available online at: .

1145 Author contribution

D.L. and T.B. designed the landslide detection workflow. T.B. and all co-authors participated to the discussion, writing and reviewing of this paper. T.B produced the figures and the code.

Competing interests

The authors declare that they have no conflict of interest.

1150 Acknowledgements

This project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement no. 803721), from the Agence Nationale de la Recherche (grant no. ANR-14-CE33-0005), from the LiDAR topobathymetric platform <u>of the Rennes University</u> and from the Brittany region-(project LIDAREAU).

Mis en forme : Motif : Transparente (Blanc)

1155 References

Aerial Surveys, Aerial photographs derived from two surveys of the study area carried out in 2014 to 2015 and in 2016 to 2017, by Aerial Surveys Ltd, 2017.

Ankerst, M., Breunig, M. M., Kriegel, H.-P. and Sander, J.: OPTICS, ACM SIGMOD Rec., 28(2), 49–60, doi:10.1145/304181.304187, 1999.

160 Aryal, A., Brooks, B. A., Reid, M. E., Bawden, G. W. and Pawlak, G. R.: Displacement fields from point cloud data: <u>Application of particle imaging velocimetry to landslide geodesy</u>, J. Geophys. Res. Earth Surf., 117(1), 1–15, doi:10.1029/2011JF002161, 2012.

Behling, R., Roessner, S., Kaufmann, H. and Kleinschmit, B.: Automated spatiotemporal landslide mapping over large areas using rapideye time series data, Remote Sens., 6(9), 8026–8055, doi:10.3390/rs6098026, 2014.

165 Behling, R., Roessner, S., Golovko, D. and Kleinschmit, B.: Derivation of long-term spatiotemporal landslide activity A multi-sensor time series approach, Remote Sens. Environ., 186, 88–104, doi:10.1016/j.rse.2016.07.017, 2016. Benjamin, J., Rosser, N. J. and Brain, M. J.: Emergent characteristics of rockfall inventories captured at a regional scale, Earth Surf. Process. Landforms, 45(12), 2773–2787, doi:10.1002/esp.4929, 2020.

Besl, P. J. and McKay, N. D.: A Method for Registration of 3-D Shapes, IEEE Trans. Pattern Anal. Mach. Intell., 14(2), 239– 256, doi:10.1109/34.121791, 1992.

Bossi, G., Cavalli, M., Crema, S., Frigerio, S., Quan Luna, B., Mantovani, M., Marcato, G., Schenato, L. and Pasuto, A.: Multitemporal LiDAR-DTMs as a tool for modelling a complex landslide: A case study in the Rotolon catchment (eastern Italian Alps), Nat. Hazards Earth Syst. Sci., 15(4), 715–722, doi:10.5194/nhess 15–715–2015, 2015.

Brunetti, M. T., Guzzetti, F. and Rossi, M.: Probability distributions of landslide volumes, Nonlinear Process. Geophys., 16(2), 175 <u>179–188, doi:10.5194/npg-16-179-2009, 2009.</u>

Bull, J. M., Miller, H., Gravley, D. M., Costello, D., Hikuroa, D. C. H. and Dix, J. K.: Assessing debris flows using LIDAR differencing: 18 May 2005 Matata event, New Zealand, Geomorphology, 124(1–2), 75–84, doi:10.1016/j.geomorph.2010.08.011, 2010.

 <u>Carrea</u>, D., Abellan, A., Derron, M., Gauvin, N. and Jaboyedoff, M.: MATLAB Virtual Toolbox for Retrospective Rockfall
 <u>Source Detection and Volume Estimation Using 3D Point Clouds: A Case Study of a Subalpine Molasse Cliff, 2021.</u> <u>CloudCompare (version 2.11) [GPL software]. (2020). Retrieved from http://www.cloudcompare.org/</u> Corsini, A., Borgatti, L., Cervi, F., Dahne, A., Ronchetti, F. and Sterzai, P.: Estimating mass-wasting processes in active earth slides - Earth flows with time-series of High-Resolution DEMs from photogrammetry and airborne LiDAR, Nat. Hazards Earth Syst. Sci., 9(2), 433–439, doi:10.5194/nhess-9-433-2009, 2009.

- 1185
 DiBiase, R. A. and Lamb, M. P.: Dry sediment loading of headwater channels fuels post-wildfire debris flows in bedrock landscapes, Geology, 48(2), 189–193, doi:10.1130/G46847.1, 2020.

 Dolan, J.F.: Data collection and processing report LiDAR survey of five fault segments (Estern Clarence, Western Clarence, Central Eastern Awatere, West Wairau and East Hope-Conway) of the Malborough fault system on the Northwestern portion of New Zealand's south island. Ph.D., University of southern California, 11 pp., 2014
- 1190
 Dolan J.F, Rhodes E.J.. Marlborough Fault System, South Island, New Zealand, airborne lidar. National Center for Airborne Laser Mapping (NCALM), distributed by OpenTopography. http://dx.doi.org/10.5069/G9G44N75, 2016.

 Dussauge, C., Grasso, J.-R. and Helmstetter, A.: Statistical analysis of rockfall volume distributions: Implications for rockfall dynamics, J. Geophys. Res. Solid Earth, 108(B6), doi:10.1029/2001jb000650, 2003.

Esposito, G., Salvini, R., Matano, F., Sacchi, M., Danzi, M., Somma, R. and Troise, C.: Multitemporal monitoring of a coastal
 landslide through SfM-derived point cloud comparison, Photogramm. Rec., 32(160), 459–479, doi:10.1111/phor.12218, 2017.
 Fan, Y., Clark, M., Lawrence, D. M., Swenson, S., Band, L. E., Brantley, S. L., Brooks, P. D., Dietrich, W. E., Flores, A.,

 Grant, G., Kirchner, J. W., Mackay, D. S., McDonnell, J. J., Milly, P. C. D., Sullivan, P. L., Tague, C., Ajami, H., Chaney, N., Hartmann, A., Hazenberg, P., McNamara, J., Pelletier, J., Perket, J., Rouholahnejad-Freund, E., Wagener, T., Zeng, X., Beighley, E., Buzan, J., Huang, M., Livneh, B., Mohanty, B. P., Nijssen, B., Safeeq, M., Shen, C., van Verseveld, W., Volk,
 J. and Yamazaki, D.: Hillslope Hydrology in Global Change Research and Earth System Modeling, Water Resour. Res., 1737–

<u>1772</u>, doi:10.1029/2018WR023903, 2019.
 Frattini, P. and Crosta, G. B.: The role of material properties and landscape morphology on landslide size distributions, Earth Planet. Sci. Lett., 361, 310–319, doi:10.1016/j.epsl.2012.10.029, 2013.

Giordan, D., Allasia, P., Manconi, A., Baldo, M., Santangelo, M., Cardinali, M., Corazza, A., Albanese, V., Lollino, G. and
 Guzzetti, F.: Geomorphology Morphological and kinematic evolution of a large earth fl ow: The Montaguto landslide, southern Italy, Geomorphology, 187, 61–79, doi:10.1016/j.geomorph.2012.12.035, 2013.

Glennie, C.: Rigorous 3D error analysis of kinematic scanning LIDAR systems, J. Appl. Geod., 1(3), 147–157, doi:10.1515/jag.2007.017, 2008.

Glennie, C. L., Hinojosa-Corona, A., Nissen, E., Kusari, A., Oskin, M. E., Arrowsmith, J. R. and Borsa, A.: Optimization of

1210 legacy lidar data sets for measuring near-field earthquake displacements, Geophys. Res. Lett., 41(10), 3494–3501, doi:10.1002/2014GL059919, 2014.

Guzzetti, F., Malamud, B. D., Turcotte, D. L. and Reichenbach, P.: Power-law correlations of landslide areas in central Italy, Earth Planet. Sci. Lett., 195(3–4), 169–183, doi:10.1016/S0012-821X(01)00589-1, 2002.

Guzzetti, F., Ardizzone, F., Cardinali, M., Rossi, M. and Valigi, D.: Landslide volumes and landslide mobilization rates in

1215 Umbria, central Italy, Earth Planet. Sci. Lett., 279(3–4), 222–229, doi:10.1016/j.epsl.2009.01.005, 2009.

Mis en forme : Anglais (Royaume-Uni)

- Guzzetti, F., Mondini, A. C., Cardinali, M., Fiorucci, F., Santangelo, M. and Chang, K. T.: Landslide inventory maps: New tools for an old problem, Earth-Science Rev., 112(1–2), 42–66, doi:10.1016/j.earscirev.2012.02.001, 2012. Hovius, N., Stark, C. P. and Allen, P. A.: Sediment flux from a mountain belt derived by landslide mapping, Geology, 25(3), 231, doi:10.1130/0091-7613(1997)025<0231:SFFAMB>2.3.CO;2, 1997.
- 1220 Hungr, O., Leroueil, S. and Picarelli, L.: The Varnes classification of landslide types, an update, Landslides, 11(2), 167–194, doi:10.1007/s10346-013-0436-y, 2014.

James, M. R., Robson, S. and Smith, M. W.: 3-D uncertainty-based topographic change detection with structure-from-motion photogrammetry: precision maps for ground control and directly georeferenced surveys, Earth Surf. Process. Landforms, 42(12), 1769–1788, doi:10.1002/esp.4125, 2017.

James, P. I., Ph, D., Dolan, J. F. and Hall, Z.: Data Collection and Processing Report LiDAR survey of five fault segments (Eastern Clarence, Western Clarence, Central Eastern Awatere, West Wairau and East Hope Conway) of the Marlborough Fault System on the Northwestern portion of New Zealand 's S., (213), n.d.

Jeandet, L., Steer, P., Lague, D. and Davy, P.: Coulomb Mechanics and Relief Constraints Explain Landslide Size Distribution, Geophys. Res. Lett., 46(8), 4258–4266, doi:10.1029/2019GL082351, 2019.

1230 Keefer, D. K.: The importance of earthquake-induced landslides to long-term slope erosion and slope-failure hazards in seismically active regions, Geomorphology, 10(1–4), 265–284, doi:10.1016/0169-555X(94)90021-3, 1994. Lague, D., Brodu, N. and Leroux, J.: Accurate 3D comparison of complex topography with terrestrial laser scanner:

Application to the Rangitikei canyon (N-Z), ISPRS J. Photogramm. Remote Sens., 82, 10–26, doi:10.1016/j.isprsjprs.2013.04.009, 2013.

Larsen, I. J., Montgomery, D. R. and Korup, O.: Landslide erosion controlled by hillslope material, Nat. Geosci., 3(4), 247–251, doi:10.1038/ngeo776, 20102010a.

Larsen, I. J., Montgomery, D. R. and Korup, O.: Landslide erosion controlled by hillslope material, Nat. Geosci., 3(4), 247–251, doi:10.1038/ngeo776, 2010b.

Li, G., West, A. J., Densmore, A. L., Jin, Z., Parker, R. N. and Hilton, R. G.: Seismic mountain building: Landslides associated
 with the 2008 Wenchuan earthquake in the context of a generalized model for earthquake volume balance, Geochemistry,
 Geophys. Geosystems, 15(4), 833–844, doi:10.1002/2013GC005067, 2014.

Lumia, R., Shapiro, L. and Zuniga, O.: A new connected components algorithm for virtual memory computers, Comput. Vision, Graph. Image Process., 22(2), 287–300, doi:10.1016/0734-189X(83)90071-3, 1983.

Malamud, B. D. and Turcotte, D. L.: Self-organized criticality applied to natural hazards, Nat. Hazards, 20(2–3), 93–116, doi:10.1023/A:1008014000515, 1999.

Malamud, B. D., Turcotte, D. L., Guzzetti, F. and Reichenbach, P.: Landslide inventories and their statistical properties, Earth Surf. Process. Landforms, 29(6), 687–711, doi:10.1002/esp.1064, 2004.

Marc, O. and Hovius, N.: Amalgamation in landslide maps: Effects and automatic detection, Nat. Hazards Earth Syst. Sci., 15(4), 723–733, doi:10.5194/nhess-15-723-2015, 2015a2015.

1250 Marc, O. and Hovius, N.: Amalgamation in landslide maps: Effects and automatic detection, Nat. Hazards Earth Syst. Sci., 15(4), 723–733, doi:10.5194/nhcss-15-723-2015, 2015b.

Marc, O., Hovius, N. and Meunier, P.: The mass balance of earthquakes and earthquake sequences, Geophys. Res. Lett., 43(8), 3708–3716, doi:10.1002/2016GL068333, 2016.

Marc, O., Behling, R., Andermann, C., Turowski, J. M., Illien, L., Roessner, S. and Hovius, N.: Long-term erosion of the

1255 Nepal Himalayas by bedrock landsliding: The role of monsoons, earthquakes and giant landslides, Earth Surf. Dyn., 7(1), 107– 128, doi:10.5194/esurf-7-107-2019, 2019.

Martha, T. R., Kerle, N., Jetten, V., van Westen, C. J. and Kumar, K. V.: Characterising spectral, spatial and morphometric properties of landslides for semi-automatic detection using object-oriented methods, Geomorphology, 116(1–2), 24–36, doi:10.1016/j.geomorph.2009.10.004, 2010.

Martin Ester, Hans-Peter Kriegel, Jiirg Sander, X. X.: A Density-Based Algorithm for Discovering Clusters in Large Spatial Databases with Noise, Compr. Chemom., 96(34), 226–231 [online] Available from: https://www.aaai.org/Papers/KDD/1996/KDD96-037.pdf?source=post_page, 1996.

Massey, C., Townsend, D., Rathje, E., Allstadt, K. E., Lukovic, B., Kaneko, Y., Bradley, B., Wartman, J., Jibson, R. W., Petley, D. N., Horspool, N., Hamling, I., Carey, J., Cox, S., Davidson, J., Dellow, S., Godt, J. W., Holden, C., Jones, K., Kaiser,

1265 A., Little, M., Lyndsell, B., McColl, S., Morgenstern, R., Rengers, F. K., Rhoades, D., Rosser, B., Strong, D., Singeisen, C. and Villeneuve, M.: Landslides triggered by the 14 November 2016 Mw 7.8 Kaikōura earthquake, New Zealand, Bull. Seismol. Soc. Am., 108(3B), 1630–1648, doi:10.1785/0120170305, 2018.

Massey, C. I., Townsend, D., Jones, K., Lukovic, B., Rhoades, D., Morgenstern, R., Rosser, B., Ries, W., Howarth, J., Hamling, I., Petley, D., Clark, M., Wartman, J., Litchfield, N. and Olsen, M.: Volume characteristics of landslides triggered by the M

1270 W 7.8 2016 Kaikōura Earthquake, New Zealand, derived from digital surface difference modelling, J. Geophys. Res. Earth Surf., 0–3, doi:10.1029/2019jf005163, 2020.

McInnes, L., Healy, J. and Astels, S.: hdbscan: Hierarchical density based clustering, J. Open Source Softw., 2(11), 205, doi:10.21105/joss.00205, 2017.

Medwedeff, W. G., Clark, M. K., Zekkos, D. and West, A. J.: Characteristic landslide distributions: An investigation of landscape controls on landslide size, Earth Planet. Sci. Lett., 539, 116203, doi:10.1016/j.epsl.2020.116203, 2020.

Mora, O. E., Gabriela Lenzano, M., Toth, C. K., Grejner-Brzezinska, D. A. and Fayne, J. V.: Landslide change detection based on Multi-Temporal airborne LIDAR-derived DEMs, Geosci., 8(1), 6–8, doi:10.3390/geosciences8010023, 2018.
Mouyen, M., Steer, P., Chang, K.-J., Le Moigne, N., Hwang, C., Hsieh, W.-C., Jeandet, L., Longuevergne, L., Cheng, C.-C., Boy, J.-P. and Masson, F.: Quantifying sediment mass redistribution from joint time-lapse gravimetry and photogrammetry

1280 surveys, Earth Surf. Dyn-Discuss., (July), 1-37., 8(2), 555–577, doi:10.5194/esurf-2019-35, 20198-555-2020, 2020. Parker, R. N., Densmore, A. L., Rosser, N. J., De Michele, M., Li, Y., Huang, R., Whadcoat, S. and Petley, D. N.: Mass wasting triggered by the 2008 Wenchuan earthquake is greater than orogenic growth, Nat. Geosci., 4(7), 449–452, doi:10.1038/ngeo1154, 2011. Passalacqua, P., Belmont, P., Staley, D. M., Simley, J. D., Arrowsmith, J. R., Bode, C. A., Crosby, C., DeLong, S. B., Glenn,

1285 N. F., Kelly, S. A., Lague, D., Sangireddy, H., Schaffrath, K., Tarboton, D. G., Wasklewicz, T. and Wheaton, J. M.: Analyzing high resolution topography for advancing the understanding of mass and energy transfer through landscapes: A review, Earth-Science Rev., 148, 174–193, doi:10.1016/j.earscirev.2015.05.012, 2015.

1290

Pradhan, B., Jebur, M. N., Shafri, H. Z. M. and Tehrany, M. S.: Data fusion technique using wavelet transform and taguchi methods for automatic landslide detection from airborne laser scanning data and quickbird satellite imagery, IEEE Trans. Geosci. Remote Sens., 54(3), 1610–1622, doi:10.1109/TGRS.2015.2484325, 2016.

Stark, C. P. and Guzzetti, F.: Landslide rupture and the probability distribution of mobilized debris volumes, J. Geophys. Res. Earth Surf., 114(2), 1–16, doi:10.1029/2008JF001008, 2009.

Stumpf, A., Malet, J. P., Allemand, P. and Ulrich, P.: Surface reconstruction and landslide displacement measurements with Pléiades satellite images, ISPRS J. Photogramm. Remote Sens., 95, 1–12, doi:10.1016/j.isprsjprs.2014.05.008, 2014.

1295 <u>Stark, C. P. and Hovius, N.: The characterization of landslide size distributions, Geophys. Res. Lett.</u>, 28(6), 1091–1094, doi:10.1029/2000GL008527, 2001.

Stumpf, A., Malet, J. P., Allemand, P., Pierrot-Deseilligny, M. and Skupinski, G.: Ground-based multi-view photogrammetry for the monitoring of landslide deformation and erosion, Geomorphology, 231(October), 130–145, doi:10.1016/j.geomorph.2014.10.039, 2015.

1300 Tanyaş, H., van Westen, C. J., Allstadt, K. E. and Jibson, R. W.: Factors controlling landslide frequency-area distributions, Earth Surf. Process. Landforms, 44(4), 900–917, doi:10.1002/esp.4543, 2019.

Teza, G., Galgaro, A., Zaltron, N. and Genevois, R.: Terrestrial laser scanner to detect landslide displacement fields: A new approach, Int. J. Remote Sens., 28(16), 3425–3446, doi:10.1080/01431160601024234, 2007.

Tonini, M. and Abellan, A.: Rockfall detection from terrestrial lidar point clouds: A clustering approach using R, J. Spat. Inf. Sci., 8(1), 95–110, doi:10.5311/JOSIS.2014.8.123, 2014.

Ventura, G., Vilardo, G., Terranova, C. and Sessa, E. B.: Tracking and evolution of complex active landslides by multitemporal airborne LiDAR data: The Montaguto landslide (Southern Italy), Remote Sens. Environ., 115(12), 3237–3248, doi:10.1016/j.rse.2011.07.007, 2011.

Wagner, W., Lague, D., Mohrig, D., Passalacqua, P., Shaw, J. and Moffett, K.: Elevation change and stability on a prograding delta, Geophys. Res. Lett., 44(4), 1786–1794, doi:10.1002/2016GL072070, 2017.

Wheaton, J. M., Brasington, J., Darby, S. E. and Sear, D. A.: Accounting for uncertainty in DEMs from repeat topographic surveys: Improved sediment budgets, Earth Surf. Process. Landforms, 35(2), 136–156, doi:10.1002/esp.1886, 2010.

Williams, J. G., Rosser, N. J., Hardy, R. J., Brain, M. J. and Afana, A. A.: Optimising 4-D surface change detection: An approach for capturing rockfall magnitude-frequency, Earth Surf. Dyn., 6(1), 101–119, doi:10.5194/esurf-6-101-2018, 2018.

1315 Zhong, C., Liu, Y., Gao, P., Chen, W., Li, H., Hou, Y., Nuremanguli, T. and Ma, H.: Landslide mapping with remote sensing: challenges and opportunities, Int. J. Remote Sens., 41(4), 1555–1581, doi:10.1080/01431161.2019.1672904, 2020.

