

# Unraveling the hydrology and sediment balance of an ungauged lake in the Sudano-Sahelian region of West Africa using remote sensing

Silvan Ragettli <sup>1</sup>, Tabea Donauer <sup>1,2</sup>, Peter Molnar <sup>2</sup>, Ron Delnoije <sup>3</sup>, and Tobias Siegfried <sup>1,4</sup>

<sup>1</sup>hydrosolutions Ltd., Venusstrasse 29, 8050 Zurich, Switzerland

<sup>2</sup>ETH Zurich, Institute of Environmental Engineering, Zurich, Switzerland

<sup>3</sup>Caritas Switzerland, Bamako, Mali

<sup>4</sup>ETH Zurich, Institute of Science, Technology and Policy, Zurich, Switzerland

**Correspondence:** Silvan Ragettli (ragettli@hydrosolutions.ch)

## Abstract.

The presence of ephemeral ponds and perennial lakes in the Sudano-Sahelian region of West Africa is strongly variable in space and time. Yet, they have important ecological functions and societies are reliant on their surface waters for their lives and livelihoods. It is essential to monitor and understand the dynamics of these lakes to assess past, present, and future water resource changes. In this paper, we present an innovative approach to unravel the sediment and water balance of Lac Wég-  
5 nia, a small ungauged lake in Mali near the capital of Bamako. The approach uses optical remote sensing data to identify the shoreline positions over a period of 22 years (2000-2021) and then attributes water surface heights (WSHs) to each ob-  
servation using the lake bathymetry. ~~The method~~ We then present a novel methodology to identify and quantitatively analyze deposition and erosion patterns at lake shores and in lake beds. The method therefore represents a significant advancement  
10 over previous attempts to remotely monitor lakes in the West African drylands, since it considers not only changes in water depth to explain recent declining trends in lake areas, but also changes in the storage capacity. ~~We~~ At Lac Wég-  
nia, we recognize silting at the tributaries to the lake, but overall, erosion processes are dominant and threaten the persistence of the lake because of ~~a continuous decrease of the floor level at the outflow. This explains the decreasing trend in WSH even for the~~  
~~wet-season~~ progressive erosion through the natural levee at the lake outlet. This factor contributes by  $66 \pm 18\%$  to the decreasing  
15 WSH trend, while  $34 \pm 18\%$  of the dry-season lake level changes are explained by increasing evaporation from the lake and by possibly falling groundwater tables. Due to the decreasing reservoir capacity of the lake, WSHs are declining even in the wet  
season, in spite of positive rainfall patterns.

## 1 Introduction

In arid and semi-arid areas of West Africa, small reservoirs and natural lakes improve the reliability of water supplies for  
20 livestock and humans and allow the diversification of agricultural activities at the locale scale (Fowe et al., 2015). Wetlands are important for biodiversity maintenance, ecosystem functioning and conservation (e.g. Brouwer et al., 2014). At the same time, water resources in Sub-Saharan West Africa are under increasing pressure due to climatic changes, population growth and land degradation (Leblanc et al., 2008; Favreau et al., 2009; Oyebande and Odunuga, 2013). Changes in land use and land

cover can have unexpected consequences on the dynamics of surface waters. Famously, a phenomenon referred to as the "the Sahelian paradox" led to an increase in surface water despite a general precipitation decline during the last decades of the 20th century. The phenomenon has been first reported for small watersheds in Burkina Faso by Albergel (1987), and later also for several other watersheds in the West African Sahel (Descroix et al., 2009; Amogu et al., 2010). Increasing runoff coefficients because of overall vegetation decay due to the erosion of shallow soils and long drought periods have been identified as one of the main drivers of the seemingly paradoxical eco-hydrological changes (Dardel et al., 2014; Gal et al., 2017). In addition, the Sahel has seen a tendency toward rising daily precipitation extremes (Frappart et al., 2009; Panthou et al., 2014), and increasingly concentrated runoff (Gal et al., 2017). The combination of all these effects leads to both higher inflow (Gal et al., 2016) and higher sediment input to Sahelian lakes. The first has been manifested by a spectacular increase in pond and lake areas in the pastoral Sahel, such as the Gourma region in northern Mali (Gardelle et al., 2010; Gal et al., 2017), and the latter by observations of increasing turbidity and suspended particulate matter in lakes and ponds of the western Sahel (Robert et al., 2017).

While the water availability in some natural freshwater reservoirs in the arid and semi-arid regions of Sub-Saharan West Africa benefited from these changes in precipitation and runoff patterns, other lakes have seen strong declines in surface area. As such, Lake Chad is the most famous example. The surface area of Lake Chad decreased by more than 90 percent between the 1960s and the 1980s (Pham-Duc et al., 2020; Mahmood and Jia, 2019; Gao et al., 2011). The shrinkage of Lake Chad has been attributed to severe droughts and increased irrigation withdrawals (Coe and Foley, 2001). The lake split in two parts in 1972. Because the southern pool receives more than 95% of river inflow, the northern pool ran completely dry in the 1980s and has hardly recovered since then (Lemoalle et al., 2012). Excess water spilling to the northern pool is not sufficient to maintain a permanent free water surface and, even without irrigation, the current climatology does not favour a single lake (Gao et al., 2011).

In the past decades, Lake Chad has become a symbol of ongoing climate change and thus has attracted a lot of research attention. Meanwhile, hydrological change at thousands of small ephemeral ponds and perennial lakes in the region remains to be investigated (Haas et al., 2009). Such lakes are often located in isolated regions with no road access during the rainy season, and the inflows to the vast majority of these water bodies are completely ungauged (Fowe et al., 2015; Gal et al., 2016). The methods developed and applied to investigate Lake Chad changes are not easily transferable to small and ungauged water bodies. Most commonly, satellite radar and laser altimetry have been used for determining variations in water surface heights in time (Crétaux and Birkett, 2006; Zhu et al., 2017; Buma et al., 2018; Pham-Duc et al., 2020), but the method is restricted to large lakes ( $>50 \text{ km}^2$ ) due to the poor density of altimetry tracks and the low revisit times (Crétaux et al., 2016; Avisse et al., 2017). The lack of inflow observations in small water bodies in the Sahel makes the calibration of hydrological models for simulating the effects of human water use and climate variability on water storage and surface area (Gao et al., 2011) or for assessing streamflow trends (Mahmood and Jia, 2019) difficult, if not impossible.

Among the few studies that unravelled the water balance of small water bodies ( $<10 \text{ km}^2$ ) in arid and semi-arid regions of Sub-Saharan West Africa, Fowe et al. (2015) measured rainfall, evaporation, and reservoir water level at a small reservoir in Burkina Faso for a two-year period. They concluded that available water resources in the studied system were adequate to

fulfill existing demands. Soti et al. (2010) presented the application of a simple hydrological model to 98 seasonal ponds in North Senegal for water level simulations. The spatio-temporal dynamics of the ponds were successfully reproduced, but the model required daily field data for calibration (rainfall, water level), and its performance strongly depended on the quality of available rainfall inputs. Gal et al. (2016) has combined area-volume (AV) relationships of three small Sahelian lakes with daily evaporation and precipitation data to estimate water inflow to the lakes. They succeeded to quantify the processes behind the Sahelian paradox by showing that the ratio between annual water inflow and precipitation has increased in the last 60 years. The study by Gal et al. (2016) demonstrated that it is possible to unravel the hydrology of small Sahelian lakes without in-situ measurements. However, deriving inflows by empirical AV scaling relationships disregards the sedimentation of natural lakes. The Sahel region is marked by a high degree of weathering due to the climatic conditions (Nippes, 1984) and increasing soil erosion due to land degradation and concentrated runoff (Karambiri et al., 2003; Amogu, 2009; Descroix et al., 2009). Constant AV relationships are ignoring the fact that the reservoir capacity of Sahelian lakes may naturally change due to sediment deposition and erosion.

The objectives of our study are: (1) to develop and test a new method for quantifying both the sediment and the water balance of an ungauged lake (Lac Wégna in Mali) based on remote sensing information, (2) to quantify the evolution of water surface elevation and surface area over the last twenty-two years in the lake, and (3) to attribute possible causes to observed changes and identify adequate measures to safeguard the ecological balance and environmental equilibrium of the lake.

The method we are proposing is based on the waterline method (Mason et al., 1995). The waterline (or shoreline) refers to the water-land boundary and can be regarded as a contour line that connects points of equal elevation. The general methodology consists of detecting the ever-shifting edge of water bodies in remotely sensed images using image processing techniques and assigning heights to shoreline points using water level information or bathymetry data. The method is a widely used technique for constructing intertidal DEMs (Salameh et al., 2019). Morphological change can then be quantitatively estimated based on DEMs generated for different years or seasons (e.g. Mason et al., 1999; Ryu et al., 2008; Heygster et al., 2010; Li et al., 2014; Xu et al., 2016). Only in recent years, likely because of better data coverage and availability of remote sensing imagery, the method has been adapted to generate time-series of water surface heights (WSH) of lakes and reservoirs (Tseng et al., 2016; Ma et al., 2019; Weekley and Li, 2019; Yue and Liu, 2019; Militino et al., 2020; Xu et al., 2020) ~~or for Water~~, or for water volume estimates of desert lakes ~~Armon et al. (2020)~~ (Armon et al., 2020). The method is only applicable to recently filled reservoirs or other water bodies where the water level has increased above the level at the time the elevation data were collected. The method has not yet been employed in Sub-Saharan West Africa, despite the fact that the region is particularly suitable for an application of the method, because bathymetric surveys can be carried out towards the end of the dry season, when the lake levels are at their lowest.

For the present work we apply the waterline method with a digital elevation model (DEM) derived from an unmanned aerial vehicle (UAV) survey in May 2019. The shorelines of Lac Wégna are identified by leveraging the Landsat and Sentinel-2 image archives. A novel methodology is presented to identify and quantitatively analyze deposition and erosion patterns at the lake shores and ~~within~~ the lake bed by mapping the temporal evolution of shoreline position anomalies. Finally, reservoir

capacity changes and storage variations are retrieved, which allows us to carry out a detailed water balance analysis of Lac Wégnia.

## 95 2 Study site and climate

Lac Wégnia (13° 18'00"N, 08° 07'46"W) is located in south-west Mali, approximately 75 km north of Bamakao (Figure 1), in the watershed of the Senegal River and more specifically in the watershed of the Baoulé River, the main tributary of Bakoy River. With an average annual rainfall of about 850 mm the lake is at the boundary between the Sahelian and the Sudanian eco-climate. The climate is characterized by convective heavy rainfalls during the wet season resulting from the West-African monsoon, and a long dry season. The rainy season is short, extending typically from late June to mid-September. The morphology of the surrounding region is characterized by the predominance of sandstone plateaus often covered with ferruginous crusts between 300 and 400 m altitude (de La Rocque and Renoullin, 2015).

In 2013 Lac Wégnia was designated as a RAMSAR site (Coulibaly et al., 2013) and is thus part of the RAMSAR list of wetlands of international importance. The entire RAMSAR site has an area of 3,900 ha and includes also several smaller lakes and ponds in the vicinity of Lac Wégnia. The freshwater lakes and marshes of the Lac Wégnia RAMSAR site are unique in the region for their ecological characteristics and natural state (Coulibaly et al., 2013). Lac Wégnia plays an essential role in the natural control of floods. The seasonal water retention by the lake is important for the wetlands and the entire surrounding area. About 12,000 people depend directly on the lake and its surroundings for food and for economic activities such as fishing, raising livestock and agriculture (DNEF/PAZU, 2018).


Lac Wégnia has two main tributaries (Figure 1), one from the south (catchment area 742 km<sup>2</sup>) and one from the east (384 km<sup>2</sup>). The entire catchment area of the lake is about 1157 km<sup>2</sup>. The lake drains at its northwestern end through a narrow gully, but outflow from the lake is only activated during the wet season. During the entire dry season the river bed of the [effluent outlet](#) and of the tributaries are dry. Towards the end of the wet season the lake extends to an area of about 1500 ha, but then continuously decreases in size during the dry season. While at the beginning of the century the lake rarely decreased to areas of less than 200 ha, this is now common. In recent years the surface water area has decreased to less than 10 ha in late May and early June (de La Rocque and Renoullin, 2015). To safeguard the ecological balance, there is urgent need to understand the causes of recent water area trends and to assess the changes in lake water storage.

## 3 Data

### 3.1 UAV data

The UAVs eBee and RTK from SenseFly were used for the realization of the [drone-aerial](#) survey on 9/10 May 2019. The UAVs were mounted with a senseFly S.O.D.A camera with a 20 megapixel sensor. Its lens was fixed at a focal length of 35 mm and the altitude of the flights was 180 m. All the aerial photographs were processed using the commercial software Agisoft Photoscan to generate the DEM. The orthomosaic images (Figure 1a) have a spatial resolution of 3.28 cm and the DEM a





**Figure 1.** Overview map of Lac Wégénia. a) **Ortho-image-of-the-drone-footage-Orthoimage mosaic** from **UAV on 9/10 May 2019**. The **water area-waterline** at level 330 m asl (based on the UAV-DEM) and on the **day-days** of the **drone-UAV** flights (328.7 m asl) are shown. The outflow is activated if the water level reaches above 329.8 m asl. b) Outline of the two main contributing catchments and location of Lac Wégénia in Mali.

resolution of 6 cm. Based on three ground control points, the mean error in X and Y direction was estimated to be 1.6 cm and  
 125 5.6 cm in Z direction, respectively. More technical details on the topographic survey are provided by Vandemeulebrouck et al. (2019).

### 3.2 Satellite remote sensing data

This research utilizes high spatial resolution remote sensing data from the following satellite missions: Landsat 5 (L5, 1984-  
 130 2012), Landsat 7 (L7, 1999-present), Landsat 8 (L8, 2013-present) and Sentinel-2 (2015-present). We process surface reflectance images from all available scenes in the L5, L7, L8 and S2 archive from the study period October 1999 - May 2021 in Google Earth Engine (GEE, Gorelick et al., 2017).

### 3.3 Meteorological data

Meteorological data used in this study is provided by various gridded datasets (Table 1). We use all seven precipitation products that are available for the study region through the Earth Engine Data Catalog. Two out of the seven products also provide the  
 135 necessary inputs for the calculation of evaporation rates from open water surfaces (Section 4.2: GLDAS (Rodell et al., 2004) and ERA5 (Hersbach et al., 2020)). All datasets are characterized by a high spatial (5-25 km) and temporal (hourly-daily) resolution.

In-situ observations are available from a station of the Trans-African Hydro-Meteorological Observatory (TAHMO) project (van de Giesen et al., 2014) in Guioyo, approximately 25 km north-west of Lac Wégénia. We have set up the station in February  
 140 2020 within a fenced school compound. The station measures precipitation, air temperature, incoming shortwave radiation,

**Table 1.** Meteorological datasets used in this study. Also indicated are wet season precipitation trends for Lac Wégénia that are significant at the 0.01 level (the values in brackets represent the precipitation change from 2000 to 2020 in percent). G: gauge; S: satellite; R: reanalysis; P: precipitation;  $T_a$ : air temperature;  $T_d$ : dewpoint temperature; W: wind, RAD: solar radiation, Qair: specific humidity; Pr: surface pressure; NP: near present; POS: positive trend; N: no trend.

Name	GEE Code	Data Sources	Variables Used	Temporal Coverage	Temporal Resolution	Spatial Resolution	P Trend Wet Season
CHIRPS	UCSB-CHG/CHIRPS/DAILY	S, R, G	P	1981-NP	daily	0.05°	POS (+23.4%)
ERA5	ECMWF/ERA5_LAND/HOURLY	R	P, $T_a$ , $T_d$ , W, RAD	1981-NP	hourly	0.25°	POS (+34.1%)
GLDAS	NASA/GLDAS/V021/NOAH/G025/T3H	S, G	P, $T_a$ , W, RAD, Qair, Pr	2000-NP	3-Hourly	0.25°	N
GPM	NASA/GPM_L3/IMERG_V06	S, R, G	P	2000-NP	3-Hourly	0.1°	N
GSMaP	JAXA/GPM_L3/GSMaP/v6/reanalysis	S, R, G	P	2000-2013	hourly	0.1°	POS (+24.1%)
	JAXA/GPM_L3/GSMaP/v6/operational	S, R, G	P	2014-NP	hourly	0.1°	
PERSIANN-CDR	NOAA/PERSIANN-CDR	S, G	P	1983-NP	daily	0.25°	N
TRMM 3B42	TRMM/3B42	S, G	P	1998-2019	3-Hourly	0.25°	N
Ensemble-mean			P	2000-2020			POS (+21.2%)

relative humidity, atmospheric pressure, wind speed and wind direction with the ATMOS41 automatic weather station from METER. Wind data from the station are not used because of the anomalous wind conditions within the enclosed school compound where the station was set up. Furthermore, due to prolonged dry periods and bad maintenance, likely related to school closings during the Covid-19 pandemic, dust accumulated on the shortwave radiation sensor. Solar radiation data from the station ~~was~~ were therefore also not used.

## 4 Methods

### 4.1 Lake water balance

The equation of lake level change over a given period is defined as follows (Eq. 1):

$$\Delta h = \sum_{i=t_1}^{t_2} (E_i + P_i + Q_i) \quad (1)$$

where  $\Delta h$  is the change in WSH (mm) over a time period  $t_1$  to  $t_2$  and  $E_i$ ,  $P_i$  and  $Q_i$  (mm/day) are the daily evaporation, precipitation and net inflow to the lake, respectively. The methodology to derive  $\Delta h$ ,  $E_i$  and  $P_i$  is described below. In the absence of discharge measurements,  $Q_i$  is used to close the water balance and includes all fluxes at the subsurface or surface, such as interactions with groundwater, surface water in- and outflow, and water losses due to human and animal consumption.

The water balance components are identified for 22 ~~dry seasons~~ dry seasons between October 1999 to May 2021. The analysis focuses ~~only~~ on the loss part of the year to explain the ecologically most critical conditions for the lake. The ~~wet-season water balance is not investigated in this work, also because of the higher uncertainties due to the absence of local precipitation~~

~~measurements and the presence of clouds which reduce the availability of remote sensing imagery.~~ The period of analysis was fixed from 1 October to 15 May (227 days) to ensure comparability between years.

## 4.2 Evaporation from open water

160 The Penman equation is commonly used in the literature to estimate evaporation from lake surfaces (e.g. Gal et al., 2016; Schulz et al., 2020). This equation is based on the energy balance and aerodynamic constraints. We use the 1948 version of the Penman model (Penman, 1948) implemented in the R package 'Evapotranspiration' (Guo et al., 2016). Open-water evaporation is estimated using the function `ET.Penman()`, whereas the arguments are set so that (1) the time-step for calculation is daily; (2) the Penman 1948 wind function (Penman, 1948) is used to estimate the mass transfer component in the Penman model  
165 that influences the rate of movement of water vapor away from the evaporating surface; and (3) the evaporative surface is open water (albedo = 0.08, roughness height = 0.001m). The required inputs are solar radiation ( $RAD$ ), relative humidity ( $RH$ ), air-temperature ( $T_a$ ) and wind speed ( $W$ ). Due to the unavailability of nearby station data for the entire study period we assume that the weather data above the lake can be best approximated by the data from gridded products (Table 1).

For the present study these inputs are provided through the GLDAS and ERA5 datasets, respectively. The following ERA5  
170 climate variables are used in the computation of evaporation:  $T_a$ ,  $RAD$ , 2 m dew point temperature ( $T_d$ ) and wind speed at 10 m above ground level. Relative humidity is calculated from  $T_a$  and  $T_d$  via the Magnus approximation (Alduchov and Eskridge, 1996). To compute GLDAS evaporation, the same variables are used except that relative humidity is converted from specific humidity, near surface air pressure and  $T_a$ . Each variable is validated against station data if available from the TAHMO station in Guioyo. The Penman model is then applied separately with inputs from each of the two datasets. The final time series of  
175 open-water evaporation is obtained by taking the arithmetic mean of the two datasets.


## 4.3 Precipitation

We use the gridded rainfall products (Table 1) to estimate precipitation at Lac Wégna, and the TAHMO station data of 2020 for validation. It can be expected that the different gridded products have a substantially different performance in representing the spatio-temporal rainfall patterns (Dembélé et al., 2020). Here, we only assess the water balance of the dry period, where  
180 rainfall is scarce and where the different products generally agree well with each other (Figure 2). We therefore use the daily ensemble-mean of all 8 available products as an input for the precipitation component of the water balance.

## 4.4 Water surface heights (WSH)

WSH identification is developed below and implemented as a fully automated processing chain in GEE. The procedure involves the following main steps: i) remote sensing image selection and pre-processing, ii) water surface detection, iii) shoreline  
185 detection and iv) surface elevation retrieval.

### 4.4.1 Remote sensing image pre-processing



**Figure 2.** Climate diagram for Guioyo (located 25 km north-west of Lac Wégénia) with data from the period March 2020 - February 2021. 'Station' refers to the TAHMO station data and 'Gridded' refers the ensemble-mean of the gridded global datasets (Table 1). The error bars represent the full range of values among gridded datasets.

~~The All satellite images with a cloud percentage over the study area greater than 30% are excluded from the analysis. The remaining satellite images are co-registered with the Ortho-image-orthoimage of the UAV survey in a step-wise manner. First, we selected-select an S2 image that was taken approximately on the same day as the UAV survey (11 May 2019). This image was-is co-registered with the Ortho-imageorthoimage. We then assumed-assume that the misalignment of images within the set of images from the same sensor is neglectable (Storey et al., 2016; Nguyen et al., 2020) and applied-negligible (Storey et al., 2016; Nguyen et al., 2020) and apply the same displacement to all S2 images. For the Landsat sensors no images were-are available from the date of the UAV survey. L7 and L8 images are thus co-registered with already aligned S2 images on the same day (25 April 2020 and 11 November 2020, respectively). The L5 and S2 mission periods do not overlap. In a final step L5 images are thus co-registered with a L7 image (9 June 2007). More details about co-registration in GEE are provided by Nguyen et al. (2020). All satellite images with a cloud percentage over the study area greater than 30% are excluded from the analysis.~~

#### 4.4.2 Water surface detection

Water absorbs most radiation at near-infrared wavelengths and beyond. As a result, water can be easily detected by using spectral indices. Here we use the modification of the normalized difference water index (MNDWI) for land-water classification (Xu, 2006):

$$MNDWI = (Green - MIR)/(Green + MIR) \quad (2)$$

where *MIR* is reflectance in the middle infrared band, and *Green* is reflectance in the green band. The MNDWI has been extensively applied for water mapping (e.g. Donchyts et al., 2016; Tseng et al., 2016; Ma et al., 2019) and its good performance  
205 has been shown for both Landsat and Sentinel-2 images (Kwang et al., 2017; Yang et al., 2020).

We use a non-parametric unsupervised method based on the Canny edge filter and Otsu thresholding to distinguish between water and non-water pixels, following Donchyts et al. (2016). The Otsu algorithm (Otsu, 1979) is a widely-used dynamic threshold method (e.g. Ma et al., 2019; Asfaw et al., 2020; Yang et al., 2020). The method identifies an optimal threshold to distinguish two image classes by maximising the inter-class variance computed from a normalized image histogram. This  
210 requires a bimodal histogram distribution. If land dominates the image over water, the histograms are unbalanced. The Canny edge filter is thus used to reduce the sampling region only to those areas near water-land edges. The Canny method first uses a Gaussian filter to smooth the image in order to remove the noise and then finds edges by looking for local maxima of the image intensity gradients. We use the Canny edge algorithm with the following parameters to process all images:  $\sigma = 0.7$  (standard deviation of the Gaussian smoothing kernel),  $th = 0.7$  (threshold used to define the sensitivity of the gradient magnitude filter),  
215 an image pixel resolution of 30 m and a buffer around the edges of 60 m.

Binary water images are obtained at the native resolution of the sensors (30 m for Landsat, 10 m for Sentinel-2). The area of Lac Wégénia can be obtained from these images after gap-filling. A simple focal mode filter is applied to fill data gaps and void stripes in Landsat 7 images. Note that gap filling is not required for WSH retrieval, which is another advantage of the method over AV scaling.

#### 220 4.4.3 Shoreline detection and elevation retrieval

The shoreline is defined as the water/land boundary of the binary water image. To retrieve the elevation of the shoreline, a 10-m buffer is added on both sides of the edge. Within this buffer we sample all DEM pixel values at a 10-m resolution, and use the median to calculate a single WSH. Weekley and Li (2019) obtained slightly better results using the mean instead of the median. However, the median is less sensitive to noise and shoreline elevation anomalies (see Section 4.5).

225 A variety of factors such as local slope, mixed pixels, and water detection accuracy can impact the accuracy of the retrieved WSH (Tseng et al., 2016; Weekley and Li, 2019). Because surface water may not be correctly identified under canopies, we mask all boundary pixels that are adjacent to lush vegetation ( $NDVI > 0.5$ ). Note that at Lac Wégénia this situation only occurs during the wet season, when the lake is completely filled. Pixels where the retrieved mean erosion/deposition rate exceeds 10 *mm/year* are also removed from calculating the final WSH (see Section 4.5 below). Unfortunately, no in-situ water level data  
230 are available for Lac Wégénia for a validation of the retrieved WSH data. We therefore only assess the relative accuracy of the approach by comparing WSH data obtained for the same or subsequent days from different images (acquired by Landsat and Sentinel-2 satellites, respectively).

#### 4.5 Sediment balance

The waterline method is based on the assumption of common heights of geocoded waterline pixels (Salameh et al., 2019).  
235 However, this assumption is only valid if either the elevation information is available exactly for the time of the lake boundary

acquisition, or if the bathymetry of the lake does not change over time. In our case a DEM is only available for May 2019, and it is very likely that over the study period 1999-2021 there are changes in the lake lake shore and bed topography due to sediment deposition and erosion. Deposition occurs preferentially on sediment deposit cones, while lake shore erosion may take place where the banks are not protected by littoral vegetation and where rills and gullies are formed. Such local topographic changes become visible by comparing the waterlines of two scenes which represent approximately the same water level. At sediment deposition cones the waterline of the older scene bends much more inland than the more recent scene (Figure 3a), and vice versa at erosion zones. If such 'shoreline anomalies' are not too numerous, the median of all shoreline pixel elevations still provides a valid estimate of the water surface elevation, even if the lake boundary of an older scene is projected on the recent lake bathymetry. The difference between the median elevation of all shoreline pixels and a pixel elevation at a shoreline anomaly is then equal to the elevation change that has occurred at that point. In the following, we call these deviations from the median 'shoreline elevation anomalies' (SEAs):

$$SEA_{i,t} = WSH_t - SE_{i,t} \quad (3)$$


$SEA_{i,t}$  in Eq. 3 is the SEA at time  $t$  at pixel  $i$ ,  $SE_{i,t}$  is the shoreline elevation at pixel  $i$  according to the current bathymetry, and  $WSH_t$  is the median of all shoreline pixel elevations. If a SEA is positive, then erosion has since occurred, and if it is negative, deposition has occurred.

SEAs also occur if the scenes providing the lake boundaries are not well aligned with the DEM, or if the shoreline delineation is erroneous. For this reason it is important to look at the evolution of SEAs over time to get a robust picture of the nature of geomorphic change on the lake shoreline. SEAs should be continuously changing over time at deposition or erosion zones. ~~Not the SEAs per se point to deposition and erosion processes, but the slope of SEA change over time~~ While individual dates' SEA values may represent noise, the longer-term trend in SEA values ( $\Delta SEA$ , units  $mm/year$ ) point to deposition and erosion processes. Robustly increasing or decreasing SEA slopes can then be assumed to be equivalent to sediment deposition or erosion rates, respectively. Furthermore, SEAs may occur because of topographic slopes within the  $\pm 10m$  buffer that is used for sampling shoreline pixels. For this reason, SEAs extracted at 10m pixel resolution are smoothed by applying a morphological mean filter within 30m square kernels.

The complete procedure to extract maps of  $\Delta SEA$  can be summarized as follows: 1) Identifying the WSH of a given scene as described in Section 4.4.3. 2) Mapping of SEAs within the  $\pm 10m$  buffer of each lake boundary. 3) Smoothing of SEAs with the morphological mean filter. 4) Taking the mean of all SEAs over a given pixel for a given hydrological year, resulting in 22 annual SEA maps (hydrological years 2000-2021). 5) Applying a non-parametric Sen's slope estimator calculate  $\Delta SEA$ . Sen's slope is less sensitive to outliers than the common least squares estimate using linear regression (Sen, 1968).

The validity of the procedure depends on the assumption that the median shoreline pixel elevation is a robust estimator of actual WSH. To test this assumption, steps 1-5 above are applied iteratively, by always masking out in step 1 those areas where absolute  $\Delta SEA$  exceeds  $10 mm/year$ . Therefore, locations where anomalies occur get excluded from calculating WSH. After each iteration the average  $\Delta SEA$  within the lake bed is calculated (hereafter referred to as the 'sediment balance'), as well as





**Figure 3.** a) Shoreline elevation anomalies of a Landsat-7 scene from 8 April 2002. b) Slope of shoreline elevation anomalies ( $\Delta$ SEA) 2000-2021 in meter per year. Shown are all all 10-m pixels where data points are available from at least six years. c) Gap filled and outlier corrected map of  $\Delta$ SEA 2000-2021. Red and blue pixels point to sediment deposition and erosion, respectively. This map is used to calculate the sediment balance of Lac Wégénia. The background image is a Google Earth image from 23 March 2013 (© Google Earth 2021).

the fraction of the area where absolute  $\Delta$ SEA does not exceed  $10 \text{ mm/year}$ . If both indicators converge to stable values after 10 iterations, the resulting  $\Delta$ SEA map can be used to identify the deposition and erosion areas that need to be masked for the calculations of the final WSH values.

Because Lac Wégénia is not an ephemeral lake but shrinks to a small size each dry season,  $\Delta$ SEA cannot be calculated for those lake bed pixels which are rarely or never dry. We apply a minimum threshold of six annual SEA values (30%) that need to be available in order to calculate  $\Delta$ SEA. Data gaps in the map (Figure 3b) are filled with a focal mean filter (Figure 3c) if pixels with  $\Delta$ SEA values are present within a two-pixel (20m) radius.

#### 4.6 Trend analysis

We look for trends in the seasonal mean values of each water balance component (Eq. 1). Regression slopes are estimated using the method of Theil (1950) and Sen (1968), thereafter called Sen's slopes, and uncertainty ranges are provided by the 95% CI of the Sen's slope estimate computed using the Gilbert (1987) modification of the Theil/Sen Method. The significance of the trend is assessed by Kendall's nonparametric test for a monotonic trend (Kendall, 1975).

To explain the observed lake level trends we perform an attribution analysis. Three main factors determine the lake level at the end of the dry season: i) the initial lake level, ii) the mean rate at which the lake level decreases over the dry season and iii)

the length of the dry season. Changes in these three independent factors over the last 22 years can explain the observed lake level trends:

$$285 \quad \Delta h_{tot} = \Delta h_{rate} + \Delta h_{ini} + \Delta h_{\Delta t} \approx \Delta h_{obs} \quad (4)$$

whereas  $\Delta h_{rate}$  represents the lake level change that is due to the change in the rate at which the lake level decreases over the ~~dry-season~~dry season.  $\Delta h_{ini}$  is the change in initial lake levels, and  $\Delta h_{\Delta t}$  represents the lake level change due to changes in the timing of the ~~wet-season-between~~wet season. The sum of all effects ( $\Delta h_{tot}$ ) should be approximately equal to the observed difference in dry-season lake levels ( $\Delta h_{obs}$ ). Each factor is quantified based on the available WSH time-series as explained in  
290 Sections 4.6.1 - 4.6.3 below.

#### 4.6.1 Dry-season lake level change rates

The number of available WSH data points varies between years due to clouds and dust storms and due to the different mission periods of the satellites. To enable comparison of WSH change rates it is therefore necessary to homogenize the WSH time series. For each hydrological year, the available data are extrapolated to cover the full ~~dry-season~~dry season period from 1  
295 October to 15 May. The steps for extrapolation of the data are the following: 1) Smoothing the WSH time-series with a 7-day window running-mean filter. 2) Calculation of the WSH change rate ( $\Delta h$ , units *mm/day*) between all subsequent dry-season data points that are separated by 8-16 days (16 days is the usual Landsat overpass interval). 3) The day of the year (DOY) of the last day of each interval is attributed to each available data point. The cloud of points is converted into a time series of average  $\Delta h$  seasonality by smoothing again with a 7-day window running-mean filter. 4) Data gaps are filled by using the average  $\Delta h$   
300 seasonality as follows:

$$\Delta h_{gap} = \sum_{i=t_1}^{t_2} \Delta h_{ref_i} \times \frac{\Delta h_{obs_{t_3-t_4}}}{\sum_{i=t_3}^{t_4} \Delta h_{ref_i}} \quad (5)$$

where  $\Delta h_{gap}$  is the interpolated WSH change (units in *mm*) for a given time period of missing data between  $t_1$  to  $t_2$ .  $\Delta h_{ref_i}$  is the reference WSH change (units in *mm/day*) described by the average  $\Delta h$  seasonality for a given DOY, and  $\Delta h_{obs_{t_3-t_4}}$  is the observed WSH difference between  $t_3$  to  $t_4$ . The time period  $t_3$  to  $t_4$  has to cover at least 50% of the entire period 1  
305 October to 15 May. Hydrological years for which less than 50% of the dry period is covered by available WSH observations are not considered for the  $\Delta h_{rate}$  trend analysis. For all other hydrological years, an average  $\Delta h_{rate}$  is calculated based on the gap filled dry-season WSH difference. The Sen's slope test is applied to assess the multi-year trend in  $\Delta h_{rate}$ . The gap filled dry-season WSH difference is also used together with  $E$  and  $P$  to derive  $\Delta Q$  for each hydrological year based on Eq. 1.

#### 4.6.2 Initial lake levels

310 During the ~~wetseason~~wet season, when the lake is completely full, the lake level raises above the elevation of the outlet and consequently the outflow becomes activated. However, shortly after the end of the wet season ~~it can be assumed that the lake~~



level is approximately equal to, due to the lack of further inflow into the lake, the lake level equals the elevation of the outlet. This (hereafter also called the 'dead storage level') and runoff from the lake dries up. This dead storage level can be seen as the maximum storage level and therefore the initial water level at the beginning of the dry season. The each dry season. The dead storage level may change over time because of geomorphological changes in the outflow river bed at of the natural levee at the lake outlet, at scales that are however too fine to resolve with our sediment balance approach. No direct measurements of the outlet elevation dead storage level are available except for 2019, where the minimum elevation of the outflow channel was 329.8 m asl. The initial lake level for As a proxy for past dead storage levels we thus determine the initial dry-season lake levels of each hydrological year is therefore approximated by the lake level determined for. The October 1st WSHs of the homogenized WSH time series (see Section 4.6.1) are used for this purpose. The Sen's slope test is then applied to assess the changes in initial lake levels ( $\Delta h_{ini}$ ).

### 4.6.3 Timing of the wet season

To determine the beginning and the end of the wet season we calculate weekly totals of open-water evaporation and compare them with the precipitation sum of each calendar week. The beginning of the wet season is then defined as the first week in the year where the weekly precipitation sum exceeds the weekly evaporation. Accordingly, the dry season starts the week after the last week in the year where weekly P exceeds weekly ET. Changes in the DOY of the dry season onset are assessed by applying the Sen's slope test. To translate these changes into millimeters of water ( $\Delta h_{\Delta t}$ ), the Sen estimate of the slope is multiplied by the multi-annual mean daily lake level change calculated based on the average  $\Delta h$  seasonality (see Section 4.6.1).

If the lake level decreases below 328.64 m asl the lake level cannot be determined because the bathymetry below that level is unknown. For some years we therefore have data gaps in the WSH time series in late May and June. For this reason, the effect of changes in the timing of the onset of the wet season on water levels is not assessed quantitatively. Because such data gaps rarely occur before May 15th, only WSH data points until that day are considered for assessing the change in end-of-dry season lake levels.

## 5 Results

### 5.1 Validation of gridded datasets

The following variables from the gridded datasets can be validated against station data from Guioyo: precipitation, air temperature and relative humidity (Figure 2). Precipitation and relative humidity reveal a strong seasonality with a peak around August. From November to April precipitation is practically zero. Temperature is relatively constant throughout most of the year (July to January), with slightly higher values towards the end of the dry season (April/May). The gridded datasets reproduce this seasonality very well (Figure 2). Also in terms of absolute differences the gridded datasets agree well with the station data: the mean monthly absolute difference between the ensemble of gridded datasets and the measurements is only 0.6°C (temperature), 12 mm (precipitation) and 8% (relative humidity), respectively.

## 5.2 Lake water areas

In total, 541 satellite images from 527 days within the period 1 October 1999 to 30 June 2021 fulfill the quality criteria and are available to extract WSH data (Figure 4a). The number of available scenes per year increases strongly in the year 2013, when Landsat 8 was launched, and again in 2016, when Sentinel-2 data became available. The minimum number of scenes available per year is 4 (years 2001 and 2004), whereas the maximum is 70 (year 2020).


The extracted lake areas reveal a strong seasonality in lake extent, ranging between 1 ha and 157 ha (Figure 4a). The lake has never fallen entirely dry in the study period (de La Rocque and Renoullin, 2015).

81.9 % of the 10 m pixels within the maximum lake extent area represented the shoreline in at least one scene over the entire study period. For 5.8 % of the area no data are available because of data gaps in the DEM. The remaining 12.3 % of the area either never represented the shoreline or were masked from the DEM because of adjoining canopies below which the shoreline could not be seen.

## 5.3 Sediment deposition and erosion areas

The iterative approach to identify shoreline elevation anomalies converged to stable solutions after about five iterations (Figure 5). After 10 iterations, the fraction of the area where absolute  $\Delta$ SEA does not exceed 10 mm/year converged to about 67%. This means that 33% of the pixels for which  $\Delta$ SEA estimates are available represent deposition or erosion areas that needed to be masked for obtaining the final WSHs. The sediment balance 2000-2021 of the lake bed ~~when WSH is at outflow level (329.8 m) below the dead storage level in May 2019~~ converged to a value of -44 mm (Figure 5). The negative sign means that there is more erosion than deposition in the lake bed. The sediment balance could also be determined for some areas that are presently located above the ~~present outflow~~ dead storage level - because they were at a lower level in the past or because they represented the shoreline during the wet season when the lake ~~level rose above the outflow level~~ outflow was activated. Here, the sediment balance was +44 mm, ~~which means that~~ meaning there is more deposition than erosion. Overall, the average of all pixels where the point sediment balance could be determined is -12 mm in 21 years.

Areas where we observe erosion are distributed over a larger area (20% of all pixels with a valid result) than the areas where we observe deposition (13%). The average net sediment deposition rate at locations with more deposition than erosion is 28 mm/year, whereas at locations with net erosion the average rate is -16 mm/year. Net sediment deposition is concentrated at a few locations such as the river deltas of the southern and eastern tributaries (Figure 3c). The highest average deposition rates are identified at the western shore of the lake, where the southern tributary flows into the lake (up to +62 mm/year). The erosion areas, on the other hand, are stretched along nearly the entire lake shore (Figure 3c), whereas the average erosion rates per pixel never exceed -20 mm/year.




**Figure 4.** Time Series of a) lake area and b) lake water level retrieved from Landsat 5/7/8 and Sentinel-2 optical satellite imagery for the period 1 October 1999 until 30 June 2021. N is the number of scenes available from each sensor. In total 541 scenes are represented. c) Annual average quarterly lake areas and b) lake levels and associated linear trend lines. Lake levels from 15 May in (d) represent the level at the approximate end of the dry season and are identified based on extrapolated lake levels (Figure 10).

#### 5.4 Lake water surface heights

The maximum WSH of the entire study period is 330.98 m asl, reached on October 17, 2002. Assuming that the minimum level was not much below the minimum detectable WSH of 328.64 m asl, the lake levels vary within a range of not more than 375 2.5 meters (Figure 4b).

The annual average quarterly lake levels reveal negative trends across all seasons (Figure 4d). All trends are significant at the 0.01 level except the Q3 trend (July-September;  $p$ -value = 0.028). The Sen slope of the linear trend lines indicates an average WSH decrease between -0.46 m (Q3) and -0.71 m (Q2: April-June) over the 22-year study period.

20 out of the 541 scenes represent a lake extent that was equal or smaller than on 9/10 May 2019. Such data points representing a lake level below 328.64 m asl still needed to be considered for the calculation of quarterly average lake levels. For 380 the sake of simplicity a WSH of 328.64 m asl was assigned to such scenes.




**Figure 5.** Lake sediment balance for the period 2000-2021 (average  $\Delta SEA$  within the lake bed) as well as the fraction of the area where absolute  $\Delta SEA$  does not exceed  $10$  mm/year, as a function of the iteration number.

More than one satellite image is available for 14 days, and from another 43 days satellite imagery are available from the subsequent day. Excluding two days where the exact water level could not be determined because of the holes in the DEM, we obtain in total 55 pairs of scenes suitable for analyzing the WSH error. Overall, the absolute WSH errors vary between 0.2 and 161 mm. The median absolute WSH error between scenes from the same day ( $\Delta t = 0$  days,  $N = 13$ ) is 25 mm, and 33 mm if the scenes are from subsequent days ( $\Delta t = 1$ ,  $N = 42$ ; Figure 6a). If the slope at the waterline was less or equal than  $1^\circ$ , the median absolute WSH error is only 15 mm ( $\Delta t \leq 1$ ,  $N = 17$ ), and 51 mm if the slope was above  $1^\circ$  ( $\Delta t \leq 1$ ,  $N = 38$ ).


## 5.5 Water balance components

Of the four water balance components, evaporation rates ( $E$ ) and daily WSH changes ( $\Delta h_{rate}$ ) show the most pronounced seasonality over the course of the dry season (Figure 7). Daily rates of  $E$  increase from about  $7$  mm/d in October to about  $10$  mm/d in April.  $\Delta h_{rate}$  shows a similar behaviour, but the rates are about  $2$  mm/d lower than the daily rates of  $E$ . Because  $P$  is usually zero during the dry season, the difference between  $E$  and  $\Delta h_{rate}$  is made up by net inflow ( $Q$ ). Net inflow is positive, which means that inflow is higher than outflow. Only at the beginning of the dry season, in October, outflow from the lake might be still higher than inflow ( $Q < 0$  mm/d), but the uncertainty in the calculated rates is high (Figure 7).

The average seasonality of  $\Delta h_{rate}$  that is described above is used to fill data gaps in the WSH time series and therefore enabling us to calculate average rates for the dry season of each hydrological year 2000 to 2021 (Figure 8). Only in two years (2000 and 2004) the available observations cover less than 50% of the dry season, and WSHs of these years were therefore not extrapolated. The Sen's slopes of the remaining 19 annual values indicate a positive trend in daily rates of  $E$  and  $\Delta h_{rate}$ , a negative trend in  $Q$  and no trend in  $P$  (Figure 8).




**Figure 6.** Analysis of the relative error between Water Surface Heights (WSH) extracted from Landsat 7/8 scenes and Sentinel-2 scenes. a) Box-plot of the absolute WSH error between scenes of the same ( $\Delta t = 0$  days) and of subsequent days ( $\Delta t = 1$  day). N is the number of scene pairs available for comparison. The central mark of each box is the median, the edges are the 25th and 75th percentiles, the whiskers extend to the most extreme data points. b) Average slopes of waterline pixels and absolute WSH error between scenes of the same or subsequent days ( $\Delta t \leq 1$  day).



**Figure 7.** Rates of water balance components (lake level change:  $\Delta h_{rate}$ , net inflow:  $Q$ , precipitation:  $P$ , evaporation:  $E$ ) during the dry season (1 October until 15 May). The lines and error bars indicate the mean and standard deviation, respectively, over available data points for 15-day periods. For precipitation the median and the 95% confidence interval is shown instead of the mean and the standard deviation.

## 400 5.6 Attribution analysis

The increasing trend in accelerating dry-season WSH change rates lead to decreasing decrease leads to lower lake levels at the end of the dry season. Over the study period 2000-2021 the observed change The observed trends in  $\Delta h_{rate}$  cause a decrease in




**Figure 8.** Average daily rates of water balance components estimated for the ~~dry-seasons~~ dry seasons 2000-2021 (lake level change:  $\Delta h_{rate}$ , net inflow:  $Q$ , precipitation:  $P$ , evaporation:  $E$ ). The transparent areas show the 95% CI of the linear regression slope.

end-of-dry-season lake levels between 37 mm and 406 mm over the 22-year period (Figure 9), considering the 95% confidence interval (CI) of the Sen slope of the linear regression (Figure 8). The increase in  $\Delta h_{rate}$  accelerating lake level decrease can be explained by the increase in direct evaporation from the lake, explaining 62 to 186 mm of the observed negative trend in lake levels. Likely, also a decrease in net inflow contributed to a decrease in WSHs. However, according to the test for a monotonic trend, there is a probability of 14% that net inflow has increased rather than decreased. The 95% CI ranges from an impact on the lake level between +50 mm to -338 mm that is due to changes in net inflow (Figure 9).

The observed lake level decrease over the 22-year period is much higher than what can be explained by the changes in dry-season water balance components. The average lake levels of the months January-March decreased by 644 mm (Figure 4c and Figure 9, 95% CI: 451-865 mm). The extrapolated lake levels for May 15th (Figure 10a) decreased by 414-845 mm (Figure 4c). Even the average lake levels of the wet season decreased by 458 mm (Q3 in Figure 4c), but the uncertainty of the regression is high (95% CI: 33-853 mm). Variations in the timing of the ~~dry-season~~ dry season can also not explain the observed lake level trends (Figure 11). The test for a monotonic trend does not indicate that an earlier or later end of the wet season has a significant impact on the multi-year trend in WSH ( $\Delta h_{\Delta t}$  in Figure 9).

In spite of an increasing trend in wet season precipitation (ensemble-mean of all precipitation products; see Table 1), the initial lake levels at the beginning of the dry season have been decreasing over time (Figure 10). The decreasing initial lake levels explain 260-647 mm of the observed overall dry-season lake level decrease (95% CI,  $\Delta h_{ini}$  in Figure 9).

The sum of the Sen's slope for  $\Delta h_{ini}$ ,  $\Delta h_{rate}$  and  $\Delta h_{\Delta t}$  results in a reconstructed lake level decrease of 631 mm (95% CI: 377-958 mm,  $\Delta h_{tot}$  in Figure 9), which is very similar to the measured lake level decrease ( $644 \pm 207$  mm,  $\Delta h_{meas}$  in Figure 9). Changes in  $\Delta h_{rate}$  explain about  $34 \pm 18\%$  of the decrease,  $\Delta h_{\Delta t}$  explains  $0 \pm 11\%$ , and the changes in initial lake levels explains the largest portion of the reconstructed dry-season lake level changes ( $66 \pm 18\%$ ).




**Figure 9.** Impacts of hydrological changes on end-of-dry-season lake levels (95% CI).  $\Delta h_{rate}$  represents the increasing rate of WSH decline during the [dry-season-dry season](#) that is due to changes in precipitation ( $P$ ), open-water evaporation ( $E$ ) and net inflow ( $Q$ ).  $\Delta h_{ini}$  represents the impact of lower initial lake levels at the beginning of the [dry-season-dry season](#) and  $\Delta h_{\Delta t}$  represents the lake level change due to changes in the timing of the [wet-season-wet season](#).  $\Delta h_{tot}$  is the sum of  $\Delta h_{rate}$ ,  $\Delta h_{ini}$  and  $\Delta h_{\Delta t}$ .  $\Delta h_{meas}$  is the measured difference in dry-season lake levels between 2000 and 2021 ( $Q1$  in Figure 4).

## 6 Discussion

The careful separation of the lake sediment and the lake water balance allows us to unambiguously attribute causes to the  
 425 observed trend of an ever more diminishing lake surface (Figure 4c). The average over all grid points is negative ( $-43 \pm 1$  mm  
 over the period 2000-2021), which means that there is more erosion than deposition, and therefore silting is not the cause of the  
 observed lake area decrease (minus 22-54 ha across all seasons, see Figure 4c). Still, as expected, net sediment deposition is  
 evident at the [mouths-depositional plains downstream](#) of the two tributaries. With the derived sedimentation and erosion rates  
 for each pixel we can reconstruct the bathymetry of Lac Wégénia from the beginning of the century, and compare the lake areas  
 430 for given WSHs. If the WSH is between 329.4 and 329.9 m asl, the lake area today is up to 4.5 ha smaller than 21 years ago  
 (Figure 12a), which represents about 5% area loss.

At an elevation range between 328.7 and 329.3 m asl, the lake has seen a net erosion of the lake bed (Figure 12). [According  
 to the sediment balance, about 40,000  \$m^3\$  of soil eroded from this zone over the last 21 years.](#) The areas which see a net erosion  
 of the ground are characterized by gentle slopes and are frequently visited by livestock for watering. The bare silty soil dries  
 435 out during the dry season, gets mobilized by the cattle and then gets suspended in the water when the water is rising again.  
 Our calculations cannot clarify if from there the sediments are moved to deeper areas of the lake where they deposit again, or  
 if they get flushed away during the wet season. Given the fine grain size of the material we suspect that the latter is the case.

The attribution analysis has revealed that the main cause of the decreasing dry-season water level trend are lower initial lake  
 levels at the beginning of the dry season (Figure 9). The initial lake levels are crucial for the persistence of the lake during




**Figure 10.** a) Dry-season water levels for each hydrological year 2000-2021. The crosses indicate the extrapolated WSH on October 1st, which is used as a proxy for the floor level at the outflow. Values above 330.4 m asl are considered as outliers and are not considered for extrapolation. b) Time-series of extrapolated WSH on October 1st. Error bars represent the range of values obtained by considering the uncertainty in the rates used for extrapolation (Figure 7). The transparent area indicates the 95% CI of the linear regression slope. The dotted red line shows an alternative interpretation of the data, speculating that a single strong erosive event in 2011 may have lowered the outflow level by approximately 29 cm.

440 the dry season, because the lake does not see any surface water inflow over a period of about eight months. Less than 30% of the water that evaporates is replaced by net inflow through groundwater exchange (Figure 8). Decreasing initial lake levels therefore imperatively lead to decreasing WSHs at the end of the dry season. The lake might even run completely dry in the future, which is something that has never occurred in the past decades.

The lake levels at the end of the wet season mainly depend on the base level at the outflow, which defines the dead storage volume of the lake. The sediment balance around the location of the outlet indicate net erosion rates of  $10 \pm 13$  mm per year, which is less than the  $20 \pm 3$  mm per year obtained for  $\Delta h_{ini}$  (Figure 9). However, the outflow channel is only about 5 m wide, and therefore below the pixel resolution of the sediment balance map (Figure 3c). A hand-made dam with a height of about 50 cm made out of sand bags was present at the location during field visits in 2019 and 2020 (Figure 13). According to






**Figure 11.** Date of the beginning of the ~~dry-season~~ dry season based on gauge-corrected satellite data (black line). The ~~dry-season~~ dry season is defined as the portion of the year where open-water evaporation (E) exceeds precipitation. Weeks with sufficient precipitation to satisfy E are marked in grey. The dotted red line indicates the linear regression line based on the Sen's slope estimator.

information from local residents, the dam is not able to withstand the speed of the water leaving the lake during the rainy season and thus collapses, but has been rebuilt each year since 2009 to reduce the outflow of water from the lake. As a consequence of the collapse of the dam, the flow velocities ~~temporarily~~ increase, which ~~may lead to~~ leads to temporarily higher erosion rates. The step between 2010 and 2011 in the time series of the October 1st water level (Figure 10b) coincides with the timing of the first construction of the dam. The average reconstructed water levels are 29 cm higher at the beginning of the dry seasons 1999-2010 than over the period 2011-2020 (Figure 10b). The intervention in the river bed in 2009 may thus have entailed a strong erosive event during the wet season of the year 2011.

~~A lower outflow level explains also the tendency of lower WSHs during the wet season. Of course, lower WSHs at the beginning of the dry season could also be caused by changes in the wet-season water balance. However, the lake exceeded a level of 329.8 m asl during each wet season of the observation period (Figure 4d), in spite of constant or increasing precipitation b). The lake thus continues to exceed the dead storage level of May 2019, which means that during the wet season, the lake recovers from the low WSHs at the end of the dry season. The duration of the wet season did also not change significantly over the observation period (Figure 11). Our analysis even reveals positive wet-season precipitation trends for Lac Wégna (Table 1;-), confirming recent findings by e.g. Nouaceur and Murarescu (2020) or Bodian et al. (2020)). A lake level of 329.8 m asl today is 1 m above the outflow level, but about 0.4 m less. These findings do not suggest that the observed changes in initial WSH at the beginning of the century. Consequently, more outflow is generated for the same WSH, and higher inflows are dry season depend on wet-season water balance changes. On the other hand, a lower dead storage level can explain the tendency of lower WSHs during the wet season (Figure 4d), because with a lower base level at the outflow, much higher inflows would be required to reach the same water levels. Following this interpretation, according to Figure 10b, the dead storage level of Lac~~



**Figure 12.** a) Difference in lake area in function of water surface height (WSH), based on the bathymetries for May 2019 and May 2000, respectively. The error bars reflect the 95% CI of the sediment erosion and deposition rates that were used to reconstruct the bathymetry of the year 2000. b) Lake contour lines for a WSH of 328.8 m asl and 329.6 m asl, respectively, considering the bathymetries of the year 2000 and 2019.

Wégnia has decreased by 0.3 to 0.6 meters. This is equivalent to a storage volume loss of 300,000 to 700,000 m<sup>3</sup>. About 25% to 50% of the storage capacity has therefore been lost since the beginning of the century.

470 The present study also indicates a possible decrease of net inflow to the lake during the dry season, and an increase of direct evaporation from the lake (Figure 9). Increasing evaporation may be related to increasing air-temperature (Touré Halimatou et al., 2017). Since net inflow is predominantly positive (Figure 7), but there is no surface inflow to the lake during the ~~dryseason~~dry season, the inflow enters the lake through groundwater exchange. If the groundwater levels are dropping then this contribution is reducing and the lake levels gradually decrease. Groundwater is not continuously monitored in the region, and it is therefore not possible to validate this finding. Our findings highlight the need for the monitoring of groundwater in the region, which has an important ecological role and which is an important resource for human activities.

475

## 7 ~~Accuracy~~Uncertainty assessment

~~The analysis has benefited from several factors that facilitated the application of the waterline method at the study site:-~~

- ~~- Cloud-free meteorological conditions during the dry season.-~~
- 480 ~~- Strong natural fluctuations of the water level.-~~
- ~~- Shallow slopes at the waterline.-~~
- ~~- The availability of a high resolution DEM that also captures the bathymetry of the lake for low water levels.-~~



**Figure 13.** Photo of the hand-made dam at the outlet of Lac Wégnia (9 February 2020, Source: Tobias Siegfried).

485 The climate and geomorphology of the study region is characteristic for large areas in Sub-Saharan West Africa. The first three points are therefore valid for hundreds of water bodies in the Sahel and beyond. The present study can be a showcase for the monitoring of West African lakes using remote sensing, under the condition that the bathymetry is available. Our study has shown that a single drone survey is sufficient to satisfy this point. However, we are aware that because of the remoteness of the area or for security reasons a visit with a drone is rarely feasible. Satellite altimetry can therefore be a promising alternative for data collection in the field. Armon et al. (2020) have shown that determining the bathymetry of shallow desert lakes using ICESat-2 altimetric tracks is possible. For Lac Wégnia, however, ICESat-2 cross-sections are not yet available for the central part of the lake.

490 Shallow slopes Shallow slopes greatly increase the accuracy of the waterline approach (Tseng et al., 2016). The steeper the slope, the larger the elevation range within a Landsat or Sentinel-2 pixel that represents the lake shore. The average slope of shoreline pixels at Lac Wégnia is between  $0.2^\circ$  and  $2.25^\circ$  per scene, with an average of  $1.06^\circ$  across all scenes that represent a WSH below outflow level (329.8 m asl). Assuming a horizontal error of the waterline position of one pixel (i.e., 30 m for Landsat scenes and 10 m for Sentinel-2 scenes), and a slope of  $1.06^\circ$ , we obtain vertical errors of 0.56 m (Landsat) and 0.18 m (Sentinel-2), respectively. The average number of 10-m shoreline pixels per scene is  $n=671$  (WSH below 329.8 m asl, excluding masked pixels). Assuming that the vertical error estimates above represents the standard deviation ( $\sigma$ ) of each pixel-wise WSH estimate, we obtain a standard error of the WSH equal to  $\sigma/\sqrt{n}$ , and therefore 21 mm (Landsat) and 7 mm (Sentinel-2), respectively. These theoretical errors agree well with the identified relative errors (Figure 6), and demonstrate that the waterline approach provides sufficient accuracy for the purpose of identifying WSHs at Lac Wégnia.

500 For the shoreline elevation anomalies the same considerations on accuracy apply as for the WSH estimates. The accuracy of the sediment balance estimates then mainly depends on the adequacy of the regression slopes fitted to the SEAs. For individual

pixels, the average  $1-\sigma$  CI of the Sen's slope is quite large ( $\pm 7.8$  mm/year, resulting in an uncertainty of the pixel-wise sediment balance of  $\pm 163$  mm over 21 years). Sediment balances of individual pixels should therefore be interpreted with care. However, the total number of pixels for which sediment balances could be calculated is  $n=10,790$ , and the standard error of the lake sediment balance is therefore only  $\pm 1.6$  mm. The resulting deposition/erosion patterns (Figure 3) agree well with the expected patterns (see section above), which demonstrates the suitability of the approach.

The point sediment balances at individual pixels are sensitive to errors in the coregistration. According to Nguyen et al. (2020), the random offset differences between Landsat 8 and Sentinel-2 can be reduced to less than 2 m in most of the pixels with the displacement() function in GEE. We thus tested the sensitivity of the lake sediment balance to a random error in coregistration by adding a random error with a normal distribution ( $\mu=0$ ,  $\sigma=2$  m) to the determined displacements (both in x and y direction). The resulting lake sediment balance over the 22 years study period changed by +9 mm from -44 mm to -35 mm, which can be considered as an acceptable error range.

The uncertainty assessment above confirms the findings of previous studies (e.g., Tseng et al., 2016) that the accuracy of the waterline method greatly benefits from shallow slopes at the waterline, a sufficiently large number of shoreline pixels, and a low shoreline positioning uncertainty. Furthermore, our analysis benefits from a high relative vertical accuracy of the DEM, cloud-free meteorological conditions during the dry season, and strong natural fluctuations of the water level. With the exception of the availability of a high-resolution DEM, the factors named above are valid for hundreds of water bodies in the Sahel and beyond. Assuming similar boundary conditions for other water bodies in the region and an acceptable sediment balance standard error of 10 mm, our approach can also be applied to ponds and reservoirs that are up to 40 times smaller than Lac Wégénia (i.e., average surface water areas of up to 2.5 hectares).

Regarding the availability of lake bathymetries, our study has shown that a single UAV survey is sufficient to satisfy this point. However, we recognize that UAV surveys are impractical in many locations due to security concerns and the remoteness of the water bodies in the region. Satellite altimetry can therefore be a promising alternative for data collection in the field. Armon et al. (2020) have shown that determining the bathymetry of shallow desert lakes using ICESat-2 altimetric tracks is possible. For Lac Wégénia, however, ICESat-2 cross-sections are not yet available for the central part of the lake.

## 8 Conclusions

This work has demonstrated the utility of the waterline method for extracting the water levels of Lac Wégénia, a Malian lake at the boundary between the Sahelian and the Sudanian eco-climate. 541 WSH data points were obtained for the period October 1999 to June 2021. The data reveal that the lake is dwindling at alarming rates, with a decrease of the seasonal average WSH between  $22$  mm/year and  $33$  mm/year, which translates to a wet-season area loss of 17% and an end-of-dry-season area decrease of 64% between 2000 and 2021. Based on gridded global datasets and the observed WSH changes we have successfully unravelled the dry-season water balance of the lake. The analysis revealed that a change in the water balance components explains only  $34\pm 18\%$  of the overall lake level decrease, while the reduction of ~~storage volume by erosion of the~~ gully the initial storage volume at the beginning of the dry season explains  $66\pm 18\%$  of the observed changes. Erosion through

the natural levee at the outlet of the lake is identified as the main ~~driver (66±18~~cause of this storage volume loss. An estimated 25% ) of the observed changes to 50% of the water storage capacity of Lac Wégénia has been lost since the beginning of the century. Future interventions for safeguarding the wetlands of the RAMSAR site should focus on preventing erosion at the outlet channel. In this respect, efforts by local villagers to artificially ~~rise~~raise the water table of the lake through improvised  
540 dams may be counterproductive, as they increase erosion rates if they are not properly constructed.

The waterline method was further developed in this study to identify shoreline elevation anomalies, which indicate locations with significant sediment erosion or deposition. This novel contribution to the waterline method enables the calculation of sediment balances for pixels that are frequently representing the shoreline. Moreover, accounting for SEAs allows to unambiguously separate lake level and terrain height changes. We could show that no significant silting had taken place within the  
545 study period of 21 years. ~~Erosion of the lake shores has even led to an increase of the storage volume by about 15000 m<sup>3</sup> below 328.8 m asl. (which is the present floor level at the outflow).~~ When contemplating the sedimentation and erosion of natural lakes, important parallels can be drawn for the planning of reservoirs. The proposed method and the presented results have therefore numerous potential applications.

A remarkable fining finding of this study is that the lake levels are decreasing in spite of precipitation trends that indicate a  
550 possible increase of wet season precipitation. This conclusion does not lack a certain irony, because large areas of the Sahel region saw a surface water increase despite a general precipitation decline during the last decades of the 20th century. While the 'first' Sahelian paradox could be related to large-scale eco-hydrological changes, the paradox reported in this study has its main cause in the local management of the lake. However, the present study also indicates a possible decrease of net inflow to the lake during the dry season, and an increase of direct evaporation from the lake. Both factors could also negatively impact  
555 the persistence of other water bodies in the region. While the present study can be a showcase for monitoring Sahelian lakes using remote sensing, it is hoped that the hydrological trends at Lac Wégénia are not symptomatic for the entire region.

*Data availability.* The pixel sediment balances of Lac Wégénia can be accessed and visualized through an Earth Engine application (<https://hydrosolutions.users.earthengine.app/view/wegenia-sb>). This application allows users to click on any point in the lake to view the annual SEAs and the fitted regression slopes. The application also provides access to all available water surface area and WSH data points. The  
560 sediment balance script along with the input data that are required to apply it to Lac Wégénia can be freely accessed from <https://github.com/hydrosolutions/GEE-SedimentBalance>.

*Author contributions.* TS and RD planned this investigation and are responsible for field observations. SR designed and conceptualized the research, and analysed and interpreted data together with TB. SR wrote the paper with critical review and input from PM. All co-authors participated in the co-editing of the manuscript.

565 *Competing interests.* The authors declare that they have no conflict of interest.

*Acknowledgements.* All the participants in the field visits are gratefully acknowledged, namely Moussa Savadogo, Cissé Bocar, Hirosi Pascal Dakouo and Robert Naudascher. We are grateful to Sylvatrop Consulting directed by Sylvain Dufour for carrying out the UAV survey in May 2019. Sylvatrop Consulting also processed the aerial images and generated the DEM. We thank Rebecca Hochreutener and Abdouramane Yoroté from TAHMO for organizational and technical assistance. This research is supported by the SAWEL program “Improved Food security and nutrition in the Sahel by safeguarding wetlands through ecologically sustainable agricultural water management” carried out by Wetlands International, Caritas Switzerland, the International Water Management Institute and hydrosolutions GmbH, with financial support from the Swiss Agency for Development and Cooperation (SDC).

## References

- Albergel, J.: Sécheresse, désertification et ressources en eau de surface — application aux petits bassins du Burkina Faso, IAHS-AISH  
575 publication, pp. 355–365, 1987.
- Alduchov, O. A. and Eskridge, R. E.: Improved Magnus form approximation of saturation vapor pressure, *Journal of Applied Meteorology*,  
35, 601–609, [https://doi.org/10.1175/1520-0450\(1996\)035<0601:IMFAOS>2.0.CO;2](https://doi.org/10.1175/1520-0450(1996)035<0601:IMFAOS>2.0.CO;2), 1996.
- Amogu, O.: La dégradation des espaces sahéliens et ses conséquences sur l’alluvionnement du fleuve Niger moyen, Ph.D. thesis, Université  
Joseph Fourier Grenoble 1, 2009.
- 580 Amogu, O., Descroix, L., Yéro, K. S., Breton, E. L., Mamadou, I., Ali, A., Vischel, T., Bader, J. C., Moussa, I. B., Gautier, E., Boubkraoui,  
S., and Belleudy, P.: Increasing river flows in the Sahel?, *Water (Switzerland)*, 2, 170–199, <https://doi.org/10.3390/w2020170>, 2010.
- Armon, M., Dente, E., Shmilovitz, Y., Mushkin, A., Cohen, T. J., Morin, E., and Enzel, Y.: Determining Bathymetry  
of Shallow and Ephemeral Desert Lakes Using Satellite Imagery and Altimetry, *Geophysical Research Letters*, 47, 1–9,  
<https://doi.org/10.1029/2020GL087367>, 2020.
- 585 Asfaw, W., Haile, A. T., and Rientjes, T.: Combining multisource satellite data to estimate storage variation of a lake in the Rift Valley Basin,  
Ethiopia, *International Journal of Applied Earth Observation and Geoinformation*, 89, 102 095, <https://doi.org/10.1016/j.jag.2020.102095>,  
2020.
- Avisse, N., Tilmant, A., François Müller, M., and Zhang, H.: Monitoring small reservoirs’ storage with satellite remote sensing in inaccessible  
areas, *Hydrology and Earth System Sciences*, 21, 6445–6459, <https://doi.org/10.5194/hess-21-6445-2017>, 2017.
- 590 Bodian, A., Diop, L., Panthou, G., Dacosta, H., Deme, A., Dezetter, A., Ndiaye, P. M., Diouf, I., and Visch, T.: Recent trend in hydroclimatic  
conditions in the Senegal River basin, *Water (Switzerland)*, 12, 1–12, <https://doi.org/10.3390/w12020436>, 2020.
- Brouwer, J., Abdoul Kader, H. A., and Sommerhalter, T.: Wetlands help maintain wetland and dryland biodiversity in the Sa-  
hel, but that role is under threat: An example from 80 years of changes at Lake Tabalak in Niger, *Biodiversity*, 15, 203–219,  
<https://doi.org/10.1080/14888386.2014.934714>, 2014.
- 595 Buma, W. G., Lee, S. I., and Seo, J. Y.: Recent surface water extent of lake Chad from multispectral sensors and GRACE, *Sensors (Switzer-  
land)*, 18, <https://doi.org/10.3390/s18072082>, 2018.
- Coe, M. T. and Foley, J. A.: Human and natural impacts on the water resources of the Lake Chad basin, *Journal of Geophysical Research  
Atmospheres*, 106, 3349–3356, <https://doi.org/10.1029/2000JD900587>, 2001.
- Coulibaly, I., Traoré, N., Timbo, S., and Dembélé, I.: Fiche descriptive sur les zones humides Ramsar (FDR) - Lac Wégnia, Tech. rep.,  
600 <https://rsis.ramsar.org/RISapp/files/RISrep/ML2127RIS.pdf>, 2013.
- Crétaux, J. F. and Birkett, C.: Lake studies from satellite radar altimetry, *Comptes Rendus - Geoscience*, 338, 1098–1112,  
<https://doi.org/10.1016/j.crte.2006.08.002>, 2006.
- Crétaux, J. F., Abarca-del Río, R., Bergé-Nguyen, M., Arsen, A., Drolon, V., Clos, G., and Maisongrande, P.: Lake Volume Monitoring from  
Space, *Surveys in Geophysics*, 37, 269–305, <https://doi.org/10.1007/s10712-016-9362-6>, 2016.
- 605 Dardel, C., Kergoat, L., Hiernaux, P., Grippa, M., Mougin, E., Ciais, P., and Nguyen, C. C.: Rain-use-efficiency: What it tells us about the  
conflicting sahel greening and sahelian paradox, *Remote Sensing*, 6, 3446–3474, <https://doi.org/10.3390/rs6043446>, 2014.
- de La Rocque, J. and Renoullin, M.: Synthèse environnementale du Lac Wégnia, Tech. rep., CEREG International, Rodez (FR), 2015.
- Dembélé, M., Schaeffli, B., and Van De Giesen, N.: Suitability of 17 gridded rainfall and temperature datasets for large-scale hydrological  
modelling in West Africa, *Hydrology and Earth System Sciences*, 24, 5379–5406, <https://doi.org/10.5194/hess-24-5379-2020>, 2020.



- 610 Descroix, L., Mahé, G., Lebel, T., Favreau, G., Galle, S., Gautier, E., Olivry, J. C., Albergel, J., Amogu, O., Cappelaere, B., Dessouassi, R., Diedhiou, A., Le Breton, E., Mamadou, I., and Sighomnou, D.: Spatio-temporal variability of hydrological regimes around the boundaries between Sahelian and Sudanian areas of West Africa: A synthesis, *Journal of Hydrology*, 375, 90–102, <https://doi.org/10.1016/j.jhydrol.2008.12.012>, 2009.
- DNEF/PAZU: Plan d'aménagement de gestion du Lac Wégénia - Projet "Eco-Lac Wégénia", Tech. rep., Ministère de l'Environnement, de  
615 l'Assainissement et du Développement Durable. Direction Nationale des Eaux et Forêts, Bamako, 2018.
- Donchyts, G., Schellekens, J., Winsemius, H., Eisemann, E., and van de Giesen, N.: A 30 m resolution surfacewater mask including estimation of positional and thematic differences using landsat 8, SRTM and OPenStreetMap: A case study in the Murray-Darling basin, Australia, *Remote Sensing*, 8, <https://doi.org/10.3390/rs8050386>, 2016.
- Favreau, G., Cappelaere, B., Massuel, S., Leblanc, M., Boucher, M., Boulain, N., and Leduc, C.: Land clearing, climate variability, and water  
620 resources increase in semiarid southwest Niger: A review, *Water Resources Research*, 45, 1–18, <https://doi.org/10.1029/2007WR006785>, 2009.
- Fowe, T., Karambiri, H., Paturel, J. E., Poussin, J. C., and Cecchi, P.: Water balance of small reservoirs in the Volta basin: A case study of Boura reservoir in Burkina Faso, *Agricultural Water Management*, 152, 99–109, <https://doi.org/10.1016/j.agwat.2015.01.006>, 2015.
- Frappart, F., Hiernaux, P., Guichard, F., Mougin, E., Kergoat, L., Arjounin, M., Lavenu, F., Koité, M., Paturel, J. E., and  
625 Lebel, T.: Rainfall regime across the Sahel band in the Gourma region, Mali, *Journal of Hydrology*, 375, 128–142, <https://doi.org/10.1016/j.jhydrol.2009.03.007>, 2009.
- Gal, L., Grippa, M., Hiernaux, P., Peugeot, C., Mougin, E., and Kergoat, L.: Changes in lakes water volume and runoff over ungauged Sahelian watersheds, *Journal of Hydrology*, 540, 1176–1188, <https://doi.org/10.1016/j.jhydrol.2016.07.035>, 2016.
- Gal, L., Grippa, M., Hiernaux, P., Pons, L., and Kergoat, L.: The paradoxical evolution of runoff in the pastoral Sahel: Analysis of the  
630 hydrological changes over the Agoufou watershed (Mali) using the KINEROS-2 model, *Hydrology and Earth System Sciences*, 21, 4591–4613, <https://doi.org/10.5194/hess-21-4591-2017>, 2017.
- Gao, H., Bohn, T. J., Podest, E., McDonald, K. C., and Lettenmaier, D. P.: On the causes of the shrinking of Lake Chad, *Environmental Research Letters*, 6, <https://doi.org/10.1088/1748-9326/6/3/034021>, 2011.
- Gardelle, J., Hiernaux, P., Kergoat, L., and Grippa, M.: Less rain, more water in ponds: A remote sensing study of the dynamics of  
635 surface waters from 1950 to present in pastoral Sahel (Gourma region, Mali), *Hydrology and Earth System Sciences*, 14, 309–324, <https://doi.org/10.5194/hess-14-309-2010>, 2010.
- Gilbert, R. O.: *Statistical methods for environmental pollution monitoring*, New York, 1987.
- Gorelick, N., Hancher, M., Dixon, M., Ilyushchenko, S., Thau, D., and Moore, R.: Google Earth Engine: Planetary-scale geospatial analysis for everyone, *Remote Sensing of Environment*, 202, 18–27, <https://doi.org/10.1016/j.rse.2017.06.031>, 2017.
- 640 Guo, D., Westra, S., and Maier, H. R.: An R package for modelling actual, potential and reference evapotranspiration, *Environmental Modelling and Software*, 78, 216–224, <https://doi.org/10.1016/j.envsoft.2015.12.019>, 2016.
- Haas, E. M., Bartholomé, E., and Combal, B.: Time series analysis of optical remote sensing data for the mapping of temporary surface water bodies in sub-Saharan western Africa, *Journal of Hydrology*, 370, 52–63, <https://doi.org/10.1016/j.jhydrol.2009.02.052>, 2009.
- Hersbach, H., Bell, B., Berrisford, P., Hirahara, S., Horányi, A., Muñoz-Sabater, J., Nicolas, J., Peubey, C., Radu, R., Schepers, D., Simons, A., Soci, C., Abdalla, S., Abellan, X., Balsamo, G., Bechtold, P., Biavati, G., Bidlot, J., Bonavita, M., De Chiara, G., Dahlgren, P., Dee, D., Diamantakis, M., Dragani, R., Flemming, J., Forbes, R., Fuentes, M., Geer, A., Haimberger, L., Healy, S., Hogan, R. J., Hólm, E., Janisková, M., Keeley, S., Laloyaux, P., Lopez, P., Lupu, C., Radnoti, G., de Rosnay, P., Rozum, I., Vamborg, F., Vil-



- laume, S., and Thépaut, J. N.: The ERA5 global reanalysis, *Quarterly Journal of the Royal Meteorological Society*, 146, 1999–2049, <https://doi.org/10.1002/qj.3803>, 2020.
- 650 Heygster, G., Dannenberg, J., and Notholt, J.: Topographic mapping of the German tidal flats analyzing SAR images with the waterline method, *IEEE Transactions on Geoscience and Remote Sensing*, 48, 1019–1030, <https://doi.org/10.1109/TGRS.2009.2031843>, 2010.
- Karambiri, H., Ribolzi, O., Delhoume, J. P., Ducloux, J., Coudrain-Ribstein, A., and Casenave, A.: Importance of soil surface characteristics on water erosion in a small grazed Sahelian catchment, *Hydrological Processes*, 17, 1495–1507, <https://doi.org/10.1002/hyp.1195>, 2003.
- Kendall, M.: *Rank Correlation Methods*, London, 1975.
- 655 Kwang, C., Jnr, E. M. O., and Amoah, A. S.: Comparing of Landsat 8 and Sentinel 2A using Water Extraction Indexes over Volta River, *Journal of Geography and Geology*, 10, 1, <https://doi.org/10.5539/jgg.v10n1p1>, 2017.
- Leblanc, M. J., Favreau, G., Massuel, S., Tweed, S. O., Loireau, M., and Cappelaere, B.: Land clearance and hydrological change in the Sahel: SW Niger, *Global and Planetary Change*, 61, 135–150, <https://doi.org/10.1016/j.gloplacha.2007.08.011>, 2008.
- Lemoalle, J., Bader, J. C., Leblanc, M., and Sedick, A.: Recent changes in Lake Chad: Observations, simulations and management options (1973–2011), *Global and Planetary Change*, 80–81, 247–254, <https://doi.org/10.1016/j.gloplacha.2011.07.004>, 2012.
- 660 Li, Z., Heygster, G., and Notholt, J.: Intertidal topographic maps and morphological changes in the German Wadden Sea between 1996–1999 and 2006–2009 from the waterline method and SAR images, *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 7, 3210–3224, <https://doi.org/10.1109/JSTARS.2014.2313062>, 2014.
- Ma, Y., Xu, N., Sun, J., Wang, X. H., Yang, F., and Li, S.: Estimating water levels and volumes of lakes dated back to the 1980s using Landsat 665 imagery and photon-counting lidar datasets, *Remote Sensing of Environment*, 232, 111–128, <https://doi.org/10.1016/j.rse.2019.111287>, 2019.
- Mahmood, R. and Jia, S.: Assessment of hydro-climatic trends and causes of dramatically declining stream flow to Lake Chad, Africa, using a hydrological approach, *Science of the Total Environment*, 675, 122–140, <https://doi.org/10.1016/j.scitotenv.2019.04.219>, 2019.
- Mason, D. C., Davenport, I. J., Robinson, G. J., Flather, R. A., and McCartney, B. S.: Construction of an inter-tidal digital elevation model 670 by the ‘Water-Line’ Method, *Geophysical Research Letters*, 22, 3187–3190, <https://doi.org/10.1029/95GL03168>, 1995.
- Mason, D. C., Amin, M., Davenport, I. J., Flather, R. A., Robinson, G. J., and Smith, J. A.: Measurement of recent inter-tidal sediment transport in Morecambe Bay using the waterline method, *Estuarine, Coastal and Shelf Science*, 49, 427–456, <https://doi.org/10.1006/ecss.1999.0508>, 1999.
- Militino, A. F., Montesino-SanMartin, M., Pérez-Goya, U., and Ugarte, M. D.: Using RGISTools to estimate water levels in reservoirs and 675 lakes, *Remote Sensing*, 12, 1–19, <https://doi.org/10.3390/rs12121934>, 2020.
- Nguyen, M. D., Baez-Villanueva, O. M., Bui, D. D., Nguyen, P. T., and Ribbe, L.: Harmonization of Landsat and Sentinel 2 for Crop Monitoring in Drought Prone Areas: Case studies of Ninh Thuan (Vietnam) and Bekaa (Lebanon), *Remote Sensing*, 12, 1–18, <https://doi.org/10.3390/rs12020281>, 2020.
- Nippes, K. R.: Sedimentation in shallow depressions - A case study of Lake Magui, Western Mali/West Africa, *GeoJournal*, 9, 335–341, 680 <https://doi.org/10.1007/BF00171597>, 1984.
- Nouaceur, Z. and Murarescu, O.: Rainfall variability and trend analysis of rainfall in west Africa (Senegal, Mauritania, Burkina Faso), *Water (Switzerland)*, 12, <https://doi.org/10.3390/W12061754>, 2020.
- Otsu, N.: A threshold selection method from gray-level histograms, *IEEE Trans Syst Man Cybern*, SMC-9, 62–66, <https://doi.org/10.1109/tsmc.1979.4310076>, 1979.

- 685 Oyebande, L. and Odunuga, S.: Climate Change Impact on Water Resources at the Transboundary Level in West Africa: The Cases of the Senegal, Niger and Volta Basins, *The Open Hydrology Journal*, 4, 163–172, <https://doi.org/10.2174/1874378101004010163>, 2013.
- Panthou, G., Vischel, T., and Lebel, T.: Recent trends in the regime of extreme rainfall in the Central Sahel, *International Journal of Climatology*, 34, 3998–4006, <https://doi.org/10.1002/joc.3984>, 2014.
- Penman, H. L.: Natural evaporation from open water, bare soil and grass, *Proceedings of the Royal Society of London. Series A, Mathematical and physical sciences*, 193, 120–145, <https://doi.org/10.1098/rspa.1948.0037>, 1948.
- 690 Pham-Duc, B., Sylvestre, F., Papa, F., Frappart, F., Bouchez, C., and Crétaux, J. F.: The Lake Chad hydrology under current climate change, *Scientific Reports*, 10, 1–10, <https://doi.org/10.1038/s41598-020-62417-w>, 2020.
- Robert, E., Kergoat, L., Soumaguel, N., Merlet, S., Martinez, J. M., Diawara, M., and Grippa, M.: Analysis of suspended particulate matter and its drivers in Sahelian Ponds and Lakes by remote sensing (landsat and MODIS): Gourma Region, Mali, *Remote Sensing*, 9, 695 <https://doi.org/10.3390/rs9121272>, 2017.
- Rodell, M., Houser, P. R., Jambor, U., Gottschalck, J., Mitchell, K., Meng, C. J., Arsenault, K., Cosgrove, B., Radakovich, J., Bosilovich, M., Entin, J. K., Walker, J. P., Lohmann, D., and Toll, D.: The Global Land Data Assimilation System, *Bulletin of the American Meteorological Society*, 85, 381–394, <https://doi.org/10.1175/BAMS-85-3-381>, 2004.
- Ryu, J. H., Kim, C. H., Lee, Y. K., Won, J. S., Chun, S. S., and Lee, S.: Detecting the intertidal morphologic change using satellite data, *Estuarine, Coastal and Shelf Science*, 78, 623–632, <https://doi.org/10.1016/j.ecss.2008.01.020>, 2008.
- 700 Salameh, E., Frappart, F., Almar, R., Baptista, P., Heygster, G., Lubac, B., Raucoles, D., Almeida, L. P., Bergsma, E. W., Capo, S., De Michele, M. D., Idier, D., Li, Z., Marieu, V., Poupardin, A., Silva, P. A., Turki, I., and Laignel, B.: Monitoring Beach Topography and Nearshore Bathymetry Using Spaceborne Remote Sensing: A Review, *Remote Sensing*, 11, <https://doi.org/10.3390/rs11192212>, 2019.
- Schulz, S., Darehshouri, S., Hassanzadeh, E., Tajrishy, M., and Schüth, C.: Climate change or irrigated agriculture – what drives the water level decline of Lake Urmia, *Scientific Reports*, 10, 1–10, <https://doi.org/10.1038/s41598-019-57150-y>, 2020.
- 705 Sen, P. K.: Estimates of the Regression Coefficient Based on Kendall’s Tau, *Journal of the American Statistical Association*, 63, 1379–1389, <https://doi.org/10.1080/01621459.1968.10480934>, 1968.
- Soti, V., Puech, C., Lo Seen, D., Bertran, A., Vignolles, C., Mondet, B., Dessay, N., and Tran, A.: The potential for remote sensing and hydrologic modelling to assess the spatio-temporal dynamics of ponds in the Ferlo Region (Senegal), *Hydrology and Earth System Sciences*, 14, 1449–1464, <https://doi.org/10.5194/hess-14-1449-2010>, 2010.
- 710 Storey, J., Roy, D. P., Masek, J., Gascon, F., Dwyer, J., and Choate, M.: A note on the temporary misregistration of Landsat-8 Operational Land Imager (OLI) and Sentinel-2 Multi Spectral Instrument (MSI) imagery, *Remote Sensing of Environment*, 186, 121–122, <https://doi.org/10.1016/j.rse.2016.08.025>, 2016.
- Theil, H.: A Rank-Invariant Method of Linear and Polynomial Regression Analysis, I-II, *Proc. Kon. Ned. Akad. v. Wetensch. A.*, 53, 386–715 392, 521–525, 1397–1412, 1950.
- Touré Halimatou, A., Kalifa, T., and Kyei-Baffour, N.: Assessment of changing trends of daily precipitation and temperature extremes in Bamako and Ségou in Mali from 1961- 2014, *Weather and Climate Extremes*, 18, 8–16, <https://doi.org/10.1016/j.wace.2017.09.002>, 2017.
- 720 Tseng, K. H., Shum, C. K., Kim, J. W., Wang, X., Zhu, K., and Cheng, X.: Integrating Landsat Imageries and Digital Elevation Models to Infer Water Level Change in Hoover Dam, *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 9, 1696–1709, <https://doi.org/10.1109/JSTARS.2015.2500599>, 2016.
- van de Giesen, N., Hut, R., and Selker, J.: The Trans-African Hydro-Meteorological Observatory (TAHMO), *Wiley Interdisciplinary Reviews: Water*, 1, 341–348, <https://doi.org/10.1002/wat2.1034>, 2014.

- Vandemeulebrouck, P., Fauchet, J.-S., and Dufour, S.: Production de données photogrammétriques pour la création de données topographiques et d'une orthomosaïque de haute précision; Lac Wegnia - Mali, Tech. rep., Sylvatrop Consulting, Conakry, Guinea, 2019.
- 725 Weekley, D. and Li, X.: Tracking Multidecadal Lake Water Dynamics with Landsat Imagery and Topography/Bathymetry, *Water Resources Research*, 55, 8350–8367, <https://doi.org/10.1029/2019WR025500>, 2019.
- Xu, H.: Modification of normalised difference water index (NDWI) to enhance open water features in remotely sensed imagery, *International Journal of Remote Sensing*, 27, 3025–3033, <https://doi.org/10.1080/01431160600589179>, 2006.
- Xu, N., Ma, Y., Zhang, W., Wang, X. H., Yang, F., and Su, D.: Monitoring annual changes of lake water levels and volumes over 1984–2018  
730 using landsat imagery and ICESat-2 data, *Remote Sensing*, 12, 1–22, <https://doi.org/10.3390/rs12234004>, 2020.
- Xu, Z., jin Kim, D., Kim, S. H., Cho, Y. K., and Lee, S. G.: Estimation of seasonal topographic variation in tidal flats using waterline method: A case study in Gomso and Hampyeong Bay, South Korea, *Estuarine, Coastal and Shelf Science*, 183, 213–220, <https://doi.org/10.1016/j.ecss.2016.10.026>, 2016.
- Yang, X., Chen, Y., and Wang, J.: Combined use of Sentinel-2 and Landsat 8 to monitor water surface area dynamics using Google Earth  
735 Engine, *Remote Sensing Letters*, 11, 687–696, <https://doi.org/10.1080/2150704X.2020.1757780>, 2020.
- Yue, H. and Liu, Y.: Variations in the lake area, water level, and water volume of Hongjiannao Lake during 1986–2018 based on Landsat and ASTER GDEM data, *Environmental Monitoring and Assessment*, 191, <https://doi.org/10.1007/s10661-019-7715-6>, 2019.
- Zhu, W., Yan, J., and Jia, S.: Monitoring recent fluctuations of the southern pool of lake chad using multiple remote sensing data: Implications for water balance analysis, *Remote Sensing*, 9, <https://doi.org/10.3390/rs9101032>, 2017.