

Coupling between downstream variations of channel width and local pool-riffle bed topography

Shawn M. Chartrand¹, A. Mark Jellinek², Marwan A. Hassan³, and Carles Ferrer-Boix⁴

¹School of Environmental Science, Simon Fraser University, Burnaby, British Columbia, Canada.

²Department of Earth, Ocean and Atmospheric Sciences, University of British Columbia, Vancouver, British Columbia, Canada.

³Department of Geography, University of British Columbia, Vancouver, British Columbia, Canada.

⁴Department of Civil and Environmental Engineering, Technical University of Catalonia, Barcelona, Spain.

Correspondence: Shawn M. Chartrand (shawn_chartrand@sfu.ca)

Abstract. A potential control of downstream channel width variations on the structure and planform of pool-riffle sequence local bed topography is a key to the dynamics of gravel-bed rivers. How established pool-riffle sequences respond to time-varying ~~shifts in the channel width~~ changes of channel width at specific locations, however, is largely unexplored and challenging to address with field-based study. ~~Aeeordingly, here~~ Here, we report results of a flume experiment aimed at building understanding of ~~the response of how~~ statistically steady pool-riffle ~~sequences to~~ sequence profiles adjust to spatially prescribed channel width ~~adjustments~~ changes. We find that local bed slopes near steady-state conditions inversely correlate with local ~~width change dynamics, and agree~~ downstream width gradients when the upstream sediment supply approximates the estimated transport capacity. This result constrains conditions prior to, and following the imposed local width changes. Furthermore, this relationship between local channel bed slope and downstream width gradient is consistent with expectations from scaling theory, and a broad set of field-based, numerical and experimental studies (n=88). ~~We also find that coarse sediment release from~~ However, upstream disruptions to coarse sediment supply through actions such as dam removal can ~~temporally flip~~ result in a transient flipping of the expected inverse correlation between bed slope and width gradient, collectively highlighting that ~~local conditions are important for understanding river morphology, and would be overlooked if analysis instead emphasized spatial averaging~~ understanding local conditions is critical before typically-implemented spatial averaging schemes can be reliably applied.

1 Introduction

Gravel-bed rivers commonly ~~exhibit~~ show downstream variations of channel width over distances that are comparable to, or greater than the local mean width—the length scale for “local” used here (~~Wolman, 1955; Richards, 1976~~). ~~A critical implication~~ (see, e.g. Wolman, 1955; Richards, 1976; Furbish et al., 1998). ~~An important effect~~ of downstream width ~~change-variation~~ is the associated differences among spatial patterns of bed sediment erosion and deposition, which includes features such as pools and riffles (~~e.g. Richards, 1976; Carling, 1991; Clifford, 1993; Sear, 1996; Thompson et al., 1998; Wilkinson et al., 2004; White et al., 2010~~ (e.g. Richards, 1976; Carling, 1991; Clifford, 1993; Sear, 1996; Furbish et al., 1998; Thompson et al., 1998; Wilkinson et al., 2004; White et al., 2010)).

. It has been shown that pool-riffle sequences are mechanically coupled to ~~width changes through downstream variations of the section-averaged flow velocity~~ (Repetto et al., 2002; Chartrand et al., 2018; Morgan, 2018) downstream width variations through associated differences of the width-averaged flow velocity (Repetto et al., 2002; Chartrand et al., 2018; Morgan, 2018, also see Furbish et al., 2018) (Fig. 1), and consequently the mean near-bed shear velocity and shear stress (Carling and Wood, 1994; Cao et al., 2003; Wilkinson et al., 2004; MacWilliams et al., 2006, also see MacVicar & Roy, 2007).

Downstream ~~changes to the section-averaged~~ differences of the width-averaged flow velocity and near-bed shear stress give rise to varying momentum fluxes delivered to the gravel bed surface. Over ~~time periods of~~ years to decades or ~~more~~ longer, the fluctuating magnitude of momentum fluxes associated with ~~different~~ flood and sediment supply events of varying magnitude and duration (intensity) shapes the local bed topography and surface grain size distribution through sediment particle entrainment and deposition (Chartrand et al., 2019), and bed load transport more generally (e.g. Church, 2006). Event-specific feedbacks between the flow, bed topography, bed sediment texture and bed load transport continually refines and further shapes local bed architectures (Leopold et al., 1964; Parker, 2007), and generally determines whether there is a tendency for net local deposition or erosion along pool-riffle sequences (Wilkinson et al., 2004; MacWilliams et al., 2006; de Almeida and Rodríguez, 2011, 2012; Brown and Pasternack, 2017; Chartrand et al., 2018). The combination of ~~the above these~~ factors provides a basic ~~idea of how pool-riffles develop~~ construct for the formation of pool-riffle sequences along gravel-bed rivers with downstream width variations. At narrowing channel segments flows speed up and deliver relatively more momentum flux to the bed surface leading to net erosion, whereas at widening segments flows slow down and deliver less momentum flux favouring net deposition (see Furbish et al., 1998). However, the specifics of how pool-riffle sequences respond to ~~dynamic shifts in~~ temporal changes of local width conditions and evolve to statistically steady-state bed topography ~~remains are~~ largely unexplored. This knowledge gap has implications for anticipating and projecting gravel-bed river responses to restoration actions and dam removal (East et al., 2015; Gartner et al., 2015; Magilligan et al., 2016; Harrison et al., 2018; De Rego et al., 2020), coarse sediment management at upstream reservoirs (Chartrand, 2022) and effects related to climate change which are likely to influence basin hydrology, the intensity and magnitude of flood events, and sediment production (East and Sankey, 2020).

Here, we ~~begin to examine this knowledge gap~~ make progress using scaling theory understood through an analog experiment ~~supported by a broad~~ the results of which are in line with an extensive data set drawn from the literature. We address the question of how a pool-riffle channel segment responds to local ~~adjustments of bank position, and specifically whether topographic responses~~ temporal changes of channel width, and whether topographic adjustments conform to expectations of an inverse correlation between ~~local bed slope $S_{local}(x)$ and downstream width change~~ the local dimensionless downstream width gradient $\Delta w(x)$ and bed slope $S_{local}(x)$ (Fig. 1)? The width gradient is calculated as the quotient of the downstream width difference between two points where the direction of width variation changes, divided by the downstream distance between these points. The bed slope is calculated as the quotient of the bed elevation difference between the same two points where the direction of width variation changes, also divided by the downstream distance between these points. An inverse correlation in the present sense provides two possible conditions: $-\Delta w(x)$ (downstream narrowing), $+S_{local}(x)$ (positive downstream slope), and $+\Delta w(x)$ (downstream widening), $-S_{local}(x)$ (negative or adverse downstream slope) (see Brown and Pasternack, 2017, for a complementary discussion). To this end, the paper is structured in the following way. In the next section we present a

scaling argument that offers a general explanation for the inverse correlation between ~~local bed slope $S_{local}(x)$ and downstream variations of channel width~~ the local downstream width gradient $\Delta w(x)$ and bed slope $S_{local}(x)$. Local bed slope is a basic
 60 descriptor of topographic conditions, and collectively over many mean widths in length describes the bed architecture. Following explanation of the scaling theory we describe the physical experiment, and then ~~we~~ present our results followed by a discussion of the implications of our work with respect to natural rivers. Throughout the text we refer to spatial differences of channel width as “variations”, and temporal differences of channel width at specific locations as “changes”.

~~Our results will~~ We show that adjustments of local bed slope following prescriptive temporal changes to channel ~~bank~~
 65 ~~positions~~ width generally follow an expected inverse correlation. This outcome is consistent with a new and expanded data set drawn from the literature representing available field-based studies, and results from numerical analyses and analog experiments (n=88). In particular, ~~through one literature data set we learn that~~ actions such as dam removal which impulsively increases the supply of bed load sediment to downstream river reaches can ~~temporally flip~~ cause a transient flipping of the expected inverse correlation between ~~local bed slope and downstream width change~~ the local downstream width gradient and bed
 70 slope due to pool filling (e.g. Lisle and Hilton, 1992), and smoothing of the local topographic profile. ~~This outcome provides an opportunity and motivation to expand~~ The timing and sequence of hydrograph events post dam removal may also play a role in downstream bed profile dynamics (Nelson et al., 2015; Morgan and Nelson, 2021). We use the transient flipping of the expected inverse correlation between $\Delta w(x)$ and $S_{local}(x)$ to expand interpretation of the proposed scaling theory, and ~~provides~~ suggest further context for expected short-term river dynamics associated with dam removal and similar transient
 75 events which disrupt upstream coarse sediment supplies (Cui et al., 2006; East et al., 2015; De Rego et al., 2020).

2 Theory

Assuming steady-state conditions, the local bed slope $S_{local}(x)$ between two points ~~of width change where the direction of~~ width variation changes along a river profile can be expressed as the product of two terms (see Chartrand et al., 2018, for more details regarding assumptions and derivation):

$$S_{local}(x) \sim \Lambda \left(\Delta \bar{U}_x^* \right). \quad (1)$$

80 The bed architecture stability parameter Λ sets the relative magnitude of the local channel profile in terms of characteristic time scales for the flow t_f , and gravel-bed river topographic adjustment t_y :

$$\Lambda = \underbrace{\left(\frac{[\rho' g D_{90f}]^{0.5}}{\varepsilon w} \right)}_{1/t_y} \underbrace{\left(\frac{D_{90f}}{u^*} \right)}_{t_f} = \frac{t_f}{t_y}, \quad (2)$$

where $\rho' = [(\rho_s/\rho_w) - 1]$, $\rho_s = 2650 \text{ kg/m}^3$ is the density of sediment, $\rho_w = 1000 \text{ kg/m}^{-3}$ is the density of water, $g = 9.81$ is the acceleration of gravity, D_{90f} is the grain size for which 90% of all particles of the sediment supply are smaller, $\varepsilon = (1 - \phi)$ is the solid fraction in the bed, $\phi = 0.4$ is the volume-averaged streambed porosity of the active layer $L_a = kD_i$ (Hirano, 1971), k




Figure 1. Conceptual diagram illustrating an inverse correlation between channel width and the section-average width-average flow velocity, or the local shear velocity, and the likely resulting bed topography profile. The inverse correlation has been shown to occur along river segments, and has been reproduced by numerical simulations of pool-riffle sequences as well as analogue physical experiments (Thompson et al., 1999; de Almeida and Rodríguez, 2012; Bolla Pittaluga et al., 2014; Nelson et al., 2015; Chartrand et al., 2018). The gray arrows indicate that the location of the velocity maxima (and minima) shift depending on the flow stage (Wilkinson et al., 2004). Photograph at right shows a gravel-bed river at spring rising snowmelt stage with a width change gradient from points 1 to 2 over a distance $n\bar{w}(x)$, where n can vary from 1 and higher. Bed architecture at point 1 is a riffle and at point 2 is a pool. Flow direction is from top to bottom of image. Note the broken water surface as flow transitions into the narrower location at point 2. Photograph by S.M. Chartrand, Flat Creek, near Jackson Hole, WY, U.S.A.

85 is constant between 1 and 2 (Parker, 2008), D_{τ} is a bed surface grain size commonly taken to be the D_{90} , w is the local channel width and u_* is the local shear velocity defined as $(g\bar{d}S)^{0.5}$ where \bar{d} is the section-averaged width-averaged water depth.

Here, the topographic adjustment time is a time scale for particle mixtures to aggregate or disaggregate, and is a metric for the tendency for sediment particle deposition or entrainment, respectively. The topographic adjustment time t_y is set by the relative mass (i.e. size) of the D_{90f} , the packing condition of the bed surface sediments which governs particle-particle stress coupling and the local channel width. The flow time t_f indicates the intensity of momentum flux delivered to the gravel-bed surface (cf. Yalin, 1971; Carling and Orr, 2000). The flow time is set by the magnitude of the shear velocity, in comparison to the relative mass of the D_{90f} . Critically, A identifies an inherent covariation between the flow velocity and channel width which governs the resilience of pool-riffle bed architecture (see updated discussion of pool-riffle maintenance in Morgan and Nelson, 2021) (Fig. 1).

95 The dimensionless velocity change $\Delta\bar{U}_x^*$ quantifies the acceleration between two locations moving downstream where width change occurs:

$$\Delta U_x^* = \bar{U}_x^*(x) - \bar{U}_x^*(x + \Delta x), \quad (3)$$




Figure 2. Experimental design of channel width gradients for Phases 1 and 2 of PRE4. (a) Overhead view of the Phase 1 experimental channel showing how channel width changes in the downstream direction. Phase 1 ended at elapsed time 960 min (see Table 1). (b) Overhead view of the Phase 2 experimental channel showing how channel width changes in the downstream direction. Phase 2 began following Phase 1. Color shading for both (a) and (b) represents a relatively smoothed elevation condition for illustration only. The Phase 2 width configuration corresponds to the setup reported by Chartrand et al. (2018). (c) Downstream channel width gradients for Phases 1 and 2, connected by lines for illustration only. Points are plotted at locations which correspond to the red squares of (a), which set the downstream differencing length scale and locations where mean local width was calculated. Values above the zero width gradient line represent widening conditions and those below represent narrowing. Dashed red polygon highlights the location from approximately station 10.6 to 8.15 m where the bank positions were manipulated at elapsed time 960 min per the experimental design.

and specifically,

$$\bar{U}_x^* \approx \left(\frac{\bar{U}_x}{(\rho' g d)^{0.5}} \right), \quad (4)$$

where \bar{U}_x^* is a dimensionless wave speed or Froude number $Fr = \bar{U}_x / (g L_c)^{0.5}$, the square of which expresses a balance between (a) the kinetic energy available in the velocity field to do work to deform the bed and (b) the restoring potential energy in the bed topography, and. The parameter \bar{U}_x is the section-averaged flow velocity-width-averaged flow velocity and L_c a characteristic length. Local downstream gradients of dimensionless bed load transport vary inversely with dimensionless

velocity gradients related to the role of \bar{d} in setting the magnitude of $\Delta\bar{U}_x^*$, for example $\Delta q_{bx}^* \sim -\Delta\bar{U}_x^*$ (see Chartrand et al., 2018). Consequently, we assume that profile disturbances propagate at a wave speed which scales as spatial differences in \bar{U}_x^* . Positive differences of \bar{U}_x^* drive profile changes upstream to downstream, and negative differences vice versa. In relation to $S_{local}(x)$, a key take away is that the sign of $\Delta\bar{U}_x^*$ is determined on the basis of how downstream differences between \bar{U}_x and \bar{d}_x compare. As a result, this parameter captures how velocity and depth comparatively respond to downstream width changes, which itself could be dependent upon local bed surface texture conditions, or spatial patterns of bed topography (Wolman, 1955). These points highlight how the effects of downstream width change are implicitly represented in Eq. 1, bridging a connection with Fig. (1). For the experiments discussed next we treat channel width and its local changes as an independent, random variable, and the local bed slope as a dependent, random variable.

3 Experimental Design and Methods

Here, we present a new analog experiment referred to as Pool-riffle Experiment 4 (PRE4), and revise and analyze in greater detail an extensive series published previously (Chartrand et al., 2018, 2019; Hassan et al., 2021). PRE4 was designed specifically to characterize local bed topographic responses to ~~shifting bank positions, while upstream water and sediment supplies are maintained until~~ locally-specific temporal changes of channel width, after approximate topographic steady-state conditions were achieved. The pre- and post-width change periods are referred to as Phases 1 and 2, respectively (Table 1). This transient experiment was accomplished by manually adjusting the positions of rigid plywood channel walls inset within a flume over a length centrally-located segment of roughly 3 m (Fig. 2), ~~where under previous experimental conditions the downstream width change configuration included.~~ This basic set-up provided for experimental conditions with two distinct downstream channel width configurations for the region of interest, characterized by associated patterns of downstream width variations (Fig. 2c). The Phase 2 downstream width variation configuration was used for prior experiments (Chartrand et al., 2018), and includes a prominent widening and narrowing sequence (Chartrand et al., 2018). We choose to focus on a flume segment with relatively large ~~width change gradients~~ downstream width variations based on the hypothesis that a measurable response would occur and thus facilitate testing against prior results and Eq. 1 (Fig. 2c).

PRE4 was conducted in a 15 m long and 1 m wide flume, with downstream variations of channel width modelled from a 75-m-long reach of East Creek, University of British Columbia Malcolm Knapp Research Forest, B.C., Canada. The field prototype is a small, gravel-bed stream with pool and riffle bed architecture along the model reach. The experimental channel sidewalls were inset within the larger flume and constructed from rough-faced veneer-grade D plywood with a surface roughness ranging from 1 to 4 mm. Water and sediment were supplied at the upstream end of the flume, and water was recirculated via a pump. Sediment was introduced at the upstream end of the flume via a conveyor system, and was captured at the downstream end of the flume in a wire mesh basket. Prior to capture, sediment sizes of the time-averaged transported load were estimated using a light table imaging device (Frey et al., 2003; Zimmermann et al., 2008; Chartrand et al., 2018).

Both the sediment supply and flume-bed sediments had the same distribution of sizes ranging from 0.5 to 32 mm, with a geometric mean grain size of 7.3 mm and a D_{90} of 21.3 mm. Bed topography was captured using a camera-laser system

Table 1. Experimental details for PRE4

Experimental conditions during PRE4. (a) Photographs at elapsed time 960 and 1752 min, taken just downstream of the narrowest channel segment. The location of the installed plywood to narrow the channel from station 10.6–8.15 m is highlighted. Water supply of 5 L/s for image on left and 2 L/s for image on right. Compare these images with Fig. 6a of Chartrand et al. (2018). (b) Bed topography at elapsed time 960 min after reaching approximate transport steady-state. Red squares show locations where channel width and bed elevation were sampled to understand correlations between downstream width change and local bed slope. (c) Topographic profile for experimental conditions at elapsed time 960 min (thick black line), with the profile at 720 min shown for discussion (thin orange line). (d) Bed topography at elapsed time 1752 min after reaching approximate transport steady-state. The bank positions were adjusted from approximately station 10.6 to 8.15 m, denoted by the dashed red polygon. (e) Topographic profile for experimental conditions at elapsed time 1752 min (thick black line), with the profile at 1680 min shown for discussion (thin orange line). Water surface profiles were smoothed using a downstream windowed mean over a length scale of 0.5 m. Topographic profiles were spatially-averaged from digital elevation models for a centred cross-stream length scale of 0.160 m. Zero crossing lines calculated per Richards (1976). “P” and “R” indicate pool and riffle, respectively, with smaller font used for less pronounced topographic features.

PRE4 Phase	t_e	Q_w	Q_{ss}	\overline{Q}_{sf}	D'_g	D'_{90}	\bar{w}	DEM/Photo
(-)	(min)	($l s^{-1}$)	($kg min^{-1}$)	($kg min^{-1}$)	(-)	(-)	(m)	(-)
1	0	-	-	-	-	-	yes	
1	270	50	0.65	0.16	0.75	0.57	0.52	yes
1	480	50	0.65	0.13	0.85	0.65	0.52	yes
1	720	50	0.65	0.34	0.90	0.66	0.52	yes
1	960	50	0.65	0.57	0.80	0.65	0.52	yes
		Width	Reduction	Removed	Between	Phases		
2	1200	50	0.65	0.33	0.76	0.64	0.55	yes
2	1440	50	0.65	0.22	0.84	0.70	0.55	yes
2	1680	50	0.65	0.48	0.87	0.69	0.55	yes
2	1752	50	0.65	1.51	0.81	0.64	0.55	yes

a. t_e : the elapsed time, which indicates the end time for the specified interval.

b. At the elapsed times shown, upstream supplies were stopped, the flume drained and measurements made.

c. Q_w : water supply rate; Q_{ss} : sediment supply rate; \overline{Q}_{sf} : time-averaged sediment flux at flume outlet.

d. Grain size metrics are for the sediment flux at the flume outlet.

e. ' denotes normalized by sediment supply grain size.




Figure 3. Experimental conditions at approximate topographic steady-state times during PRE4 for Phases 1 and 2. (a) Photographs at elapsed time 960 and 1752 min, taken just downstream of the narrowest channel segment. The location of the installed plywood to narrow the channel from station 10.6-8.15 m is highlighted. Water supply of 5 l s^{-1} for image on left and 2 l s^{-1} for image on right. (b) Bed topography at elapsed time 960 min. Red squares show locations where channel width and bed elevation were sampled to understand correlations between downstream width change and local bed slope. (c) Topographic profile at elapsed time 960 min (thick black line), with the profile at 720 min shown for discussion (thin orange line). (d) Bed topography at elapsed time 1752 min. The bank positions were adjusted from station 10.6 to 8.15 m, denoted by the dashed red polygon. (e) Topographic profile at elapsed time 1752 min (thick black line), with the profile at 1680 min shown for discussion (thin orange line). Water surface profiles were smoothed using a downstream windowed mean over a length scale of 0.5 m. Topographic profiles were spatially-averaged from digital elevation models for a centred cross-stream length scale of 0.160 m. Zero crossing lines calculated per Richards (1976). "P" stands for pool, and "R" for riffle, with smaller font used for more subtle features.

135 with a resolution of 1 mm in the longitudinal, lateral and vertical planes. Width variations of the experimental flume provide a range of downstream ~~gradients~~ channel width gradients $\Delta w(x)$ ranging from (-0.26) to (+0.47) (Fig. 2c). The largest local width measured 0.758 m at station 9.960 m (during Phase 2) and the smallest width measured 0.37 m at station 8.150 m (both phases). The Phase 1 downstream width configuration had ~~an average a mean~~ width \bar{w} of 0.52 m, and the Phase 2 configuration 0.55 m.

140 ~~Experimental details for PRE4~~ PRE4 was carried out in two phases. The first phase Phase 1 of PRE4 was conducted with a width reduction in place, and the second with ~~the width reduction~~ it removed (Table 1 and Fig. 2). At the start of PRE4 Phase 1 we installed two pieces of plywood to connect bank positions from station 10.625 to 8.150 m ~~to produce a constant~~ producing a negative width gradient between these locations of (-0.06) ~~and~~ i.e. a gradual linear narrowing of the channel. The flume bed was then smoothed to a near-constant downstream bed slope of (+0.015). Next, we ran water flow at 50 L/s s⁻¹, and supplied
145 sediment at the approximate transport capacity and mass flow rate of 0.65 kg /min min⁻¹. The water flow rate scales as slightly higher than an assumed 2-year return period flood in East Creek.

Phase 1 was complete when approximate topographic steady-state was achieved at elapsed time \approx 960 min (compare orange and black profiles in Fig. 23c and see video in the online repository). At this stage the plywood pieces from station 10.625 to 8.150 m were carefully removed to minimize disturbance of the bed surface sediments and local topography, and sediment was
150 added to the regions that were located behind the plywood walls to match the local Phase 1 bed slope. We then started Phase 2 of PRE4 by resuming the same upstream water and sediment supply rates used during Phase 1. Phase 2 was carried out until approximate topographic steady-state was achieved at elapsed time \approx 1750 min (compare orange and black profiles in Fig. 23e and see video in the online repository). Measurements were made at several points during Phases 1 and 2 of the experiment: elapsed times 270, 480, 720, 960, 1200, 1440, 1680 and 1752 min (Table 1). To facilitate measurements the water and sediment
155 supplies were stopped, and the flume drained at the indicated times. In the discussion below we address a pool feature as the bed surface which occurs below the zero-crossing line, and a riffle feature that which occurs above (Richards, 1976) (Figs. 2e ~~and 2e4a and 4b~~). Different morphologic classification systems exist (e.g. Carling and Orr, 2000; Wyrick et al., 2014), but here we choose a basic definition to reflect that we ran analogue experiments to natural settings.

4 Results

160 4.1 Topographic Response to Changes in Width

Figure 2-3 shows images, digital elevation models and profiles of experimental conditions at the end of Phases 1 and 2 of PRE4. At the end of Phase 1 the bed topography of the experimental channel consisted of the following sequence of features from upstream to downstream: pool-riffle-pool-riffle-pool-riffle (Figs. 2b ~~and 23b and 3c~~). Riffle features during Phase 1 are co-located with zones of channel widening, and pool features with zones of channel narrowing (Figs. 2b ~~and 23b and 3c~~). The
165 downstream width gradients associated with these topographic features ranges from (-0.09)–(+0.47), narrowing and widening, respectively (Fig. 2c). The riffle-pool sequence from stations 13 to 7 m was the most prominent topographic feature of Phase 1 with a maximum elevation difference from riffle to pool of approximately ~~0.15~~ 0.07 m (Figs. 2a–2e 3b and 3c, and Fig. 4a), and




Figure 4. Detrended bed elevation profiles showing a zero-crossing line for Phases 1 and 2 of PRE4. (a) Bed elevation profile at t960 min, and (b) bed elevation profile at t1752 min, each calculated as width-averaged elevations at a resolution of 2 mm. Both profiles are fit with a zero-crossing line (Richards, 1976). The elevation profiles do not have a trend, and were sampled from the raw digital elevation models (see Chartrand et al. (2018) for more details regarding measurement methods for flume-bed elevations). Pool-like features are shown with blue shading below the zero-crossing line.

downstream width gradients of (+0.07) and (-0.06), respectively (Fig. 2c). This riffle-pool unit is illustrated in the left image of Fig. 2a. The 3a. Differences relative to the zero-crossing line indicates indicate that the riffle had a maximum amplitude of approximately (+0.250.024) m which occurred at station 12.6 m, whereas the pool had a maximum amplitude of (-0.3-0.045) m which occurred at station 8.3 m (Fig. 2e4a). An additional riffle feature was observed with its crest near station 3.7 m, with a maximum amplitude of (+0.250.025) m. Less pronounced pool features formed at two other locations centred around stations 15.0 and 4.1 m.

At the end of Phase 2 the bed topography consisted of the following sequence of features from upstream to downstream: pool-riffle-riffle-pool-riffle (Figs. 2d and 23d and 3e). As with Phase 1, riffle and pool features during Phase 2 are collocated with zones of widening and narrowing, respectively, for width gradients ranging from (-0.26)–(+0.47) (Fig. 2c). The riffle-pool unit from stations 10.8 to 7 m was the most prominent topographic feature of Phase 2 with a maximum elevation difference from riffle to pool of approximately 0.11-0.07 m (Figs. 2d-2e3d and 3e, and Fig. 4a), and downstream width gradients of (+0.35) and (-0.26), respectively (Fig. 2c). This riffle-pool unit is illustrated in the right image of Fig. 2a. The 3a. Differences relative to the zero-crossing line indicates indicate that the riffle had a maximum amplitude of approximately (+0.350.035) m which occurred at stations 9.7 to 10 m, whereas the pool had a maximum amplitude of (-0.2-0.037) m which occurred at station 7.8 m (Fig. 2e4b). As with Phase 1, an additional riffle feature was observed with its crest near station 3.7 m, with a maximum amplitude of (+0.200.02) m, and an additional riffle is observed centered-centred around station 12 m. This feature has a maximum amplitude of (+0.10)-m-0.021) m (Fig. 4a). Two additional pool features formed at locations centred around stations 15.0 and 4.1 m.




Figure 5. Bed elevation and profile changes after the width reduction was removed. (a) DEM of difference between t960 and t1200 min. The width profile for t960 used to show elevation differences because it was narrower within the central part of the flume compared to t1200 min. Width profile following t960 min shown with the light gray lines. (b) Trended mean channel bed profiles for t960, t1200, t1440, t1680 and t1752 min. Dashed red box lines up with region where the width reduction was removed following t960 min. Profiles calculated as width-averaged conditions with a resolution of 0.002 m.

Local average bed slope $S_{local}(x)$ as a function of the downstream change to channel width $\Delta w(x)$ for PRE4, and a wide range of additional field, numerical and experimental studies. **Present experiment:**—Phase 1 PRE4, and—Phase 2 PRE4 at locations where channel width is adjusted during the experiment;—Phase 1 PRE4, and—Phase 2 PRE4 at locations where width remains unchanged during the experiment;—Result from Chartrand et al. (2018) comparable to PRE4 for the same downstream width change gradient. **Literature-based data sets:**—Chartrand et al. (2018) which includes data from Thompson et al. (1999) field, de Almeida and Rodríguez (2012) numerical, Bolla Pittaluga et al. (2014) numerical and Nelson et al. (2015) experiment;—Includes data from Richards (1976) field, Cao et al. (2003) numerical and Vahidi et al. (2020) experiment; Red triangles include data from Brew et al. (2015) field;—For the period before the Elwha and Glines Canyon Dams were removed on the Elwha River,—Following removal of the Elwha Dam, and all but 30 feet of the Glines Canyon Dam, in the spring prior to the freshet floods, and—In the late summer after the freshet floods, and with the remaining 30 feet of Glines Canyon Dam still in place. See Appendix A for more details regarding the literature-based data sets. Plotted lines represent the centre of a distribution of predicted values using Eq. 1 for differing values of the packing fraction ϵ (see Chartrand et al., 2022, <https://figshare.com/s/87632500284009e3330f>). Distribution of predicted values shown with hatching for $\epsilon=0.40$. Figure 5 shows a DEM of Difference (DoD) between elapsed times 960 and 1200 min, and width-averaged channel bed elevation profiles for elapsed times 960, 1200, 1440, 1680 and 1752 min. Following removal of the width reduction at t960 min, bed elevation conditions adjusted through deposition focused within the central part of the flume where the width reduction was

removed (Fig. 3 and Figs 5a and 5b). Over the course of 240 min following elapsed time t960 min, a width averaged depth of 0 to 0.06 m of sediment was deposited between stations 10.6 to 8.1 m, with maximum deposition depths centred around stations 9.9 and 9.1 m (Fig. 5b). At the resolution of the underlying DEMs, deposition was spatially variable over the central region and tapers off in the upstream and downstream directions (Fig. 5a). Outside of the region between stations 10.6 to 8.1 m, bed elevation profiles are comparable prior to, and after the width reduction was removed. Furthermore, following elapsed time t1200 min, adjustment of the elevation profile was relatively minor with width averaged differences ranging from 0.004 to 0.007 m (Fig. 5b), or smaller than the geometric mean grain size.

4.2 Covariation of Width Change and Local Bed Slope

Figure 3-6 shows how local bed slopes vary according to associated downstream width ~~change conditions~~ gradients, and has four quadrants that describe the correlation between $S_{local}(x)$ and $\Delta w(x)$. The upper left and lower right quadrants mark inverse correlations, whereas the upper right and lower left describe direct correlations. Phase 1 and 2 results of PRE4 are broken down into two separate categories for plotting: (1) sites at which the width gradient changes between Phases 1 and 2, and (2) sites at which the width ~~change~~-gradient is fixed for both phases of PRE4.

Local bed slope and width ~~conditions~~ gradients for both phases of PRE4 are consistent with expectations of an inverse correlation between ~~$S_{local}(x)$ and $\Delta w(x)$~~ and $S_{local}(x)$ of Eq. 1. At locations where the width gradient changes during the experiment, the Phase 1 steady-state topographic conditions converge at $\Delta w(x) = (-0.06)$, and $S_{local}(x)$ ranges from $(+0.026)$ to $(+0.035)$. Following adjustment of the downstream width gradients at the start of Phase 2 (Fig. 2ec), the Phase 1 steady-state topographic conditions evolve according to the prescribed width changes: $\Delta w(x) = (-0.26)$ and $S_{local}(x) = (+0.49)$, $\Delta w(x) = (-0.19)$ and $S_{local}(x) = (+0.27)$, and $\Delta w(x) = (+0.35)$ and $S_{local}(x) = (-0.01)$. At locations where the width gradients were fixed over the duration of PRE4, the Phase 1 and 2 bed slopes are similar. For example, Stations 4–3.5 m at steady-state $S_{local}(x) = (-0.23)$ for Phase 1, and (-0.21) for Phase 2 (Fig. 36). The trend of local bed slopes for PRE4 across the ~~width change~~ downstream width gradient parameter space corresponds to the scaling theory (Eq. 1) before and following the width ~~adjustments~~ changes (Fig. 23). More generally, the scaling theory projects a non-linear slope response for downstream ~~changes to width~~ width gradients, with a tendency toward flat segments of bed at ~~$\Delta(x) \sim \Delta w(x) \sim (+0.10)$~~ . For width ~~changes~~ gradients away from this transition point, projections of local bed slope are increasingly positive and negative, for narrowing and widening channel segments, respectively, and correlates with the bed packing condition ε .

Data sets from published field studies, numerical and analog experiments generally agree with expectations of an inverse correlation between $S_{local}(x)$ and $\Delta w(x)$ ($n=88$). On the basis of Eq. 1, data for natural rivers with reported downstream width variations includes the river Fowey, Cornwall, UK (Richards, 1976), North Saint Vrain Creek, CO, USA (Thompson et al., 1999) and the Elwha River, WA, USA (Brew et al., 2015). Data for numerical experiments with downstream width variations includes de Almeida and Rodríguez (2012), Bolla Pittaluga et al. (2014) and Cao et al. (2003). Data for analog experiments with downstream width variations includes Nelson et al. (2015), Chartrand et al. (2018) and Vahidi et al. (2020). A few studies merit specific mention. Bed slope responses for PRE4 show strong agreement with prior experimental results completed with the same set-up, but for which the downstream sequence of channel width was fixed (Chartrand et al., 2018).




Figure 6. Local average bed slope $S_{local}(x)$ as a function of the downstream channel width gradient $\Delta w(x)$ for PRE4, and a wide range of additional field, numerical and experimental studies. **Present experiment:** \blacklozenge –Phase 1 PRE4, and \bullet –Phase 2 PRE4 at locations where channel width is adjusted during the experiment; \blacklozenge –Phase 1 PRE4, and \bullet –Phase 2 PRE4 at locations where width remains unchanged during the experiment; \bullet –Result from Chartrand et al. (2018) comparable to PRE4 for the same downstream width gradient. **Literature-based data sets:** \bullet –Chartrand et al. (2018) which includes data from Thompson et al. (1999) [field], de Almeida and Rodríguez (2012) [numerical], Bolla Pittaluga et al. (2014) [numerical] and Nelson et al. (2015) [experiment]; \square –Includes data from Richards (1976) [field], Cao et al. (2003) [numerical] and Vahidi et al. (2020) [experiment]; Red triangles include data from Brew et al. (2015) [field]; \blacktriangleleft –For the period before the Elwha and Glines Canyon Dams were removed on the Elwha River, \blacktriangle –Following removal of the Elwha Dam, and all but 30 feet of the Glines Canyon Dam, in the spring prior to the freshet floods, and \blacktriangleright –In the late summer after the freshet floods, and with the remaining 30 feet of Glines Canyon Dam still in place. See Appendix A for more details regarding the literature-based data sets \square . Plotted lines represent the centre of a distribution of predicted values using Eq. 1 for differing values of the packing fraction ε . See Appendix A and the online repository (Chartrand et al., 2022) for calculation procedure of Eq. 1. Distribution of predicted values shown with hatching for $\phi=0.40$.

In particular, PRE4 local steady-state bed slopes following [the prescribed](#) width changes are consistent with prior outcomes for the same downstream width gradients, and are also consistent at locations where width gradients were unchanged for the duration of the experiments, for example, at Stations 4–3.5 m (Fig. 36). Results of monitoring downstream bed elevation conditions before and during removal of the Elwha and Glines Canyon dams on the Elwha River show a range of local bed

240 slope responses. Before dam removals $S_{local}(x)$ and $\Delta w(x)$ were inversely correlated (July 20, 2011). After removal of the Elwha dam and during staged removal of the Glines Canyon dam, $S_{local}(x)$ and $\Delta w(x)$ were directly correlated at three of six sites (May 2013) following the first winter runoff season. Several months later and following the first summer snowmelt runoff season $S_{local}(x)$ and $\Delta w(x)$ were inversely correlated at four of six sites (Fig. 36) (August 2013).

5 Discussion and Applications to Natural Rivers

245 Our scaling theory makes explicit predictions for local $S_{local}(x)$ and $\Delta w(x)$ conditions favouring the deposition of material to the bed to form riffles ($\Delta w(x) \rightsquigarrow > 0.10 \Delta w(x) \rightsquigarrow > 0.10$), the erosion of material from the bed to form pools ($\Delta w(x) \rightsquigarrow < -0.10 \Delta w(x) \rightsquigarrow < -0.10$) and intermediate regimes where both processes occur in concert ($\Delta w(x) \Rightarrow 0 \Delta w(x) \Rightarrow 0$) (Fig. 36). Accordingly, here we discuss the primary implications of our combined results and theoretical expectations for natural rivers, including the importance of local width conditions as well as transient watershed processes that can contribute to time varying bed slope responses.

250 The PRE4 experimental channel exhibits distinct topographic patterns between Phases 1 and 2 that are correlated to the specific downstream patterns of channel width change-variation (Figs. 2 and 33, 4 and 6). During Phase 1 the upper and central portion of the experimental channel from Stations 14–7 m included a zone of expansion followed by a relatively long zone of narrowing. This downstream organization of channel width led to development of a prominent pool-riffle-pool topographic response. Despite the moderate width gradient (-0.06), the pool feature had the largest associated amplitude of the experiment,

255 (-0.30-0.045) m, according to the zero-crossing line method (Richards, 1976). During Phase 2 the width was adjusted from Stations 10.6 to 8.1 m to include an abrupt zone of widening (+0.35) and then narrowing (-0.19 and -0.26). This change led to development of a prominent riffle-pool sequence, whereas in Phase 1 this region was occupied by a riffle tail transitioning to a pool. The Phase 2 zone of widening resulted in a riffle with the largest overall amplitude of the experiment, (+0.35) m, and the pool had a marginally smaller amplitude compared to the Phase 1 pool of the same location, (-0.20-0.035) m.

260 These results are important because they demonstrate that topographic responses within variable-width channel segments are strongly controlled by the quantitative character of width change (Richards, 1976; Cao et al., 2003; MacWilliams et al., 2006; de Almeida et al., 2018; Richards, 1976; Cao et al., 2003; MacWilliams et al., 2006; de Almeida and Rodríguez, 2012; Nelson et al., 2015; Chartrand et al., 2018). More specifically, results for our geometrically simple experimental set-ups, as well as that for literature-based data sets of Fig. 3-6 (see Appendix AB) indicate that inflections in the profile curvature are generally locked with associated points or regions of

265 width-change-where the width gradient changes direction (Fig. 23): high points (riffles) along a profile are commonly aligned near to places where a widening segment changes to a narrowing one, and low points (pools) near to places where a narrowing segment changes to a widening one. This outcome is explained by the scaling theory Eq. 1 as width-regulated feedbacks of local hydrodynamics and momentum exchange between the flow and the bed (Furbish et al., 1998), and consequently bed load sediment transport, depending on the grain size composition of the upstream sediment supply and the local bed packing

270 state (also see Cao et al., 2003; Wilkinson et al., 2004; Bolla Pittaluga et al., 2014; Ferrer-Boix et al., 2016; Chartrand et al., 2018, 2019).

The spatial correlation between ~~local bed slope and width change conditions reported here~~ the local channel width gradient and bed slope includes comparatively more nuanced information which is ~~equally important~~ important and merits discussion. For example, although a local width minimum at Station 8.15 m did not change between Phases 1 and 2, the zone of maximum depth in the associated pool feature shifted its relative position. During Phase 1 the point of maximum amplitude in the pool occurred upstream of the location of minimum width at Station 8.2 m, whereas it occurred downstream of it during Phase 2 at Station 7.8 m (Figs. 3 and 4). This result highlights that differing downstream configurations of width change can influence subtle aspects of pool morphology and dynamics (Carling and Wood, 1994; Thompson et al., 1998; Cao et al., 2003; Wilkinson et al., 2004; Thompson and McCarrick, 2010). Furthermore, a novelty of the topographic adjustments observed for PRE4 is the demonstration that simple manipulations of experimental width conditions for steady upstream supplies of water and sediment can yield a surprisingly diverse set of responses, which are consistent with expectations of the scaling theory (Fig. 36). However, unsteady upstream supplies of water and sediment ~~can produce an even greater range of also~~ yield relatively large pool-riffle topographic responses (e.g. Brew et al., 2015; Vahidi et al., 2020; Morgan and Nelson, 2021) (e.g. Lisle and Hilton, 1992; Brew et al., 2015; East et al., 2015; Vahidi et al., 2020; Morgan and Nelson, 2021), including lateral channel shifting and re-activation due to pool filling, etc. (e.g. East et al., 2015) and reduction of topographic (bar-pool) amplitude (Morgan and Nelson, 2021). The critical take away here is that local channel width conditions matter ~~, and provide~~ (Nelson et al., 2015; Brown and Pasternack, 2017; Chartrand et al., 2018), the context of which provides a rich understanding ~~of for~~ general topographic and bed architecture conditions within gravel-bed rivers. Similar importance is also attributed to downstream variations of valley width in relation to the longitudinal profile of riffle-pool river segments (Sawyer et al., 2010; White et al., 2010). Accordingly, explicit or implicit spatial averaging of channel and bed architecture geometry over distances that are greater than that describing local width ~~changes variations~~ can mask the correlations demonstrated here (Fig. 36). For example, consider the Phases 1 and 2 flume-wide average channel widths of 0.52 and 0.55 m, respectively. Averaging the bed profiles of Fig. 2-3 over the flume length yields slopes of 0.014 and 0.014, respectively. Consequently, ~~similar average widths yield similar bed slopes identical bed slopes occur for similar flume-wide average channel width conditions and the same upstream water and sediment supplies~~, demonstrating a loss of information relative to the results presented here (Byrne et al., 2021).

A range of factors or processes not easily captured by the present scaling theory (Eq. 1) are relevant to setting the time-dependent local bed slope, and are therefore important ~~to for~~ understanding gravel-bed river channel morphology. Specifically, factors that contribute to, and may potentially overprint ~~width change driven pool-riffle slope variations width variation driven downstream bed slope differences~~ include effects of the stochastic nature of bed load transport (e.g. Furbish and Doane, 2021) (e.g. Furbish and Doane, 2021; Hassan et al., 2022), which make explicit "local" definitions of the flow time scale t_f and the bed adjustment time scale t_y challenging ~~, including~~. However, Eqs. 2 and 4 indicate that the local bed slope at or near steady-state is set by how the coarse fraction of the bed surface compares to the bed packing fraction, width and shear velocity, and in turn how, through Λ , these quantities compare to the dimensionless downstream velocity change. The key here is that if all of any of these quantities show change for a relatively long period of time (e.g. $\gg t_y$ or t_f), for example, due to a disturbance in the upstream sediment supply, it is likely that the steady-state bed slope as a result of this change will differ from the pre-disturbance condition. Figure 6 suggests that as long as the local width variation condition does change appreciable, the

pre- and post-disturbance bed slopes will be comparable, and have an inverse correlation with $\Delta w(x)$. Second, identification of appropriate response scales for pool-riffle gravel-bed rivers are made complicated if time-dependent variations in the upstream supply of sediment (Dolan et al., 1978; Lisle and Hilton, 1992, 1999; de Almeida and Rodríguez, 2011; Brew et al., 2015; Vahidi et al., 2020; Morgan and Nelson, 2021) and water (Brew et al., 2015; Nelson et al., 2015; Morgan and Nelson, 2021, and see discussions) occur over time scales comparable to that associated with achieving steady-state topographic conditions, because river segments are continually responding to upstream disturbances (Ferrer-Boix and Hassan, 2014). Last, strong transient variations of local bed surface sediment texture (Dolan et al., 1978; Lisle, 1986) and bank material composition over length scales $< \bar{w}$ (Wolman, 1955; Richards, 1976), or landsliding within river segments where valley wall processes are coupled to the channel (Whiting and Bradley, 1993; Hassan et al., 2019) can lead to new local channel widths and bed topographic responses where the latter is decoupled from the former. In particular, the influence of upstream sediment supply to local bed topographic responses has been studied extensively in the field and ~~the~~ laboratory, and may be a primary factor that influences the correlation between ~~local bed slope and downstream width change~~ the local downstream width gradient and bed slope (Fig. 3-6) (see helpful discussions in East et al., 2015; Morgan and Nelson, 2021).

320 Previously it was unclear whether pool-riffles express direct correlations between ~~$(S_{local}(x))$ and $(\Delta w(x))$~~ $\Delta w(x)$ and $S_{local}(x)$ —i.e. the upper right and lower-left quadrants of Fig. 3 ~~(Chartrand et al., 2018, also see Brown and Pasternack, 2017 and note that t~~ 6 (Chartrand et al., 2018, also see Brown and Pasternack, 2017 and note that their covariance convention differs in sign to the width gradient. Field-based observations prior to, and following substantial removal of the Elwha and Glines Canyon Dams on the Elwha River, WA, U.S.A. suggest that an increase in the upstream supply of bed load sediment (see East et al., 2015) without a

325 substantial local adjustment to the downstream pattern of ~~width change~~ channel width is sufficient for pool-riffle segments to have a relatively ~~and generally~~ short-lived, site-specific direct correlation between ~~local bed slope and the downstream width change condition~~ the local downstream width gradient and bed slope (Fig. 36) (see Fig. 5 of Brew et al., 2015). For example, ~~this circumstance is demonstrated for a riffle with~~ prior to dam removal a riffle located between stations 50,500–50,000 ft (from the river mouth) had a local width gradient $\Delta w(x)=(+0.137)$, which has an inverse correlation prior to dam removal

330 with and a local bed slope $S_{local}=(-0.003)$. Following removal of the Elwha and most of the Glines Canyon Dam, the spring freshet transported an increased bed load sediment supply to the reach, resulting in ~~local deposition and development of a direct correlation with a changed local bed slope of $S_{local}=+0.008$, and a site-specific direct correlation with the width gradient—i.e. upper right quadrant of Fig. 6 with $+\Delta w(x)$, $+S_{local}(x)$~~ . Following completion of the spring freshet and summer storm season, ~~an a site-specific~~ inverse correlation was re-established with $S_{local}=(-0.001)$. A similar trend is observed

335 for a riffle with $\Delta w(x)=(+0.151)$ located between stations 51, however 488–50,935 ft. However, S_{local} does not quite reach negative, or downstream adverse slope conditions following the spring freshet and summer storm season. On the other hand, a pool with $\Delta w(x)=(-0.25)$ located between stations 50,935–50,950 ft shows a significant response to the dam removal, but does not quite express a site-specific direct correlation. Prior to dam removal and following the spring freshet and summer storm season $S_{local} \sim S_{local} \sim (+0.018)$. During the spring freshet the local bed slope decreases considerably due to pool filling

340 through sediment deposition and has an approximately flat downstream profile. At the end of the runoff season local bed slope has recovered to near pre-dam removal conditions with $S_{local} \sim S_{local} \sim (+0.016)$. These results highlight that the observa-

tions of ~~Brew et al. (2015)~~ [Brew et al. \(2015\)](#); [East et al. \(2015\)](#) and also the numerical and physical experiments of Cao et al. (2003); Wilkinson et al. (2004); MacWilliams et al. (2006); de Almeida and Rodríguez (2011, 2012); Vahidi et al. (2020) and Morgan and Nelson (2021) are important because they provide evidence that pool-riffle river segments can exhibit a broad and dynamic range of conditions between downstream ~~changes of channel width~~ [channel width gradients](#) and bed topography depending on the upstream supplies of water and sediment. In particular, the Elwha River data set suggests it is possible for pool-riffles to ~~have a~~ [exhibit a relatively short-lived](#) direct correlation between ~~local bed slope and channel width change~~ [\$\Delta w\(x\)\$ and \$S_{local}\(x\)\$](#) (see Brown and Pasternack, 2017, for more discussion of direct correlations), presenting an opportunity to more carefully examine the role of upstream sediment supply in setting the local bed slope in relation to downstream width variations ([Morgan and Nelson, 2021](#)), which are understood here through the scaling theory Eq. 1. Adaptations of the scaling theory may likely require the direct incorporation of upstream sediment supply relative to the estimated steady-state transport capacity, with perhaps dependence on u_* and D_{90f} .

6 Concluding Remarks

An important result of our work is that local bed topography responds to temporal changes in downstream patterns of channel width in a manner consistent with a wide range of field-based, numerical and experimental data (n=88) understood through scaling theory. River segments that exhibit riffles, or locations of net deposition in association with increasing river widths can flip, and express pools, or locations of net erosion, if the width configuration changes to a narrowing condition, and vice versa. This inverse correlation between ~~local bed slope and downstream width change~~ [the local downstream width gradient and bed slope](#) can be disturbed over relatively short time scales due to increases in the upstream supply of bed load sediment associated with dam removal. A critical implication of these results is that what matters it is not simply that width ~~changes~~ [varies along a river reach](#). Topographic responses are strongly conditioned by *how* width specifically ~~changes~~ [varies](#), and in particular the magnitude of width ~~change~~ [variation](#) relative to the length scale over which ~~change occurs~~ [differences occur](#). This means that local conditions at the scale of the channel width are important to understanding the ~~dynamical behavior~~ [topographic structure](#) of gravel-bed mountain rivers. A key uncertainty of our work is identification of suitable local scales for the flow and channel topographic response during periods of transience such as, for example, following the removal of upstream dams. The associated impulsive release of coarse sediment to downstream reaches can overwhelm the local average properties of coupling between the flow and downstream width variations, leading to decoupled local bed slope responses. We believe a more informed ~~persepective~~ [perspective](#) on this topic guided by theory can aid in ongoing and future environmental planning efforts which emphasize identification of how rivers may respond and adjust to altered processes as a result of infrastructure decisions and, importantly, climate change. This position in turn will benefit identification of natural resource protection and river restoration strategies that anticipate future river dynamics, and therefore can provide for more resilient river corridors.

Code and data availability. Appendix B and an online repository (discussed below) contain the data for Richards (1976), Cao et al. (2003), Brew et al. (2015) and Vahidi et al. (2020) plotted in Fig. 6. Other literature-based data shown in Fig. 6 is published with Chartrand et al. (2018) and Chartrand et al. (2017), but has also been included in an online repository. Additionally, the online repository contains the topographic, elevation and water surface profiles plotted in Fig. 3, and all of the data as well as the calculation procedure used to develop Fig. 6. The calculations are contained within a Python Jupyter Notebook. The online repository is presently set as private. However, for peer review it can be accessed at: <https://figshare.com/s/87632500284009e3330f>. Following peer review and publication the repository will be made public with the following Digital Object Identifier: 10.6084/m9.figshare.20152235. At that time we will prepare a ReadMe.txt set of instructions for use of the data and script contained within the online repository.

Video supplement. Two videos of experimental channel conditions at elapsed times 960 and 1752 min are provided in the online repository mentioned in the code and data availability section.

Appendix A: ~~Content of Appendices~~ Calculation Procedure for Fig. 6

~~The appendices here~~ In Fig. 6 of the main text we show three curves and one stippled region calculated using Eq. 1. The code used to complete the calculations and produce the figure are contained within an online repository accessible with the following Digital Object Identifier: 10.6084/m9.figshare.20152235. To augment the code posted at the online repository, and to motivate future use and advancement of the numerical work presented, below we provide a brief overview of how the curves and stippled region of Fig. 6 are calculated, beginning with the core assumption underlying our numerical approach. The assumption is supported by prior experimental measurements based on the same flume set-up reported here (Chartrand et al., 2018), and for six different topographic steady-state conditions grouped under three different categories of water flow—42, 60 and 80 l s⁻¹. Whereas the scaling expression Eq. 1 shows good agreement with the various experimental, numerical and field-based conditions reported here (Fig. 6), the assumption should be more fully examined with future experimental and numerical analysis.

There are two challenges in expressing Eq. 1 within the context of $\Delta w(x)$ (Fig. 6). First, providing estimates for how the random variables \bar{d} (local width-averaged water depth), S (local water surface slope), \bar{U}_x (local width-averaged flow velocity) and u_* (local shear velocity) vary for given local w (width) conditions. Second, understanding how the combined effect of these same parameters represented by Eq. 1 are distributed across different downstream width gradients $\Delta w(x)$. We address these challenges by using applicable and prior experimental results to provide plausible estimates for the random variables, as well as how each may vary over $\Delta w(x)$ given a specific set of downstream width configurations and experimental conditions.

The core assumption we make is that \bar{d} , S , \bar{U}_x (and the gradient of local width-averaged flow velocities) and u_* each vary inversely with the local width, as well as the downstream width gradient (see Figs. 13 and S2 of Chartrand et al., 2018 and Fig. 10 of Furbish et al., 1998). For example, we assume that the local water depth is deeper where width is relatively narrow, or narrowing, compared to locations where width is relatively wide, or widening. Based on the prior experimental results this assumption is reasonable. However, the relationship between the downstream dimensionless velocity change $\Delta \bar{U}_x^*$ and width

change $\Delta w(x)$ shows considerable uncertainty for relatively small positive values of the downstream width gradient (see Fig. 13 of Chartrand et al., 2018)

All calculations for Eq. 1 are as shown in Fig. 6 are done for the three different flow rates mentioned above—42, 60 and 80 $l s^{-1}$. Then, results for \bar{d} and \bar{U}_x are used to calculate the downstream dimensionless velocity Eq. 4, \bar{U}_x^* , and the downstream dimensionless velocity change Eq. 3, $\Delta \bar{U}_x^*$ (Steps 3c–3e of the Jupyter Notebook in the online repository). Results for \bar{d} and S are used to calculate the local shear velocity u_* , defined as $(g\bar{d}S)^{0.5}$ (Step 3h of the Jupyter Notebook in the online repository). With these calculation steps completed we have the data needed to evaluate Eq. 1 by calculating the lambda parameter, and then using these results along with the downstream dimensionless velocity change outcomes to calculate the local channel bed slope S_{local} (Steps 3i and 3j of the Jupyter Notebook in the online repository).

At each of the above steps we calculate minimum, average and maximum values based on the distribution of underlying parameter values for each experimental flow rate (22 values for each parameter and flow rate given 11 different downstream width configurations). The stippled region shown in Fig. 6 is based on the estimated maximum and minimum bounding curves across all three flow rates for a bed porosity of $\phi=0.40$. These curves are found by fitting polynomials to the estimated and interpolated distribution of S_{local} values using Eq. 1, for all steady-state topographic and water flow conditions, given the associated downstream width gradients (Step 3k of the Jupyter Notebook in the online repository). Use of polynomials was done to extend the experimental observations from $\Delta w(x)=(-0.30:+0.45)$ to $\Delta w(x)=(-0.55:+0.65)$, using a step size of 0.01 $\Delta w(x)$. The solid, dashed and dashed-dotted curves represent the average S_{local} conditions between the estimated maximum and minimum bounding curves for bed porosity's of $\phi=0.30, 0.40$ and 0.50 and the three water flow rates.

Appendix B: Literature Data Sets

Below we provide data derived from the literature that is included within Figure 3-Fig. 6 of the main article, and which was not published as a part of prior work (Chartrand et al., 2018). Relevant figures from the literature were loaded into PlotDigitizer (©pOrbital 2022) and data was extracted after setting the scale of the axes and by placing points at locations associated with width directional change. If there was uncertainty regarding correspondence between width direction change and the bed elevation profile, point placement was guided by locations where the profile changed direction. Data was then exported to a text file and plotted using a Python-based script to produce Fig. 3-6. Below we provide screenshots (Figures S1-S5B1-B5) from PlotDigitizer for data derived from Richards (1976), Cao et al. (2003), Brew et al. (2015) and Vahidi et al. (2020). We also provide the resulting data in table form (Tables S1-S5B1-B5). The data shown in the tables below is also contained within an online repository along with the Fig. 3-6 plotting script that will be made public after publication with the following Digital Object Identifier: 10.6084/m9.figshare.20152235.

Appendix B: Richards, 1976, Figure Fig. 3




Figure 3. Bed profile and width series; reach 1, upper river Fowey.

Figure Appendix B.: Modified [Figure Fig. 3](#) of Richards (1976) showing the locations of channel width and elevation profile measurements indicated by the open circles. The width series is at the top of the image and the elevation profile series is at the bottom. Units are meters. Flow is right to left in the image.

B.2 Richards, 1976, [Figure Fig. 4](#)

Table Appendix B.: Measurement details for [Figure-Fig. 3](#) of Richards (1976)

Key (number) (-)	Station (m)	Width (m)	BE (m)	$\Delta w(x)$ (-)	$S_{local}(x)$ (-)
1	91.10	5.74	1.78	-0.298	0.054
2	87.09	4.55	1.56	-	-
2	87.09	4.55	1.56	0.186	-0.014
3	78.20	6.20	1.69	-	-
3	78.20	6.20	1.69	-0.328	0.038
4	72.27	4.25	1.46	-	-
4	72.27	4.25	1.46	0.182	-0.021
5	67.18	5.18	1.57	-	-
6	64.73	5.84	1.45	-0.225	0.035
7	57.55	4.22	1.19	-	-
7	57.55	4.22	1.19	0.106	-0.012
8	46.70	5.37	1.32	-	-
9	31.64	4.75	1.19	0.264	-0.036
10	24.27	6.69	1.45	-	-
10	24.27	6.69	1.45	-0.204	0.035
11	15.00	4.80	1.13	-	-

a. Key begins with first measurement point at upstream end of Fig. 1.

b. BE: Bed Elevation.

Table B.2. Measurement details for [Figure-Fig. 4](#) of Richards (1976)

Key (number) (-)	Station (m)	Width (m)	BE (m)	$\Delta w(x)$ (-)	$S_{local}(x)$ (-)
1	77.80	5.94	0.62	-0.238	0.035
2	71.83	4.52	0.41	-	-
2	71.83	4.52	0.41	0.169	-0.021
3	66.10	5.49	0.53	-	-
3	55.00	6.15	0.38	-0.109	0.009
4	44.13	4.96	0.28	-	-
4	44.13	4.96	0.28	0.073	-0.020
5	26.63	6.23	0.63	-	-
5	26.63	6.23	0.63	-0.085	0.015
6	6.35	4.50	0.32	-	-

a. Key begins with first measurement point at upstream end of Fig. 3.

b. BE: Bed Elevation.




Figure B.2. Modified Figure-Fig. 4 of Richards (1976) showing the locations of channel width and elevation profile measurements indicated by the open circles. The width series is at the top of the image and the elevation profile series is at the bottom. Units are meters. Flow is right to left in the image.

Table B.3. Measurement details for Figure-Fig. 4 of Cao et al. (2003)

Key (number)	Station	Width	BE	$\Delta w(x)$	$S_{local}(x)$
(-)	(m)	(m)	(m)	(-)	(-)
1	148.09	6.8	-3.56	0.176	-0.008
2	100.59	15.2	-3.19	-	-
2	100.59	15.2	-3.19	-0.119	0.012
3	36.57	7.5	-3.96	-	-
3	36.57	7.5	-3.96	0.040	0.003
4	0.56	9.0	-4.08	-	-

- a. Key begins with first measurement point at upstream end of Fig. 6.
b. Channel stationing was flipped to have zero at the downstream end.
c. BE: Bed Elevation.

B.4 Brew et al., 2015, Figure-Fig. 5




Figure B.3. Modified Figures 4 (top) and 3 (bottom) of Cao et al. (2003) showing the locations of channel width and elevation profile measurements indicated by the open circles. The bed elevation series is at the top of the image and the width series is at the bottom. Here channel width was measured as the distance in between the points at the two bounding edge positions at a given channel station. Units are meters. Flow is left to right in the image.

Table B.4. Measurement details for [Figure Fig. 5](#) of Brew et al. (2015)

Key (number)	Station	Width	BE	BE	BE	$\Delta w(x)$	$S_{local}(x)$	$S_{local}(x)$	$S_{local}(x)$
(-)	(m)	(m)	(m)	(-)	(-)	(-)	(-)	(-)	(-)
1	52791	187	267.1	269.9	269.9	-0.203	0.017	0.007	0.012
2	52560	140	263.2	268.3	267.1	-	-	-	-
2	52560	140	263.2	268.3	267.1	0.374	-0.005	0.003	0.003
3	52196	276	264.9	267.2	265.9	-	-	-	-
3	52196	276	264.9	267.2	265.9	-0.200	0.016	0.011	0.011
4	51626	111	253.8	259.4	258.3	-	-	-	-
4	51488	134	253.8	259.4	258.3	0.151	-0.001	0.007	0.001
5	50935	218	254.5	255.5	255.1	-	-	-	-
5	50935	218	254.5	255.5	255.1	-0.253	0.018	0.0	0.016
6	50590	131	248.2	255.5	249.6	-	-	-	-
6	50590	130	248.2	255.5	249.6	0.137	-0.003	0.008	-0.001
7	50002	211	249.9	250.7	250.2	-	-	-	-

a. Key begins with first measurement point at upstream end of Fig. 4.

b. BE: Bed Elevation.

c. Bed Elevation and $S_{local}(x)$ ordered column-wise: July 2011, May 2013, August 2013.




Figure B.4. Modified [Figure Fig. 5](#) of Brew et al. (2015) showing the locations of channel width and elevation profile measurements indicated by the open circles. Width measurements are approximate averages of the three series shown. Elevation measurements were made for each profile by shifting the indicated points straight down to the next profile line below the top one (orange). Units are [meters](#)[feet](#). Flow is right to left in the image.

B.5 Vahidi et al., 2020, [Figure Fig. 3](#)

Table B.5. Measurement details for [Figure Fig. 5](#) of Vahidi et al. (2020)

Key (number)	Station	Width	BE	BE	$\Delta w(x)$	$S_{local}(x)$	$S_{local}(x)$
(-)	(m)	(m)	(m)	(-)	(-)	(-)	(-)
1	9.5	0.64	2.22	2.22	0.000	0.002	0.001
2	7.5	0.64	2.22	2.21	-	-	-
2	7.5	0.64	2.22	2.21	-0.126	0.023	0.021
3	5.6	0.4	2.17	2.17	-	-	-
3	5.6	0.4	2.17	2.17	0.150	-0.023	-0.023
4	4.0	0.64	2.21	2.21	-	-	-
4	4.0	0.64	2.21	2.21	0.000	0.006	0.004
5	2.0	0.64	2.20	2.20	-	-	-
5	2.0	0.64	2.20	2.20	-0.12	0.035	0.014
6	0.0	0.4	2.13	2.17	-	-	-

- Key begins with first measurement point at upstream end of Fig. 5.
- Channel stationing was flipped to have zero at the downstream end.
- BE: Bed Elevation.
- Bed Elevation and $S_{local}(x)$ ordered column-wise: Experiment 1, Experiment 4.




Figure B.5. Modified [Figure Fig. 5](#) of Vahidi et al. (2020) showing the locations of channel width and elevation profile measurements indicated by the open circles. The elevation profile series is at the top of the image. Width measurements were taken from [Figure Fig. 1](#) of Vahidi et al. (2020). Elevation measurements were made for Experiments 1 and 4 by shifting the indicated points straight up to the Experiment 4 line where they do not overlap. Units are meters. Flow is from left to right in the image.

Author contributions. SMC ran the experiment and processed all experimental data. SMC, AMJ and MAH designed the experiment. All authors discussed methodologies of analyzing the experimental data. SMC wrote the draft manuscript, and all authors edited the final manuscript. Sabir Hossain assisted with collecting data from published sources, and SMC reviewed and cross-checked all literature-derived sources included in Fig. 3.

Competing interests. The authors declare no conflicts of interest relevant to this research.

Acknowledgements. SMC was funded through an Alexander Graham Bell Canada Graduate Scholarship awarded from the National Sciences and Engineering Research Council Canada, a Mitacs Accelerate Program Fellowship, and by Simon Fraser University. Flume experiments were generously supported by an NSERC Discovery grant, and a Canada Foundation for Innovation grant to MH. Support for AMJ was provided through an NSERC grant.

References

- Bolla Pittaluga, M., Luchi, R., and Seminara, G.: On the equilibrium profile of river beds, *Journal of Geophysical Research: Earth Surface*, 119, <https://doi.org/10.1002/2013JF002806>, 2014.
- 450 Brew, A., Morgan, J., and Nelson, P.: Bankfull width controls on riffle-pool morphology under conditions of increased sediment supply: Field observations during the Elwha River dam removal project, in: 3rd Joint Federal Interagency Conference on Sedimentation and Hydrologic Modeling, p. 11, Reno, NV, 2015.
- Brown, R. A. and Pasternack, G. B.: Bed and width oscillations form coherent patterns in a partially confined, regulated gravel-cobble-bedded river adjusting to anthropogenic disturbances, *Earth Surface Dynamics*, 5, 1–20, <https://doi.org/10.5194/esurf-5-1-2017>, 2017.
- 455 Byrne, C. F., Pasternack, G. B., Guillon, H., Lane, B. A., and Sandoval-Solis, S.: Channel Constriction Predicts Pool-Riffle Velocity Reversals Across Landscapes, *Geophysical Research Letters*, 48, e2021GL094378, <https://doi.org/10.1029/2021GL094378>, 2021.
- Cao, Z., Carling, P., and Oakey, R.: Flow reversal over a natural pool-riffle sequence: a computational study, *Earth Surface Processes and Landforms*, 28, 689–705, <https://doi.org/10.1002/esp.466>, 2003.
- Carling, P.: An appraisal of the velocity-reversal hypothesis for stable pool-riffle sequences in the river Severn, England, *Earth Surface Processes and Landforms*, 16, 19–31, <https://doi.org/10.1002/esp.3290160104>, 1991.
- 460 Carling, P. and Orr, H.: Morphology of riffle-pool sequences in the River Severn, England, *Earth Surface Processes and Landforms*, 25, 369–384, [https://doi.org/http://doi.wiley.com/10.1002/\(SICI\)1096-9837\(200004\)25:4%3C369::AID-ESP60%3E3.0.CO;2-M](https://doi.org/http://doi.wiley.com/10.1002/(SICI)1096-9837(200004)25:4%3C369::AID-ESP60%3E3.0.CO;2-M), 2000.
- Carling, P. and Wood, N.: Simulation of flow over pool-riffle topography: A consideration of the velocity reversal hypothesis, *Earth Surface Processes and Landforms*, 19, 319–332, <https://doi.org/10.1002/esp.3290190404>, 1994.
- 465 Chartrand, S. M.: Environmental Planning of River Corridors Considering Climate Change: A Brief Perspective, in: *Recent Trends in River Corridor Management*, edited by Chembolu, V. and Dutta, S., pp. 27–38, Springer Nature Singapore, Singapore, <https://doi.org/10.1007/978-981-16-9933-72>, 2022.
- Chartrand, S. M., Jellinek, A. M., Hassan, M. A., and Ferrer-Boix, C.: Experimental data set for morphodynamics of a width-variable gravel-bed stream: new insights on pool-riffle formation, *Mendeley Data*, <https://doi.org/10.17632/zmjvt32gj3.3>, 2017.
- 470 Chartrand, S. M., Jellinek, A. M., Hassan, M. A., and Ferrer-Boix, C.: Morphodynamics of a Width-Variable Gravel Bed Stream: New Insights on Pool-Riffle Formation From Physical Experiments, *Journal of Geophysical Research: Earth Surface*, 123, 2735–2766, <https://doi.org/10.1029/2017JF004533>, 2018.
- Chartrand, S. M., Jellinek, A. M., Hassan, M. A., and Ferrer-Boix, C.: What controls the disequilibrium state of gravel-bed rivers?, *Earth Surface Processes and Landforms*, 44, 3020–3041, <https://doi.org/10.1002/esp.4695>, 2019.
- 475 Church, M.: Bed material transport and the morphology of alluvial river channels, *Annual Review of Earth and Planetary Sciences*, 34, 325–354, <https://doi.org/10.1146/annurev.earth.33.092203.122721>, publisher: Annual Reviews, 2006.
- Clifford, N. J.: Formation of riffle—pool sequences: field evidence for an autogenetic process, *Sedimentary Geology*, 85, 39–51, 1993.
- Cui, Y., Parker, G., Braudrick, C., Dietrich, W. E., and Cluer, B.: Dam Removal Express Assessment Models (DREAM), *Journal of Hydraulic Research*, 44, 291–307, <https://doi.org/10.1080/00221686.2006.9521683>, 2006.
- 480 de Almeida, G. A. M. and Rodríguez, J. F.: Understanding pool-riffle dynamics through continuous morphological simulations, *Water Resources Research*, 47, W01502–W01502, <https://doi.org/10.1029/2010WR009170>, 2011.
- de Almeida, G. A. M. and Rodríguez, J. F.: Spontaneous formation and degradation of pool-riffle morphology and sediment sorting using a simple fractional transport model, *Geophysical Research Letters*, 39, L06407–L06407, <https://doi.org/10.1029/2012GL051059>, 2012.

- De Rego, K., Lauer, J. W., Eaton, B., and Hassan, M.: A decadal-scale numerical model for wandering, cobble-bedded rivers subject to disturbance, *Earth Surface Processes and Landforms*, 45, 912–927, <https://doi.org/10.1002/esp.4784>, 2020.
- 485 Dolan, R., Howard, A., and Trimble, D.: Structural control of the rapids and pools of the Colorado River in the Grand Canyon., *Science* (New York, N.Y.), 202, 629–31, <https://doi.org/10.1126/science.202.4368.629>, 1978.
- East, A. E. and Sankey, J. B.: Geomorphic and Sedimentary Effects of Modern Climate Change: Current and Anticipated Future Conditions in the Western United States, *Reviews of Geophysics*, 58, e2019RG000692, <https://doi.org/10.1029/2019RG000692>, 2020.
- 490 East, A. E., Pess, G. R., Bountry, J. A., Magirl, C. S., Ritchie, A. C., Logan, J. B., Randle, T. J., Mastin, M. C., Minear, J. T., Duda, J. J., Liermann, M. C., McHenry, M. L., Beechie, T. J., and Shafroth, P. B.: Large-scale dam removal on the Elwha River, Washington, USA: River channel and floodplain geomorphic change, *Geomorphology*, 228, 765–786, <https://doi.org/10.1016/j.geomorph.2014.08.028>, 2015.
- Ferrer-Boix, C. and Hassan, M. A.: Influence of the sediment supply texture on morphological adjustments in gravel-bed rivers, *Water Resources Research*, 50, 8868–8890, <https://doi.org/10.1002/2013WR015117>, 2014.
- 495 Ferrer-Boix, C., Chartrand, S. M., Hassan, M. A., Martín-Vide, J. P., Parker, G., Martín-Vide, J. P., and Parker, G.: On how spatial variations of channel width influence river profile curvature, *Geophysical Research Letters*, 43, 6313–6323, <https://doi.org/10.1002/2016GL069824>, 2016.
- Frey, P., Ducottet, C., and Jay, J.: Fluctuations of bed load solid discharge and grain size distribution on steep slopes with image analysis, *Journal of Experimental Fluids*, 35, 589–597, <https://doi.org/10.1007/s00348-003-0707-9>, 2003.
- 500 Furbish, D. J. and Doane, T. H.: Rarefied particle motions on hillslopes – Part 4: Philosophy, *Earth Surface Dynamics*, 9, 629–664, <https://doi.org/10.5194/esurf-9-629-2021>, 2021.
- Furbish, D. J., Thorne, S. D., Byrd, T. C., Warburton, J., Cudney, J. J., and Handel, R. W.: Irregular bed forms in steep, rough channels: 2. Field observations, *Water Resources Research*, 34, 3649–3659, <https://doi.org/10.1029/98WR02338>, 1998.
- Gartner, J. D., Magilligan, F. J., and Renshaw, C. E.: Predicting the type, location and magnitude of geomorphic responses to dam removal: Role of hydrologic and geomorphic constraints, *Geomorphology*, 251, 20–30, <https://doi.org/10.1016/j.geomorph.2015.02.023>, 2015.
- 505 Harrison, L. R., East, A. E., Smith, D. P., Logan, J. B., Bond, R. M., Nicol, C. L., Williams, T. H., Boughton, D. A., Chow, K., and Luna, L.: River response to large-dam removal in a Mediterranean hydroclimatic setting: Carmel River, California, USA, *Earth Surface Processes and Landforms*, 43, 3009–3021, <https://doi.org/10.1002/esp.4464>, 2018.
- Hassan, M. A., Bird, S., Reid, D., Ferrer-Boix, C., Hogan, D., Brardinoni, F., and Chartrand, S.: Variable hillslope-channel coupling and channel characteristics of forested mountain streams in glaciated landscapes, *Earth Surface Processes and Landforms*, 44, 736–751, <https://doi.org/10.1002/esp.4527>, 2019.
- 510 Hassan, M. A., Radić, V., Buckrell, E., Chartrand, S. M., and McDowell, C.: Pool-Riffle Adjustment Due to Changes in Flow and Sediment Supply, *Water Resources Research*, 57, e2020WR028048, <https://doi.org/10.1029/2020WR028048>, 2021.
- Hassan, M. A., Chartrand, S. M., Radić, V., Ferrer-Boix, C., Buckrell, E., and McDowell, C.: Experiments on the Sediment Transport Along Pool-Riffle Unit, *Water Resources Research*, 58, e2022WR032796, <https://doi.org/10.1029/2022WR032796>, publisher: John Wiley & Sons, Ltd, 2022.
- 515 Hirano, M.: River-bed degradation with armoring, *Proceedings of the Japan Society of Civil Engineers*, 1971, 55–65, 1971.
- Leopold, L. B., Wolman, M. G., and Miller, J. P.: *Fluvial Processes in Geomorphology*, WH Freeman, San Francisco, pages: 522, 1964.
- Lisle, T. E.: Stabilization of a gravel channel by large streamside obstructions and bedrock bends, Jacoby Creek, northwestern California, *Geological Society of America Bulletin*, 97, 999–1011, 1986.
- 520

- Lisle, T. E. and Hilton, S.: The volume of fine sediment in pools: an index of sediment supply in gravel-bed streams, *Journal of the American Water Resources Association*, 28, 371–383, 1992.
- Lisle, T. E. and Hilton, S.: Fine bed material in pools of natural gravel bed channels, *Water Resources Research*, 35, 1291–1304, <https://doi.org/10.1029/1998WR900088>, 1999.
- 525 MacWilliams, M. L., Wheaton, J. M., Pasternack, G. B., Street, R. L., and Kitanidis, P. K.: Flow convergence routing hypothesis for pool-riffle maintenance in alluvial rivers, *Water Resources Research*, 42, <https://doi.org/10.1029/2005WR004391>, 2006.
- Magilligan, F., Graber, B., Nislow, K., Chipman, J., Sneddon, C., and Fox, C.: River restoration by dam removal: Enhancing connectivity at watershed scales, *Elementa: Science of the Anthropocene*, 4, <https://doi.org/10.12952/journal.elementa.000108>, 2016.
- Morgan, J. A.: The effects of sediment supply, width variations, and unsteady flow on riffle-pool dynamics, Ph.D. thesis, Colorado State University, 2018.
- 530 Morgan, J. A. and Nelson, P. A.: Experimental investigation of the morphodynamic response of riffles and pools to unsteady flow and increased sediment supply, *Earth surface processes and landforms*, 46, 869–886, <https://doi.org/10.1002/esp.5072>, 2021.
- Nelson, P. A., Brew, A. K., and Morgan, J. A.: Morphodynamic response of a variable-width channel to changes in sediment supply, *Water Resources Research*, 51, 5717–5734, <https://doi.org/10.1002/2014WR016806>, 2015.
- 535 Parker, G.: 1D sediment transport morphodynamics with applications to rivers and turbidity currents, e-book edn., 2007.
- Parker, G.: Transport of gravel and sediment mixtures, in: *Sedimentation Engineering: Theory, Measurements, Modeling and Practice (ASCE Manuals and Reports on Engineering Practice No. 110)*, edited by Garcia, M., pp. 165–251, ASCE, Reston, VA, 2008.
- Repetto, R., Tubino, M., and Paola, C.: Planimetric instability of channels with variable width, *Journal of Fluid Mechanics*, 457, 79–109, <https://doi.org/10.1017/S0022112001007595>, 2002.
- 540 Richards, K. S.: Channel width and the riffle-pool sequence, *Geological Society of America Bulletin*, 87, 883–883, 1976.
- Sawyer, A. M., Pasternack, G. B., Moir, H. J., and Fulton, A. a.: Riffle-pool maintenance and flow convergence routing observed on a large gravel-bed river, *Geomorphology*, 114, 143–160, <https://doi.org/10.1016/j.geomorph.2009.06.021>, publisher: Elsevier B.V., 2010.
- Sear, D.: Sediment transport processes in pool-riffle sequences, *Earth Surface Processes and Landforms*, 21, 241–262, [https://doi.org/10.1002/\(SICI\)1096-9837\(199603\)21:3<241::AID-ESP623>3.0.CO;2-1](https://doi.org/10.1002/(SICI)1096-9837(199603)21:3<241::AID-ESP623>3.0.CO;2-1), 1996.
- 545 Thompson, D. and McCarrick, C.: A flume experiment on the effect of constriction shape on the formation of forced pools, *Hydrology and Earth System Sciences*, 14, 1321–1330, <https://doi.org/10.5194/hess-14-1321-2010>, 2010.
- Thompson, D., Nelson, J. M., and Wohl, E.: Interactions between pool geometry and hydraulics, *Water Resources Research*, 34, 3673–3681, <https://doi.org/10.1029/1998WR900004>, 1998.
- Thompson, D., Wohl, E., and Jarrett, R.: Velocity reversals and sediment sorting in pools and riffles controlled by channel constrictions, *Geomorphology*, 27, 229–241, 1999.
- 550 Vahidi, E., Rodríguez, J. F., Bayne, E., and Saco, P. M.: One flood is not enough: pool-riffle self-maintenance under time-varying flows and non-equilibrium multi-fractional sediment transport, *Water Resources Research*, 56, e2019WR026818, <https://doi.org/10.1029/2019WR026818>, 2020.
- White, J. Q., Pasternack, G. B., and Moir, H. J.: Valley width variation influences riffle-pool location and persistence on a rapidly incising gravel-bed river, *Geomorphology*, 121, 206–221, <https://doi.org/10.1016/j.geomorph.2010.04.012>, 2010.
- 555 Whiting, P. J. and Bradley, J. B.: A process-based classification system for headwater streams, *Earth Surface Processes and Landforms*, 18, 603–612, <https://doi.org/10.1002/esp.3290180704>, 1993.

- Wilkinson, S. N., Keller, R. J., and Rutherford, I. D.: Phase-shifts in shear stress as an explanation for the maintenance of pool–riffle sequences, *Earth Surface Processes and Landforms*, 29, 737–753, <https://doi.org/10.1002/esp.1066>, 2004.
- 560 Wolman, M. G.: The natural channel of Brandywine creek, Pennsylvania, United States Geological Survey Professional Paper 271, pp. 63–63, 1955.
- Wyrick, J., Senter, A., and Pasternack, G.: Revealing the natural complexity of fluvial morphology through 2D hydrodynamic delineation of river landforms, *Geomorphology*, 210, 14–22, <https://doi.org/10.1016/j.geomorph.2013.12.013>, 2014.
- Yalin, M.: On the formation of dunes and meanders, in: Proceedings of the 14th Congress of the International Association for Hydraulic
565 Research, pp. C101–108, IAHR, Paris, 1971.
- Zimmermann, A. E., Church, M., and Hassan, M. A.: Video-based gravel transport measurements with a flume mounted light table, *Earth Surface Processes and Landforms*, 33, 2285–2296, 2008.